

**Model: AEA1415EXA**
**Product Description**

**Type:** Reciprocating  
**Application:** LBP - Low Back Pressure  
**Refrigerant:** R-22  
**Voltage/Frequency:** 115V ~ 60Hz 100V ~ 50Hz  
**Version:** N/A


**Product Specifications**
**Performance**

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	115V ~ 60HZ	1500	378	440	410	3.66	.92	1.07	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)

**General**

**Evaporating Temp. Range:** -34.4°C to -12.2°C (-30°F to 10°F)  
**Motor Torque:** Low Start Torque (LST)  
**Compressor Cooling:** Fan

**Mechanical**

**Weight:** 29  
**Weight Unit of Measure:** LB  
**Displacement (cc):** 11.291  
**Oil Type:** Synthetic Alkylate  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 473

**Electrical**

**Voltage Range (50 Hz):** 90-110  
**Voltage Range (60 Hz):** 103-127  
**Locked Rotor Amps (LRA):** 39  
**Rated Load Amps (RLA 50 Hz):** 0  
**Rated Load Amps (RLA 60 Hz):** 5.2  
**Max. Continuous Current (MCC in Amps):** 0  
**Motor Resistance (Ohm) - Main:** .871  
**Motor Resistance (Ohm) - Start:** 15.22  
**Motor Type:** CSIR  
**Overload Type:** N/A  
**Relay Type:** N/A

**Agency Approval**

cURus Recognized