

Model: AWA9514ZXT

Version:

N/A

Product Description

Type: Reciprocating
Application: CBP - Commercial Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 200-230V 3~ 60Hz 200-220V 3~ 50Hz



Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
ARI	230V 3~ 60HZ	14300	3604	4190	2480	5.77	1.45	1.69	-6.7°C (20°F)	49°C (120°F)	35°C (95°F)	4.4°C (40°F)	49°C (120°F)

General

Evaporating Temp. Range: N/A
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 70
Weight Unit of Measure: LB
Displacement (cc): 51.327
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 1141

Electrical

Voltage Range (50 Hz): 180-242
Voltage Range (60 Hz): 180-254
Locked Rotor Amps (LRA): 63.4
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 7.3
Max. Continuous Current (MCC in Amps): 15.5
Motor Resistance (Ohm) - Main: 1.28
Motor Resistance (Ohm) - Start: N/A
Motor Type: 3PH
Overload Type: N/A
Relay Type: N/A

Agency Approval

cURus Recognized