Integrated front fins

manage airflow into the cutter deck to

ensure a fluid movement of air through the cutting chamber into the bag.

ProStripe[™] 560 - features in detail

Commercial Briggs & Stratton 4-stroke petrol engine with Readystart™

features a cast-iron cylinder sleeve and dual filtration air-intake.

Soft-grip handle bar

with an over-centre OPC control mechanism to reduce operator fatigue.

Single spring-assisted height of cut mechanism

easily adjusts through 8 increments between 13mm (0.5") and 60mm (2.4").

Durable die-cast Aluminium deck

with a robust high-impact ABS polymer deck liner promotes superior air-flow and collection capabilities.

70 litre bag capacity

provides ample capacity for you to keep mowing the perfect stripe, after stripe.

Full width integrated rear roller

for the perfect striped finish. The unique 'ribbed' profile provides added traction in damp conditions or on undulating terrain.

Zero-turn with zero-turf damage!

The unique split rear-roller with integrated differential enables on the spot turns with no risk of turf damage.

For the rigors of commercial mowing, handle bar supports provide added rigidity whilst the front bumper bar ensures added deck durability.

TORO® PROFESSIONAL SERVICES

Toro Financing Many flexible financing options are available to meet your specific operational requirements.

Toro Genuine Parts Keep the productivity and performance of your equipment at its peak by using genuine Toro replacement parts. Find and identify your replacement parts online at www.Toro.com/partsviewer.

Toro Training Toro Technical Service Schools are available from your local distributor. Explore the training and customer care areas of Toro.com and ToroNSN.com for readily available on-line education and training materials.

Products depicted in this brochure are for demonstration purposes only. Actual products offered for sale may vary.

	SPECIFICATIONS - PROSTRIPE™560	
	ENGINE	Commercial grade Briggs & Stratton 850 Series with Readystart™
	STARTER	Recoil – Zone Start
	TRANSMISSION	Single speed auto-drive – 4.4km/h (2.7mph)
	CUTTING SYSTEM	Single Steel Blade
	CUTTING WIDTH	560mm (22")
	HEIGHT OF CUT	13 – 60mm (0.5" – 2.4") through 8 increments
	BAG CAPACITY	70 Litres
	NET WEIGHT	51kg (112lbs)
	WARRANTY	2-Year Limited Warranty
	CERTIFICATION	Meets CE & ANSI Legislative Requirements. Engine certified to meet EPA/CARB emissions requirements.

