

Super Funny Pipe®

- 20' (6m), 50' (16m), 100' (30,5m) Coils
- Up to 120 psi (8,3 Bar)

Toro® Super Funny Pipe is practical and saves time. Whether you are installing a new system or replacing an old sprinkler, Super Funny Pipe makes the job easier.



Super Funny Pipe Friction Loss Data

	GPM Flow						
GPM	1	2	3	4	5	6	7
PSI Loss	0.01	0.02	0.06	0.09	0.15	0.21	0.27

This chart indicates the amount of pressure loss (psi) per foot of Super Funny Pipe at stated flow rates (GPM).

Features & Benefits

Flexible, Thick-walled Polyethylene Pipe

Super Funny Pipe is a high-strength poly tubing that solves tough sprinkler installation and replacement problems. It acts as an extension cord between the water line and the sprinkler.

Easy Installation For Problem Areas

One of the most useful and time-saving sprinkler installation aids whether you are installing a new system or replacing an old sprinkler. Also comes pre-assembled as the Super Funny Pipe Swing Joints in 8" (20,3cm) and 12" (30,5cm) lengths or just get the individual fittings as needed.

Specifications

Dimensions

- Wall thickness: .10" ± .01 (2,5mm ± 0,25)
- Inside diameter: .49" ± 0.005 (12,4mm ± 0,13)
- Outside diameter: .70" (17.8mm)

Operating Specifications and Features

- Maximum pressure: 120 psi (8,3 Bar)
- Cushions sprinklers from external impact
- Connects to sprinklers and Toro fittings

Warranty

Two years

Super Funny Pipe Model List

Model	Description
850-23	20' (6,1m) Length, 3/8" (9,5mm) Polyethylene Pipe
850-24	50' (15,2m) Coil, 3/8" (9,5mm) Polyethylene Pipe
850-25	100' (30,4m) Coil, 3/8" (9,5mm) Polyethylene Pipe