How to avoid TD-W8961NDv3 been exploited for internet attacks


In 2014, it is reported that many wireless routers can potentially be used by hackers, to attack some servers in the internet. Here is the detail of this issue: http://www.theguardian.com/technology/2014/apr/01/uk-wifi-routers-internet-attacks

We've found that our TD-W8961ND v3 has this issue and fixed it by upgrading to the latest firmware. Below is the detailed instruction how to get it fixed:

- Download version 140305 from http://uk.tp-link.com/resources/software/TD-W8961ND_V3_140305_UK.zip and extract the file to somewhere on your PC
- Download version 140331 from http://uk.tp-link.com/resources/software/TD-W8961ND V3 140331 UK.zip and extract the file to somewhere on your PC
- 3. Follow these instructions to upgrade to 140305.

Step 1

Log into TD-W8961ND v3's web manage page by typing http://192.168.1.1 in the address bar of the web browser (such as Internet Explorer, Firefox). The **username** and **password** are both **admin** unless you have changed it before.



Step 2

Click **Maintenance ->Firmware** click the **Browse** button to choose the firmware you already extracted in the folder.



Step 3

Click the **UPGRADE** button. The device will reboot automatically after the upgrading has been finished. Please wait about 3 minutes.

Step 4

Click **Status-> Device Info**, verify that the router's firmware has been upgraded.

TP-LINK®				300Mbps Wireless N ADSL2+ Modem Router			
Status	Quick Start	Interface Setup	Advanced Setup	Access Managemo	Maintenan	ce Status	Help
	Device In	fo Sys	stem Log	Statistics			
Device Information							
	Firmware Version : Build 140305 Rel.04531						
	MAC Address : f8:1a:67:e7:1a:85						
LAN		ID 44	d 400 400 4				
	IP Address : 192.168.1.1 Subnet Mask : 255 255 255 0						
	DHCP Server: Enabled						
Wireless		51101 5	CIVEL . Ellabica				
	Current Connected Wireless Clients number is				0	Refresh	
	ID		MAC				


4. Follow the steps above again to upgrade it to 140331

After upgrading the firmware to 140331, you unit will not be involved in the attacking.


Besides, to make your device more secure, you can keep remote access function of your router disabled if it is not essential to you. To do this, you can:

Step 1

Log into TD-W8961ND v3's web manage page by typing http://192.168.1.1 in the address bar of the web browser (such as Internet Explorer, Firefox). The **username** and **password** are both **admin** unless you have changed it before.



Step 2
Click Access Managenment -> ACL, and make sure the Interface is LAN.



For any questions or help please call our TP-LINK 24 hour technical support line 0845 147 0017 or e-mail support.uk@tp-link.com .