

ULTRA

Ultra BOX nForce SLI Socket 939 Barebone

ULTRA BOX

Ultra Box nForce SLI Socket 939 Barebone

A perfect combination of power and performance is in this lightweight, compact package. By using Ultra Product's popular MicroFly case, rock-solid Ultra power supplies and bleeding edge motherboards, Ultra offers an excellent value with great upgrade potential. Our Socket 939 AMD barebone system uses the latest, micro ATX nForce4 SLI based motherboard featuring two PCI-e x16 slots, four DDR memory slots, 8-channel AC'97 audio and Gigabit LAN. An X-Finity 500W power supply is included to ensure ample power for your new gaming machine!

Includes

- nForce SLI Socket 939 Motherboard
- X-Finity 500 Watt Power Supply
- MicroFly Micro ATX Case
- 120mm Rear Exhaust Fan
- 80mm Front Intake Fan



nForce 4 SLI Socket 939

Specifications	
Form Factor	microATX
Processor Interface	Socket 939
Processors Supported	AMD Athlon 64 FX AMD Athlon 64 X2
Front Side Bus	1000MHz
Chipset	nVIDIA nForce4 SLI
Memory Slots	4
Number of Pins (Memory)	184-Pin
Maximum Memory Supported	4GB
Memory Supported	DDR266 (PC2100) DDR333 (PC2700) DDR400 (PC3200)
Audio Channels	8 Channels
Audio Chipset	AC '97 CODEC
Supported IDE Devices	2
Serial ATA Headers	4
Fan Connectors	4
S/PDIF Connectors	2



MicroFly Micro ATX Case

- Specifications**
- Color: Silver w/ Clear Side
 - Material: High Grade Aluminum
 - Dimensions: 15"x11.25"x9"
 - Drive Bay:
 - 2 - External 5.25" Bays
 - 1 - External 3.5" Bay
 - 2 - Internal 3.5" Hard Drive Bays
 - * Form Factor: ATX
 - * Expansion Slots: 4 Standard Slots
 - * Case Fans:
 - 1 - 120 mm
 - 1 - 80mm
 - * LEDs:
 - Green - Power
 - Orange - Hard Drive Access
 - * Switches:
 - Power
 - Reset
 - * Easy access front panel:
 - 2 - USB 2.0
 - 1 - Firewire
 - 1 - Headphone
 - 1 - Microphone
 - Temperature Display



500W X-Finity Power Supply

- Specifications**
- Total Output Power: 500W (Full Load, Nominal Input Voltage)
 - Efficiency: 70% Typical at Full Load and Nominal Input Voltage

Input

AC Input Voltage: 115V/230V
AC Input Frequency: 50-60Hz
AC Input Currents:

- 8.5A (RMS) for 115VAC input
- 5.5A (RMS) for 230VAC input

OUTPUT						500 Watt	
Max Output Current	+3.3VDC	+5VDC	+12VDC1	+12VDC2	-12VDC	+5VSB	
	30A	30A	16A	18A	0.6A	2.5A	
	160 W		384W		7.2 W	12.5W	
Max Combined Wattage	481 W				19.7 W		
							500 W

- Supports AMD and Intel Motherboards
- NVIDIA® SLI™ Ready
- Low Acoustic Noise
- 120mm Fan
- Meets ATX Version 2.2, v1.3, and ATX 12V Version 2.2 Specifications
- Short Circuit Protection
- In-Rush Current Protection
- Thermal Overload Cutoff Protection
- MTBF > 100,000 Hours at Full Load, 110VAC and 25°C Ambient Condition
- FCC and UL Recognized

Ultra Box nForce SLI Socket 939 Barebone

Part #: ULT33164
UPC#: 022769331645
Dimensions: 15"x11.25"x9"

ULTRA
1-800-830-0051
www.ultraproducts.com

ULTRA