

For wall mount installation use.

# Slide to turn on or off the baby unit. PARENT UNIT OVERVIEW

6 ON/OFF switch

STORAGE

Why do I get glare or blurry display on my screen when viewing my baby at night?

Why does the parent beep?

in **Split** mode:



When you are not going to use the baby monitor for some time, remove the rechargeable battery from the parent unit. Store the parent unit, the baby unit and the adapters in a cool and dry place.

of frequently asked about the baby monitor. If you cannot chphones.com, or contact 1 (800) 595-9511 for custome

Make sure the power is not controlled by a wall switch.

Why is my screen in black The screen is in black and white during night-time or in a dark room when the night vision and white?

The screen is black and white during night-time or in a dark room when the night vision and white?

To the following in the order intend for common rune:

18 months of the control intended for common rune:

2. Remove the batteries in the parent unit. Then, install the batteries again.

2. While the vector beloates correcting overwhealth the batteries again.

3. Was few seconds beloates correcting overwhealth the bally units and the parent unit.

5. Was for the parent unit to synchronize with the bally units. Allow up to one minute for this to take place.

Perhaps the baby unit is not connected to the power. Insert the appliance plug into the baby unit and put the adapter in a well socket. Then, side the ON/OFF switch to ON to switch on the baby unit and to establish connection with the parent unit

During night-time or in a dark room, the surroundings and other interfering factors, like lightings, objects, colors and backgrounds may affect the image quality on your parent unit screen. Adjust the baby unit's angle or place the baby unit at a higher level to prevent glare and blurry display.

The parent unit and baby units may be too close to each other.

Move the parent unit and with your thin the baby units until the noise stops; OR

Turn down the volume of your present unit.

The baby units may be out of range. Move the parent unit closer to the baby units (but not test than 5 face).

The parent unit may not have enough charge for the parent unit to perform normally. Charge the battery in the parent unit for up to 3 hours.

If your parent unit is in Split mode, some of your baby units may detect sounds.

temperature of your baby's room may be too high or too low. Why does the parent unit. You may have set the VOX sensitivity level to **Highest** when the sound alert (and vibration) beep/vibrate frequently feature is turned on. The parent unit notifies you of all sounds including background noise.

sature is turned on. The parent unit notities you of all sounds includ vith beeps (and vibration). Adjust the VOX sensitivity to a lower level

may have used the battery for a long time. Replace a new battery.

aps the parent unit is not connected to the power. Insert the appliance plug into the nt unit and put the adapter in a wall socket. Then, <u>press and hold POWER</u> to switch on sarent unit and to establish connection with the baby unit.

 $^{\mathrm{Q}}_{_{^{\!\!\!\!A}_{\!\!\!\!A}}}$  Frequently asked questions

# 

10

11

press and hold to move the zoomed image upward.

PARENT UNIT LIGHTS

. On when the parent unit is linked to the baby unit.

When the parent unit is talking to the baby unit; o

On when the parent unit is talking to the baby unit.

When the parent unit is in Split mode

**IMPORTANT SAFETY INSTRUCTIONS** 

PARENT UNIT OVERVIEW (CON'T)				
VIEW / LCD ON/OFF Microphone POWER TALK  - Press and hold to talk to the selected baby unit.  - While in a menu, press to return to the main menu or idle screen.	12	While in a menu, press to choose an item. While viewing images in Single CA or Patrol mode, press and hold to pan the baby unit camera rightware. While viewing zoomed image, press and hold to move the zoomed image rightward. While in Spilt mode, press to mow the selection box rightward.		
<ul> <li>While viewing images in Single CAM or Patrol mode, press and hold to pan the baby unit camera leftward.</li> </ul>	13	MENU/SELECT     Press to enter the menu.     While in a menu, press to choose a item, or save a setting.		
While viewing zoomed image, press and hold to move the zoomed image leftward. While in Split mode, press to move the selection box leftward.  While in a menu, press to scroll up. While viewing images in Single	14	While in a menu, press to scroll dow     While viewing images in Single CA     or Patrol mode, press and hold to 1     the baby unit camera downward.     While viewing zoomed image,     press and hold to move the     zoomed image downward.		
CAM or Patrol mode, press and hold to tilt the baby unit camera	15	Antenna		
nota to fill the baby unit camera upward.	16	Stand		
<ul> <li>While viewing zoomed image,</li> </ul>	17	Speaker		

Flashes when the link to the baby unit being viewed in Single CAM or Patrol mode is lost; or when the link to at least one baby unit being viewed in Split mode is lost.

. On when the parent unit is connected to AC power, or the battery is charging

Flashes when the parent unit battery is low and needs charging.
 Off when the parent unit is disconnected from AC power.

When using your equipment, basic safety precautions should always be followed to reduce the risk of fire, electric shock and injury, including the following:

state is treasured.

As a first of the state of the state

used to the parel only. To not dispose of batheries in a fire. They may explode, Dispose of lasted bathery according to the Use only the adjuster, budded with the protection. Increase datapies profession, but the provided protection of the provided protection of the provided protection. But you import adaptive. Durplet of VIC 2.50.

But you will provide a provided prov

a radiation or mean register.

a repush objects of any kind into this product through the slots because they may touch dangerous voltage points or
te a short circuit. Never spill liquid of any kind on the product. creates before fruits. Never gail listed of anymes are origin review and occlusion that men makes the contribution of the cont

18 Power jack

	[	P.	ARENT UNIT ICO
	۱	Status	icons
•		Tal	Connection status  · III displays when strong sign and the parent unit.  · IIII or IIII displays when more the baby unit and the pare  • III displays when the link be
		u	Lullaby - Displays when the baby un
		910r 920r 930r 930r	Displays the number of the and Patrol mode.     Displays the baby unit num
1		•	Patrol mode  Displays when the parent u  For VM5262-2 only.
1		88	Split mode Displays when the parent u For VM5262-2 only
		2	Night vision Displays when the baby uni
		R	Zoom Displays when the current
		¶à	Temperature alert tone Displays when the tempera
		°F or °C	Real-time temperature  • Displays the real-time temp

THE RBRC® SEAL

RF radiation exposure statement

FCC AND IC REGULATIONS

_ FARENT UNIT ICONS					
Status	sicons				
Til	Connection status  * Midplays when strong signal strength is detected between the baby unit and the parent unit.  * Mid or Mid slays when moderate or low signal strength is detected between the baby unit and the parent unit.  * T displays when the link between the baby unit and the parent unit is lost.				
n	Lullaby Displays when the baby unit being viewed is playing lullaby.				
910r 910r 910r 910r	Current view status  Displays the number of the baby unit that is being viewed when in Single CAM and Patrol mode.  Displays the baby unit number of the selected baby unit when in Split mode.				
•	Patrol mode  Displays when the parent unit is in Patrol mode. For VMS262-2 only.				
88	Split mode  Displays when the parent unit is in Split mode. For VMS262-2 only				
2	Night vision  Displays when the baby unit being viewed has activated the night vision feature.				

### night vision feature. image on the parent unit has zoomed in.

erature alert tone is set on.

Displays the real-time temperature detected by the baby unit in Fahrenheit (°F) or Celsius (°C) (e.g. 57 °F or 14 °C).

Mute alert

Displays when the parent unit is talking to the baby unit.
Displays when Split mode is turned on. (80) IIIIIIII 9-level sound indicator

\*\*Ill 10 3 bars) indicates low sound level detected by the baby unit.

Ill (10 5 bars) indicates low sound level detected by the baby unit.

Ill (10 6 bars) indicates moderate sound level detected by the baby unit. Speaker volume Displays the parent unit speaker volume level while adjusting.

The RBRC<sup>®</sup> seal on the lithium-ion battery indicates that VTech Communications, Inc. is voluntarily participating in an industry program to collect and recycle these batteries at the end of their usefu when taken out of service within the United States and Canada. participating in in industry program to cloted and recycle these batteries at me tow or were work-tered in the clothed faster and clothed state and clothed and compared or municipal variety, which may be litigated in your area.

Industrian the program of the p

displays solid when the battery is fully charged.

displays when the battery is low and needs charging.

AC power without battery

Displays when the parent unit is connected to AC power without the battery.

RBRC® and 1 (800) 8 BATTERY® are registered trademarks of the Rechargeable Battery Recycling Corporation

CP PM 12

compliant has been treated and found to comply, with the requirement for a Class B digital device unider Far 13 of the final interface of the Class B digital device unider Far 13 of the final interface on a residential installation. The experience of presents, uses and can plate to dis frequency energy many from the complex of the complex

sees early of use, the ECC has established criteria for the amount of reads frequency energy that can be afoly absorbed.

Sees afony of use, the ECC has established criteria for the amount of reads frequency energy that can be afoly absorbed.

CC criteria. The baby unit shall be installed and used such that parts of all persons body are maintained at a distance of contrastly 8 in IQ only or more. The transmitter and antenna of the parent unit shall be left also sail to IQ contrastly 8 in IQ only or more. The transmitter and antenna of the parent unit shall be left also sail 1 in IQ.5 only from your

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Developme Canada's licence-exempt RSI(s). Operation is subject to the following two conditions:

(1) This device may not cause interference.

(2) This device man accept any interference, including interference that may cause undestred operation of the device.

The term "IC" before the certification/registration number only signifiles that the industry Canada technical specifications were mist.

er.
duct meets the applicable Innovation. Science and Economic Development Canada technical specifications

the baby unit complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The baby unit should be installed and operated with a minimum distance of 8 in (20 cm) between the baby unit and all persons' body. Use of other

Battery empty.
Powering off ... The battery is empty and needs to be recharged.

FOR CETL COMPLIANCE ONLY

Warning icons and messages

Volume on CAM

Main menu icons

Battery low at Parent Unit The battery level of the parent unit is very low and needs to be recharged. Sound detected at The sound level exceeds the threshold at CAM # in Split mode.

United the site of a blesseries opposited, only or oak plasmer?

Claimant families in bringing parties of interest parties and progress.

Committed the interest parties of the site of the parties of th

decidentifying electronic in production of control of c

% **No link to CAM #** \* The selected baby unit is out of range or is turned off.

Monitoring mode

If you have two baby units, you can select a monitoring mode (Single CAM, Patrol or Split).

For VMS262-2 only.

Language
• You can select a language (English, French or Spanish) to be used in all screen displays.

Rename

• You can choose a specific name for the baby unit from a pre-defined name list.

VXX Sensitivity
VXX Sensitivi

Lullaby on CAM

You can choose a lullaby or soothing sound to comfort your baby.

will men rum of ragain after 50 seconds of no sound defection.

Temperature

You can choose to set the maximum/ minimum temperature and rum on the

Temperature select rone, so that the parent unit beeps whenever the room

temperature defected by the baby unit falls outside of the delired temperature range.

Exercises the selection of the properature in a selection of the parent rum of th

You can adjust the volume of baby units which determines the lullaby volume and talkback volume transmitted from parent unit.

**/ibration**You can turn on the vibration alert so that the parent unit vibrates when it receives **No link alert, Sound alert in split-view** or **Temperature alert tone** after turning on the respective alert tone.

You can change the brightness of the parent unit screen, or turn on the **Dim Mode**to save name?

when the link between the parent unit and the baby unit is lost; or when the baby unit detects sounds while in **Split** mode.

Alert Tone
You can set the parent unit to beep

when the parent unit operates in low battery condition:

Temperature too high at CAM #

The temperature detected by the baby unit is higher/lower than the desired temperature alert range. Temperature

too low at CAM # Powering on... The parent unit is turning on The parent unit is searching for baby units.

Auto Timer of Iuliaby is The timer that determines the remaining play time for the Iuliabies reset is restarted.

\$ The parent unit has just been connected to AC power

# represents the baby unit number.

### NIGHT VISION

The baby unit has infrared LEDs that allow you to see your baby clearly at night or in a dark room. When the baby unit being viewed detects low light levels, the infrared LEDs are switched on automatically. The images from the baby unit are in black and white, and 2 papears on the scree

■ Notes nal if you see a short white glare on your parent unit screen as the baby unit is adapting to

S TIP

Depending on the surroundings and other interfering factors, like lightings, objects, colors and backgrounds, the video quality may vary. Adjust the baby unit's angle or place the baby unit at a higher level to prevent glare and blurry display.

### **MOUNT THE BABY UNIT (OPTIONAL)**

Your baby monitor comes ready for tabletop use. You can also choose to mount your baby monitor on the wall. See Mount the baby unit (optional) in the **Quick Start Guide** for the wall

### GENERAL PRODUCT CARE

To keep this product working well and looking good, follow these guidelines:

• Avoid putting it near heating appliances and devices that generate electrical noise (for example, motors or fluorescent lamps).

or fluorescent lamps).
DO NOT expose it to direct sunlight or moisture.
Avoid dropping the product or treating it roughly.
Clean with a soft cloth.
DO NOT immerse the parent unit and the baby unit in water and do not clean them under the tap.

DO NOT use cleaning spray or liquid cleaners.

Make sure the baby unit and parent unit are dry before you connect them to the mains again

# I IMITED WARRANTY What does this limited warranty cover? The manufacture of this VPich Product warrants to the holder of a valid proof of purchase ("Consume" or "you") that the Product and all accessors provided in the sales package ("Product") are the from detect in material and workmanthly, pursuant to the following terms and conditions, when intalled and used namely and in accordance with the Product product and a condition of the VPI pursuant to the following terms and conditions, when intalled and used namely and in accordance with the Product product and Consumer for Products purchased and used in the VPI pursuant for the

What will VTech do if the Product is not free from defects in materials and workmanship during the limited warranty period ("Materially Defective Product")?

# During the limited warranty protect. VEX-or sutherized service representative will repair or representative warranty protect. VEX-or sutherized service representative will repair or representative will repair or represent protect. If we repair the Product, we may use peer or refurbined repaircement parts. If we receive the Product, with repair called a will as more or interfactive direct parts are or interfactive product the repair repair. We will repair remedy. VEX-or will repair repair or replacement Products to you in working condition. You should expect the repair replacement of the properties of the repair repair.

reputations in the date applications you clay.

Here long is the limited warranty period extended for CNE (I) YEAR from the date of purchase. If VTech regain or replaces a Subtractive Detector in Product under the terms of this limited warranty, this limited warranty due applies to the replaced or replacement Product for a placed or office in Year Organization or the CNE (I) YEAR from the date the repeated or replacement Product for a placed or office in Year Organization or the CNE (I) YEAR from the date the repeated or replacement Product is subtracted to your ordinary or the CNE (I) YEAR from the date the repeated or replacement Product is subtracted by the CNE (I) YEAR from the date the repeated or replacement Product is subtracted by the CNE (I) YEAR from the date the repeated or replacement Product is subtracted by the VNE (I) YEAR from the date of the VNE (I) YEAR from the date of the VNE or the VNE (I) YEAR from the date of the VNE or the VNE or

Product that has been subjected to misuse, accident, shipping or other physical damage, improper installation, abnorma operation or handling, neglect, inundation, fire, water or other liquid intrusion; or

specialisms on initiating, neglect, inuncation, tire, water of other flourid intrusion; or Froduct that has been damaged due to repair, alteration or modification by anyone other than an authorized service expessionative of VTect; or Froduct to the excent that the problem experienced is caused by signal conditions, network reliability, or cable or reduct to the expert that the problem experienced is caused by signal conditions, network reliability, or cable or

e adent that the problem expenienced is caused by signal conditions, network reliability, or cable or ms; or s extent that the problem is caused by use with non-VTech accessories; or warranty/quality stickers, product serial number plates or electronic serial numbers have been removed.

assists or remoterous registers; or Product purchased, used, serviced, or shipped for repair from outside the United States of America or Canada, or used Product purchased, used, serviceose (including but not limited to Product used for rental purposes); or Product returned without a valid proof of purchase (see Item 2 below); or Charges for installation or set up, adjustment of customer controls; and installation or repair of systems outside the unit.

c. Larges for installation of set up, adjustment of customers commost, and installation or repair of systems counted the unit. How do you get warranty service. The IUSA, please visit our website at www.vfechphones.com or call 1 (800) 595-9511. In Canada, go to www.vfechcanada.com or call 2 (800) 267-3737.
NOTE: Before calling for service, please review the user's manual - a check of the Product's controls and features may save your service.

notes there camp for territor, please review the car's manual\* a check of the Product's corrick and features may save your services. The product is made to the product of the product of

ide your name, complete and correct mailing address, and telephone number.

Chem initiations

The initiations complete and exclusive agreement between you and VToch. It supersedes all other written or oral communications related to their Product. VToch provides no other warrantee for their Product. The warranty exclusively exclusively. The exclusive exclusively exclusively exclusively exclusively exclusively exclusively. The exclusive exclusively exclusive exclu

The deather of york you spoke, say a pass, any own any own are one rays, where or the pass. It is considered that the pass of the pass of

Utilises or entreposare le produit à une interprisatare entre o °C (2°C 1°) et 40°C (204° 1°), in Neposeup son et aprespare du le froide cou des debres contiemes, aire qu'ai battimire destroit un cale à l'entrelate pas pris d'une source de d'auflige. La bloco plan ne doir pas être seposie à la chalura rescenire lette que si la turisire du sorbie cau feur. Autres des capitals de l'entrelate pas pris d'une source de d'auflige. La bloco plan ne doir pas étre seposie à la chalura rescenire lette que si la turisire du sorbie des referries (ni, laur moirs 1 même () piede) de l'enfent ou l'autres-rescuit que l'entrelate à l'entrelate de l'entrelate de partie des réferries (ni, laur moirs 1 même () piede) de l'enfent ou l'autres-rescuit que l'entrelate à l'entrelate de l'entrelate de la part de bielle. Ne jumis couvrir le montheur ou l'unite (i) portaite avec un article situit servireire ou un convenire. se une se reserve du consensus.

"D'ultres équipements électroniques peuvent produire des interférences sur votre moniteur vidéo et audio. Tentez d'installer votre moniteur vidéo ou audio à l'écart des appareits électroniques tels que des routeurs sans fils, radios, téléphones cellulaires, interphones, moniteurs, téléphones, certainateurs peuvonais, électrominaigner et féliphones sans fil.

CONSERVEZ CES INSTRUCTIONS

ez le produit à une température entre 0 ° C (32 ° F) et 40 ° C (104 ° F).

eitmerne er oriogium (v.u.) osis teles-tons, la imme with recommance aux misciscinis.

Votu devriate maintenin les disposalifs sans fil à au moins six pouces du simulateur cardiaques.

Votu devriate maintenin les disposalifs sans fil à au moins six pouces du simulateur cardiaque, les que disposalifs sans fil à au moins six pouces des la finalitateur cardiaque, les que disposalifs sans fil à promisme de cardiaque, les que des six pour les disfinates de finalitateur cardiaque, les que des six pour les disfinates de simulateur dispositifs sans fil à promismité de caux que.

Champs électromagnétiques (EMF)
Ce produit de VTech est conforme à te correctement en suivant les instruction

# was up-aimore with a mismum distance or is in Q0 cm) between the baby unit and all persons' body. Use of other may not ensure compliance with FCC RF exposure guidelines. This transmitter must not be co-located or operating on with any other antenna or transmitter. This equipment complies also with Industry Canada RSS-102 with respect Health Code of for Exposure of Humans to RF Floids. CALIFORNIA ENERGY COMMISSION BATTERY

CHARGING TESTING MODE is set up to comply with the energy-conserving standards right out of the box. Follow the instri the battery. The CEC battery charging testing mode is activated while charging. Even if the pai white the CFC battery charging testing mode is activated while it is powered off and charging.

The baby unit also picks up other sounds than those of your baby. Adjust the VOX sensitivity level to a lower level or lower the parent unit speaker volume. Why don't I hear a sound/ The parent unit speaker volume may be too low. Press ™ **©** to increase the volume why can't I hear my baby \(\frac{1}{100}\) \(\f You may have set a low VCX sensitivity level. See **Adjust the sound sensitivity of the baby** unit to set to a higher level.

The baby units may be out of range. Move the parent unit closer to the baby units (but not less than 3 feet).

connection lost every now and then? Why are there

Other electronic and wireless products may cause interference with your baby monitor. Try installing your baby monitor as far away from these devices as possible. If you power on only one baby unit, your parent unit may display \$\mathbb{Z}\$ and \$\tilde{\mathbb{N}}\$ No link to CAM #, and the LINK LED light flashes. Press VIEW to switch to the baby unit you have powered on.

SAVE THESE INSTRUCTIONS Use and sit tion the product as a temperature between EFF and IGNF.

The control of the product class is reposated by the product of the product class to a healing outstrand state of the product class to a healing outstrand the product class to the product class to the product of the such of the product class to the product of the product class to the product clas

Precautions for users of Implanted cardiac pacemakers
Cardiac pacemakers (applies only to digital condises devices)
Wireless Technology Research, LLC (Willy, an independent research entity, led a multidisciplinary evaluation of the
interference between portable wireless devices and implanted cardiac pacemakers. Supported by the U.S. Food and Drug
Administration, WIRI recommends to physicians that:

W lets evaluation did not continy any risk to bystandars with pacemakers from other persons using wreess devices Electromagnetic fields (EMF). This VToch product compiles with all standards regarding electromagnetic fields (EMF) if handled properly and acc the instructions in links user's manual, the product it is also to be used based on scientific evidence available today.