Go to www.vtechphones.com to register your product for enhanced warranty support and the latest VTech

vtech

Quick start quide



For more support information



AI ⊚ DG V2 :tuqtuC

Daby unit and parent unit power adapters: Parent unit: 3.8V 2100mAh Lithium-ion battery Maximum power allowed by FCC and IC. Acrual operating range may vary according to environmental conditions at the time of use.

Reby unit: 24U5 - 24/5 MHz rensmit frequency TECHNICAL SPECIFICATIONS

Press @ to zoom in or out

VM818HD

Full Color HD Video Monitor

uld always be followed to reduce the risk of fire, ele-ck and injury, including the following: Follow all warnings and instructions marked on the product.

Adult setup is required. CAUTION: Do not install the baby unit at a height above 7 meters

his product is intended as an aid. It is not a substitute for esponsible and proper adult supervision and should not be sed as such.

Power adapter infor

Model: VTOsetunasuo

Rechargeable battery inform
Li-lon battery, 3.8V2100mAh
Zhongshan Tianmao Battery Co., Ltd.
Model Number: BP1763

Model Number: BPIX63
The power adapters are intended to be correctly o
in a vertical or floor mount position. The prongs are
designed to hold the plug in place if it is plugged i
realize under-the-table or cabinet outlet.

Unplug this product from the wall outlet before cleaning.
Do not use liquid or aerosol cleaners. Use a damp cloth for

Do not use liquid or aerosol cleaners. Use a damp cloth for cleaning.

Do not cut off the power adapters to replace them with other plugs, as this causes a hazardous situation.

Do not allow anything to rest on the power cords. Do not install this product where the cords may be walked on or crimped.

or place this product on an unstable table, shelf, stand her unstable surfaces. This product should not be placed in any area where proper ventilation is not provided. Slots and openings in the back or bottom of this product are provided for ventilation. To protect them from overheating, these

Never push objects of any kind into this product through
the close because they may touch depending unitaria.

IMPORTANT SAFFTY INSTRUCTIONS

unted.

To us broad be the be assert exception every time you turn to the property of the prop

.... Use and store the product at a temperature between 32°F and 104°F.


Do not expose the product to extreme cold, heat or direct sunlight. Do not put the product close to a heating

should not be exposed to excessive heat such as whine or fire

Warning-Strangulation Hazard-Children have STRANGLED in cords. Keep this cord out of the reach of children (more than 3 ft (Q-m) away). Do not remove this

telephones.
autions for users of implanted cardiac pacemakers
iliac pacemakers (applies only to digital cordiess device
sless Technology Research, LLC (WTR), an independer
srch entity, led a multidisciplinary evaluation of the
freence helytugen postable users/exresearch entity, led a muttidisciplinary evaluation of the interference between portable wireless devices and implanted cardiac pacemakers. Supported by the U.S. Food and Drug Administration. WTR recommends to investigate that

pacemaker, such as in a breast pocker, when it is turned C WTR's evaluation did not identify any risk to bystanders with pacemakers from other persons using wireless devices. Electromagnetic fields (EMF)
This VTech product compiles with all standards regarding electromagnetic fields (EMF). Handled properly and according to the instructions in this user's manual, the product is safe to be used based on scientific evidence available tool.





CONNECT THE BABY MONITOR

BNOTES

The rechargeable battery in the parent unit is built-i

Use only the power adapters supplied with this product.

Make sure the parent unit and the baby unit are not connected to the switch controlled electric outlets. Connect the power adapters in a vertical or floor mount position

Connect the power adapters in a vertical or floor mount position only. The adapter's prongs are not designed to hold the weight of the parent unit and the baby unit, so do not connect them to any ceiling, under-the-table, or cabinet outlets. Otherwise, the adapters may not properly connect to the outlets. Make sure the parent unit, the baby unit and the power adapter cords are out of reach of children.

To maintain compliance with the ECC's RF exposure quidelines place the haby unit at least 20cm from pearby person

OVERVIEW - BABY UNIT

Raise the parent unit antenna for better reception







CONNECT THE BABY MONITOR (CONT'D)

Charge the parent unit battery before use When you have connected and turned on the parent unit, the battery will be charged automatically.

■Notes

Before using the baby monitor for the first time, charge the parent unit battery for 12 hours. When the parent unit battery is fully charged, the battery icon becomes solid It takes longer to charge the hattery when

the parent unit is turned on. To shorten the charging time, turn the parent unit off while charging.
The standby time varies depending on the

sensitivity level you set, your actual use and the age of the battery.


The hattery icon indicates the hattery status (see the following table)

The screen displays
The collight flashes.
The collight flashes.
The collight flashes.
The collight flashes.
The battery has very little charge and may be used for only a short time.

Charge without interruption (about 30 minutes).

The battery icon becomes The battery is fully charged. To keep the battery charged, connect it to AC power when not in use.

POWER ON OR OFF THE BABY MONITOR



POSITIONING THE BABY MONITOR









0

0

The default volume of your parent unit is level 3, and the maximum volume is level 5. If you experience high-pitched screeching noise from your baby monitor while positioning:

Make sure your baby unit and parent unit are more than 3 feet (1 meter) apart, OR Lower the volume of your parent unit.



baby unit and parent unit, your parent unit displays image from the baby unit, and the LINK LED light turns on.


The green LED light of the baby unit turns on.



BASIC OPERATION - PARENT UNIT

Adjust speaker volume

Press -VOL / VOL+ to adjust your parent unit speaker volume. It determines the volume of sound transmitted from your baby unit.



Talk to your baby via the baby unit

Press and hold the TALK key.

 When the icon displays on screen, speak to your parent unit. Your voice is transmitted to the baby unit. 3. When finish talking, release

the TALK key and hear your baby again



You can turn on or off the parent unit

unit. You can still hear sound from the baby unit.

- Press POWER on the parent unit to
- Press any keys on the parent unit to turn on the screen again.



Turn on/off the parent unit screen

turn off the screen.



screen without powering off the parent



Hee the menu

Press MENU to enter the menu, choose a menu item, or save a setting. You can use the parent unit for advanced settings or operations, such as to play or stop the baby unit lullaby, or to adjust the baby unit sound sensitivity.



- Press ∧, ∨, <or> to scroll among the
- Press SELECT to select an item, or to save a setting.
- Press TALK to return to the live video
- Press to go to the Help & info page.



Overview - Parent unit



- LINK LED light COULED light
- 3- level sound indicator light
- TALK / 🕏 Press and hold to talk to the baby unit.
- When in the main menu, press to go to the Help & Info page.
- Arrow keys
- MENU/SELECT 11 POWER / LCD ON/OFF 12 Power jack
- 8 -VOL/VOL+ Increase or decrease parent unit's volume.

- 14 Antenna
- 10 Speaker



Infrared LEDs

9

- Camera lens Light sensor
- Microphone Night light
- Night light ON/OFF key
- 7 LED indicator
- 8 Power ON/OFF switch
- 9 Speaker 10 Antenna 11 Power jack
- - 14 Pair button

NEED HELP?

For operations and guides to help you using your video monito and for latest information and supports, go and check the online help topics and online FAQs.



Go to https://help.vtechphones.com/vm818hd; OR Scan the QR code on the right. Launch the camera app or QR code scanner app on your smartphone or tablet. Hold the device's camera up to the QR code and frame it. Tap the notification to trigger the redirection of the online help.

 If the QR code is not clearly displayed, adjust your camera's focus by moving your device closer or further away until it is clear. You can also call our Customer Support at 1 (800) 595-9511 [in US] or 1 (800) 267-7377 [in Canada] for help.

PARENT UNIT ICONS



- Temperature censor Position the sensor horizontally for its Optimal usage.

 CAUTION
 - Do not bend the temperature sensor

13 Threaded socket for wall mounting





Turn on/off Sound Detection Alert.

Turn on/off Motion Alert

 Select motion Sensitivity level. (See Motion Detection section)

Main menu icons Main menu

Monitoring mode (When paired with VM818-0HD only)




Baby unit 1 in Single mode



Patrol mode

12 Split mode

\$00°







· You can also set the timer to stop playing after 15, 30 or 60 minutes, or playing non



Select sound Sensitivity level.

 Turn on/off Auto Wake Up function. (See Sound Detection and Auto Wake Up

Main menu

Turn on/off Temperature Alert.

Set the parent unit to beep whenever the room temperature detected by the baby unit falls outside of the set temperature range.

Select Minimum temperature for aler range.

Select Maximum temperature for alert · Select temperature Format

Set temperature display in Fahrenheit (°F) or Celsius (°C).

 Adjust parent unit screen Brightness Turn on/off Dim Mode



General settings

0

 Turn on/off Night Light. Turn on/off baby unit's Status LED.

Adjust baby unit's speaker Volume.

 Turn on/off Low Battery Alert Tone Set the parent unit to beep whe battery is low. . Turn on/off No Link Alert Tone

Set the parent unit to beep when the link between the parent unit and the baby unit is lost.

Add Baby Unit Remove Baby Unit

Status icons

2.11

Current view status

The baby unit number that is being viewed when in: - Single CAM mode

Melodies or soothing

sound are turned on

Night light is turned

Parent unit speaker is

Battery status

- Patrol mode " When paired with VM818-0HD only). Split mode (* When paired with VM818-0HD only).

Split mode
(* When paired with
VM818-0HD only)

Patrol mode </ VM818-0HD only)


Sound detection

8 Temperature alert is turned on. Motion alert is turned 26°C Real-time

94











Baby unit detects temperature exceeds the set





Sound Detection and Auto Wake UP

Adjust sound detection sensitivity

You can turn on Sound Detection Alert and adjust the Sound Sensitivity to detect sounds and turn on the parent unit while its screen is switched off or dimmed

When the baby unit detects sounds that exceed certain levels, the parent unit screen will turn on and the baby unit starts transmitting the sounds to the parent unit, and you can

If you have turned on **Sound Detection Alert**, the parent unit beeps when the baby unit

Level 3 (Highest)	Level 2 (Medium)	Level 1 (Lowest)
9	2.000	2
The parent unit screen and speaker turn on for very small sounds, including background noises from your baby's room.	The parent unit screen and speaker turns on for loud babbling and louder sounds from your baby. The parent unit remains quiet when your baby makes soft sounds.	The parent unit screen and speaker turn on for loud crying or screeching sounds from your baby. The parent unit remains quiet when your baby makes soft sounds.

Sound activated screen and audio - Auto Wake Up

The parent unit screen stays off to save power when the baby unit does not detect sound.

not detect sound.
When Auto Wake Up is turned on, once the baby unit detects sounds that are louder than the chosen sound sensitivity level, the parent unit screen and speaker will turn on automatically. The parent unit then turns off again after 50 seconds of no sound detection.

■Notes

- If you have muted the parent unit speaker, only the parent unit screen will turn on when a sound is detected.
- will turn on when a sound is detected

 If you have turned on Auto Wake

 Up but turned off Sound Detection
 Alert, the parent unit will wake up
 when the baby unit detects sounds
 that are louder than the chosen sound
 sentitivity level

MOTION DETECTION

Adjust motion detection sensitivity

You can turn on Motion Alert and adjust the Motion Sensitivity to detect motions and turn on the parent unit while its screen is switched off or dimmed.

When the baby unit's camera detects motions that exceed certain levels, the parent unit screen will turn on and the baby unit starts transmitting sounds to the parent unit, and you can see and hear your baby

If you have turned on Motion Alert, the parent unit beeps when the baby unit detects

	Level 3 (Highest)	Level 2 (Medium)	Level 1 (Lowest)
	*	*	* *
DESCRIPTION	The parent unit screen and speaker turn on for small motions, such as yawning or stretching.	The parent unit screen and speaker turns on for normal daily motions, such as people walking around the house.	The parent unit screen and speaker turn on for large motions, such as children are chasing or jumping around.

NIGHT VISION



The baby unit has infrared LEDs that allow Ine bary unit has intrared LEUs in that allow you to see your baby clearly at night or in a dark room. When the baby unit being viewed detects low light levels, the infrared LEDs are switched on automatically. The images from the baby unit are in black and white, and % appears on the screen.

Notes

- It is normal to see a short white glare on you parent unit screen as the baby unit is adapting to the dark environment. When the infrared LEDs are on, it is normal for

8% Tip

Depending on the surroundings and other Depending on the surroundings and other interfering factors, like lighting, objects, colors and backgrounds, the video quality may vary. Adjust the baby unit's angle or place the baby unit at a higher elevation to prevent glare and blurry displays.

The parent unit display will dim to conserve energy after 5 minutes of inactivity, in



FOR PAIRING WITH VM818-0HD ONLY



Change different views - Single CAM
Select baby unit 1 1.41.41 Select baby unit 1 11 or baby unit 2 2 1 to

view the image from the baby unit. Change different views - Patrol

Select Patrol mode as your monitoring mode to alternately view the image from baby units 11 man 2 man every 10 seconds





Select Split mode as your monitoring mode to view the images from both baby units at once.

M Note

while in **Split mode**, you can press **<** or **>** to highlight the view of the baby unit 1 1 (1) or baby unit 2 (2) (1), and hear the sounds transmitted from the baby unit.

MOUNT THE BABY UNIT ON DRY WALL (OPTIONAL)

MOTES

- ita. Af the coult. Year many moned to more have the second and anothers consented at many at once habit contra
- a pencil to mark the top and the bottom holes as shown. Remove the wall mount bracket and drill two holes in the wall (7/32 inch drill bit).



- 2. If you drill the holes into a stud, go to step 3.
- If you drill the holes into an object other than a stud, insert the wall
 anchors into the holes. Tap gently on the ends with a hammer until the wall anchors are flush with the wall.

3. Align the wall mount bracket and screws with the holes in the wall as shown. Tighten the screw in the middle hole first, so that the wall mount bracket position is fixed. You can tighten the other screw in the top hole.

4. Place the baby unit on the wall mount bracket.

bottom to secure the baby unit

Tighten the screw into the threaded socket at the



3. Insert the screws into the holes and tighten the screws until only 1/4 inch



4. Place the baby unit on the wall mount bracket. Tighten the screw into the threaded socket at the bottom to secure the baby unit. Align the holes on the wall mount bracket with the screws on the wall, and slide the wall mount bracket down until it locks into place



5. You can maximize your baby unit's viewing angles by tilting the wall mount bracket Hold the baby unit, and then rotate the knob in anticlockwise direction. This will loosen the joint of the wall mount bracket. Tilt your baby unit up or down to adjust to your preferred angle. Then, rotate the knob in clockwise direction to fighten the joint and





$^{\mathrm{Q}_{\mathrm{s}_{\!A}}}$ Frequently asked questions Below are the questions most frequently asked about the baby monitor.

Why does the baby

Try the following (in the order listed) for common cure: Disconnect the power to the baby units and the parent unit.

2. Whilt a few seconds before connecting power back to the baby units and the parent unit.
3. Turn on the baby units and the parent unit.
4. Wait for the parent unit to synchronize with the baby units. Allow up to one minute for

Why don't the lights of the baby unit and parent unit shattery is depleted. Insert the appliance plug into the parent unit and put the adapter in a wall socket. The parent unit will establish connection with unit go on when I switch the baby unit.

Perhaps the parent unit's battery is depleted. Insert the appliance plug into the parent unit will establish connection with unit go on when I switch the baby unit.

Perhaps the parent unit's battery is depleted. Insert the appliance plug into the parent unit will establish connection with unit go on when I switch the baby unit.

Perhaps the baby unit is not connected to the power. Insert the app baby unit and put the adapter in a wall socket. Then, slide the $\mathfrak O$ **ON/OFF** to switch on the baby unit and to establish connection with the parent unit.

Make sure the power is not controlled by a wall switch. onnected to AC power?

Why is my screen in black
The screen is in black and white during night-time or in a dark room when the night vision feature is activated. This is normal. Why do I get glare or blurry display on my

During night-time or in a dark room, the surroundings and other interfering factors, like lightlings, objects, colors and backgrounds may affect the image quality on your parent unit screen. Adjust the baby unit's angle or place the baby unit at a higher level to

screen when viewing my baby at night? prevent glare and blurry display. Why does the baby The parent unit and baby units may be too close to each othe monitor produce a high-pitched noise?

 Move the parent unit away from the baby units until the noise stops; OR
 Turn down the volume of your parent unit. The baby units may be out of range. Move the parent unit closer to the baby units (but not less than 3 feet).

The parent unit may not have enough charge for the parent unit to perform norm Charge the battery in the parent unit until the battery icon becomes solid

The temperature of your baby's room may be too high or too low. Why don't I hear a round / The parent unit meaker volume may be too low. Press VOI + to increase the w

The baby units may be out of range. Move the parent unit closer to the baby units (but not less than 3 feet).

If you power on only one baby unit, your parent unit may display Make sure baby unit X is on or move closer to baby unit X, and the LINK LED light flashes. Switch to the baby unit

THE RBRC SEAL

The RBBC seal on the lithium-ion battery indicates that VTech Communications, inc. is voluntarily participating in an industry program to collect and recycle these batteries at the end of their useful lives, when taken out of service within the United States and Canada.

The program provides a convenient alternative to placing used lithium-ion batteries into the trash or municipal water, which may be littlegal in your area.

The RRRC Seal and 1 (800) 8 RATTERY® are registered trademarks of California Inc.

FCC AND IC REGULATIONS

test 15 augment has been tested and found to comply with the requirements for a Class B digital device under Part 15 of the air Communications Commission (ECF of Jules. These requirements are intended to provide reasonable protection significant for the provider reasonable protection significant to the provider reasonable provider reasonable reason

Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
 Connect the deeler or an experienced radioff VI scholina for help.
 WARNING: Change or modifications to this equipment not expressly approved by the party responsible for compliance could void the user's sulthority to operate the equipment.

This Class B digital apparatus complies with Canadian requirement: CAN ICES-3 (B)/NMB-3(B)

Industry Canada

erm "IC." before the certification/registration number only signifies that the Industry Canada technical specifications were roduct meets the applicable Innovation, Science and Economic Development Canada technical specifications

RF radiation exposure statement

CALIFORNIA ENERGY COMMISSION BATTERY CHARGING TESTING MODE

This baby monitor meets the California Energy Commission (CEC) regulations for energy consumption. Your baby monitor is set up to comply with the energy-conserving standards right out of the box. Follow the instructions to install and charged the battery. The CEC battery charging resides made is activated while charging, be wift the parent unit is paired to baby units, the CEC battery charging testing mode is activated while it is powered off and charging.

FOR CETL COMPLIANCE ONLY

Mesures de sécurité importantes La plaque signalétique appliquée est située au bas du socie de l'unite du bébé.

Observez toutes les instructions et mises en garde inscrites sur

l'appareil. L'installation par un adulte est requise. MISE EN GARDE: N'installez pas l'unité du bébé à une hauteur

supérieure à 2 mètres.

Ce produit à été concu pour être un dispositif d'appoint soulement. Il river pas le remplacement d'une supérvision responsable et adéquate par un adute et ne devrait pas être utilité comme séle.

Congrue de la conque pour être utilisé en tant que monitour médical.

Nutilisée na ces secondes d'actives de la conque pour être utilisé en tant que monitour médical.

moniteur médical. Nutilisez pas cet appareil près de l'eau ni de toute autre source d'humidité, par exemple, près d'une balgnoire, cuve à lessive, évier de cuisine, dans un sous-soi humide ni près d'une piscine, dans un soussoi humide ou une douché. allowers, the way of the un source hamide or une obuline. MMSE DI AGROS Utilized in unement by pile forum. Un riscuse d'oraction pourrait survenir is un maurait type de joil est utilisé pour l'unité du pracer. La pile ne peut just site sources à des températures entrêmes élevées ou basses et à une fabble presson d'air à haute affinde pendant fullification, pur l'acceptant de l'acceptant de l'acceptant de seu ou dans un four c'hadd ou l'écrarement ou le discoupage eu ou dans un four de l'aute de l'aute eu ou de l'aute de l'aute de l'aute eu ou de l'aute de l'aute eu ou de l'aute de l'aute eu ou de l'aute de l'aute eu d'aute eu d'aute l'entreposage ou le transport. L'élimination de la pile dans le feu ou dans un four chaud, ou l'écrasement ou le découpag mécanique de la pile peuvent entraîner une explosion. Laiss la pile dans un environnement à température extrêmement élevée peut entraîner une explosion ou la fuite d'un l'ajudie

ou d'un gaz inflammable. Une pile soumise à une pression d'air exfrêmement basse peut provequer une explission ou une fuite de liquide ou de gaz inflammable. Eliminer la pile usagée conformément inflammable. Eliminer la pile usagée conformément aux informations du Sceau RBR.

Informations sur les adapta
Sortie: 5 V CC 1000mA.
VTech Telecommunications Ltd.

Modèle: VTOSEUSUS:200

Modèle: VTOSEUSUS:200

Modèle: VTOSEUSUS:200

Informations sur les piles rechargeables: 3,8V 2100mAh Lithium-ion han Tianmao battery Co. Ltd.

Lorsqu'ils sont branchés dans une prise de courant, les adaptateurs secteur ont été concus pour être orientés

dans une prise au plafond, sous une table ou dans un meubl Pour les PRODUITS À BRANCHER À UNE PRISE DE COURAN la prise de courant doit être installée près du produit afin

aerosos. Unisez un chimon numide pour le nemoyer. Débranchez les cordons d'alimentation avant de remplacer le bloc-piles. Ne coupez pas les cordons d'alimentation pour remplacer les fiches; de riest pour mésonter un danner intentiel

Ne laissez aucun objet reposer ni appuyer sur le cordon d'alimentation. N'inétallez pas cet appareil dans un endroit où l'on risque d'écraser le cordon d'alimentation ou de le

ou for registro dictions in detector authernmentor to pre-pletinar. Ne fallise fonctionner cet appareill guilvec le type d'allimentation indiqué sur l'étiquette. Si vous ne consain d'allimentation indiqué sur l'étiquette. Si vous ne consain d'allimentation indiqué sur l'étiquette. Si vous ne consain d'allimentation de l'acceptance de l'acceptance de l'acceptance d'acceptance de l'acceptance de l'acceptance de l'acceptance l'acceptance de l'acceptance de l'acceptance l'acceptance de l'acceptance de l'acceptance l

rallonges electriques.

Ne places pas cei apparell sur un chariot, meuble, trépied, support de montage in table chancolants.

Les trous et ouvertures du beilter, situés à l'arrière de l'apparell ou sous coluird, servent à adrer l'apparell. Pour l'empêcher de surchauffra, ne bloques sout àucun priteur. Les trous et ouvertures du boîtier, situés à l'arrière de l'appareil ou sous celui-ci, servent à aérier l'appareil. Pour l'empôcher de surchauffer, ne bloquez sous àucun prétext ces ouvertures et n'empôchez pas l'aération adéquate de l'annareil en le nairant sur un lit d'ayan tants ou troi de autre

SL.

produit.

Afin de réduire les risques d'électrocution, ne démontez pas cet appareil, mais apportez-le dans un centre de service autorisé. L'ouverture du boîtier ou le retrait de toutes pièces

segmentage incomerci pour plare la sulta protective dels risques in your deprise travels incompress designed chaques de rolle est a service antique a protective de la compression de silva de verifier di celles ci na sorti compression de la compression del compression de la compression de la compression de la compr

Mises en garde

1. Utilisez et entreposez le produit à une température entre 0 ° C
(32 ° F) et 40 ° C (304 ° F). d'exposez pas cet appareil à des froids ou des chaleurs extrêmes, ainsi qu'à la lumière directe du soleil. Ne l'installez sas près d'une source de chauffage.

Le bloc-piles ne doit pas être exposé à la chaleur excessive telle que la lumière du soleil ou àu feu.

tello quida l'aumière du solati ou du feu.

Avertissement - Biscaue de strangulation condom. Service de condom la co D'autres équipements électroniques peuvent produire des interférences sur votre moniteur vidéo et audio. Tentez distribler entre moniteur vidéo ou audio à l'écratique audio.

électroniques tels que des routeurs sans fil, radios, téléphon cellulaires, interphones, moniteurs, téléphones, ordinateurs personale, électroméraneurs et téléphones par fil

Simulateurs cardiaques implantes dans forganisme Las simulateurs cardiaques implantes dans forganisme Las simulateurs cardiaques (ne s'applique qu'aux dispositifs numériques sans fil): L'organisme "Mireless Tochnology Research, LLC (WTR); une time de recherche Indépendante, a mené une evisuation pluridisciplinaire des interférences entre les téléphones sans fil portants de las stimulateurs cardiaques implantes dans froramis contatts et las stimulateurs cardiaques implantes dans froramis pluridisciplinaire des interférences entre les téléphones sans fil portaifs et les stimulateurs cardiaques implantés dans l'organiss Appuyée par l'Administration des aliments et droques (FDA) de Etats-Unis, la firme WTR recommande aux médicins:

Etats-Unix, la firmo VITR recommande aux médicidris.

Avis aux détenturs de stimulaturus cardiaques

Vous devier maintenir ets dispositifs sant fill à au moints six

Is no dévieur PAS placer le biléphone sans fill d'inrechement sur le fimulateur cardiaque, tel quie dans une poche de chemise, forcague calul et et et nimanzius, cardiaque, tel quie dans une poche de chemise, forcague calul et et et nimanzius.

NENT PAS de la comment de cardiaque que pour les détentes de l'expecte pour les détentes de simulateurs cardiaques causés par les gens qui utilisent dispositis sans fil a promitté de causer.

Champs électromagnétiques (EMF)
Ce produit de VTech est conforme à toutes les normes se rannortant aux champs électromagnétiques (EMF) standard

LIMITED WARRANTY

What does this limited warranty cover?

wast oos the limited warranty cover?

The manufacture of his VI fich Product warrants to the holder of a valid proof of purchase ("Consumer" or "you") that the Product and all accessories provided in the sales package ("Product") are free from defects in material and workmanship, pursuant to the following terms and workmanship, pursuant to the following terms and workmanship, pursuant to the following terms and in the product operating instructions. This limited warranty settends only to the Consumer for Product purchased and used in the United States of America and Canada.

Canada. What will Visch do if the Product is not free from defects in materials and workmanking during the limited warranty has been as the product in materials and workmanking during the limited warranty bronds. Uncleich a sunderside service in presentative will require or replace at Visch's opportunities of the Product, we many product and the Product, we may be replaced to the Product, as we may be replaced to the Product of the Pr

How long is the limited warranty period? How long is the immere warrany period. The himsted warrany period of the Product extends for ONE (1) FEAR from the date of purchase. If VTech repairs or options as Martinghi Deletiche Product under the terms of replaces a Martinghi Deletiche Product under the terms of replaces or replaces and the state of repairs of the product for a partial of either (a) of days from the date the repaired or replacement Product for a partial of either (a) of days from the date the repaired or replacement Product is shipped to you or (b) the time remaining on the original one-year warrany; whichever is longer.

What is not covered by this limited warranty?

This limited warranty does not cover Product that has been subjected to misuse, accident. shipping or other physical damage, improper installation, abnormal operation or handling, neglect, inundation, fire, water or other liquid intrusion; or

Product that has been damaged due to repair, alteration or modification by anyone other than an authorized service representative of VTech; or

service representative or viecn; or Product to the extent that the problem experienced is caused by signal conditions, network reliability, or cable or antenna systems; or Product to the extent that the problem is caused by use with non-VTech accessories: or

with non-VTech accessories; or 5. Product whose warranty/quality stickers, product serial number plates or electronic serial numbers have been removed, aftered or rendered illegible; or Product purchased, used, serviced, or shipped for repair from outside the United States of America or Canada, or used for commercial or institutional purposes (including but not limited to Products used for rental purposes); or Product returned without a valid proof of purchase (see item 2 below); or

Charges for installation or set up, adjustment of customer controls, and installation or repair of systems outside the unit

To obtain warranty service in the USA, please visit our website at www.vtechphones.com.or.call 1 (800) 595-9511 NOTE: Before calling for service, please review the user's manual - a check of the Product's controls and features may save you a service call

Save you a service can.

Except as provided by applicable law, you assume the risk of loss or damage during transit and transportation and are responsible for delivery or handling charges incurred in the transport of the Product(s) to the service location. Vitech

this limited warranty, or proof of purchase does not meet the terms of this limited warranty, VTech will notify you and will request that you authorise the cost of repair pior to any further repair activity. You must pay for the cost of repair an return shipping costs for the repair of Products that are not covered by this limited warranty.

What must you return with the Product to get warranty

- Return the entire original package and contents includ the Product to the VTech service location along with a description of the malfunction or difficulty; and
- Include a "valid proof of purchase" (sales receipt) identifying the Product purchased (Product model) and the date of purchase or receipt; and

Other limitations:

This warranty is the complete and exclusive agreement between you and Virech. It superredes all other written to accommunitations related to the Product. Virech provides on a communitation related to the Product. Virech provides by describes all of Virech's responsibilities regarding the Product. These are no other express warranties. Not one is authorized to make modifications to this limited warranty and you should not rely on any such modifications. State (Provincial Law Rights: This warranty gives you specific legal right, and you may do have defer right, which way from state to state when the product may be compared to the product of the product of

or province to province.

Limitations: Implied warranties, including those of fitness for a particular purpose and merchantability (an unwritten warranty that the Product is fit for ordinary use) are limited to one year from the date of purchase. Some state provinces do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you warranty lasts, so the above limitation may not apply to by in no event shall Viech be lable for any inclined, special, inclidental, consequential, or similar damages (including, the Product or other associated equipment, the cold for substitute equipment, and claims by third parties) restrict from the use of this Product. Some states/provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion.

nay not apply to you Please retain your original sales receipt as proof of purchase.

DISCLAIMER AND LIMITATION OF LIABILITY

VTech Communications, Inc. and its suppliers assume no responsibility for any damage or loss resulting from the use of this user's manual. VTech Communications, Inc. and its suppliers assume no responsibility for any loss or claims by third parties that may arise through the use of this product.

Company: VTech Communications. Inc.

Address: 9020 SW Washington Square Road - Ste 555 Tigard, OR 97223, United States Phone: 1 (800) 595-9511 in the U.S. or 1 (800) 267-7377 in Canada