印刷提醒您

務必請後續使用檔案人員和您對稿打樣確認無誤後,再進行印刷 以免後續若有印刷成品上的爭議,可染設計概難負責,敬請注意

刀模尺寸提醒您

務必請貴司配合之廠商和您核對尺寸打樣確認無誤後,再進行印刷 以免後續若有印刷成品上的爭議,可染設計概難負責,敬請注意

VS-1880

完成尺寸: 8.5X8.5cm 單色雙面印刷

8.5cm ____

Step 3 : Connect to the mini amplifier When pairing is successful, the red/blue indicator will turn off. Then, green LED dim each 5 seconds.

If pairing can not be finished in a period of time (approx. 2 minutes), Ampio M2

will return to standby mode. You may need to repeat step 1 to step 3 until pairing

If the Bluetooth device is Bluetooth stereo audio supported(with A2DP profile), you can listen to music with Ampio M2. You may adjust the volume by pressing the Volume Up(+) or Volume Down(-) button.

Volume cypy of worker bowney bounds.

If the Bluetooth device is ANRCP profile supported as well, you may control music playback by short pressing MFE → 1 · For Play / Pause.

Long press the Volume Up(+) for 3 seconds for music track forward.

Long press the Volume Down(-) for 3 seconds for music track backward.

5.Making a call

Using the phone keys to make a call

Dial the number on the smart phone as you normally do. Once the call has been set up, the sound will be transmitted to Ampio M2 automatically.

Double press MFB • I▶ to initiate voice dial function of mobile phone.

Long Press MFB • • I• of Ampio M2 for 3 seconds to initiate last dial number function of mobile phone.

- When Ampio M2 is powered on, and there is an incoming call, you will hear a ring tone.

 When the ring tone is heard, short press the MFB ••• to answer the call.

By Long pressing MFB ♠ • I► for 3 seconds when there's an incoming, it will reject the incoming call.

Regulatory Compliance

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions :

- This device may not cause harmful interference, and
- This device must accept any interference received, including interference that may cause undesired operation.

FCC Certification

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmly interference to radio communications. However, there is no guarantee that interference with not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna

- Increase the separation between the equipment and receiver.

 Connect the equipment into an outlet on a circuit different from that to which the
- Consult the dealer or an experienced radio/TV technician for help Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

摺頁示意圖

Declaration of Conformity

Hereby, Vencer Co., Ltd. declares that this product is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC.




經型式認證合格之低功率射頻電機,非經許可,公司、商號或使用均不得擅 自變更頻率、加大功率或變更原設計之特性及功能。

低功率射頻電機之使用不得影響飛航安全及干擾合法通信;經發現有干擾 現象時,應立即停用,並改善至無干擾時方得繼續使用。前項合法通信,指依 電信法規定作業之無線電通信。低功率射頻電機須忍受合法通信或工業、科 學及醫療用電波輻射性電機設備之干擾。

Headphone Mini Amplifier

封面


Ampio M2 VS-1880



The Headphone Mini Amplifier which is developed with the latest Bluetooth technology can connect to other Bluetooth devices such as mobile phones, desktops, laptops and PDAs with HSP or HFP(for voice) or A2D P(for music) profile supported



Getting Started



Buttons

| Current Status | Previous Status | | |
|--|---|--|--|
| Power on | Power off | Slide the button to on position | |
| Power off | Power on standby | Slide the button to on position | |
| Pairing | Power on standby | Long Press MFB 	• I▶ 3 second: | |
| Accept a call/End a callStart Music/Stop Music | Incoming call/Active call Music play/Music pause | Short press MFB 	• ▶ | |
| Reject a call | Incoming call | Press MFB 	• ► 3 seconds | |
| Reject a call | Connected Standby | Press MFB 	• ► 3 seconds | |
| Mute | Active call | Short press Volume Up(+)& down(-) button simultaneously | |
| Volume Up | Active call/music | Short press Volume Up(+) button | |
| Volume Down | Active call/music | Short press Volume down(-) button | |
| Next (Music Track Forward) | Music play | Long press Volume Up(+) for 3 seconds | |
| Previous(Music Track Backward) | Music play | Long press (-) Volume down(-) for 3 seconds | |
| Reset Pairing List | Power on standby | Long press Volume Up(+)& Down(-) 6 seconds | |

LEDs

| Status | Blue LED | Green LED | Red LED | Voice Prompt |
|-----------------------|------------------------|-------------------|---------------|------------------------------|
| Power on | Flash once | _ | _ | Power on |
| Power off | - | - | Flash once | Power off |
| Pairing | Quickly Flash | _ | Quickly Flash | Pairing |
| Connected | - | Dim/ 5 seconds | - | Your headset is connected |
| Disconnected | 2 times / 5 seconds | (— () | - | Your headset is disconnected |
| A2DP streaming | 3-4 | Dim/5 seconds | - | - |
| HFP on call | Dim/5 sec | 1-1 | 5-5 | _ |
| Pairing Successful | ,— i | | _ | Paired |
| Pairing failed | | _ | - | Unsuccessful |
| Reset Pairing | Flash 2 times | - | Flash 2 times | - |
| Charging | - | - | On | - |
| Charging completed | On | - | - | = |

1.Charging Battery and playing music from USB

The mini amplifier comes with a built-in rechargeable battery. The battery is not fully charged when it is new. Plug the charging cable to micro USB and the red LED indicator on the mini amplifier will light on.

When the battery is fully charged, the red LED indicator will be turned off.

When the backey is ruley traigled, in the label manager and charging cable to connect with a laptop and Ampio MZ. The laptop installs the appropriate USB audio driver automatically to eet up. Ampio MZ are a sound card. The audio device "Ampio MZ" will be shown in the laptop after configuration is successful.

You may select the music from the laptop to be played. Green LED remains on when music streaming.

2.Turning the Mini Amplifier On or Off

- -To turn the mini amplifier on :
 Turn the On/Off switch to On oposition, and blue LED indicator of Ampio
 M2 flashes once to turn Ampio M2 on.
 -To turn the mini amplifier off :
 Turn the On/Off switch to off position, and then red LED indicator of the
 Ampio M2 flashes once to turn Ampio M2 off.

You are required to pair Ampio M2 with your Bluetooth smart phone/audio device/PC/PDA before using the mini amplifier.

Step 1 : Turn on the mini amplifier. Hold and keep pressing the S1 button for 3 seconds until the blue and the red LED indicator flash alternatively. The headset is now

Step 2: Initiate pairing process on your Bluetooth smart phone/Audio Device/PC/PDA to pair with Ampio M2. After searching, you can find the device name "Ampio M2.

CU

വ

 ∞