

NMP-550

NETWORK MEDIA PLAYER

SMIL-Compatible Network Media Player

ViewSonic's NMP-550 Network Media Player supports a full range of media formats and SMIL-enabled applications. It's IP-enabled and includes Signage Manager Express software so you can remotely control, schedule and manage multiple devices from virtually anywhere. Download content during non-peak hours and store on the 4GB of local storage. You can also locally upload content via the USB port and have it automatically play back. The small form factor is still powerful enough to deliver smooth playback of up to Full HD 1080p digital video. The NMP-550 is equipped to handle many layers of high-quality graphics, text, and video and is a cost-effective solution because you don't need a PC at each display.



- > Easy audio and video streaming with content-rich video and graphics
- > SMIL-compatible media player
- > 4GB local storage
- > Upload new content via Ethernet or USB
- > Lower total cost of ownership (TCO)
- > Network ready for easy installation
- > Signage Manager Express software included

NMP-550 NETWORK MEDIA PLAYER






Upload and automatically play content via the USB port.



ViewSonic® recommends our commercial displays, open frame display or any ViewSonic large screen LCD or LCD TV and the included Signage Manager Express software for use with the NMP-550 to give you the best possible digital signage results.

OPERATING SYSTEM	Linux
SUPPORTING PROTOCOLS	TCP/IP, HTTP
INSTALLED SOFTWARE	I-SMIL, player
NETWORK MANAGEMENT	Signage Manager Express
CONNECTORS	10/100 Ethernet, RCA audio
DISPLAY	HDMI, VGA
AUDIO	RCA stereo analog
NETWORK	10/100 Ethernet
USB	USB (x1)
DECODING	Video MPEG-1, 2, 4; H.264, VC-1 Audio MPEG-1 (layers 1 & 2), MP3
STREAMING PROTOCOL	Types HTTP, local file playback
RESOLUTIONS	640x480, 800x600, 1024x768, 1280x1024, 1280x768, 1366x768, 1920x1080
IMAGE FILE	Formats JPEG, PNG
SCANNING FORMAT	SDTV 480i, EDTV 480p, HDTV 720p, 1080p
SCREEN ROTATION	Landscape, portrait (+90°, -90°)
POWER	DC 12V (max), 100-240V AC
OPERATING CONDITIONS	Temperature 50°-104°F (10°-40°C) Humidity 20-85% (non-condensing)
DIMENSIONS (W x H x D)	Physical 8.3" x 6.0" x 1.9" (211mm x 153mm x 43mm)
WEIGHT	Net 2.5 lb. (1.1 kg)
REGULATIONS	UL, cUL, FCC (Class A/B), TUV, CCC, CE, LVDS, CB, BSMI, CISPR, RoHS
PACKAGE CONTENTS	Media player, AC adapter, Ethernet cable, audio cable, mounting bracket, Quick Start Guide, User Guide on CD, Signage Manager Express CD
WARRANTY	One-year limited warranty on parts and labor.

	ViewSonic Digital Signage Software Partners	Recommended Network Media Player
1:1	 Intelligent solutions for friendly communication	NMP-610
1:50 (LAN)		NMP-530
100+ (WAN)	Signage Manager Express	NMP-550
Offsite Hosted		NMP-600 NMP-610



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968



ViewSonic Corporation's OMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2011 ViewSonic Corporation. All rights reserved. [15700-00B-05/11] NMP-550-1

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com