

# Titan 15



TITAN 15 User's Manual



**2-WAY PROFESSIONAL  
PASSIVE LOUDSPEAKER**

[www.wharfedalepro.com](http://www.wharfedalepro.com)



# Titan 15

## U S E R ' S M A N U A L

Titan 15 is the latest innovation from Wharfedale Pro. A high performance passive speaker system designed around your needs. High output, punchy low end and extended high frequency response that's equally at home with music and speech. An ultra-lightweight composite enclosure that's designed to be stand mounted, arrayed or even used as a floor monitor. Compact, lightweight and affordable, the Titan 15 still packs professional drivers that deliver unmatched performance.





## TITAN 15 2-way Portable, Passive Loudspeaker

### Warnings & Safety Instructions

1. **READ ALL INSTRUCTIONS** carefully and become familiar with the features and functions of this product before operating it.
2. **RETAIN THESE INSTRUCTIONS** for future reference.
3. **COMPLY WITH ALL WARNINGS** – All warnings and instructions for this product should be adhered to.
4. **USE WITH AMPLIFIERS** – In order to avoid damage to drivers and other equipment, it is advisable to establish and follow a routine for powering up and powering down a sound system. With all system components connected, turn on source equipment (mixers, signal processors, record and playback units, etc.) BEFORE powering up amplifiers. Transient voltages from powering up source equipment can damage speakers if amplifiers are turned on when these sources are powered up. Make sure that amplifier volumes are set to their minimum settings and power up any system amplifiers LAST. It is recommended that all system components be allowed to stabilize for several seconds before any source signals are introduced or level setting adjustments are made.

Similarly, when shutting systems down, turn all amplifiers off first, before powering down any other system components.

5. **CABLES** – Do not use shielded or microphone cables for connection between amplifiers and speakers. Use only approved speaker cables with proper connectors.
6. **RIGGING – SUSPENDING – MOUNTING** – Rigging, suspending and mounting of this speaker system can expose members of the public to serious health and risks and even death. **UNDER NO CIRCUMSTANCES ATTEMPT TO RIG, SUSPEND OR OTHERWISE MOUNT THIS SYSTEM UNLESS YOU ARE FULLY QUALIFIED AND CERTIFIED TO DO SO BY RELEVANT LOCAL, STATE AND NATIONAL AUTHORITIES. ALL RELEVANT SAFETY REGULATIONS MUST BE FOLLOWED. IF YOU ARE NOT PROPERLY QUALIFIED OR DO NOT KNOW OF PERTINENT REGULATIONS, CONSULT QUALIFIED PERSONNEL FOR ADVICE.**
7. **CAUTION** – These professional loudspeaker systems are capable of generating very high sound pressure levels. Use care with placement and operation to avoid exposure to excessive volume levels that can cause permanent hearing damage if operated to extremes.
8. **SERVICE** – There are no user serviceable parts inside this product. Users should not attempt to service this product. Warranty nullification could result if this is attempted.

## Thank you for purchasing the Wharfedale Pro TITAN 15!

The TITAN 15 is a new addition to our Titan Series which is based on our popular TITAN 12 model. The TITAN 15 offers superior acoustical voicing and new drivers that provide a smooth high end response and a punchy, tight low end bass response in a portable composite enclosure.

### Features:

- + Custom designed, heavy duty 15" low frequency driver
- + 2" titanium high frequency compression driver
- + 90 x 60 degree integral Elliptical Wave Guide for even high frequency dispersion
- + Built in Linkwitz-Riley crossover at 1.8kHz
- + DTF™ Dynamic Thermal Filament – Integral High-Frequency Driver  
Overload protection
- + Design for a wide variety of sound reinforcement applications
- + Built in, rubberized easy-grip handles for convenient transportation
- + Integral pole mount adapter for stand mounting
- + Trapezoidal shape for vertical arrays and horizontal stage monitor use
- + Top stacking feature for easy integration of multiple enclosures
- + Ten M8 threaded rigging inserts for several hang-mount options
- + Bottom mounted M8 threaded inserts that fit the OmniMount® 60.0 footprint
- + Injection molded enclosure construction
- + Integral cord wrap and cable anchor molded into the enclosure
- + NL4 input connectors

### Operation

The TITAN 15 is a passive, two-way, speaker system that provides an 8 ohm impedance load, per enclosure, to each output channel of the system power amplifier. Multiple TITAN 15 enclosures can be “daisy-chained”, in parallel, with the impedance load dropping in half with each additional enclosure. In other words, two TITAN 15 enclosures, connected in parallel, will provide a 4 Ohm impedance load. Like wise, three TITAN 15 enclosures connected in parallel will provide a 2 ohm impedance load to the amplifier. Be aware that some amplifiers are not designed to accept loads as low as 2 ohms and loads this low can result in decreased performance and overheating of the amplifier and can cause damage



to amplifier electronics. Consult the manufacturers operating manual for the amplifier before connecting multiple speakers together.

The HIGH FREQUENCY EQ switch provides a 3dB boost to the high frequency driver for long throw applications. Switch selections are “BOOST” (3dB increase) and “FLAT” (no increase).

## Connections

The TITAN 12 PRO input connections from the output of the amplifier will be via 1/4” phone jacks or Speakon® NL4 connectors that are located on the rear mounted input plate. NL4 connector pin wiring is configured as follows:

+1 = Positive

-1 = Negative

## Optional Accessories

- + **Wall mount bracket** – Enables surface mounting with pan and tilt positioning for fixed installations
- + **Titan Tour Bag** – Ballistic nylon zippered carrying bag with storage pocket for cables.





## TITAN 15 Specifications

<b>Loudspeaker Type:</b>	15" 2-way
<b>Frequency Response +/-3dB:</b>	50–18KHz
<b>Sensitivity 1W@1M:</b>	97dB
<b>High Frequency Coverage (H x V):</b>	90° x 60°
<b>Peak SPL:</b>	129dB
<b>System Impedance:</b>	8 ohm

### POWER HANDLING CAPABILITY (watts)

<b>Continuous:</b>	400W
<b>Music:</b>	800W
<b>Peak:</b>	1600W

### LOW FREQUENCY DRIVER

<b>Size (mm / inches):</b>	381mm / 15"
<b>Coil Size (mm / inches):</b>	75mm / 3"

### HIGH FREQUENCY DRIVER

<b>Type:</b>	Compression Driver
<b>Coil Size (mm / Inches):</b>	51mm / 2"
<b>Exit Size (mm / inches):</b>	25mm / 1"
<b>Diaphragm Material:</b>	Titanium
<b>High Frequency Driver Protection:</b>	DTF™- Dynamic Thermal Filament (2 x SK3 Bulb)

### HIGH FREQUENCY HORN

<b>Type:</b>	EWG™-Elliptical Wave Guide
<b>Throat Size (inches):</b>	25mm / 1"

### CROSSOVER

<b>Type:</b>	2-way
<b>Frequency / Filter:</b>	1.8kHz/12dB per oct.

### ENCLOSURE

<b>Shape:</b>	Trapezoidal for vertical array and horizontal stage monitor applications
<b>Material:</b>	Molded polypropylene
<b>Rigging / Bracket Options:</b>	+ (10) M8 threaded rigging points for safe flown applications + (4) M8 threaded inserts on bottom in Omnimount 60.0-type footprint + Pole-mount receptacle with lock screw + Optional wall-mount bracket

### CONNECTIONS

<b>Rear Panel Input Connectors:</b>	(2) NL4 connectors (parallel)
<b>Net Weight (kg / lbs.):</b>	22kg / 48.4 lbs.
<b>Gross Weight (kg / lbs.):</b>	25kg / 55 lbs.
<b>Dimensions (H x W x D):</b>	708.3 x 477.8 x 401.77mm / 27.9" x 18.8" x 15.8"

**\*Features, details and specifications subject to change without notice**







## **THE WHARFEDALE PRO ADVANTAGE**

While other companies increasingly out-source manufacturing, we continue to add to our factory; already at 1.5 million square feet in size. That's because at Wharfedale Pro we design, engineer, tool and manufacture each and every component that goes into our speaker systems. All of which helps explain how we can pack so much technology, performance and quality into our products at an incredibly low cost. Recognized since 1932 as a pioneering brand, Wharfedale Pro is now part of the International Audio Group with operations and distribution worldwide. Our mission remains to design and build the very best Pro Audio gear possible, with great technologies, abundant features and unmatched quality at the very lowest possible cost. That's the Wharfedale Pro advantage!





## UNPACKING

All Wharfedale Pro products are fully checked before leaving the factory. After unpacking please inspect cabinets for any physical damage. Please retain the shipping carton if possible and internal packing material in case the unit needs to be returned. Please check as soon as possible that the unit is functioning. In the event of any damage, please contact your dealer immediately.

## WHARFEDALE PRO LIMITED WARRANTY \*

Wharfedale Titan loudspeaker systems are warranted to be clear of manufacturing or materials defects for a period of one year from the original date of purchase. In the event of malfunction, contact your authorized Wharfedale Professional dealer or distributor for information.

\* Be aware that warranty details may differ from country to country. Contact your dealer or distributor for information. These terms do not infringe your statutory rights.

**\* Details and specifications subject to change without notice.**

© 2006 Wharfedale Pro is a member of the International Audio Group .  
IAG House, Sovereign Court, Ermine Business Park, Huntingdon, Cambridgeshire, PE29 6XU

### WHARFEDALE PRO [USA]

ph: +1.877.440.0888  
ph: +1.425.861.3909  
fx: +1.425.861.3906

### WHARFEDALE PRO [UK]

ph: +44 (0) 845 4580011  
ph: +44 (0) 1480 447700  
fx: +44 (0) 1480 431767

### WHARFEDALE PRO [GERMANY]

ph: +49 (0) 2161-61783-0  
fx: +49 (0) 2161-6178350

### WHARFEDALE PRO [INT.]

ph: +86 (0) 755 8209 6639  
fx: +86 (0) 755 8209 0203

[www.wharfedalepro.com](http://www.wharfedalepro.com)