NEUTRON EMC LAI

FCC ID: NW7M5I

Attachment

User's Manual

WARNING

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver in connected.
- Consult the dealer or an experienced radio / TV technician for technician for help.

Notice:

- (1) A Unshielded-type power cord is required in order to meet FCC emission limits and also to prevent interference to the nearby radio and television reception. It is essential that only the supplied power cord by used.
- (2) Use only shielded cables to connect I/O devices to this equipment.
- (3) Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

MUO5I Users Manual

Model No.: MUO5I series.

Description: 2 keys 420 DPI Printed Mouse, PS/2 and Serial Mouse integrated.

Cable: 5 feet in length with Mini-DIN 6 pin connector.

PS/2 Mode: Direct connect to PC's PS/2 mouse port.

MS Serial Mode: Use a Mini-DIN 6F to DB-9F adapter to connect PC's COM

port.

Oscillator frequency: 32768 Hz.

Power Consumption:

PS/2 mode: Maximum 75 mW, 15 mA at 5V DC.

MS mode: Maximum 120 mW, 10 mA at 12V DC

Hardware Resolution up to 420 DPI.

Optical / Mechanical Interrupt Wheel design for smooth tracking pickups.

None-toxic and fancy cartoon picture printed.