

Xerox[®] Color C60/C70 Printer Color Multifunction Printer

To interactively build and configure your own Xerox[®] Color C60/C70, please visit **www.buildyourownxerox.com**.





nd-white		
ppm		
) ppm) ppm ; ppm , ppm		
/ ppm ppm ppm / ppm		
; ppm ; ppm ; ppm ; ppm ; ppm		
nd-white		
i ipm 35 sheets Ite		
' ppm I 8 sheets ite		
Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis). ¹		
10,000 to 50,000 pages per month ²		
Xerox® EA toner with Ultra Low Melt Technology (2400 x 2400 dots per inch)		
International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan		
)) 2 3 3 1 1 1 1 1 1		

Accessories			
	Offcot Catch Travi		
Accessories Optionαl	Offset Catch Tray High Capacity Feeder (A4) 1 Tray Oversized High Capacity Feeder with Storage Bin 2 Tray Oversized High Capacity Feeder Interface Module BR Finisher (includes Vertical Transport Kit) BR Booklet Maker Finisher (includes Vertical Transport Kit) C Fold / Z Fold Unit for BR Finisher or BR Booklet Maker Finisher Standard Finisher (requires Interface Module) Standard Finisher with Booklet Maker (requires Interface Module) C/Z Folder for Standard Finisher (requires Interface Module and Standard Finisher with or without Booklet Maker) GBC® AdvancedPunch™ (requires Interface Module and Standard Finisher with or without Booklet Maker) Xerox® SquareFold® Trimmer Module (requires Interface Module and Standard Finisher with Booklet Maker) Convenience Stapler Xerox® EX-i C60/C70 Print Server Powered by Fiery® Xerox® FeeFlow Print Server Integrated for the Xerox® Color C60/C70 Printer Xerox® EX C60/C70 Print Server Powered by Fiery®		
	Foreign Device Interface Kit Mobility Plate Envelope Fuser Kit USB Hub XMPie® Variable Data Printing PostScript Kit (recommended for Xerox® Integrated Color Server for the Xerox® Color C60/C70 – PostScript Kit not used with Fiery or FreeFlow Print Servers) Media Card Reader VOIP Fax 1 (3 Line Outside N. America) Fax Kits Server Fax Kit Common Access Card Enablement Kit Xerox® Scan to PC Desktop® Xerox Secure Access Unified ID System® Equitac Office®		
Electrical Requirements			
North America	Voltage: 110-127V Frequency: 50/60 Hz +/- 3 % , 20 A		
Europe	Voltage: 220-240V Frequency: 50/60 Hz +/- 3%, 10 A		
Accessories North America: Europe:	Each module requires 120V, 15 A Each module requires 220V, 10 A		
Power Consumption			
Running (Average)	C60: 1,052 watts; C70: 1,250 watts		
Sleep Mode (Average)	3 watts (Default time to Sleep mode = 2 min.)		
Low Power Mode Recovery Time	Less than 20 seconds		
Operating Environment			
Required Temperature Range	50° to 82° F / 10° to 28° C (Relative Humidity I	ess than 62.5% when temp is 32°C or less)	
Required Relative Humidity	15% to 85% (no condensation)		
Sound Power Levels	Operating: 6.8 B(A); Standby: 3.6 B(A)		
Sound Pressure Levels	Operating: 56 dB(A); Standby: 18 dB(A)		
Weight (approximate base unit only)	604 lb., 273 kg		
Dimensions	Width	Depth	Height
Base Unit with Offset Catch Tray	62 in. / 1,574 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with BR Finisher	79.1 in. / 2,009 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with BR Booklet Maker Finisher	81.4 in. / 2,068 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with BR Booklet Maker Finisher and C Fold / Z Fold Unit	90.6 in. / 2,301 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with Standard Finisher	97.7 in. / 2481 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with Booklet Maker Finisher	122.9 in. / 3,121.7 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
GBC® AdvancedPunch™	12 in. / 305 mm	28.5 in. / 724 mm	38.5 in. / 978 mm
Xerox [®] SquareFold [®] Trimmer	42 in. / 1,066.3 mm	28.5 in. / 724 mm	22 in. / 558.8 mm

High Capacity Feeder	15.3 in. / 389 mm	24.2 in. / 614 mm	14.8 in. / 377 mm
One Tray Oversized High	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
Capacity Feeder Two Tray Oversized High	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
Capacity Feeder	50.7 11.7 500 11111	50.0 m. / / 02 mm	5.1 10.7 572 1000
Certifications			
Graphic Arts Credentials	FOGRA certification*	nt server / controller selected) . go to www.xerox.com/OfficeCertifications .	
	PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3™ (certified) IDEAlliance Digital Press Certified to (*requires an additional Print Server op		
Paper Handling			
Single-pass Automatic Document	t Feeder		
Capacity ³	250 sheets of plain paper – 20 lb. / 7	5 gsm	
Speed	Up to 200 ipm color / 200 ipm black-	and-white (2-sided, 8.5 x 11 in. / A4)	
Paper Sizes	Custom sizes: 5.5 x 8.5 in. to 11 x 17	in. / A5 to A3	
Weights	16 to 53 lb. bond / 38 to 200 gsm		
Bypass Tray			
Capacity ³	Up to 250 sheets		
Sizes	Custom sizes: 4 x 6 in. to 13 x 19 in. /	102 x 152 mm to 330.2 x 482.6 mm (A5 to SRA3)	
Weights	18 lb. bond to 110 lb. cover / 64 to 30	00 gsm (uncoated and coated)	
Envelope Capacity	30 to 50 envelopes		
Envelope Sizes	 #10 Commercial, Monarch (including custom size), C4, C5 (Available as Tray 5. Paper Size Default within tools) run flap open at the trail edge) Custom sizes: 7.5 x 6.7 in. to 9.45 x 6.81 in. / 190 x 170 mm to 240 x 173 mm Digital Laser envelopes recommended 		
Envelope Weights	75 to 90 gsm		
Trays 1 to 4			
Capacity ³	Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,140 sheets		
Sizes	Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A5 Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / B Tray 4: 7.25 x 10.5 in., 8.5 x 11 in. / B	to A3 5, A4	
Weights	18 lb. bond to 80 lb. cover / 64 to 220 Trays 1 and 2: up to 256 gsm uncoat		
Optional High Capacity Feeder (H	ICF)		
Capacity ³	2,000 sheets		
Sizes	7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)		
Weights	18 lb. bond to 80 lb. cover / 64 to 220 gsm (uncoated and coated)		
Optional Oversized High Capacity	y Feeder (OHCF) – 1 or 2 Tray Options		
Capacity ³	1 Tray OHCF: 2,000 sheets plus Stora 2 Tray OHCF: 4,000 sheets	ge Cabinet	

Sizes	1 Tray OHCF: 7.2 x 10 in. / 182 x 250 mm (B5) to 13 x 19.2 in. / 330 x 488 mm (SRA3) 2 Tray OHCF: 4 x 6 in. / 102 x 152 mm to 13 x 19.2 in. / 330 x 488 mm (SRA3)		
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm (uncoated and coated)		
Total Capacity			
Standard Capacity	3,260 sheets (includes Bypass Tray and Trays 1-4)		
Maximum Capacity	7,260 sheets (includes Bypass Tray, Trays 1-4 and Two-tray Oversized High Capacity Feeder)		
Automatic Two-Sided	 80 lb. / 220 gsm auto duplex 110 lb. cover / 300 gsm manual duplex for all stocks from bypass trays and optional Oversized High Capacity Feeder 		
Finishing			
Offset Catch Tray			
Capacity ³	500-sheet stacking		
Optional BR Finisher (Requires Ve	ertical Transport Kit)		
Capacity ³	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11x17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4		
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling		
Weights	16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated)		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported		
Hole Punch North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)		
Optional BR Booklet Maker Finisl	ner (Requires Vertical Transport Kit)		
Capacity ³	Offsetting Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in. / A3 / SRA3		
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling		
Weights	16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated)		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported		
Hole Punch North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)		
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, 12 x 18 in., SRA3 supported		
Optional C Fold / Z Fold Unit (Op	tional with BR Finisher and BR Booklet Maker Finisher)		
Types	C Fold, Z Fold and Z Half Fold		
Capacity ³	40 sheets		
Sizes	C Fold and Z Fold: Letter – 8.5 x 11 in. / A4 SEF only Z Half Fold: Tabloid – 11 x 17 in. / A3 only		
Weights	16 lb. to 24 lb. bond / 64 to 90 gsm		
Output Tray	Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold		
Optional Standard Finisher (requires Interface Module)			
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 3,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4		
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3		
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm		
Multiposition Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm		

Hole-punching			
North America: Europe:	2-3 Hole Punch 2-4 Hole Punch		
Luiope.	4 Hole Swedish Punch (Optional)		
Interposing Capacity			
Capacity:	200 sheets of 128 gsm		
Sizes:	5.5 x 8.5 in, 8 x 10 in, 8.5 x 11 in, 8.5 x 14 in, 8.5 x 12.5 in, 11 x 15 in, 11 x 17 in. / A3, A4, B4, B5		
Weights:	18 lb. bond to 80 lb. cover / 64 to 220 gsm		
Decurling	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings		
Optional Standard Finisher with E	Booklet Maker (requires Interface Module)		
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 2,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4		
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3		
Weights	18 lb. bond to 110 lb. cover / 64 to 300 qsm		
Multiposition Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm		
Hole-punching North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)		
Internating Con			
Interposing Capacity Capacity:	200 sheets of 128 gsm		
Sizes:	5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5		
Weights:	18 lb. bond to 80 lb. cover / 64 to 220 gsm		
Decurling	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings		
Booklet Making Capacity	Saddle-stitch 2 to 25 sheets of 79 gsm (uncoated)		
	Bi-fold up to 5 sheets 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in., 13 x 18 in. / A4, B4, A3, SRA3		
Optional GBC [®] AdvancedPunch (C	Dptional with Standard Finisher – requires Interface Module)		
Punch Configuration Sizes	8.5 x 11 in. / 216 x 279 mm to 13 x 19.2 in. / 330 x 488 mm		
Weights	20 lb. bond to 80 lb. cover / 75 to 216 gsm (uncoated and coated)		
	Wide selection of slide-in / slide-out GBC punch die sets available		
Ontional Vorox [®] SaugroFold [®] Trim	mer Module (Optional with Standard Finisher – requires Interface Module)		
Capacity	5 to 20-sheet booklets (up to 80 imaged sides) at 24 lb. / 90 gsm 5 to 25-sheet booklets (up to 100 imaged sides) at 20 lb. / 80 gsm		
Sizes	Custom sizes: 8.5 x 11 in. to 13 x 18 in. / A4 to SRA3		
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm		
Convenience Stapler			
Capacity	50 sheets (24 lb. / 90 gsm media)		
Print			
Print Resolution	Up to 2400 x 2400 dpi		
Line Screens			
Registration	600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected) • Advanced registration technology for tighter control • Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (Available with Xerox® EX C60/C70 Print Server Powered by Fiery® and Xerox® FreeFlow® Print Server Integrated for the Xerox® Color C60/C70 Printer)		
First saint and Thus	+ 1.2 mm front to back registration		
First-print-out Time	PS- A4 LEF Simplex Color 10.4 seconds / Black-and-white 8.5 seconds		
Print Features	 A true multifunction product – print, copy, fax and scan, including scan to PC, USB or email, and mobile printing Benchmark image quality with 2400 x 2400 dpi resolution and EA low melt toner for a smooth, offset-like finish Makes mobile printing simpler and more convenient Expansive media range lets you print everything from postcards to posters, both coated and uncoated stock, up to 300 gsm Xerox Extensible Interface Platform® (EIP) allows you to connect to third-party software solutions that you can access from the touch-screen of the device Your choice of servers to best fit your environment: Xerox® Integrated Color Server for the Xerox® Color C60/C70 Printer Xerox® EX-i C60/C70 Print Server Powered by Fiery® Xerox® FreeFlow® Print Server Integrated for the Xerox® Color C60/C70 Printer Xerox® TreeFlow® Print Server Powered by Fiery® Inline finishing options offer a professional polish with stapling, hole-punching, folding and booklet making for presentations, brochures, reports and newsletters Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support 		

Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox devices in every new location. Plug into a new network and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Print Solutions			
Xerox® Mobile Print Cloud (Optional)	Xerox [®] Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft [®] Office [®] rendering and more. Print what you need, when, where and how you need it.		
Xerox® Mobile Print Solution (Optional)	Xerox [®] Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox [®] Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.		
Сору			
First-copy-out Time From the Platen: From the DADF:	As fast as 7.8 seconds color / 5.1 seconds black-and-white As fast as 9.6 seconds color / 5.3 seconds black-and-white		
Warm Up Time	90 seconds (from cold powered down to Ready Copy)		
Digital Imaging	Auto color Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Color balance, color shift and saturation		
Reduce / Enlarge	Variable zoom from 25% to 400% in 1% increments		
	Anamorphic zoom Six user-programmable percentages		
Special Features	Auto paper select Auto reduction/enlargement to fit selected paper size Auto tray switching Automatic job recovery Auto color selection Area Designation Poster mode Annotation Single/Dual color Booklet creation Multi-up - 2, 4 or 8 up Repeat Image Negative image Murror image Covers insertion (front only, front and back, back only, blank or printed) Build bole chables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Job interrupt Bookle special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Job interrupt Book copying Sample job Mixed size originals Sheet Insert Starping Z-in 1 X Y Zoom Zoom Range 25 to 400% Margin Shift Photo Mode Preset Reduce / Enlarge		

Scan	
Concurrency	Scan while printing or while it is transferring scan to network or fax jobs
Scan Features	Mixed size originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job
Input Speed	Up to 200 images per minute color and black-and-white
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
Maximum Scan Area	Originals up to 11 x 17 in. / A3
Network Print Services	Novell NDPS Novell Pserver / NDS Port 9100 RFC 1179 (LPR) Print to Mailbox and Release
File Formats	PDF Image Only PDF (Searchable) PDF (Linearized) PDF (A-1 Level A) TIFF V6 JFIF XPS
Document Management Fields (Metadata)	One to six user-programmable metadata fields per scan job Customized fields viewed on user interface Variable data entered using virtual keyboard
Scan Features	Scan to Home Scan to Desktop WIA Scan to Mallbox Scan to Mallbox Scan to Mallbox Scan to FTP Scan via NDS Scan via NDS Scan via HTTP Scan via HTTP Scan via HTTPS Scan to USB Storage Device Scan to USB Storage Device Scan to USB Storage Device Scan to Multiple Destinations Scan to Multiple Destinations Scan to Multiple Destinations Scan to Documentum Scan to Documentum Scan to Documentum Scan to Dorinon Scan to Dorinon Scan to Dorinon Scan to Dorinon Scan to Interwoven WorkSite Scan to Interwoven WorkSite Scan to Interwoven WorkSite Scan to Microsoft Dynamics GP Scan to Microsoft Dynamics GP Scan to Microsoft SharePoint Scan to SharePoint Potal Server Scan to SharePoint Potal Server Scan to Thompson ProLaw Scan to Thompson ProLaw Scan to Web URL Scan to Web URL
Supported Scan Destinations	Scan to Exact e-Synergy Scan to Email, Scan to Folder, to PC, to Mailbox (private and public)

Scan to Email Features	Color cooping Auto Color, Grouppale Plack and white
Scan to Email Features	Color scanning, Auto Color, Grayscale, Black-and-white Direct document email from device
	Manual or directory Exchange / Notes / LDAP address searching
	Signing and encryption Email over SSL
	Preview scan job
Supported Scan Destinations (Optional)	Options include Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview
Authentication	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.
Fax (Optional) – One or Three Lin	e Fax Options
Compatibility	Color, Auto Color, Black-and-white
Maximum Scan Area	11 x 17 SEF
Fax Send Features	iFax
	Lan Fax
	IP Fax Fax Forward to Email
	Fax Forward to FTP destination
	Fax Forward to SMB destination
	Fax Forward to Fax destination
Fax Print Features	Print from USB Storage Device
	Media Print Unicode Printing
Fax Features	iFax
	Lan Fax
	IP Fax
	Fax Forward to Email
	Fax Forward to FTP destination Fax Forward to SMB destination
	Fax Forward to Fax destination
Device Management	
Xerox® CentreWare® Internet Serv	rices – Integrated Web Pages Provided by the Device
Device Status	Web server embedded in Network Controller:
	• Tray status/contents
	Consumables status
	• Alerts
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS
	Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination)Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x
	Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x
	Opera 11.x
	Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese
Remote Services	
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Xerox [®] MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting / repair process. Diagnostic data is sent to

Security	
Features	Secure Print
	IPsec IPsec Embedded Fax Port Blocking IPv6 Support IPv6 Support IPv4 and IPv6 Environments OS Security Updates 802.1X Support (IEEE Standard) Secure Login Network Authentication Xerox Secure Access Unified ID System® IP Address Restriction Job Audit Tray Data Encryption 128-bit AES Encryption 2256-bit AES Encryption Image Overwrite Common Criteria (pending)
Xerox Secure Access Unified ID System® (Optional)	Xerox Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee / student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralized print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions.
Print Server	
Xerox [®] Integrated Color Server for	the Xerox® Color C60/C70 Printer
Processor	993 MHz
Memory (ESS)	4 GB RAM
System Disk	320 GB Hard Disk Drive
Display	10.4 in. color touchscreen flat-panel
Device Operating System	VxWorks
Page Description Languages	PDF XPS®, PCL® 6 emulation HP-GL2 (direct submission) Adobe® PostScript® 3 [™] option TIFF JPEG
Operating Systems	Windows® XP SP1 & above (32 & 64 bit) Server 2003 / 2008 (32 & 64 bit) Vista (32 & 64 bit) Windows 7 (32 & 64 bit) Mac OS® 10.4 and above Citrix® Custom driver for UNIX: – AIX® 5 v5.3 – HP-UX® 11.0 / 11i v2 – Solaris® 8/9/10 – Linux® Fedora Core® 1/5 – Red Hat® ES4 – SUSE® 10/11
Print Drivers Supported	Windows 2003/XP 32 Bit Windows 2003/XP 64 Bit Windows Vista/Vista 32 Bit Windows Vista/Vista 64 Bit Windows 7 / 2008 32 Bit Windows 7 / 2008 64 Bit (Microsoft certified) Macintosh® OS 10.3.0 and UNIX N/A Bi-directional with Xerox Custom Xerox® Mobile Express Driver® XPS Print Driver Xerox® Global Print Driver®

Features	 Automatic two-sided Bi-directional Print Drivers provide device and job status Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) Secure print Delay print Embedded Web server for remote control/monitor/setup Enhanced Gloss Sample set Booklet creation Cover selection Paper selection by attribute N-up Watermarks Banner sheets Fit to new paper size Output tray selection Print calibration Print calibration Print calibration Print calibration Print from USB Plus morel
Connectivity	Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec)
	For more information, go to www.xerox.com/C70IntegratedColorServer.
Additional Print Server Options	
Xerox [®] EX-i C60/C70 Print Server P	owered by Fiery®
Processor	Intel® Pentium® G850 Processor, E200, 2.90 GHZ
Memory (ESS)	2 GB
System Disk	500 GB
Print Languages (PDL)	Adobe® PostScript® 3™ (v3019), PCL 6C (emulation), Adobe Acrobat 9
Features	 Productivity starts with a fast RIP. The Integrated Fiery Color Server enables you to print large and/or complex Microsoft® Office® documents, PowerPoint® files and color-critical PDFs accurately and quickly. Simplify and streamline your workflow. Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers. Take advantage of commonly used Fiery presets to save time when submitting jobs. With Fiery server technology, even novice users can perform complex jobs using the pre-set drivers configured for the task. Get the color right. Produce precise, exact color from all applications, platforms and formats with Fiery color management tools. Turn up the impact with variable information. Customize your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Color Server's basic variable data printing capabilities.
Connectivity	Direct Connection (Single IP)
	For more information, go to www.xerox.com/C70EXiFieryColorServer.
Xerox [®] FreeFlow [®] Print Server Inter	grated for the Xerox® Color C60/C70 Printer
Processor	Intel® Dual Core Pentium G3420 Processor
Memory (ESS)	8 GB
System Disk	1 TB 7200 SATA or equal
Print Languages (PDL)	True Adobe® PostScript® Level 1, 2, 3; Adobe® Acrobat® 9.0, PDF 1.8, PDF/X; TIFF, PCL 5c, PCL 6XL, EPS, JPEG
Features	Simple Windows 7 platform for a familiar experience Integrated / Bustled setup. Perfect for small footprint and quick and easy site setups Accepts Native Microsoft Office® files for Direct Print (from walk-up USB PowerPoint®, for example) Productive All the advantages of a Xerox Production workflow – delivered in a value-oriented solution Streamlined drag/drop submission from tablets and more Powerful Bring the power of Xerox® patented RIP technology in a value oriented solution Latest direct Adobe PDF Print Engine and GC credentials included Includes Variable Data Print / Color Management / Production Workflows Tints and Highlights fine-tuned for better accuracy Duotone, Tri-tone and Quad-tone support
Connectivity	Direct Connection (Single IP)
	For more information, go to www.xerox.com/C70FreeflowPrintServer.
Xerox [®] EX C60/C70 Print Server Po	wered by Fiery®
Processor	Intel® Core i5-2400, 4 Core, PRO80-IV, 3.10 GHz
	4 GB
Memory (ESS)	

Print Languages (PDL)	Adobe PostScript® Level 1, 2, 3; PDF/X-1a, 3 and 4; EPS; Adobe Acrobat® 9.1, Native PDF 1.3, 1.4, 1.5, 1.6 and 1.7; CT/LW; TIFF, TIFF/IT, DCS2, JPEG Microsoft Native Formats (DOC, XLS, PUB, PPT) enabled through Fiery Hot Folders feature EFI™ FreeForm 1, and FreeForm 2 VDP		
Features	 Fiery technology increases your profits by delivering high-impact docualso meets tight turnaround times and allows you to do more work by With Fiery technology, you can produce effective marketing pieces wielements such as text, images and spot colors. This feature also elimin for producing powerful marketing materials, personalized communication. Fiery ColorWise gives high-quality color out-of-the-box and integrates Spot-On and the Fiery Color Profiler Suite to control and manage colo The Fiery Command WorkStation increases your production and reduce Simplify your labor-intensive document composition and imposition tas Fiery JDF technology connects EFI solutions and Fiery-enabled solution By supporting the Adobe PDF Print Engine, Fiery servers also offer a nat your printed output from design to print. Using Fiery servers and Fiery Command Workstation, you get a new lease connectivity to Xerox® FreeFlow® for workflow automation. 	y automating manual tasks and remo- th the widest range of output options nates the need to re-program jobs, ma- tions and packaging and photo publi- the essential components of Fiery Gr or throughout your workflow. es errors and waste by centralizing job sks even more by using Fiery SeeQuence s, so you can move job information the ive end-to-end PDF workflow, therefore	ving bottlenecks that slow down production. s, including automatic identification of job aking the process simple and quick. It is ideal shing applications. raphic Arts Package, Premium Edition, Fiery management via its intuitive user interface. the Impose and Compose's intuitive interface. rough your system faster and more efficiently. e improving the consistency and flexibility of
Connectivity	Direct Connection (Single IP), Network Switch, (Dual IP)		
	For more information, go to www.xerox.com/C70EXPrintServer .		
Supplies	Description	Yield	Part Number
Customer Replaceable Items			
Toner Cartridges (Metered)	Black	30,000 pages4	006R01521
	Cyan	34,000 pages ⁴	006R01524
	Magenta	32,000 pages4	006R01523
	Yellow	34,000 pages ⁴	006R01522
Toner Cartridges (Sold)	Black	30,000 pages4	006R01655
	Cyan	34,000 pages4	006R01656
	Magenta	32,000 pages ⁴	006R01657
	Yellow	34,000 pages ⁴	006R01658
Black Drum Cartridge	1 Cartridge	190,000 pages ⁴	013R00663
Color Drum Cartridge	1 Cartridge per Color	85,000 pages4	013R00664
Charge Corotron	For Black Drum	190,000 pages ⁴	013R00650
Fuser	110V 220V	200,000 pages ⁴ 200,000 pages ⁴	008R13102 008R13065
Waste Toner Container	1 Cartridge	50,000 pages4	008R12990
Feed Roll Kits	1 Assembly	300,000 pages ⁴	008R13169
Staple Cartridges	For BR Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	For BR Booklet Maker Finisher (4 cartridges per carton)	5,000 each cartridge	008R13177
	Staple Cartridge and Waste Container for Standard Finisher	5,000 each cartridge	008R13041
Staple Refills	For BR Finisher, BR Booklet Maker Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill (15,000 total)	008R12941

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ Approximate pages. Declared Yield based on 5 page job size, 30% color and 70% Black and white ratio, using letter / A4 media. Yield will vary based on media size, image area coverage, include up length media orientation and usage patterns.

job run length, media orientation and usage patterns.

To view a product video, visit **www.xerox.com**. Build and configure your own Xerox[®] Color C60/C70 Printer at **www.buildyourownxerox.com**.



©2014 Xerox Corporation. All Rights Reserved. Xerox ®, Xerox and Design ®, CentreWare ®, ConnectKey ®, FreeFlow ®, MeterAssistant ®, Scan to PC Desktop ®, SMart Kit®, SMARTsend ®, SquareFold ®, Supplies Assistant ®, Xerox Extensible Interface Platform ® and Xerox Secure Access Unifed ID System ® and are trademarks of Xerox Corporation in the United States and/or other countries. EFI, Splash, Fiery ® and RPX-iii are trademarks of Electronics for Imaging, Inc. Product appearance, build status and/or specifications are subject to change without notice. Updated 10/14 BR10744 X60SS-01UB