Technical Specs

· · · · · · · · · · · · · · · · · · ·		
Items	Specification	
Operating System	Android 11.0 go	
CPU	Quad-core@1.5Ghz	
Memory	1GB RAM + 8GB ROM (LPDDR3)	
Display	4.0" IPS, 480*480	
Camera	2M FF(front)	
Scanner	N/A	
Cellular Network	Support 2g/3g/4g	
WIFI	IEEE 802.11 a/b/g/n(2.4G&5G)	
Bluetooth	Version 4.2, support BLE	
Payment	Support IC/NFC Card	
Interface	USB type-C、Pogo Pin	
Audio	Speaker	
Battery	1700mAh/3.85V (Rated capacity)	

ATTENTION

Warning

- Read all instructions and safety information before use to avoid injury.
- The limit operating ambient temperature of the device declared by the manufacturer is -10~45°C.

Battery safety

- Charge battery only at ambient temperatures ranging from 0~40°C.
- Dispose of used batteries according to manufacturer's instructions.
- Danger of explosion if battery is incorrectly replaced. Replace only with the same or equivalent type of battery recommended by the manufacturer.

Statement

- The equipment damage caused by natural disasters, falling, self disassembly and non-compliance with the operation specifications is not covered by the free warranty.
- Some details of this document may be inconsistent with the real object due to the update iteration of the product. Please take the real object as the standard, and our company reserves the right to interpret this document.

P12 Quick Guide

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- -Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- -Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.


RF Exposure Information:

FCC RF Exposure requirements: The highest SAR value reported under this standard during product certification for use next to the Body with the minimum separation distance of 0mm. This transmitter must not be collocated or operating in conjunction with any other antenna or transmitter.

This product is compliance to FCC RF Exposure requirements and refers to FCC website https://apps.fcc.gov/oetcf/eas/reports/GenericSearch.cfm_search for FCC ID: 2A2UU-P12

All transmission frequencies of U-NII-1,U-NII-2A and U-NII-3 comply with 47 CFR FCC Part15.407(g) and the manufacturer declares that their transmission is maintained within the U-NII-1. U-NII-2A and U-NII-3 bands.

Product Diagram



NFC Card Reader

NFC antenna locates at the bottom of the screen. It's used to sense chip and acquire data through contactless way.

IC Card Reader

Used for inserting the bank chip card and getting information securely.

Front Camera

Used to take photos or videos needed or complete commercial payment through camera base on third-party app.

Display

Set for merchants to complete business settlement and for customers to input the password to finish the payment.

Power Button

Used for change the running states of device, such as pressing 2 ~3 seconds to power on/off or screen capture and pressing 10 seconds to restart automatically when device is crashed.

Card Slot

The card slot is on the right side of the device and can be pushed out by holding the card pin like smart phones.


USB type-C


Used for device charging and plugging in peripheral device which supports OTG.

Pogo Pin

The 2-pins expanded interface is severed as the channel to connect the charging cradle for better power supply.

Card Selection Instruction





Package List

NO.	Items list	Description
1	Device	Default
2	Battery	1700mAh/3.85V (unremovable)
3	USB cable	1pcs,1m/white/type-c
4	Adapter	5V2A, Optional
5	User manual	Neutral
6	Card Pin	Default