

PRODUCT INSTRUCTION

MODEL: *ZT-906T*

PAGE: 1 OF 4

DESCRIPTION

Wireless Camera

ZT-906T

WIRELESS CAMERA USER'S MANUAL

REVISIONS		DESCRIPTION		DATE	DESIGN
SHENZHEN ZHONGWANG ELECTRON CO., LTD				APPROVAL	
PAGES TOTAL		FILE JMBER	ISSUE DATE	CHECK	
4				DESIGN	

FILE NUMBER:

MODEL: ZT-906T

PAGES: 2 OF 4

FCC Information

This device complies with part 15 of the FCC Rules, Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

CAUTION: Changes or modifications not expressly approved by Summer infant may void the users authority to operate this equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part15 of the FCC Rules.

These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications, However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna
- Increase the separation between the equipment and the receiver
- Consult the dealer or an experienced radio / TV technician for help.

Operation instruction

- 1. Connecting the receiver antenna. (Figure 1)
- 2. Connecting the 12V adapter (Figure 2), open up the switch(Figure 5),LED indicator lights up (ch1),Press the Key-press(Figure 8), LED indicator(ch1,ch2,ch3,ch4) lights up in proper order.
- 3. Connecting the audio and video (figure 4) output with the input to the monitor, the television should be set on A/V model.
- 4. Connecting the audio and video output with the input of the transmitter.
- 5. Plug power jack of DC power supply(12V, 500mA)into the power socket of the CCD camera(figure 6).(Battery of the same voltage is acceptable.)
- 6. Turning the micro-adjustment knob (figure 5)on the receiver till receiving the picture of the wireless camera.
- 7. Fine tune to the desire position till the image of CMOS camera is received.
- 8. Adjust the lens of the CMOS camera (figure 7) to best position.

Notice

- 1. The machine is supplied with many different types, please provide with electric power according the value on the label.
- 2. Obstructs by the building and so in will cause attenuation.
- 3. Normally that the machine will slightly warm up during operation.
- 4. Should any other malfunctions occur, please contact local distributor.
- 5. Under normal operational conditions, one year's warranty is granted .if there are quality problems within 3 months, this company will unconditionally replace with a new camera.

Waning

This product is for the sole purpose of security and applicable for monitoring in residential houses, shop sand companies the users shall observe local rules, regulations and laws, and shall be solely liable in this regard, this company shall not be liable for any illegalities therein.

SHENZHEN ZHONGWANG ELECTRON CO.,LTD

TEL: +86-755-8336 1499 FAX: +86-755-8336 1433

http://www.ztv.cc

	MODEL: ZT-906T	PAGES:	3 OF 4			
Technical data						
ITEM	TYPE	TYPE				
Transmission						
Frequency	2.414~2.468GHz 4cH	2.414~2.468GHz 4cH				
Electric power:	DC 12V	DC 12V				
Output power	0±3dBm	0±3dBm				
Video input:	1.0V _{P-P} (MAX)	1.0V _{P-P} (MAX)				
Power consumption currer	nt 180mA	 				
Audio input:	2V _{P-P} (Max.)	2V _{P-P} (Max.)				
Effective range (no obstacle	es) 30m					
CCD	<u> </u>					
IMAGE SENSOR	1/4 (Sharp CCD)	1/4 (Sharp CCD)				
CCD Pixel Pitch	7.2 (H) × 4.7 (V)	7.2 (H) × 4.7 (V)				
SYNC SYSTEM	INTENAL	INTENAL				
Minimum illumination	<2(IR OFF)/0(IR ON)	<2(IR OFF)/0(IR ON)				
Horizontal Resolution	420TV Line	420TV Line				
NAULTE DAL ANIGE	Mode: AWB(Zero color r	Mode: AWB(Zero color rolling)				
WHITE BALANCE	Range:3200~10000° K	Range:3200~10000° K				
GAIN CONTROL	AGC					
S/N RATIO	40dB					
ELECTRONIC SHUTTER	1/50-1/100000 sec	1/50-1/100000 sec				
GAMMA CORRECTION	0.45	0.45				
OPERATION TEMPERATURE	-20℃~50℃	-20℃~50℃				
OPERATION HUMIDITY	15%~85%RH	15%~85%RH				

