105.0 mm RF636 Manual-2.4GHz Multimedia Specifications · Removal or installation of the product. B. Setting up the Keyboard and Mouse **Keyboard with Touch Pad Function** • External causes to the product, such as absence of electrical grounding, power fluctuation, failure and/or <u>Keyboard</u> 1.Turn ON your keyboard by sliding the switch at bottom power spikes. case. (FIG. 2) System requirements Dimensions: 403 x 190x 26.2 mm Normal wear and tear. 2. Open the keyboard's battery compartment cover Weight: 850+/- 20g (with Battery) · Any other cause not related to a product defect. and insert the two pieces of AA Alkaline batteries. □ IBM® or 100% compatible PC Channel: Separate 78 channels for keyboard Make sure they are properly installed. (FIG. 3) Microsoft Windows® Operating System with unique sets ID. 3. Replace the keyboard battery compartment cover. Pentium-equivalent processor or above Radio Frequency: 2.4GHz 4. Usually the keyboard has aligned in the factory, and it One available USB port Warning Operation distance: 10 Meters can be used after inserting batteries. If the keyboard H H H Key Number: 84 Keys and touch pad cannot be recognized from system, Do not use this product in ashy, wet or oily environm Battery: 2 x AA batteries ents as these conditions can shorten the life of this please follow steps below. OS support Battery Life: 2 Month (Base on average usage) product and may cause injury to its user(s). 5.Press the ID button of receiver and the LED (RED) This is not an outdoor product. Exposing this Hot Keys: Mute \ WWW \ E-mail \ Previous page \. light will start to blink. 0 product to the elements may cause damage to the Next page · Search · Refresh. Windows 2000 product and/or may cause injury to its user(s). 6.Close to the receiver and press the ID button of Windows ME Touch Pad Do not use alcohol, petroleum, benzene or thinner-0 keyboard, and the LED (RED) light will stop blinking. Windows XP based solutions to clean this product. We recomm 2 7. If the keyboard cannot be connected after setting, Windows Vista Dimensions: 45.7*35.6*1.12 mm end wiping this product with a damp cloth only. please repeat the step 5~7 to reset the ID button. Receiver Dimensions: 41*16*8 mm Weight: 10.9a □ Interface: USB 1.1 00.00 mm Introduction Warranty Information Installation Procedure Battery Low If you feel the touch pad does not move smoothly or Before installing this product please make sure you have Thank you for purchasing our RF2.4GHz wireless This product is backed by a One-Year Manufacturer's keyboard does not work when typing, then the batteries keyboard with touch pad function. For your own safety, Warranty, starting from the date of purchase. The e one available USB port reserved for the receiver. have lost their charge, so please replace them. Also, the warranty covers for free repair in accordance with the please read this manual thoroughly before using this LED light will be blinking "Red" when there is a battery-A. Setting up the Dongle Receiver contents stated herein but does not cover wear and te product. Place for reference when necessary. low situation. ar and any malfunction or damages as results of 1.Plug the receiver into an available USB port. (FIG. 1) improper usage as stated in this manual. This warranty 1.Low-Battery is indicated by the illumination of the Contents in the package DOES NOT COVER: Keyboard Top case "Batt. Low". Please replace the The following items are included in the package. 2. Wait for Windows to install drivers for the receiver and battery when the LED lights up. 1. Any product with defaced, modified or removed serial Please make sure all items are accounted for as you keyboard. 2.We recommend using alkaline batteries for the open the package. If there was any item missing or 3. When the receiver has been properly initialized, its keyboard. 2. Damage, deterioration or malfunction resulting from: damaged, please contact the reseller where the 3. You may need to reset the ID's after replacing new LED light will stay light. Accidents, misuse, negligence, and natural hazards product was purchased or our support center. batteries for the keyboard. including: fire, water, lightning and/or other acts of 2.4GHz Wireless Keyboard x 1 Any unauthorized modifications not complying with USB 2.4GHz receiver x 1 Warning User Manual x 1 the standard product, or failure to follow instructions Please be careful when resetting the Link for the keyboard. supplied with the product. AA Alkaline batteries x2 Objects with sharp point may break and leave behind · Repair or attempted repair by unauthorized personnel. shards. · Shipping damage; consult with your retailer if the Do not mix old and new batteries, or mix different types of product is suspected of being damaged during batteries. This can cause rupture or leakage, resulting in shipping. personal injury or property damage. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. 420.0 mm TO CONVERT INTO 420x300mm未折合 例 單 位 種 比 機 C701324001 2006/02/05 RF-722 1:1 MM計 差 公 版 次

±1.0mm

70p模造紙

質

新巨企業股份有限公司

ZIPPY TECHNOLOGY CORP.

方慧

魏茂秦

認

確

敘

述

期

日

計

改

內

設

