



Service Entrance Splices

T&B Catalog Number:

CS74

UPC Number:

78378610062

Status:

Active

Description:

Aluminum 2 Inch Service Entrance Compression Splice for Wire Range
- End A: 1/0 ASCR, 1/0 Stranded, Yellow, End B: 8 Stranded, 6 Solid,
Green, Die: 5/8

Features

Constructed from Aluminum for high conductivity.
Prefilled with Oxide Inhibitor to prevent oxidation.
Color-coded and marked for easy identification.
Standards compliant. Meets ANSI C119.4 requirements.

General

Insulation Type	Non-Insulated
Material	Aluminum
Barrel Length	Standard Length
Conductor Range A ASCR	1/0
Conductor Range A Str./Sol.	1/0 Str.
Conductor Range B Str./Sol.	8 Str., 6 Sol.
Conductor A Color	Yellow
Conductor B Color	Green

Dimension Information

Length (inches)	2
Conductor A Diameter Max.	0.398
Conductor A Diameter Min.	0.368
Conductor B Diameter Max.	0.162
Conductor B Diameter Min.	0.146

Tooling

Die Series	5/8" Die Series
Hydraulic Dies	U-BG B58CS, 52
Mechanical Dies	5/8 (OD58 Tool) Peach, BG, G, TU

Packaging

T&B Inner Pack	100
Package in Units	800
T&B Sold in UOM	Each
T&B Weight Per UOM	5.38 lbs. per 100

Notes

Connector only.

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com