


DIGITAL DESIGN

SYSTEMS ARCHITECTURE, INTEGRATION AND APPLICATIONS

JULY 1985

- EEPROMs RISE TO MEET NEW SYSTEMS DEMANDS
- THE FUTURE OF FLEXIBLE DISKS
- OPENING THE SIMULATION BOTTLENECK



**ARRAY PROCESSORS:
INCREASING SPEED BY
MIPS, MOPS, FLOPS
AND GOPS**

To reach new heights in flight simulation, McDonnell Douglas turned to Gould.

High-performance is the key.

When McDonnell Douglas needed a computer/image processing system for their Flight Simulation Facility, they looked for a company with standards as high as their own. And found Gould – the world leader in providing high-performance computing and image processing power for the simulation market.


According to Dennis Gawera, Systems Manager at McDonnell Douglas' McDonnell Aircraft Company, "Processing speed was one decisive factor in choosing Gould's CONCEPT/32® machine as the host for our radar display and out-the-window scene generation."

Gould's flexibility has also impressed Gawera. "Our IP8000 Image Processing systems have allowed us to simulate many radar display modes that we hadn't even anticipated when the system was installed."

Gould sets high standards for reliability and support.

Gawera and McDonnell Douglas count on Gould's reliability every day. According to Gawera, "Our Gould minicomputer and IP8400 Image Processors have serviced our radar simulator for over two years without a single failure."

What's more, "Gould has always been most cooperative in providing us with the technical information we've needed."



Gould value is the bottom line.

"We've determined that it is cost effective to operate our Flight Simulation Facility using several interconnected Gould minicomputers instead of a mainframe," Gawera explains.

"Speed, reliability, and cost considerations have made Gould computers a mainstay for our flight simulation applications for over seven years." Gawera makes it easy to see why McDonnell Douglas turned to Gould.

Write today, and see why you too should turn to Gould.

Gould Information Systems, Department IGD
6901 W. Sunrise Blvd., Ft. Lauderdale, FL 33313
CONCEPT/32 is a registered trademark of Gould, Inc.



Circle 6 on Reader Inquiry Card

DATAcube REAL-TIME FRAME GRABBERS AT A GRABBER OF A PRICE.

Our new 128 Family gives your computer 20/20 vision.

Introducing the first family of frame grabbers: The Datacube 128 Family of full function, single boards for real-time image acquisition and color display.

Our new IVG-128, for example, instantly turns any IBM PC into an economical, multi-feature image processing system.

Our VVG-128 double high Eurocard for the VMEbus tames the harshest machine vision and inspection environments.

While our VG-128 for the Multibus and iLBX bus provides on-board arbitration logic for fast video data transfers between two host CPUs.

Each 128 Family board provides reliable, real-time digital video for machine vision inspection, teleconferencing, medical imaging, surveillance, and many other applications.

And each Datacube 128 Family board bears a striking family resemblance to each other.

The 384H x 512V x 8-bit frame store's throughput rate matches solid state CCD camera outputs exactly.

Enhanced video input phase lock loop for rock-steady picture stability.


Digitizing, storage and display for one high-resolution image or two medium resolution images under software control.

And the ability to lock three boards together for true color RGB applications.

Each 128 Family board also gives you 7.16 MHz 8-bit digitization. Multiple banks of input and output look-up tables. And red, green and blue outputs.

All as standard features. All on a single board. And all for an incredible grabber of a price. Just \$2,995.


To get your new 128 Family album of products, write: Datacube Incorporated, 4 Dearborn Road, Peabody, MA 01960. Or call (617) 535-6644 today.




DATAcube

Circle 4 on Reader Inquiry Card

SOFTWARE'S FOURTH DIMENSION.



© Digital Equipment Corporation 1985. Digital, the Digital logo, and VAXcluster are trademarks of Digital Equipment Corporation. Ada is a trademark of the U.S. Department of Defense. *In Canada: DEC of Canada Ltd. OEM Market Manager, P.O. Box 13000, Kariata, Ontario K2G9Z9. In Europe: Advertising Manager, 12 Avenue de Morgines, Case Postal 5103, CH-1213, Petit-Lancy 1, Geneva, Switzerland.



OEMs haven't a moment to lose. Just a few weeks can mean a more competitive product. In just a few months, a market opportunity can vanish.

Digital software can put time on your side.

With operating systems so rich in functions, they're complete operating environments.

With tools so varied you won't have to force-fit an application.

With the data base and information management systems you don't want to spend time writing yourself.

And as distributed computing grows more complex, Digital software keeps on saving you time. With the industry's most flexible networking strategy. With access to some of the industry's most prized applications libraries. From Ada™ to artificial intelligence. For supermicros to VAXclusters.™

Better than most competitive products, Digital software marries your chances for value added with the quick development necessary for market success. That's what makes it a best seller among OEMs.

Because with software, it's not just what you can do. It's what you can do by tomorrow.

For a copy of Digital's software brochure, call 1-800-DIGITAL, ext 509. Or send in the coupon:

Please forward a copy of Digital's software brochure.

Name _____

Title _____

Company _____

Address _____

City _____

State _____

Zip _____

Telephone _____

Ext. _____


Return to: Digital Equipment Corporation,
P.O. Box 2004, Cathedral Station, Boston,
MA 02118.*

**THE BEST ENGINEERED
COMPUTERS
IN THE WORLD.**

digital™


Circle 5 on Reader Inquiry Card

TECHNOLOGY TRENDS



COURTESY AT&T

21 AT&T announces 32-bit μ P



COURTESY ADAPTEC

31 Disk/Tape controllers adopt SCSI



COURTESY CANON USA

63 Future of flexible disks

- 21 **ICs** / AT&T To Sell 32-Bit Microprocessor Family • Bit-Slice Chips Challenge 32-Bit Microprocessors
- 25 **Imaging** / Three Flat Panel Display Technologies Mature For Use In Portable PCs
- 27 **Communications** / Schemes To Interconnect Networks Aid Wide-Area Data Transfer
- 29 **Design Tools** / Gate Array Design Update: Simulation And Routing Considerations
- 31 **Boards** / Disk/Tape Controllers Declare Independence With SCSI
- 35 **Peripherals** / Cartridge Disks Rediscovered

- 15 **Editor's Comment**
- 19 **Hotline**
- 36 **Letters**
- 81 **Reader Service**
- 87 **New Product Focus**

- 90 **New Products**
- 99 **New Literature**
- 100 **Calendar**
- 100 **Advertiser Index**

ON THE COVER

The new generation of array processors, like the Numerix MARS 432 on the cover, is finding uses in a variety of medical, seismic, scientific and signal processing applications. The MARS 432 array processor features a 30 Mflop processor, 64 Mbytes internal memory plus application libraries and Fortran compilers. John Owens photo courtesy of Numerix Corp., 20 Ossipee Rd., Newton, MA 02164 (617) 964-2500.

Published monthly thirteen times a year with two issues in November. Subscription rates for non-qualified subscribers (US and Canada) — \$40/yr; foreign — surface mail — \$50/yr; airmail — \$85/yr. Single copies — \$4. Copyright 1985 by Morgan-Grampian Publishing Company, 1050 Commonwealth Ave., Boston, MA 02215. Second class postage paid at Boston, MA and at additional mailing offices. POSTMASTER: Send address changes to Morgan-Grampian Publishing Company, Berkshire Common, Pittsfield, MA 01201 ISSN 0147-9245.

A bridge between the von Neumann architectures of the past and the SIMD/MIMD machines of the future.

COURTESY CSPI



TABLE OF CONTENTS

FEATURES

ELECTRONIC IMAGING

- 39** **Array Processors – Increasing Speed By MIPS, MOPS, FLOPS And GOPS**
- 40** **Single Vs. Double Precision Computation**
by Paz Y. Kahana
Determining whether an application requires double or single precision involves a balance between selecting the right tool for the computation and not investing more than is necessary.
- 46** **Integral Array Processor Speeds Image Processing**
by Aaron Boxer
Many scientific computation and image processing problems can be performed significantly faster on an array processor.
- 50** **Modular Array Processor Features Dual Processor Design**
by Robert Frisch and Barry Eisenstein
There are two major problems associated with array processors: lack of compute power and difficulty of use.
- 55** **Maintaining Compatibility When Upgrading The 8086/87**
by Jack Sterett, Al Brown and Gary Hornbuckle
Although the conversion from the 8086 to the 80286 is mostly a straightforward process, system designers should be aware of several details.

SYSTEMS ARCHITECTURE

- 63** **The Future Of Flexible Disks**
by Bob Hirshon
Despite the potential for significant improvement, the mainstream of flexible disk technology lags far behind the leading edge.


SEMICONDUCTOR TECHNOLOGY

- 71** **EEPROM Technologies Diversify And Find New Applications**
by Dave Wilson
To date, the EPROM market has been relatively untouched by the EEPROM technology, primarily because of the radical difference in product cost between the two devices produced with the same design rules.

DESIGN TECHNOLOGY

- 79** **Attacking The Simulation Bottleneck**
by David W. Allenbaugh
Logic simulation is a highly CPU-intensive circuit design verification task that is an essential element in the design cycle.

THE FPS 64-BIT FAMILY: CONSIDER WHY THE MOST ACCESSIBLE SUPERCOMPUTERS MAY BE THE FASTEST WAY TO DO YOUR JOB.



The new 38 MFLOPS FPS-264, with 64-bit accuracy, large storage, and architecture refined to achieve a high percentage of its peak speed. For many applications, it can provide half the performance of the most popular supercomputer. Its moderate price and exceptional support liberates supercomputing from the realm of major corporate investment and puts it within practical reach of departments and teams.

How fast can you get a supercomputer up and running is as important as how fast it runs. When you look beyond peak computing


speeds to the practical realities of compute-intensive analysis and simulation, odds are that nothing else can take your job from start to finish as fast as the FPS

64-bit supercomputer family. Here's why:

- 1. FPS protects and utilizes your existing software resources.** FPS offers you an exceptional, proven software tool set. If your investment in FORTRAN is typical, the FPS Compiler will alone be a compelling advantage.
- 2. More applications software than for any other comparable com-**

puter. Compare quantity and quality of compatible third party software packages—for structural analysis, circuit design, reservoir simulation, fluid flow analysis, chemistry and much more—and the FPS advantage widens.

- 3. The FPS 64-bit family makes supercomputing speeds affordable at the department level.** Even teams with remote access to Crays® and Cybers™ are




The FPS optimizing FORTRAN-77 Compiler lets you easily adapt code to FPS' pipelined architecture in a form that is nearly as efficient as hand-coded assembly language. With extensions for asynchronous I/O and for enhancing compatibility with other compilers, it is one of most comprehensive tools of its kind.

likely to find that the advantage of immediate, local access is well worth the sacrifice of standing in line for the "fastest" machines.

System prices start at \$300,000 (U.S.) for the 11 MFLOPS FPS-164. The new 38 MFLOPS FPS-264, starting at \$640,000,

achieves 4-5 times the speed of the FPS-164 on many applications programs. The multiple parallel processing units and peak 341 MFLOPS of the FPS 164/MAX can run many matrix computations faster than supercomputers, for less than one-tenth the price.



Family Specifications

| | FPS-264 | FPS-164/MAX | FPS-164 |
|-------------------------------|--|--|--|
| Peak speed, MFLOPS | 38 | 33-341 | 11 |
| Dynamic range | 2.8×10^{-309} to $9.0 \times 10^{+307}$ | 2.8×10^{-309} to $9.0 \times 10^{+307}$ | 2.8×10^{-309} to $9.0 \times 10^{+307}$ |
| Word size | 64 bits | 64 bits | 64 bits |
| Main memory capacity | 4.5 MWords | 15 MWords | 7.25 MWords |
| Maximum disk storage capacity | 16 Gbytes | 3 Gbytes | 3 Gbytes |
| Precision | 15 decimal digits | 15 decimal digits | 15 decimal digits |
| Vector registers | 4 x 2K | 124 x 2K (max.) | 4 x 2K |
| Scalar registers | 64 | 184 (max.) | 64 |
| Host interfaces | IBM, DEC | IBM, DEC, Sperry, Apollo | |
| Program Development Software | FORTRAN Compiler, Overlay Linker, Assembler, Object Librarian, Interactive Debugger. | | |


Family Performance Measures

| | FPS-264 | FPS-164/MAX | FPS-164 |
|---|---------|------------------------|---------------------|
| Peak MFLOPS | 38 | 15 accelerators 341 | 1 accelerator 11 |
| Peak MOPS | 190 | 1705 | 165 |
| Peak MIPS (Instructions are multi-parcel) | 19 | 5.5 | 5.5 |
| Typical MFLOPS, LINPACK Benchmark | 9.9 | 20.0 | 6.0 |
| Whetstones, KWIPS (64-bit) | 19,000 | 5440 | 5440 |
| 1000x1000 matrix multiply, seconds | 53 | 10 | 66 |
| \$K/MFLOPS (system price/peak speed) | \$17K | \$2.5K | \$12K |
| | | | \$27K |

4. The FPS family is expandable. Proven dependable. Well-supported. In other words, a safe, farsighted investment. You can upgrade your existing FPS computer, or evolve from one level of performance to another, with minimal disruption. And you can bank on a record of reliability that begins with exhaustive manufacturing testing and extends to our 30 field office service facilities worldwide.


Ask your local Floating Point sales representative to help you develop your own strategy for accessible supercomputing. Contact Floating Point Systems, Box 23489,

Portland, OR 97223.
Telex 360470
FLOATPOIN BEAV.
Sales offices worldwide.
Call (800) 635-0938.



THE PROVEN POWER IN ACCESSIBLE HIGH-SPEED COMPUTATION.





How to meet your deadline and have your coffee too.

Find a converter, your boss says. Oh no you think, this could take hours or days with the design parameters he's specified. More precious time down the tubes. That's the way it is. *Unless* you have PARAMETRIX™ from INACOM International. Our Computer Aided Access helps you find integrated circuits by parameters in seconds. Frequently updated, PARAMETRIX provides a current source of comprehensive component information. And it's the only computerized parametric retrieval package that resides on your workstation. So you can concentrate on your real job ... *Designing*. And perhaps even have time to enjoy your coffee. To learn more about PARAMETRIX, the design time saver, call 1-800-443-INFO, 303/694-4200 (In Colorado) or drop us a line.

INACOM International
4380 South Syracuse Street
Denver, Colorado 80237

INACOM
International

COMPUTER AIDED ACCESS™
We go right to the source.

Circle 9 on Reader Inquiry Card

REPRINTS

DIGITAL DESIGN will reprint any article from past or present issues. Reprints are custom printed. Minimum order: 1,000 copies. Purchase order or letter of authorization required.

Allow one month from receipt of order for delivery, unless previously arranged and confirmed.

Advertisements alone can also be reprinted. Call (617) 232-5470, and ask for reprints.

DIGITAL DESIGN

| | |
|--|--|
| Editor in Chief | John Bond |
| Managing Editor | Debra A. Lambert |
| Technology Trends | Julie Pingry, Senior Editor |
| Features: | |
| Semiconductor Technology | Dave Wilson, Executive Editor |
| Electronic Imaging | Andrew Wilson, Senior Technical Editor |
| Design Technology | Ronald E. Collett, Senior Technical Editor |
| Systems Architecture | Brita Meng, Technical Editor |
| New Products Editor | Terri Lamneck |
| Western Technical Editors (408) 356-0405 | Gregory MacNicol Joe Aseo |
| Copy Editor | Sherri Mack |
| Editorial Assistant | Tia Partin |
| Contributing Editors: | |
| Electronic Imaging Peripherals | Hugh Aldersey-Williams Bob Hirshon |
| Directory Editor | Dawn Bursk |
| Senior Art Director | Tilly Berenson |
| Advertising Production Manager | Martha Watjen |
| <hr/> | |
| Production Director | Paul Dadarria |
| Graphics: Supervisor Sr. Technician Jr. Technician | William Manning Jr. Don Schaaf Paul Christo |
| Marketing Director | Charlotte King |
| Promotion Manager | Elaine Bull |
| Marketing Assistant | Sharon Lembo |
| Research | Carolyn Wulfsberg, Peter Micheli |
| Circulation Director | Hugh J. Dowling |
| Circulation Supervisor | Nancy McPherson |
| Circulation Staff | Miriam Hlister |
| Reader Service (413) 499-2550 | Terri Giroux |
| Direct Mail | Deb Goldstein |
| Executive Administrator | Suzanne Leveque |
| Corp. Services Administrator | Janet R. Pitt |
| General Administration | Deanna Richardson, Caroline Chesnut, Tyrone Simpson, Mal Rankin, Debra James |

President,
Ronald W. Evans

Publisher,
James R. DiFilippo

Associate Publisher
Terry L. Willins

Advertising Sales

Northeast/Midwest: Terry L. Willins (In MA) (617) 232-5470, (Outside MA) (800) 223-7126, 1050 Commonwealth Avenue, Boston, MA 02215

Middle Atlantic/Southeast: Richard V. Busch (609) 921-7763, 40 Stony Brook Lane, Princeton, NJ 08540.

Northwest: Carole Sacino, (408) 356-0405, 15951 Los Gatos Blvd., Suite 7, Los Gatos, CA 95030

Southwest/South Central: Mike Prewitt, (714) 851-8550, 2041 Business Center Dr., Suite 206, Irvine, CA 92715


National Postcard Sales: Deb Goldstein (In MA) (617) 232-5470, (Outside MA) (800) 223-7126, 1050 Commonwealth Avenue, Boston, MA 02215




Actual unretouched video image of Fred Molinari, President.

“It’s easy to spot the difference between our IBM PC™-based frame grabber and the others.”

High performance and affordable cost, just \$1495 for a single plug-in board.



Laplacian Filter



False Color

Unlike other video I/O systems, the new DT2803 provides real-time image capture capabilities, digitizing a 6-bit video field every 1/30 second. An on-board, memory-mapped, dual-ported frame store memory (256 × 256 × 8) makes it ideal for the IBM PC’s 64K buffer size. And for real number crunching,

the DT2803’s external ports interface to high speed co-processors.

With our software package, VIDEOLAB™, the DT2803 is easy to use for image operations like averages, histograms, and convolutions.

So, if your application is manufacturing/automatic inspection, robotics, or medical research,

our new high performance video I/O board will really open your eyes – at an unbeatable price.

Call (617) 481-3700



Call for our new 576 pg. catalog/handbook or see it in Gold Book 1985.

| SPECIFICATIONS: DT2803 | |
|------------------------|---|
| A/D Input | RS-170 (CCIR), 6-bits at 5MHz |
| Frame Grab | 1/30 (1/25) second per field |
| LUT's | 8, 64 × 8 input; 4, 256 × 12 output |
| D/A Output | 64 colors × 64 intensities, R-G-B; 64 grey levels, monochrome |
| Frame Memory | 256 × 256 × 8 (2-bits for graphic overlays) |

DATA TRANSLATION

World Headquarters: Data Translation, Inc., 100 Locke Dr., Marlboro, MA 01752 (617) 481-3700 Tlx 951 646.

European Headquarters: Data Translation, Ltd., 13 The Business Centre, Molly Millars Lane, Wokingham Berks, RG112QZ, England Tlx: 851849862 (#D)

In Canada: (416) 625-1907.


IBM PC is a registered trademark of IBM. VIDEOLAB is a registered trademark of Data Translation, Inc.

Circle 14 on Reader Inquiry Card

VME

Color Graphics Display Controllers

- **High Resolution**
1024 x 1024, 512 x 512 pixels
Non-interlaced and interlaced formats available
- **16 Simultaneous colors**
- **Blink at 1 Hz**
- **High Performance**
Graphics generated at up to 1,200,000 pixels-per-second
Fill operations at up to 19,200,000 pixels-per-second
All planes drawn simultaneously
Line by line vertical scroll
Multiple cursors
- **GPS Subroutine Package**
Available for popular operating systems
- **Other bus architectures available**



- **High Resolution Color Monitors**
Standard or long-persistence phosphors
Available in 13 inch or 19 inch
Analog or TTL inputs
0.31 mm pitch

GSI Graphic Strategies, Inc.
PRACTICAL COMPUTERGRAPHIC SOLUTIONS

549 Weddell Drive
Sunnyvale, CA 94086
(408) 745-6500 Telex: 856 587

Circle 8 on Reader Inquiry Card

TELL US YOUR THOUGHTS

Digital Design is your forum—your inputs help keep the magazine interesting and vital to the design community. So let us know how we're doing and how we can serve you better in the future. We want to know what you like or dislike about *Digital Design*, the subjects you'd like to see us address, how you feel about the problems you face every day as design professionals.

If you have thoughts your peers should know about, put them in a letter in *Digital Design*. Have your say in your magazine! Send letters and comments to: Editor, *Digital Design*, 1050 Commonwealth Ave., Boston, MA 02215.

EDITORIAL AND SALES OFFICES

DIGITAL DESIGN, 1050 Commonwealth Avenue, Boston, MA 02215, Telephone: (617) 232-5470

MG MORGAN-GRAMPIAN

CORPORATE HEADQUARTERS

Morgan-Grampian Publishing Company, 1050 Commonwealth Avenue, Boston, MA 02215, (617) 232-5470. Brian Rowbotham, Chairman; Ronald W. Evans, President; Charles Benz, Vice President.

EXPOSITIONS GROUP


Morgan-Grampian Expositions Group, 1050 Commonwealth Avenue, Boston, MA 02215 (617) 232-EXPO. The following is a list of conferences produced by the Expositions Group:

| | |
|---------------|--------------------|
| ATE West | CADCON East |
| CADCON West | ATE Central |
| ATE Northwest | CADCON Central |
| ATE East | Electronic Imaging |

In addition to DIGITAL DESIGN, Morgan-Grampian publishes the following in the United States: Circuits Manufacturing • Electronics Test

Morgan-Grampian also publishes the following in the United Kingdom: Electronic Engineering • Control & Instrumentation • Electronics Times • What's New in Electronics • What's New in Computing • Business Computing and Communications • Communications Systems Worldwide.

DIGITAL DESIGN serves the manufacturers of computer-related OEM products. This includes primary computer and systems manufacturers, systems integrators, components and peripheral manufacturers, integrating OEM's and commercial end users. These companies manufacture products used to control machinery, equipment and information in manufacturing, material processing, machine tools, packaging, health care, defense, data processing, communications, instrumentation, and scientific and business operations.



SUBSCRIPTION POLICY

DIGITAL DESIGN is circulated only to qualified research, development and design engineers and engineering managers primarily responsible for computer products and systems in OEM plants. To obtain a complimentary subscription, request (on company letterhead) a qualification card from Circulation Director. For change of address, attach old address label from recent issue to new company letterhead or note. Send this plus request for new qualification card to:


Circulation Department, DIGITAL DESIGN, Berkshire Common, Pittsfield, MA 01201

Subscription rates: non-qualified subscribers (US and Canada) — \$40/yr; foreign — surface mail — \$50; air mail — \$85. Single copies — \$4.

Authorization to photocopy items for internal or personal use, or the internal or personal use of specific clients, is granted by Morgan-Grampian Publishing Co. for libraries and other users registered with the Copyright Clearance Center (CCC) Transactional Reporting Service, provided that the base fee of \$2.00 per copy, plus \$.25 per page is paid directly to CCC, 21 Congress St., Salem, MA 01970. 0147-9245/84 \$2.00 + \$.25.

DIGITAL DESIGN solicits editorial material and articles from engineers and scientists. Contributors should submit duplicate manuscripts typed with two spaces between lines. All illustrations should be clear; components on all schematics and line drawings should be labeled. The editors assume no responsibility for the safety or return of any unsolicited manuscripts.

The biggest selling keyboard switch in the Far East is made in the USA




Cherry MX Keymodule: Full travel, low profile, DIN compatible. It's superior technology that brings our Far Eastern customers to Cherry. The same technology that's available to you... off-the-shelf... at the lowest cost of any full-feature keyboard switch!

Cherry MX technology begins with the proven gold crossbar contact concept. Continues with low profile, easy operation, clean IC logic signals and long life (20×10^6).

Linear or tactile feel, spherical or cylindrical keycaps. Options, too: LEDs, integral diode, jumpers, momentary or alternate action. As single keymodules or in standard or custom keyboards.

For application data and samples, you need only call as far east (or west) as Cherry...or contact your local stocking Cherry distributor.



CHERRY KEYMODULES

CHERRY ELECTRICAL PRODUCTS CORP. 3631 Sunset Avenue, Waukegan, IL 60087 • 1-312-578-3500

See Us At NCC/Chicago, July 15 - 18, CHERRY BOOTH 1150.

Circle 10 on Reader Inquiry Card

"NO WAIT STATE"



- OF - THE - ART

by



Force's "NO WAIT STATE" - OF - THE - ART CPU-4 features the 68010 at 12.5MHz with 128KBytes of SRAM for your high speed applications.

Proven speed superior in benchmarks, the CPU-4 is ideal for high performance VMEbus applications. In fact, the "NO WAIT STATE" CPU-4 holds its own against 68020 CPU products operating with several wait states!

➤ Addition of the CPU-4 to Force's distinguished product family, designed and manufactured with years of VMEbus board engineering and production experience, assures you of a reliable, available, high performance CPU. CPU products available include:

CPU-1 Series The World's most popular and universal VMEbus CPU featuring 8/10MHz 68000, 128/512KBytes DRAM, 3 serial ports, RTC, and more. Over 6000 sold worldwide.

CPU-2 Series A highly versatile CPU incorporating the 8/10MHz 68010 with true "Dual Ported RAM" from 128KBytes up to 1MByte, multi protocol communications controller, floppy disk controller, PIT, and RTC.

CPU-3 Series The World's first UNIX* VMEbus board incorporating the 68010 CPU, 68451 MMU, and 68450 DMAC, 4 level bus arbiter, and serial I/O on one double Euro-card, 32 or 128K Bytes, zero wait state, SRAM CACHE mode operation

CPU-4 Series Additional features to those already mentioned include, a 68450 DMAC, 1 serial port, 2 parallel ports, RTC, and a floppy disk controller option.

NEW PRODUCT ADDITIONS

DRAM-E3M1+E3S3

➤ The 1MByte DRAM master operates stand-alone or with multiple 3MByte slaves offering optimum performance in 32 bit data/32 bit address, Byte parity check environments. Typical access time is 65ns (write) and 240ns (read) with parity generation.

CMC-1

As an intelligent monochrome or color controller for raster scan terminals, this

If the VMEbus boards you purchase aren't designed and manufactured by FORCE, chances are they aren't "NO WAIT STATE" - OF - THE - ART.

Call Force Computers today, the VMEbus specialist!

stand-alone VMEbus board offers interfaces for keyboard, lightpen, 2 serial ports and 1 Centronics parallel port.

ASCU-1/2

This new breed of high performance advanced system controller handles all exception signals on the VMEbus and contains powerful I/O devices such as a serial interface, Centronics parallel interface, 4 level bus arbiter, RTC, and GPIB interface (ASCU-2).


FORCE COMPUTERS INC.
727 University Ave.
Los Gatos, CA 95030
Phone (408) 354-3410 1
Tlx 172465
Telefax (408) 3957718

FORCE COMPUTERS GmbH
Daimlerstraße 9
D-8012 Ottobrunn
Telefon (0 89) 6 09 20 33 2
Telex 5 24 190 forc-d
Telefax (089) 6 09 77 93

FORCE COMPUTERS FRANCE
11, Rue Casteja
F-92100 Boulogne
Tel. (1) 620 37 37 3
Telex 206 304 forc-f
Telefax (1) 621 35 19

*Unix is a registered trademark of AT&T

I/O WITH I.Q.



These plug-in modules make the Mostek Intelligent VMEbus board completely user-configurable.

The Mostek VMEbus Intelligent I/O board.

VMEbus has always been a smart choice for flexible system solutions. And now, Mostek has made VMEbus even smarter. By introducing the MK75804 VMEbus Intelligent I/O board.

Using the VMEbus I/O board in your system gives you a high-performance communications interface that places minimal demands on system resources. And since we designed the I/O board to accept up to three plug-in modules, it's completely user-configurable.

You can select up to six independent, full-duplex serial channels in pairs, or combinations of serial, parallel or other interfaces. Either RS232 or RS422 for serial I/O, or a Centronics-compatible printer port, or a general-purpose, 16-bit parallel I/O port.

The choice is yours. And because the I/O board incorporates a 68000 16-bit microprocessor and 128K to 512K of DRAM, it's not just smarter. It's fast also. In fact, it's capable of a transfer rate in excess of 1 Mb/s when used with our optional four-channel DMA controller. What's more, we built in a firmware monitor, an optional power-up ROM that provides download, debug and diagnostic functions.

When you add it all up, our Intelligent I/O board is easily the most flexible hardware solution available for VMEbus applications. Which is just one of the ways we show our continuing commitment to VMEbus technology.

For more information, contact Mostek Corp., 1215 W. Crosby Road, MS2205, Carrollton, Texas 75006, or call 1-800-635-0200. In Texas, 214/466-8801. In Europe, (32) 02/762.18.80. In Japan, (03) 496-4221. In the Far East (Hong Kong), 5.681.157-9.



EDITOR'S COMMENT

Selling Technology To The Russians

No matter how tricky the Japanese are in matters of international trade, there's no chance we'll ever go to war with them again. Where would we get parts for our Toyotas and Hondas? Where would we buy our TVs, stereo systems, VCRs, Walkmans and maybe even (God forbid) our Megabit DRAMs? Meanwhile, the Mercedes, BMWs and Porsches keep on coming from the Fatherland while the Germans rake in dollars to buy our computers and microprocessors.

Despite some inequities (big ones in the case of Japan), the international trade system has kept the world out of a major war. Our economies are so intertwined that no matter how much we disagree we don't go to war over it. There may be a lesson here that could apply to our relations with the Russians.

The major areas where we have some export trade advantage (besides food) are mostly high tech items such as jet engines, aircraft, computers and semiconductors. Yet we have a government that's afraid the Russians might gain some military advantage if they buy our electronics. It's a mistake. Missiles can be guided with relatively simple microprocessors, and those computers that the Soviets can build or purchase elsewhere are adequate for some pretty sophisticated military systems. It isn't lack of technical sophistication that holds down advances in Eastern bloc electronics; it is the lack of an entrepreneurial infrastructure. We could give them all of our latest commercially available chips and computers and by the next generation of products they would be behind again. If we sell high technology to the Russians, they must eventually become dependent upon us. Our economies could eventually become meshed to a degree that war would be unlikely.

Of course, we can't be stupid about it. We should sell them the end product, not the means to produce it. Furthermore we should insist on hard currency as a means of payment. Perhaps we should tie in other purchases with the high tech items. For example, we could make them buy a Chevy with every VAX and a PC with every 68020. Of course the Japanese could also play this game—probably even better than us. But it wouldn't hurt to have the Soviet Union overrun with VCRs and Toyotas. Consider the effect that could have on Soviet society. Could totalitarianism long exist, confronted with the anarchy of rock videos?

Our government should worry less about whether the Russians buy technology that can be openly purchased around the world. The real concern should be whether we are letting the Department of Defense hamper international trade in those very areas where we are best able to compete. Given recent revelations about spying within the Navy it would seem that the DOD's time could be better spent. Operational plans are of more value to an enemy than the latest microprocessor. The health of a high technology industry that may depend on exports for 30% to 50% of its revenue is more important than catering to the paranoia of the military establishment.

— John Bond, Editor in Chief



Zycad announces high-speed simulation for every design.

No matter what size design you're doing — LSI, VLSI, VHSIC, sub-system, or whole system — there is a Zycad logic and fault simulation engine to fit your specific design verification needs. Now Zycad offers four families of simulation engines — dedicated, special-purpose processors that accelerate the design verification process far beyond conventional simulation techniques.

Logic Evaluator®

Speed and capacity to handle virtually any design verification task.

The Logic Evaluator enables both logic and fault simulation of almost any chip, component or system at speeds up to 16 million events per second. That's faster than the most expensive supercomputers, but the Logic Evaluator costs about the same as a minicomputer. Its fully modular design makes the Logic Evaluator conveniently field upgradable to a capacity of over 1 million modeling elements.

The Logic Evaluator is the right choice for large design projects or for distributed processing among several design teams.

¹MicroVAX is a registered trademark of Digital Equipment Corporation.
©1985 Zycad Corporation

Fault Evaluator

High percentage fault grading of VLSI and system designs.

The Fault Evaluator is a concurrent fault simulation engine that helps design engineers develop chips and systems that are fully tested, and helps test engineers design more effective test operands. It also permits full exercising of the logic design, revealing redundant or untestable portions of a circuit or system at the design stage.

Using a proven hardware-implemented concurrent fault simulation algorithm, the Fault Evaluator lets you process fault grading runs never before possible. And develop production tests efficiently and cost-effectively. If the quality of your product is important, the Fault Evaluator is the right choice.


Expeditor 100/200™


Introducing a powerful turnkey simulation package at a low price.

The new Expeditor is a turnkey, affordably priced logic and fault simulation package that is compact enough to fit under your desk. With it, you'll be able to simulate chips, boards or entire systems up to 32,000 modeling elements at a speed of one million events per second. So

logic and fault simulations that once took hours now take seconds.

Easily integrated by connecting to your small host, minicomputer or workstation network, the Expeditor turnkey package includes: ZILOS™, Zycad's user-friendly software interface, an Expeditor driver and an optional TTL library and hardware interface. The Expeditor is the right choice for an individual or multiple designers who need a turnkey simulation package with the speed and capacity to easily handle large designs.





rintor™

A high-speed personal simulation engine with full interactivity.

The Sprintor fits into a single bus slot of a workstation, the IBM® PC/AT and MicroVAX¹. Yet, despite its small size, the Sprintor is a powerful engine that delivers fast logic and fault simulation — up to 46,000 modeling elements at a speed of 200,000 events per second . . . perfect for chip, gate array or small system designs. And the Sprintor provides tightly coupled integration with workstation front-end software to allow full interactivity with behavioral-level language and hardware modeling systems.

For design engineers who need distributed processing capabilities plus outstanding simulation performance, all at an affordable price, the Sprintor is the right choice and will be available from workstation and PC vendors.



ystem Development Engine-SDE™

Breakthrough technology that makes concurrent hardware and software development practical.

Because it simulates up to 1.1 million modeling elements at over ONE BILLION events per second, the System Development Engine enables software development to begin as soon as the first functional block design is complete. A true “virtual hardware” system.

Years can be shaved off the system development cycle and the finished product can be superior to anything previously attainable. The System Development Engine is the right choice if you need to get a perfected electronic system to market years before the competition.

Now there is a Zycad logic and fault simulation engine available for virtually any design, host, designer team and budget. These engines represent the standard of the CAE industry, in terms of speed, price/performance, mean-time-between-failure (the Logic Evaluator is approaching two years), and the highest level of application engineer support. All of this has led to an installed base among the world's leading computer, telecommunications, semiconductor, defense and general electronic companies.

Call us today at (800) 631-5040 (In Minnesota call: 612-631-3175) and we'll send you complete information on any of our products. Or write us: Zycad Corporation, P.O. Box 12828, St. Paul, MN 55112.

Circle 11 on Reader Inquiry Card

ZYCAD™

We've been accused of refusing to break under pressure.



You Be The Judge.



In a reliability test, the Genicom 4000 line printer shuttle mechanism worked 24 hours a day

non-stop for two and a half years without a failure... that's the equivalent of 20 years normal operation.

This remarkable reliability is the result of a totally new, patented resonance shuttle mechanism. It's so perfectly balanced, vibration is virtually eliminated. And the Genicom 4000 is free of those moving parts that commonly fail in other line printers. In-

deed, the design is so innovative and simple, it has to be reliable.

The Genicom 4000 offers 300 or 600 lpm, data processing and letter quality printing, bar codes, 20 inch/sec paper slew, plus dual 6 pin tractors with paper reverse. But best of all, even under the pressure of extensive evaluations, it refused to break.

Call our Toll Free number for all the evidence.

GENICOM[®]

The Printers That Mean Business.

**See Us At
NCC '85
Booth #5511**

Genicom Corporation, Dept. 425J, Waynesboro, VA 22980. TOLL FREE 1-800-437-7468, In Virginia, call 1-703-949-1170.

Circle 16 on Reader Inquiry Card

HOTLINE

280 PSEC/GATE GATE ARRAY DEVELOPED Researchers from Mitsubishi reported on a 5000-gate gate array at the Custom IC Conference. Loaded delay time of 280 psec/gate is achieved with 3.28 mW power dissipation.

CRAY-2, SAID TO BE FASTEST SUPERCOMPUTER, INTRODUCED With two units shipped, Cray Research has formally introduced the Cray-2 with an OS based on UNIX System V. The liquid-cooled system is said to operate at 6-12 times the speed of the Cray-1 and requires 16 square feet of floor space.

DESIGN AND FOUNDRY SERVICES FOR ICs AVAILABLE FROM TEK IC foundry services for analog ASICs and CCDs are now available to the outside market from Tektronix Integrated Circuits Operation. CAD/CAE, E-beam lithography and bipolar ICs will also be offered on a contract basis.

JAPANESE CLAIM FASTEST AI MACHINE Researchers from NEC and the Institute for New Computer Technology report that they have built an AI computer that operates at 202 KLIPS (logical inferences per second) average.

DOCUMENT COMPANDING ON A CHIP AMD will introduce the 7970 compression/expansion processor for electronic document processing. Using CCITT-standard methods, the IC reduces bandwidth, time and storage requirements for bit-mapped 2-tone images by ratios as high as 50:1.

6 NSEC PROGRAMMABLE ARRAY LOGIC DEVICE INTRODUCED National Semiconductor has formally introduced the PL1016P8 PAL. The ECL device is said to be the fastest programmable device available, at a maximum input-to-output delay of 6 nsec, and is intended to replace multiple discrete ECL ICs.

ON-CHIP DIAGNOSTICS AGREED ON BY AMD, MMI A number of chips from MMI and AMD use a system of diagnostics on-chip that the firms have developed and are promoting as a standard.


GERMAN DSP TO INCLUDE MULTIPLIER, MEMORY AND I/O PORTS The UDPI 01, a new digital signal processor from ITT Intermetall, includes a 200 nsec fixed point multiplier, on-chip data and program memory and both serial and parallel ports.

COLOR WORKSTATIONS BASED ON MICROVAX II In addition to the 32-bit MicroVAX II, DEC has announced the VAXstation 520 which features a Tektronix 4125 graphics subsystem with 1280 x 1024 pixel resolution.


DECNET TO MIGRATE TO ISO STANDARD PROTOCOLS Digital Equipment Corp. has announced that DECnet protocols will be replaced with ISO OSI international standard networking software; this will allow intervendor networks with other machines supporting ISO or MAP 802.4 hardware and software.

25 NSEC 2K x 8 PROM TO DEBUT Texas Instruments plans to introduce a 2K x 8 bipolar PROM. The TBP38S16 may be available as soon as the third quarter.

TKO on the Multibus*



Supports up to four each
5 1/4" Winchester disk drives
5 1/4" floppy disk drives
QIC-02 streaming tape drives



Central Data's Multi-Media Controller (now with huge disk caching) wins another decision — with technological advantages not offered by any contenders.



This intelligent controller board delivers all the flexibility and advanced design features you need to improve the performance of any Multibus system. It supports up to four each standard 5 1/4" Winchester disk drives, 5 1/4" floppy disk drives and QIC-02 streaming tape drives. And to allow for a huge disk cache, the board includes a versatile LBX interface.

More punch from Central Data. The board's powerful 80188 processor supports a high-speed disk cache of 128K to 8 megabytes, significantly more than any contender's. New from Central Data, this

disk caching capability significantly improves throughput and performance levels for all disk drive subsystems.

Even the cache method is flexible, offering either track or sector mode by software selection. **Any** system can take advantage of this capability, including the UniPlus+* operating system offered by Central Data.

Make the winning decision. Stop sparring around with inflexible controllers — find out more about how Central Data's Multi-Media Controller can help you get the most from your Multibus system.

Call our design engineers toll-free for expert assistance with product selection and application information on this board or on our full line of quality Multibus boards.

Central Data offers a complete line of Tape and Disk Controllers. Call us for full details.

| BOARD | PROCESSOR | FLOPPY | QIC-02 | ST-506 | RAM | EPROM | FORMER PART# |
|-----------|-----------|-----------------|--------|--------|-------|-------|--------------|
| CD21/4300 | 80188 | 4-5-1/4" | 4 | 4 | 6/12K | 64K | B1030 |
| CD21/4130 | 8085A | 4-5-1/4" and 8" | — | — | 12K | 8K | 96/6130 |
| CD21/4120 | 8085A | 4-5-1/4" or 8" | — | — | 2K | 8K | 96/6120A |
| CD21/4055 | none | 4-5-1/4" | — | — | — | — | B1055 |
| CD21/4015 | none | 4-8" | — | — | — | — | B1015 |
| CD21/4029 | none | — | 4 | — | — | — | B1026 |

*Multibus is a trademark of Intel Corporation.
 UniPlus+ is a trademark of UniSoft Corporation.



Central Data

Central Data Corporation
 1602 Newton Drive
 Champaign, IL 61821-1098

TOLL FREE: (800) 482-0315
 (In Illinois: 217-359-8010)

TECHNOLOGY TRENDS

ICs

AT&T To Sell 32-Bit Microprocessor Family

AT&T has announced commercial availability of its 32-bit microprocessor chip set. Six chips and a development package consisting of UNIX-based software tools are now being offered. The announcement comes at a time when most of its competitors have already started shipping 32-bit processors. Despite the late introduction, much of the AT&T chip set is already in production.

The core of the chip set is the WE32100 microprocessor, a CMOS part housed in a 132-pin ceramic pin array. Execution speed is enhanced by an internal instruction queue and an internal instruction cache. The queue is an 8-byte FIFO that stores prefetched instructions. It is used for pipelining, enabling the microprocessor to overlap the execution of instructions while tracking each separately. The instruction cache is a 64-word on-chip cache used to increase the microprocessor's performance by reducing external memory reads for instruction fetches. When an instruction fetch from memory occurs, instruction data is placed both in the queue and in the cache. If that data is needed again it is fetched from the cache rather than from external memory, increasing the performance of the system.

The WE32100 microprocessor may be used in conjunction with the WE32101 MMU when virtual message storage is needed for a system. The MMU performs address translation by mapping virtual memory addresses to physical memory addresses. It supports both demand-paged and demand-segmented virtual memory systems and also allows the use of shared segments for intertask communication. Like the CPU, the

MMU is contained in a 132-pin ceramic pin-array package and requires a single 5V supply.

For applications that require number crunching capability, AT&T also offers the WE32106 Math Acceleration Unit (MAU). Fully compatible with the proposed IEEE standard for binary floating point arithmetic, it provides single (32-bit), double (64-bit) and double-extended precision (80-bit), in addition to add, subtract, multiply, divide, remainder, square root and compare operations. Operand, result, status and command information transfers take place over a 32-bit bidirectional data bus that provides the interface to the host microprocessor. Again a CMOS part, the MAU is housed in a 100-pin package and requires a 5V supply.

To simplify system interface functions, AT&T provides the WE32105 System Interface Unit, protocol compatible with the 32100 CPU and the 32101 MMU. It provides commonly used logic and control functions such as DMA and selectable wait-state generation for a range of system applications. Implemented in CMOS, it is housed in a 100-pin ceramic pin-array package. Other support chips, such as the WE32104 DMA controller and the WE32103 dynamic RAM controller will be available late in the year.

To aid system design, AT&T also offers a development system. The main component of the system, dubbed the WE321DS, is the 321AP Microprocessor Analysis Pod. The analysis pod can emulate the CPU, MMU and clock functions in the target system under development. It con-

tains two firmware debuggers: IMP, an assembly level debugger, and Ferret, a C symbolic debugger. The development system also includes UNIX System V-based software programs. An additional software option is available that supports logic analysis with the Hewlett-Packard 64000 logic development system.

Apart from AT&T, Motorola (Austin, TX) and National Semiconductor (Santa Clara, CA) appear to be the nearest to offering complete chip sets. Both Motorola's 68020 and the 68881 floating point unit are available now with the 68851 MMU sampling in the July/August time frame. Motorola's 68030 second generation processor may be available as soon as mid-1986. National Semiconductor's CPU, MMU and FPU are all available now in 10 MHz versions along with several support devices, such as a timing control unit, an interrupt controller and a DMA controller. A CMOS version of the 32016, the 32CT016, is expected to be available in both 6 MHz and 10 MHz versions in the third quarter. Intel (Santa Clara, CA) is expected to make a formal announcement of the long awaited iAPX386 by October.

The major market for these advanced 32-bit processors is in high-end workstations. Here, however, system builders have a lot of catching up to do, especially considering that their competitors, primarily the minicomputer houses, have the capability to introduce low-cost (\$20,000) systems based on their own captive semiconductor products.

—D. Wilson

PHOTOS COURTESY AT&T

ONLY EIKONIX[®]

DOES SO MUCH IN HIGH PERFORMANCE DIGITAL IMAGING CAMERAS.

EIKONIX[®] high-performance digital imaging cameras offer unique capabilities that clearly distinguish them from all others.

CCD or Photodiode Technology

Only EIKONIX offers a choice of high-resolution cameras employing either linear CCD (charge-coupled device) or photodiode technology. In fact, EIKONIX offers the highest-resolution CCD camera available anywhere, with up to 20 million pixels per image (4096 x 5200).

You can choose the economy and low-light capabilities of a CCD camera, or the greater dynamic range of a photodiode camera, *without sacrificing high resolution.*

Color or Monochrome

Only EIKONIX has a family of high-resolution cameras available for either monochrome (256 gray-scale levels) or color (a palette of 16 million colors) applications.

More User Control

Only EIKONIX cameras use a precision stepping-motor/lead-screw/ball-slide stage mechanism, which provides precise positioning of the array and eliminates one-dimensional

smearing. In addition, this mechanism allows asynchronous operation, so the user can control both scan speed and data collection rate. This eliminates the need for a separate "frame grabber" or dedicated processor, and frees the host computer for multi-tasking.

Buy Just What You Need

Only EIKONIX' broad product line lets OEMs and end users match needs precisely. Configurations range from bare-bones digital camera heads through complete image acquisition subsystems, including cameras, light sources, control electronics, imaging

See us at
SIGGRAPH
Booth #428

software, and interfaces for many widely used computers (including most DEC and Multibus-based systems).

More Applications

Only EIKONIX offers the performance and flexibility to handle the broadest range of the most demanding applications, including mapping, engineering drawing digitizing, graphic arts, CAD/CAM input, office automation, X-ray storage and analysis, textile pattern design, geological imaging, communications, animation and microscopy.

EIKONIX Know-How


Only EIKONIX digital imaging products are backed by our 17 years of experience in matching advanced electro-optical technology to a widening world of applications.

To find out what we can do to support your digital imaging applications, contact EIKONIX, 23 Crosby Drive, Bedford, MA 01730, (617) 275-5070.

EIKONIX[®]


Circle 56 on Reader Inquiry Card

TI's SN74AS888 series of bipolar ICs uses 8-bit slices; a combination of fabrication technologies provides fast switching times and low power consumption, typically 1.1W.



TECHNOLOGY TRENDS/ICs

Bit-Slice Chips Challenge 32-Bit Microprocessors

Despite the growing attention focused on 32-bit microprocessors, bit-slice chips offer alternative approaches. Many designers now favor segmented architectures, in contrast to the traditional universal chip approach. Functions such as graphics, memory control and I/O can be optimized if they are controlled individually. Furthermore, the architecture may be optimized for the specific application.

The performance and throughput of bit-slice devices may justify their use, in spite of higher power consumption, more packages per function and higher cost compared to microprocessors. Many of the systems that demand 32-bit performance take advantage of newer computer architectures that support pipelining and parallel processing. Additionally, newer fabrication technologies are being used for developing higher speed and lower power bit-slice devices.

Advanced Micro Devices (Sunnyvale, CA) set an industry standard with the Am2900 4-bit-slice series. The new AMD 29300 family is microcode compatible with the older 2900 series. But the

29300s are 32-bit wide chips, partitioned horizontally rather than vertically. This means that the register file is separated from the other data path elements. The chip set includes a 32-bit ALU, a 16-bit sequencer, a 64×18 bit register file, a 32×32 bit parallel multiplier and a 32-bit floating point processor. All of the chips run at a cycle time of 80 to 100 nsec. Power dissipation is high, at over 7W. Samples of the complete set are expected to be available in November.

Several companies are now offering bit-slice chips that use 8- and 16-bit vertical slices. Texas Instruments (Dallas, TX) has introduced its 8-bit-slice bipolar family, the 74AS888. For all but the year-old register file, TI's STL (Schottky transistor logic) technology is used for the family's internal logic, with interface circuitry implemented in low-power TTL. The process results in cycle times between 75 and 93 nsec. The STL gates require only a 2V power supply; the TTL section converts the signals to standard 5V levels. The combination of technologies allows the device to switch at high speeds, yet dissipate only 1.1W (typical).

Enhancements incorporated in the family include floating point normalization, BCD arithmetic and CRC for data integrity. Four parts are now offered; new devices will be announced in the future.


A new company riding on the popularity of the 2901 family is WaferScale Integration (San Jose, CA). The WS59016-C is comparable to an enhanced 16-bit version of the 2901. The chip is the equivalent of four 2901s and includes a carry-look-ahead similar to the 2902. WaferScale uses its standard-cell design system to enable a user to choose a cell from the cell library for specific architecture requirements. Fabricated in CMOS, the device consumes less than 1/27 the power of the 2901. Other cells in the library include common functions from the 2901 family such as a microprogram sequencer, a priority-interrupt expander and a status and shift control device.

Analog Devices (Norwood, MA) is offering bit-slice parts aimed at specific markets such as signal processing and analog-to-digital processing. The 16-bit chips are CMOS-based and have a 100 nsec cycle time. Samples are available now for its 32-bit floating point processor.

Cypress Semiconductor (Santa Clara, CA) offers 4-bit-slice CMOS parts that replace the 2901 family. The four units are expected to be faster than the bipolar version from AMD. Only one part is being sampled now. In addition to the 31 nsec cycle time, power consumption is less than one-fourth that of the AMD part.


Factors in the choice between bit-slice and monolithic include cost, power consumption and speed and efficiency of microcoding. While the cost of one bit-slice part may be more than another, the real cost may be in support circuitry such as PROM or RAM. All factors must be weighed against the specific requirements and demands of the application.

—MacNicol



The 7C901 bit-slice processor from Cypress Semiconductor is faster than AMD's industry-standard 2901, with a 31 nsec cycle time.

Panasonic Data Displays



And what's in back is a tightly designed chassis that offers you a range of compact displays to meet nearly any space limitations you set. You get the reduced circuit board area you want from compacts that also feature great reliability with minimal servicing.

Of course, our compacts don't sell on size alone. They offer exceptional performance, along with accessible controls and uncomplicated installation. All at affordable prices. And, to ensure quality control and long life, nearly every component is manufactured by our parent company, Matsushita Electric.

Whatever your requirements, we can meet them by offering:

- mid to super high resolution grades
- 5" to 17" monochrome and 9" to 19" color displays
- 15" and 17" monochrome page readers
- frame-mounted, fully enclosed cabinet or frameless kit
- active high voltage regulation on some models
- precision video circuits
- local engineering support

To find out more about what's behind our compact data displays, just call or write for our complete brochure. Panasonic Industrial Company, Computer Components Division, Data Display Department, One Panasonic Way, Secaucus, NJ 07094. (201) 392-4849.

Panasonic
Industrial Company

**It's what's in
back that keeps
us up front.**

Panasonic

See Us at SIGGRAPH Booth 348

Circle 24 on Reader Inquiry Card

TECHNOLOGY TRENDS

IMAGING

Three Flat Panel Display Technologies Mature For Use In Portable PCs

“Full screen” flat panel displays, based not on one technology but on three very different concepts, were revealed at this year’s Society for Information Display symposium in Orlando, FL. Liquid crystal, electroluminescent, and plasma gas discharge display technologies have all matured to the point where panels of 640×400 pixels appear technically feasible.

The significance of the full screen is that it offers display compatibility with existing personal computer equipment while the flat panel nature of the new designs brings true portability for the first time. Until now, portable terminals incorporating low-power liquid crystal displays (LCDs) have sacrificed screen size and computational ability to be able to operate from a battery.

The highest resolution on a flat panel

currently used in a commercial product is 640×256 display elements on the LCD of the Data General/One portable computer. The LCD elements are addressed in a traditional multiplexed electrode design. This gives DG’s unit, like LCD-screen portable computers from Apple, HP, Commodore, Kaypro and others, a poor screen image with low contrast and limited viewing angle.

A larger, 640×400 LCD panel demonstrated by Panelvision (Pittsburgh, PA), aims to overcome this problem by using active substrate addressing of the display. In this scheme, a thin-film transistor (Figure 1) is deposited at the site of each pixel, bringing the electronic switching needed for the display to function onto the panel itself. Most research efforts are concentrating on silicon—especially amorphous silicon—as the substrate semiconductor, but Panelvision

has chosen to pursue cadmium selenide.

Panelvision’s vice president of marketing, Thomas C. Maloney, claims the new panel has a contrast ratio of 20:1 used in a back-lit, transmissive mode of display and 8:1 for reflective viewing. Large multiplexed panels like Data General’s, which operate with reflected light, have contrast ratios less than 3:1, he claims.

In electroluminescence, the largest panel announced so far also made its debut at SID in the 640×400 resolution category. Planar Systems’ (Beaverton, OR) full page panel, designated EL66610, uses AC thin-film technology (*Digital Design*, January 1985, p. 20). The display area is larger than on Planar’s previous panel of 512×256 pixels (Figure 2) as a result of an improved electrical addressing configuration. The new electrode architecture has 200 row drivers and 2 sets of 640 column drivers, effectively halving the power consumption over the conventional layout.

Planar’s architecture also increases the time available to charge each column electrode. The drive scheme requires a 50V modulation supply, a -160V write supply and a 190V refresh supply. Maximum modulation power consumption is claimed to be 11.5W. Custom drive circuitry is fabricated in $3\mu\text{m}$ CMOS. These circuits are surface-mounted to a two-layer PC board. Overall panel thickness is about 20 mm.

Both Panelvision and Planar expect their panels to reach the market early next year. However, plasma panels of 640×400 resolution are already on the market from NEC, distributed in US by World Products (Sonoma, CA) and Panasonic (Secaucus, NJ). Panasonic uses DC drive, for a panel with 155 cd/m^2 brightness and a 100:1 contrast ratio from supply voltages of 200V and 5V. NEC, which also makes a 720×350 pixel device, uses AC technology.

—Aldersey-Williams




Figure 1: Microphotograph of the thin-film transistor substrate construction used in Panelvision's 640×400 pixel LCD.




Figure 2: Planar Systems' electroluminescent display demonstrates space-saving advantages over the CRT.

YOUR VAX IS MULTI-USER. YOUR ARRAY PROCESSOR SHOULD BE TOO.



Up to four VAX users can perform computationally-intensive scientific and engineering tasks simultaneously on Mini-MAP Plus4, CSPI's 32-bit floating point array processor. When you team your VAX with Mini-MAP Plus4, multi-user/multi-tasking applications are shifted off the VAX, freeing it for other tasks. No degradation of performance. No need to unload programs and data between jobs. And no "roll-in/roll out" overhead. These are three unique contributions that Mini-MAP Plus4 makes to array processing technology. And three reasons why Mini-MAP Plus4 is especially effective in systems where continuous AP production processing and AP program debugging must be simultaneously carried out.

High Throughput: To the VAX team, Mini-MAP Plus4 brings 28 MFLOPS and 13 MIPS of computational speed. That power, plus Mini-MAP Plus4's 64 MBytes of physical data memory, can speed your VAX-11/780 by a factor of 5 to 20 times.

FORTRAN Convenience: Mini-MAP Plus4's compiler lets you program directly in FORTRAN. And CSPI's Scientific Subroutine Library provides 300 highly optimized routines.

Compact and Energy-efficient: Mini-MAP Plus4 enters your work space easily. It requires a mere 10.5" (26.7 cm) in your DEC rack and is self-cooling. And if you need less capability now but want to upgrade later, CSPI offers a modular system that lets you build in increments.

So when user pressure is heavy and your computational tasks push against tight deadlines, you'll be glad to have Mini-MAP Plus4 on your VAX team. To find out how Mini-MAP Plus4 can work for you, call toll free 1 800 325-3110.



Circle 20 on Reader Inquiry Card

CSPI

THE ARRAY PROCESSORS

40 Linnell Circle, Billerica, Massachusetts 01821
617/272-6020 • TWX: 710-347-0176

DEC and VAX are trademarks of Digital Equipment Corporation.
Mini-MAP Plus4 is a trademark of CSPI.

TECHNOLOGY TRENDS

COMMUNICATIONS

Schemes To Interconnect Networks Aid Wide-Area Data Transfer

Communication networks have sprung up in many forms to serve department needs, creating incompatibility on a larger scale. Resources on various local area networks (LANs), wide area networks (WANs) and mainframe computer networks cannot easily be shared. Network vendors may provide gateways into widely used mainframes and noncompeting networks. The need is so great that several companies with no network of their own have introduced network interconnect products.

Banyan (Westboro, MA) was out early with a virtual networking switch (see *Digital Design*, November 1984, p. 34). Since then, California Network Systems (Milpitas, CA) has announced an OEM internetworking connectivity scheme. At this year's Interface show, ComDesign (Goleta, CA) discussed the FutureCom 2000 Integrated Area Network, and Doelz Networks (Irvine, CA) presented a virtual circuit packet switch. All of these products are designed to interconnect devices on incompatible networks.

California Network Systems' initial product line provides OEMs links from other LANs into SNA. Three products provide varying performance. The first level is a software-only SNA gateway to run on a PC card, either OEM/SNA for LAN vendor configuration or SNA/3270 for IBM PC Networks. At the next level, the company offers a ComCard on the PC bus. With an 80188 on-board, it executes the gateway function considerably faster than the PC's own 8088. The NetServer box has 14 IBM PC bus slots, one for the system master, the others for ComCards or other network interface cards.

Three levels of products are also included in the FutureCom 2000 from ComDesign. They provide a local server for Ethernet that concentrates up to 32 devices onto the LAN cable, a remote server for RS-232 WANs and a Network Server that provides a gateway between Ethernets or between Ethernet and RS-232 systems (Figure 1).

The Banyan approach uses a central virtual circuit switch in which a front end connects to various LANs, and a back end interfaces to other Banyan servers, the public data network or a host. The 68000-based system supports Ethernet, Omninet, Pronet, RS422 and Applebus LANs and 3270 emulation. Services include file, print, backup and a naming and addressing system.

Esprit One from Doelz is also a virtual circuit switch, but it uses packets that serve as envelopes for any format of data. Data bits from each connected device are enclosed in packets standard to all Doelz concentrators and switches, with no format or protocol conversion. In combination with 68000-based hardware and a real-time OS, this provides rapid transmission and low overhead.

All of these systems except the California Network scheme, which operates around SNA, use proprietary protocols, operating systems or both. This makes writing code for a specific protocol or network configuration difficult. Other shortcomings are in scope. For example, Ethernet is the only network supported by ComDesign, and SNA the only option for California Networks. In the case of Doelz, no protocol translation is used, so the network only provides a shared medium for transmission between

Figure 1: ComDesign's FutureCom 2000 system uses LS2000 local servers for concentrating devices onto Ethernet, RS2000 remote servers to concentrate onto long-haul channels and NS2000 network servers to interconnect between LANs and WANs.



devices that use compatible formats.

Another method of interconnecting between networks is to use satellite channels from Vitalink (Mountain View, CA). TransLAN, marketed jointly with DEC, operates at the link level, below the higher layer protocols. This provides high throughput, but means that only like networks can be interconnected: Vitalink connects only Ethernet to Ethernet.

Network operating systems like those from Novell (Orem, UT) and Waterloo Microsystems (Waterloo, Ontario, Canada) also allow communications between separate hardware networks. This generally provides good connectivity functions. The drawbacks are that they are only for PCs, users must learn a new system and OS software must be added.

Gateways from LAN vendors are common. Although designed to heighten the market for the company's product, they are well designed to operate from that particular LAN. If connections are mainly within the LAN with only occasional need for links into other systems, they may work well.

Digital PBX systems may also interconnect various computers and networks. For example, Micom (Chatsworth, CA) has SNA and X.25 modules for the Instant Micro600 PABX, as well as various multiplexers. The acquisition of Interlan (Boxborough, MA) suggests that a LAN interface may be forthcoming as well.

Few of the products currently available address both higher level software issues and a wide range of products. Communication software, especially between unlike machines and OSs, is complex. Now that the problem of interconnecting the various networks within one organization has been identified, the more difficult task of evaluating options must be undertaken. Universal internetworking is yet to come, but the field is opening up and the limited interfacing available may be adequate for some applications.

—Pingry

NOW-GCR AND PE STREAMERS THAT REALLY DRIVE DOWN THE COST OF OWNERSHIP.

CHOICE OF DENSITIES: The 92181 runs at 25 ips start/stop and 100 ips streaming with ANSI Standard 1600 bpi, Phase-encoded (PE) format. The 92185 runs at 25 ips and 75 ips streaming with ANSI Standard 6250 bpi, Group Coded (GCR) format; 25 ips start/stop and 75 ips streaming with PE format.



**TOLL FREE
HOTLINE**

**1-800-828-8001
EXT. 82**

**IN MINNESOTA
(612) 921-4400**

EASY TO OPERATE: touch sensitive switches and LED indicators with decimal readouts. Tape threading guides allow simple, fast loading.

MAINTAINABILITY MEANS RELIABILITY. Keystone tape units need no field adjustments of any kind. No scheduled preventive maintenance either.

AIR BEARINGS give better tape control, cut media stress and wear caused by spring-loaded guides and rollers. Tape rides on a cushion of air.

GCR TAPE PATH. Unique, patented tape path (only 13"), solid-state tension sensing, and μ P-controlled servos for precise high-density tape motion control.

SIMPLE MECHANICAL DESIGN. No tension arms, vacuum columns, capstan motors or guide rollers.

THE KEYSTONE™ SERIES

We designed the Keystone Series with built-in diagnostics and maintenance features that make it simple to operate, easy to service, low in life-cycle costs. For more information, call your local Control Data OEM Sales Representative or write: OEM Product Sales, MNB04A, Control Data Corporation, P.O. Box 0, Minneapolis, MN 55440.

GD CONTROL DATA



TECHNOLOGY TRENDS

DESIGN TOOLS

GATE ARRAY DESIGN UPDATE: Simulation And Routing Considerations

Digital Design published a three-part series on designing a digital crosspoint switch using a CMOS gate array in January, February and March of this year. An update report was then published in May. This update report focuses on simulation procedures using Valid Logic's (San Jose, CA) Scaldsystem workstation and LSI Logic's (Milpitas, CA) Design Verifier software. Considerations surrounding the proper array choice are also explored.

As described in the May update, the Design Verifier provides the designer with statistically derived interconnect wiring delays for simulation. If the Design Verifier is not used, these delays are based on a fixed fan-out. When running the Design Verifier together with the Scaldsystem, simulation and timing

analysis are performed simultaneously. When the Scaldsystem is used alone, however, the two are done independently. Preparing and executing a simulation with the Design Verifier running on the workstation is a straightforward task. Valid's CAE software executes both batch and interactive simulations. At least one batch mode simulation is run on the workstation with the same input test vectors that are used for execution of the simulation on LSI Logic's mainframe-based LDS system. Simulation on the larger computer, done after routing, uses

actual wire delays.

To execute a simulation, various files, including a test vector file, must be prepared. The designer must also construct an SMEM module, which functions as a RAM cell for the test vectors. The SMEM module for the digital crosspoint switch is shown in **Figure 1**. When adding the SMEM module to the design, values are first assigned to CLOCK ASSERTION (CLK), SIZE, NUMWDS and ADWDTH.

CLK defines the timing sequence for the test vectors. SIZE is calculated by adding up the number of input pins, bidirectional pins and enable signals. NUMWDS determines the total number of simulation patterns to be loaded into the RAM. ADWDTH is related to NUMWDS and defines the address width for the RAM. ADWDTH is the exponent of 2 that is equal to or greater than NUMWDS; since NUMWDS for the crosspoint switch is 137, ADWDTH is equal to 8. (If 2 were raised to the 7th power, the result would be 128, which would be unacceptable because it is less than 137.)

Configuring the SMEM module with all of the circuit input signals, bidirectional signals and enable lines is the next step. As illustrated, the CLK provides synchronization for directing test vectors from the SMEM module into the circuit. The final step is to compile a simulation file and execute the simulation.




Figure 2: When routing a gate array, the number of interconnections determines whether the design can be routed on a given part. Bus structures, which consume substantial area on the chip, are often the cause of routing difficulties. The graph illustrates that as the number of buses increases, the percentage of available gates decreases.




Figure 1: Running a simulation on Valid Logic's Scaldsystem and LSI Logic's Design Verifier requires the creation of an SMEM module. The SMEM module functions as a storage element for the simulation vectors. Shown is the SMEM module configured for simulation of Digital Design's digital crosspoint switch. The signals found at the output of the SMEM module are the inputs to the digital crosspoint switch.

As the design approaches the back end of the design cycle, routing becomes a crucial issue. In the previous update report, the Design Verifier provided an estimate of the routability of the design. The Verifier was run twice: once with a 1404-gate target array and once with a 2224-gate chip. With the 1404-gate chip, the design was approximately 88% automatically routable, whereas 100% auto-routing was feasible with the 2224-gate part. Consulting with LSI Logic, it was determined that the remaining 12% of connections could probably be manually routed by LSI Logic's routing specialists. In most instances where the router is unable to make the last 10% to 15% of the connections automatically, LSI will attempt to manually route the signals and thus keep the design in the smallest possible array.

In general, routing is a function of the number of gates, number of nodes, chip size, average fan-out and logic organization. Number of bus structures is another

factor that contributes to routability of a design. **Figure 2** shows that increasing the number of interconnects decreases the number of available gates. In designs with bus-oriented architectures, added difficulty in routing should be taken into account when determining the total number of gates.

Circuits demanding maximum performance from CMOS technology are accompanied by increased gate counts. Extra buffering is required that typically results in a gate count increase of 5% to 15%. For maximum performance designs, LSI Logic recommends using "AO" macrocell elements which perform low levels of gating with a single inversion in low fan-out circuits, keeping fan-out to a maximum of four or adding a buffer, minimizing the number of NOR gates, minimizing the number of gate inputs since two-input gates are much faster than four-input gates and using flip-flop Q outputs since they are valid before the complementary Q output.

This is the last report on *Digital Design's* gate array design project. Although we intended to fabricate the chip, Datacube's (Peabody, MA) system specification changed, changing the chip's functional requirements. The time needed for circuit alterations and additional design verification to meet the new specification cannot be justified in light of the project's purpose. Similarly, in its present configuration, there is little justification for incurring tooling and fabrication expenses.

We regret that the array will not be fabricated; however, the project overall has been a huge success. Going through the exercise of designing a gate array on a workstation has given *Digital Design* far greater insight into both CAD/CAE and semicustom technology. This added knowledge enables *Digital Design* to provide further in-depth analysis of the design issues surrounding this rapidly growing segment of design technology.

—Collett

DY-4 processor cards offer many and varied functions such as serial or parallel I/O; master or slave configurations; on-board CTC; dynamic RAM refresh; all sockets 28-pin bytewise RAM or EPROM configurable

68008

DSTD-168 Two serial channels; 3 channel CTC; 2 memory sockets; dynamic RAM refresh, 68000 s/w compatible

8088

DSTD-187 8087 math option; RMX co-processor; 2 serial channels; 1 memory socket; dynamic RAM refresh.

DSTD-188 8087 math option; 2 memory sockets; dynamic RAM refresh; 2 serial channels.

Z80

DSTD-101 TWO 8 bit parallel I/O ports; 4 channel CTC; 5 memory sockets; STD master


DSTD-102 Two serial I/O ports; 4 channel CTC; 3 memory sockets.

DSTD-103 Two 8 bit parallel I/O ports; 4 channel CTC; 5 memory sockets; STD slave.

Z80 CP/M operating system available; MS DOS for 8088-based cards. Additional peripheral STD cards offered including graphics, serial and parallel I/O, FDC, SASI interface, alpha-numeric CRT controller and local area networking.

68008/8088/Z80

Single Board Micro computer for the STD Bus




DSTD 103 DSTD 101 DSTD 187

DSTD 168 DSTD 102 DSTD 188

DY-4 Systems Inc.
888 Lady Ellen Place
Ottawa, Ontario K1Z 5M1
(613) 728-3711
Tlx: 06-217780

DY-4 Systems Inc.
1475 S. Bascom Ave.
Suite 202,
Campbell, CA 95008
(408) 377-9822

DY-4 Systems Inc.
Solbakken 48, DK-8450
Hammel, Denmark
(06) 96-3624
Tlx: 60938



DY-4 SYSTEMS INC.

Circle 19 on Reader Inquiry Card

TECHNOLOGY TRENDS

BOARDS

Disk/Tape Controllers Declare Independence With SCSI

Increased system throughput and device independence make the Small Computer System Interface (SCSI) a desirable choice for disk and tape controllers. Moving peripherals from the system backplane to a separate I/O bus like SCSI removes a large source of bus traffic in transfers between disk and tape and the host CPU. Furthermore, it isolates host processors and operating systems from modifications in disk and tape drive configurations.

The proposed ANSI X3T9.2 standard expands the original emphasis of the Shugart Associates Systems Interface (SASI) for floppy and rigid disk drives to include other peripheral devices as well. Under either scheme, hardware host adapters translate the unique message protocol of a specific system bus (e.g., IBM PC, Multibus, VMEbus) to a common protocol understood by all SCSI devices. In addition, software commands are issued for such generic device types as disk drives, tape drives and printers. Specific device information like sector addresses is omitted. In other words, SCSI/SASI presents a logical system interface to peripherals rather than a device-level interface.

Treating peripherals as generic classes simplifies the host operating system by moving formatting, error correction, physical sector addressing and other device-specific operations to intelligent controllers. The host operating system still retains its supervisory functions such as event scheduling and interrupt handling, but users must rewrite the device drivers to eliminate commands geared to a specific controller/peripheral combination.

SCSI peripheral controllers assume responsibility for physically addressing

devices; host processors select the appropriate logical device and specify the first block address as well as the number of data blocks to be transferred. Up to 64 Kbytes of data can be transferred with a single host command. Larger amounts of data from either single or multiple devices are accommodated through the use of chained commands.

With a system-level interface, designers can place the controller anywhere in their system—it no longer needs to reside on the host backplane. For example, rigid disk drives from several vendors now include SCSI controllers; tape and floppy drives will probably follow suit. Integrating a SCSI controller on the drive becomes more feasible as key functions like formatting, data separation and serial/deserialization are implemented in silicon (see *Digital Design*, June 1985, p. 32).

By using SCSI features like device independence and auto configure, device drivers do not need to be rewritten when changing or upgrading disks. The ACB-5500 from Adaptec controls up to four ST506/ST412 Winchester disks and includes 32-bit ECC and parity checking to improve reliability of data to the system.

Many current embedded SCSI controllers require a separate board from that used for the drive electronics. A device level interface such as ST506 or SMD is also needed to translate SCSI system level commands to the control signals executed by the drive. Drive vendors using this scheme include Cynthia Peripherals (Palo Alto, CA), Fujitsu America (Sunnyvale, CA), Iomega (Salt Lake City, UT) and Shugart Associates (Sunnyvale, CA).

Applied Information Memories (Milpitas, CA) and Xebec (Sunnyvale, CA)





Figure 1: The SCSI bus can be described as a peer-to-peer architecture. Host adapters and controllers can assume either the role of request initiators or targets to perform operations. Up to eight host adapters and eight controllers can be attached in this manner.

**An advanced
SCSI 3½-inch
Winchester Disk
Controller. . .**

**Introducing
the OMTI 3100**

Actual Size

The OMTI 3100 SCSI Intelligent Winchester Disk Controller is designed to attach up to two drives on a 3½-inch footprint PC board to the SCSI (Small Computer System Interface) bus.

The OMTI 3100 supports the industry standard ST506/412 disk drive interface for 3½-inch and 5¼-inch Winchester disks.


The host interface is the popular SCSI bus which connects through host adapters to a wide variety of system architectures for mini and micro computers. SCSI includes a high level command set which protects system software from changes as future generations of disk drives are added to the I/O configuration.

The OMTI 3100 uses our advanced VLSI chip set to implement the most compact SCSI to ST412 disk controller available today. Only ten IC's are used on the OMTI 3100 and six of the ten are proprietary to SMS.

The OMTI 3100 controller provides consecutive sector (or non-interleaved) data transfer and multisector buffering (2Kbytes) between host and peripherals. It transfers a full track in one single disk revolution and transfers data on the SCSI bus at up to 1.2 Megabyte per second.

To find out more about the little hard disk controller that offers OEM's a big performance advantage, call SMS.

The advanced OMTI 3100 is one of many finely engineered SMS components. Scientific Micro Systems, Inc. manufactures a wide range of disk and tape controllers for SCSI, PC/XT and AT compatibles, Multibus*, Q-bus and Unibus** configurations.



Scientific Micro Systems, Inc.

339 North Bernardo Avenue P.O. Box 7777 Mountain View, CA 94039
(415) 964-5700 TWX 910-379-6577 TELEX 17-2555

SALES OFFICES: Seattle, WA (206) 883-8303; Boston, MA (617) 246-2540; Atlanta, GA (404) 296-2029; Morton Grove, IL (312) 966-2711; Melrose Park, IL (312) 345-5320; Arlington, TX (817) 429-8527; Laguna Hills, CA (714) 643-8046; Greensboro, NC (919) 292-8072; Mountain View, CA (415) 964-5700; Philadelphia, PA (215) 860-8626.
DISTRIBUTORS: United States-Arrow Electronics, Inc. (516) 694-6800; Canada-Allan Crawford Associates Ltd. (416) 890-2010

*Trademark of Intel Corporation **Trademark of Digital Equipment Corporation

Circle 29 on Reader Inquiry Card

TECHNOLOGY TRENDS/BOARDS

implement the SCSI controller on the same board as the disk drive electronics. Phil Devin of Xebec notes that the company needed to add a single chip for motor control to its SCSI controller to provide complete functionality. Seagate (Scotts Valley, CA) and Tandon (Chatsworth, CA) are also investigating this approach using SCSI controller chips from Western Digital (Irvine, CA).

Tape drives with embedded SCSI controllers are a ready means to back up rigid disk drives, since the interface proposal contains a COPY command that enables streaming operations without host intervention. Also, the interface has gained industry acceptance in its present SASI implementation. Tape drive manufacturers publicly supporting SCSI include Archive Corp. (Costa Mesa, CA) and Memtec Corp. (Salem, NH).

Embedded controllers work well on the SCSI bus since they can act as initiators or targets of bus transactions and thus do not rely on the host adapter to initiate each transaction like conventional stand-alone controller/peripheral combinations. Each controller can arbitrate with other devices for the bus, select a target (e.g., tape or cartridge disk drive) and initiate a transfer to that device.

Using such command schemes, task execution and I/O processing can occur simultaneously because host adapters can be disconnected from the SCSI bus once the host processor issues an I/O command. This frees the processor to execute other tasks. Controllers also disconnect from the bus after receiving the command from the host adapter. The SCSI bus remains free for other I/O operations until data needs to be transferred between the controller and the host adapter. Furthermore, peripherals and controllers can transfer data at 1.5 Mbytes/sec along the SCSI bus. Adequate buffering on the host adapter and the controller compensates for differing transfer rates between the SCSI bus and the system bus.


Although this scheme is more efficient than the master/slave protocol typically used on system backplane buses, it tends

to move the traffic from the host bus to the SCSI bus itself. Thus, the SCSI bus may become a bottleneck rather than a solution, especially if several devices attempt to access the bus at the same time. This can occur in a multitasking SCSI environment when two or more transactions are initiated at the same time (e.g., seeking and reading from a disk while writing to tape). Several disconnect and reconnect operations can overlap as each device goes off the SCSI bus to perform internal operations and comes back on to transfer data.

Daniel Loski of Scientific Microsystems (Mountain View, CA) claims that a multifunction controller such as the OMTI 5400 is better suited for supporting multiple drives performing overlapped operations than dedicated controllers for each peripheral. A multifunction controller does not access the SCSI bus for transfers between these drives since it would not access the bus for transfers between devices attached to it, but would use internal buffers as the means of transfer. In fact, he notes that the internal buffers on a multifunction controller are much smaller than those used on dedicated controllers (8 Kbytes vs. 16 Kbytes) since information need not be stored during the arbitration and selection process.

The choice of the appropriate controller represents only half of the equation. In fact, the intelligence of the host adapter largely determines the functionality of a SCSI implementation (Figure 1). A simple adapter composed of discrete logic continues to place the brunt of I/O supervision on the host processor. However, this scheme provides an easy way to add controllers and peripherals into existing systems and is the most inexpensive SCSI option. In addition, system software remains largely unchanged since the SCSI bus acts as an extension of the system backplane.

However, system overhead is not reduced when simple host adapters are used with dedicated controllers. About 50% of system bus capacity is usually dedicated



The Scientific Microsystems OMTI 5100 controller supports two fixed or removable 5 1/4" rigid disk drives. Non-interleaved data transfers and multisector buffering provide high throughput without overburdening the host. A VLSI chip set on OMTI SCSI controllers reduces part count on the board.

to servicing I/O operations, according to Loski. Minicomputers are notorious for bogging down in multitasking environments because their operating systems cannot speed data to the processor. Adaptec (Milpitas, CA), Emulex (Costa Mesa, CA) and NCR Corp. (Wichita, KS) have tackled this problem by moving I/O processing from the host operating system to the host adapter. This effectively frees 50% of the system bus for task execution.

Increasing the intelligence of the host adapter, however, also increases its cost. For example, microprocessors or high-speed discrete logic are needed to handle the arbitration and the selection/deselection protocols for multitasking (multiple device transactions on the same controller) or multithreading (multiple transactions occurring on the same SCSI bus). These costs further increase if large buffers are needed on the host adapter to streamline transfers between devices. On the other hand, Loski notes that a multifunction controller does not require such a sophisticated host adapter since the controller implements these functions on-board.

The wide range of options available within SCSI could prove daunting for even the most sophisticated designer. From embedded controllers to intelligent host adapters, users must carefully weigh the needs of their application and pick the appropriate mix to fit their budget since SCSI offers a solution for every price range.

—Aseo

We run with a great crowd.

Complete hardware/software compatibility.

Talk about easy interfacing. You can take a ZETA 824 or ZETA 836 plotter and plug it into virtually any computer made.

What's more, you'll be ready to run because our plotters understand a variety of computer protocols. Select the model for your application then just plug in and plot.

In fact, we're a plug compatible replacement for many plotters from HP, CalComp and Tektronix. Some models of our plotter can even run directly from your IBM cluster controller. Now that's easy interfacing.

When it comes to your favorite application packages, you'll be on safe ground too. Packages such as CADAM, TechniCAD, Euclid, P-CAD, AutoCAD and many more.

The most productive plotter for the money.

You'll be getting the highest output plotters for the money with our new ZETA 824CS and ZETA 836CS. More

finished plots. More productivity. Plus, these "D" and "E" format plotters let you run either single sheet or roll media.

Easy-to-use touch controls.

Your time is valuable. So we've made our touch controls simple – yet powerful. Set speed, pen pressure, liquid ink parameters, electronic limit sensing, windowing, scaling – all at the touch of a finger. Self-test and diagnostic plots too. Let us show you dozens of other time-saving operations in a brief demonstration.

Plotter specialists.

We've been designing hardware interfaces, plotting language emulators and high performance pen plotters for over 14 years. Nicolet also provides you with worldwide sales and service support.


Give us a call. See how easy it is to join the crowd.

Call (415) 372-7568.
Nicolet Computer Graphics
Division, 777 Arnold Drive,
Martinez, CA 94553
TWX 910-481-5951

NTE Nicolet
Computer Graphics Division

CADAM is a trademark of CADAM, Inc.
TechniCAD is a trademark of Tektronix, Inc.
Euclid is a trademark of MATRA DATAVISION, Inc.
P-CAD is a trademark of Personal CAD Systems.
AutoCAD is a trademark of Autodesk, Inc.

Circle 18 on Reader Inquiry Card



TECHNOLOGY TRENDS

PERIPHERALS

Cartridge Disks Rediscovered

The resurgence of the cartridge disk as a backup medium to fixed disk drives lends credence to the saying "The more things change, the more they stay the same." Originally spurned because of their relatively high cost compared to tape, cartridge disks are proving suitable for applications requiring file-oriented backup as well as immediate access to data. They have also found a place as the primary storage medium where removability serves as a security precaution.

The latest generation of cartridge drives has solved earlier problems of poor reliability and interchangeability by taking advantage of advances in media. Cartridge drive vendors have gone to standard disk interfaces, with SMD and ST506 the most common. In fact, except for their removability, these drives behave in the same manner as fixed disk drives since the same software drivers and hardware protocols are applicable to both.

The similarity in operation makes cartridge drives easier to use for file-oriented backup than tape drives. The primary drawback to tape drives is that, as serial access devices, individual files or records cannot be accessed in the same manner as on disk drives. This means that file-oriented backup and restore operations are slow, with average access times to a given sector on tape measured in seconds rather than milliseconds. Furthermore, potential users must write different device drivers and utilities to use tape drives.

Tape drives have been used for image backup, in which the contents of a fixed rigid disk drive are transferred byte for byte onto tape. This is useful when file systems are to be restored onto the same drive after a system crash. However, an

image backup typically will not separate out defective sectors, so if users attempt to use an image backup to restore their files onto another disk drive, they may find that they cannot access any data since the defect map of the new drive will probably not match that of the old one. This also holds true when users attempt to transfer their files to a higher capacity drive.

Still, tape drives have the advantages of higher capacity and lower cost. A single cartridge disk can store from 5 Mbytes to over 40 Mbytes, compared to a single 1/4" cartridge tape which stores 20-60 Mbytes, depending on the length used (300' to 600'). Furthermore, only databases re-

quiring immediate access to individual records (like medical images or circuit netlists) can justify the high cost of cartridge disks, typically \$100 each. When retrieval times are less critical, 1/4" cartridge tapes, at around \$30 each, can be used. Users should determine which files fit the criteria mentioned above and take advantage of the benefits of both mediums.

For either backup or primary storage, cartridges provide reliability approaching that of fixed rigid drives, yet allow information to be moved from one drive to another. Cartridge disks provide a suitable alternative for applications that have outgrown the storage capacity of floppy disk drives.



PHOTO COURTESY SYQUEST




Figure 1: The disk cartridge for the Model 360 from DMA Systems undergoes a double filtration process before read/write heads are inserted. Two sets of filters clean the air as it enters and leaves the cartridge, with the disk itself acting as a centrifugal pump.

Reliability starts with the design of the cartridge itself. As with the head/disk assembly of a fixed disk drive, attempts are made to seal off outside contaminants from cartridges in a variety of ways. Two sets of filters are typically used to clean the air as it enters and leaves the cartridge (Figure 1). In addition, rubber gaskets are often used to form a tight seal around any areas where the cartridge meets the outside world (e.g., spindle). Because the disk itself acts as an air pump, the cartridge is also positively pressurized so that leaks do not occur along the seams.

To achieve the clean environment found inside fixed disk drives, cartridges usually go through a purge cycle prior to inserting the read/write heads. Amcodyne (Longmont, CO) and DMA Systems (Goleta, CA) slowly lower the heads to the disk surface—a practice often followed by fixed disk vendors who also use conventional oxide media. On the other hand, Micro Storage (Santa Clara, CA) and SyQuest (Fremont, CA) rely on the carbon overcoating on their plated

media to resist head bouncing as the heads are lowered onto a special landing zone. Cartridge and fixed disk failure rates are nearly equal: MTBF estimates of 10,000 operating hours are common.

Beyond providing a reliable medium, disk cartridges must also be designed to be moved from one drive to another and access data accurately. To assure data interchange, vendors use self-aligning spindle mounts so that runout (or off-center effects) is minimized. In addition, Amcodyne, Century Data Systems (Anaheim, CA), DMA Systems, Micro Storage and SyQuest embed servo tracks on each disk surface to provide proper head/track alignment. Control Data (Minneapolis, MN) uses dedicated servo surfaces. As a further precaution, some drives go through a routine upon insertion of a new cartridge, trying to read the inside, middle and outside tracks of the disk.

Interchange capability also extends to the interface that is used. For 8" and larger drives, the SMD interface is preferred. SMD has the necessary signals

and commands to support removability because the interface was originally designed for removable disk drives. Cartridge drives using this interface include those from Amcodyne, Century Data Systems and Control Data Corp.

However, no cartridge drive interface exists for smaller drives. In fact, the ST506 interface has had several signals redefined to support drives from DMA Systems, Micro Storage and SyQuest. These redefined signals may or may not be supported by fixed disk drive controllers. Users should work closely with the cartridge drive vendors to select controllers that support the modified signal lines as well as to make any changes needed in existing software drivers to support these changes.

Cartridge disks provide a suitable alternative to floppy disks and tapes for file backup and removable storage. However, users must gauge their applications to determine which data justifies their high cost and limited capacity. In addition, decisions about drive/controller combinations should take into consideration the level of support that the interface provides and the number of modifications to software drivers needed. —Aseo

LETTERS

Dear Editor:

As a manufacturer of C-44 compatible computer boards, I noted several errors in the table comparing CMOS computer buses on page 32 of your April 1985 issue [*Digital Design*, "PC Clones Challenge Role Of STD Bus," p. 30].

First, in addition to the NSC-800 and 80C85 processors, both the Motorola 146805E2 and the Harris 80C88 microprocessors are currently available on the C-44 bus. In fact, I believe that Onset Computer Corp.'s CPU-80C88 was the first commercially available board level product using the CMOS 80C88 processor.

Next, the C-44 bus supports a 20-bit address space, not an 8-bit address space as shown in the table.

Finally, the C-44 bus specification requires that all logic signals be buffered onto the bus. The table is incorrect in stating that signals are not buffered.

Sincerely,

James K. Elwell, Vice President
Quartic Systems Inc.
Salt Lake City, UT

Dear Editor:

In the April, 1985 issue of *Digital Design*, there is a tabulated comparison of CMOS buses on page 32 ["PC Clones Challenge Role Of STD Bus," p. 30]. There are several mistakes and omissions in the C-44 bus column.

1. Processor Supported—Only the NSC-800 and 80C85 are listed. The 80C88 and CMOS 6805 processors are also supported.


2. Address—The table shows 8 address bits for the C-44 bus. It has always had 16 bits for address and bits A16 through A19 were recently promulgated by the bus inventor, bringing the number of address bits up to 20. The C-44 bus is the only one of the three buses cited which carries the multiplexed data and address bits onto the bus. The other two buses carry de-multiplexed address and data on the bus.

3. Signals buffered onto the bus—The table says no. I have purchased and used two versions of Onset Computer Corp.'s NSC-800 cards and all processor output signals are buffered before going to the bus. I cannot say from personal knowledge that any other cards from Onset or any cards from any other manufacturer buffer the processor signals onto the bus, but I'll take a bet at long odds that they all do.

I have great interest in all CMOS board level products and CMOS bus architectures. I suggest that a truly comprehensive survey of low power products would be well received by us in the remote data collection and processing business.

Yours truly,

Jim Ellis
US Geological Survey
Office of Earthquakes, Volcanoes and Engineering
Menlo Park, CA



The only instrument that's better designed than our positioning and tracking controls.

Actually, we haven't even been trying to develop an instrument better than the human hand. Perfection is tough to improve upon.

Instead, we've been working on instruments *for* the human hand. Proportional force and displacement joysticks. Control grips. Trackballs. We've enjoyed considerable success.

As a leader in positioning and tracking controls for over a quarter of a century, we've pioneered in researching the interaction of man and machine. We've made ourselves experts in the human factors in con-



trol design. Our focus has been on the needs of the operator — not just on the needs of the system.


Because these needs can vary so widely from application to application, and from operator to operator, we offer our controls in a profusion of sizes and models, with a full range of options. And if our standard models don't meet your needs, we'll work closely with you to design one that does.

Whatever your application or company size, we're ready to give you a helping hand. Call or write:

MS **Measurement Systems, Inc.**
121 Water Street, Norwalk, CT 06854, U.S.A.
(203) 838-5561

Circle 23 on Reader Inquiry Card

INTRODUCING PCVISION™'S BIG BROTHER



You already know the other members of our PCVISION family: **The PCVISION Frame Grabber** . . . The *first* image processing hardware for the IBM PC. **ImageAction** . . . The *first* user-friendly image processing software for personal computers. Now we are pleased to introduce the newest addition to the family:

The FG-100-AT

The *first* image processing hardware module designed specifically for the IBM PC AT. The FG-100-AT is the only board on the market that takes full advantage of the speed and expanded capabilities of the IBM PC AT. It gives you all the power and flexibility of the PCVISION Frame Grabber, and includes:

- 12 bit-planes of frame memory
- Real-time arithmetic and logic processing (summation, subtraction, averaging, etc.)
- Extensive graphic overlay capabilities
- Hardware pan, scroll, and zoom
- Memory access to eight pixels simultaneously

To find out how the FG-100-AT can provide your personal computer with the high-performance image processing capabilities of systems costing much more, call our Sales

Department at any of the numbers listed or write. Dealer inquiries are invited.

Leaders by Design

IMAGING

Imaging Technology Incorporated
600 West Cummings Park, Woburn, MA 01801
(617) 938-8444 Telex 948263

Southern California Office
Northern California Office
Midwestern Office

(714) 960-7676
(408) 748-9313
(313) 855-2680

Visit Booth #139 at SIGGRAPH '85.

© 1985 IMAGING TECHNOLOGY INCORPORATED
PCVISION™ and ImageAction™ are trademarks of Imaging Technology Incorporated.
IBM is a registered trademark of International Business Machines Corporation.

Array Processors —

Increasing Speed By MIPS, MOPS, FLOPS And GOPS

by Andrew Wilson, Sr. Technical Editor

Array processors serve as a bridge between the von Neumann architectures of the past and the SIMD/MIMD architectures of the future. Acting as fast coprocessors, these machines are able to offload many of the repetitive calculations needed in scientific applications. Because of this, they have found greatest applications in image and graphics processing, finite element analysis, robotic vision systems and systems for remote sensing.

With the introduction of these machines new terminology has followed to define just how fast is fast. Manufacturers will specify performance of machines in Millions of Instructions Per Second (MIPS), Million Operations Per Second (MOPS), Floating Point Operations Per Second (FLOPS) and Giga Operations Per Second (GOPS). In bids to out-MOPS or out-FLOPS the competition, manufacturers will sometimes "benchmark" their processors on the fastest element in the system. For example, the new 29117 16-bit microprocessor from AMD (Sunnyvale, CA) features a microcycle time of 100 nsec, which transfers into a 10 MHz data rate for all instructions. Manufacturers choosing to build an array processor around the device, may then claim they have a 10 MIPS machine. Similarly, manufacturers may claim high throughputs by comparing code written in Fortran for one machine with code written in assembly language on another. Worse still, some machines are optimized for specific functions (such as one-dimensional FFTs) and perform very effectively for these functions. Thus, when benchmarked against other machines performing a very different function, they perform very badly.

To add to this confusion, the host computer-interaction must be taken into account. If, for example, an array processor is performing high-speed calculations and results need to be transferred to the host frequently, then the AP must be interrupted and the data sent over a common bus. If the bus bandwidth is small the AP will remain idle for longer than it is active, slowing system performance incredibly.

Despite this

gloom and doom, many manufacturers have introduced machines which perform very effectively, using novel implementations to improve performance. For the user or potential buyer of such machines, one thing is apparent—the applications which the machine must perform must be carefully analyzed, the computationally intensive routines effectively documented and, if possible, submitted to the array processor manufacturer. In this way the user will obtain a true application specific benchmark.

In the first of three articles, Dr. Paz Kahana of CSPI (Billerica, MA) examines the concepts of computer precision in array processors—between that of 32-bit and 64-bit machines. Following this, Aaron Boxer of Masscomp (Westford, MA) shows how an array processor can be used to speed NMR imaging functions. Finally, Robert Frisch and Barry Eisenstein from Mercury Computer Systems (Lowell, MA) discuss the design of a new array processor.



Single Vs. Double Precision Computation

by Paz Y. Kahana, Ph.D., CSPI, Billerica, MA

When performing scientific or floating point oriented calculations using a digital computer, a decision must be made about the degree of precision required for the computation and the representation of the results. Often the decision is already made because of the resources available or the budgetary or the organizational concerns. However, all active buyers of scientific computing equipment make this decision during the brand selection process of the purchasing cycle.

It has become customary among scientists and engineers to specify single precision of computer word size for tasks such as FFTs, convolutions, image, and speech and signal processing. Problems involving (large) matrices, optimization algorithms and minimizations or maximizations mostly require the higher accuracy associated with double precision computer word representation.

Determining whether an application requires double or single precision involves a balance between selecting the right tool for the computation and not investing more than is neces-




Figure 1: The function $\text{Log}_{10}F(N)$, as defined in Equation 6, is for various matrix sizes N . The broken line represents the results of a single precision calculation on a VAX 11/780 (32-bit word length). The solid line represents the results of a double precision calculation on the MAP-6420 array processor (64-bit word length, 56 bits of mantissa and 8 bits of exponent) from CSPI attached to the same VAX 11/780.

sary. Computing machines (standalone computers and attached array processors) offering double precision capability (64 bits of word size) contain more hardware logic and software and are, therefore, more expensive to develop, purchase and maintain.

The general question of accuracy and precision of physical experiments can be traced to the very fundamentals of our understanding of nature. Different computer designs may affect the way the computer handles the arithmetics, round-off errors and overflow and underflow conditions.

Scientists are limited in their ability to conduct certain measurements. Such limitations can result from poorly or incompletely defined systems of reference, inaccurate measuring tools or techniques, practical considerations and even the most basic laws of nature. When developing theoretical models or other algorithms aimed at explaining and predicting experimentally observed data, it is often necessary to introduce approximations to reduce the problem to manageable size and complexity and sometimes even to obtain a solution at all.

It is likely to expect basic measurement and approximation errors in any problem even before it reaches the computer. There is nothing that can be done about this but to make sure that the situation does not get worse by the compounding of whatever errors the computer adds in the computations.

Digital computers store numbers in a fixed size computer word, particular to the computer architectural design. In all but a small number of cases, real numbers are only approximate representations to the true numbers. Errors in computer representations may result from rounding and chopping, loss of lead digits, and overflow and underflows. If X and Y are representations of X^0 and Y^0 , we may define the relative errors σ and τ as

$$x = (1 + \sigma) x^0$$

$$y = (1 + \tau) y^0$$

Equation 1

The relative error may be positive or negative, but we assume each to be "properly bounded" for the sake of this illustration. When X and Y are multiplied, the result $X*Y$ may be represented as

$$x * y = (1 + \varphi) x^0 y^0$$

Equation 2


where $*$ denotes the computer product, and φ behaves similarly to τ and σ . By combining Equation 1 and 2, and applying proper algebra we obtain

$$x * y = (1 + \Psi) x^0 y^0$$

with

$$\Psi = \sigma + \tau + \varphi + \sigma\tau + \sigma\varphi + \tau\varphi + \sigma\tau\varphi$$

Equation 3



Since σ , φ and τ are bounded, we may only retain leading terms,

$$\Psi \approx \sigma + \tau + \varphi \quad \text{Equation 4}$$

Since we do not know the signs of the individual relative errors, we must conclude that the relative error of the product is the sum of the relative errors of the product components. Of the three error sources τ and σ originate from the computer representation of X^0 and Y^0 , and φ is because the computer performs $X*Y$ and not the true product X^0Y^0 .

If the algorithm used calls for a long series of repeated multiplications, it is not hard to realize that the error introduced in one cycle will continue to propagate during each iteration. For this reason it is necessary to determine the required number of significant digits and ensure that the relative error of the final result is outside the range of the desired significant digits.

Similar analysis may be performed for machine additions and subtractions, and the following results are obtained

$$x \oplus y = (1 + \varphi) (x^0 + y^0)$$

$$x \ominus y = (1 + \varphi) (x^0 - y^0)$$

where \oplus and \ominus are machine defined operations. If $X, Y > 0$,

$$x \oplus y = x^0 + y^0 + \sigma x^0 + \tau y^0$$

so

$$x \oplus y = (1 + \Psi) (x^0 + y^0)$$

with

$$\Psi (x^0 + y^0) = \sigma x^0 + \tau y^0$$

This means that the add relative error in $X + Y$ is at most the machine relative error in one of the terms.

The subtract case is different since there is no bound for the relative error in the result because of errors in the operands. For example, consider

$$X^0 = 1.23456776 \text{ with } X^0 = 1.2345678$$

$$Y^0 = 1.23456774 \text{ with } Y^0 = 1.2345677 \quad \text{Equation 5}$$

The floating point result of $X^0 - Y^0$ is 2.00×10^{-8} , while $X - Y = 1.00 \times 10^{-7}$. As a result of the operation, the relative error grew from an order of a millionth of a percent to 400%. It was the loss of significant digit that caused this magnification in the relative error.

A sufficient theoretical background has been established to analyze the problem of accuracy in scientific and engineering computations. Error sources will originate from the fundamental uncertainties imposed by the laws of nature (such as the uncertainty principle), errors in measurement or statistical noise in data, errors due to approximations introduced into formalisms and theories to handle data and the variety of computer related errors caused when data is manipulated. The algorithm used and the way computers perform the computations (total word length, computer algebra definitions and number of bits of the mantissa and exponent) may affect the accuracy of the result. When floating point calculations are required, it is crucial to minimize computer generated errors since they are added to all the others previously introduced to the problem.

At the heart of most scientific and engineering floating point computations there are likely to be polynomial expansions, matrix algebra and eigenanalysis, numerical integration, linear transformations as well as nonlinear integrations and transformations. Although there are many other specialized applications in use, the majority of scientific applications contain elements of the above in core solvers or as part of the calculations.

Using the simplified but important results of the relative error analysis it can be understood why matrix computations, for example, require double precision. Diagonalization of a matrix involves a total number of multiplications proportional to N^2 , where N is the dimension of the matrix. For even medium matrices the error propagation may be so large that the results will not be accurate within the required number of significant digits. Optimization problems and minima and maxima problems involve subtraction of close numbers. The resulting relative error may be so large (**Equation 5**) that no logical or subsequent arithmetic operation can be meaningful in single precision. **Equation 5** will produce correct answers to 15 significant digits in double precision but will fail in single precision. Sometimes even simple function evaluation such as $\exp(x)$ or $\sin(x)$ may produce erroneous results in single precision. In these and other cases it is necessary to work in double precision.

The disciplines where such situations arise include hydrodynamics, structural and network analysis and quantum chemistry and physics, where large matrices are handled, flow analysis and reservoir modeling, where nonlinear differential equations are being solved, and chemical kinetics, scattering and reaction dynamics, where ordinary (differential) equations on motion are integrated.

By contrast, in applications such as image rotation and compression, linear transformations are applied only a few times. Error propagation is thus contained and single precision conditions will suffice.

Similarly, FFTs and convolutions are calculated by a suitable series expansion. Convergence can be tested for by making use of enough terms, and algorithms exist to ensure it. Again, single precision will provide good accuracy in such cases.

To demonstrate the difference in computational accuracy between single and double precision a simple computation was conducted, applying a commonly used problem—matrix inverse using column pivoting technique. A particular case of an

Video Distribution Amplifier in a Chip



A low cost solution to video distribution. VBB-1 is a high performance hybrid video amplifier/line driver with two outputs. Its specifications are outstanding and it is easy to use. Two of these and you have a 1 in, 4 out D.A. \$39.00 each singles - \$28.00 each hundreds.

Call or write:

(408) 225-1425

APERT-HERZOG CORPORATION
7007 Realm Dr. B3, San Jose, CA 95119

Circle 58 on Reader Inquiry Card

CUSTOMIZED CONDUCTIVE COATINGS

Our tin oxide coated glass
is uniquely superior!

WE OFFER:

- Low resistivity (as low as 5 ohms/sq.)
- Durability and abrasion resistance
- Extremely stable coatings
- Excellent uniformity and transmission
- Detailed, fine line patterned electrodes, finished & tested to your specifications
- Low cost too!

IDEAL FOR:

- Flat panel displays and CRT face plates (PGD, LCD, EL, VFD)
- Touch sensitive panels
- EMI/RFI Shielding
- Photovoltaics
- Anywhere you need conductive glass!

CHERRY DISPLAY PRODUCTS CORPORATION

15 FOUNDERS BOULEVARD, EL PASO, TEXAS 79906, (915) 779-7774
TELEX 749-321

Circle 60 on Reader Inquiry Card

ELECTRONIC IMAGING

ill-conditioned matrix was selected, that of the Hilbert matrix defined as

$$a_{i,j} = 1 \quad (V_j)$$

$$a_{i,j} = \frac{1}{i+j-1} \quad (i \neq 1)$$

where N is the matrix dimension.

The upper left part of the matrix is

$$\underline{\underline{A}} = \begin{bmatrix} 1 & 1 & 1 & 1 & \dots \\ 1/2 & 1/3 & 1/4 & 1/5 & \dots \\ 1/3 & 1/4 & 1/5 & 1/6 & \dots \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ \vdots & \vdots & \vdots & \vdots & \vdots \end{bmatrix}$$

After the matrix is inverted, we calculate the norm function defined as

$$F(N) = \frac{1}{N^2} \sum_{i=1}^N \sum_{j=1}^N \left[\sum_{k=1}^N a(i,k)a^{-1}(k,j) - \delta_{ij} \right] \quad \text{Equation 6}$$

This norm should vanish under ultimate precision conditions.

In **Figure 1** the behavior of $\text{Log}_{10}F(N)$ is plotted as the matrix dimension N is varied for both single and double precision calculations. The broken line represents the single precision (32 bits) results on a VAX 11/780. The solid line represents the results of the same calculation performed on the MAP-6420 array processor from CSPI (Billerica, MA) attached to the same VAX 11/780 in double precision (64-bit word length, 56 bits of mantissa and 8 bits of exponent).

There is a serious lack of precision in the single precision computation even for small matrices. For larger matrices neither computation is accurate, but the double precision run provides more accurate results over a range of matrix size.


This test is particularly demanding and is not expected to be encountered often in real applications. The matrix elements become of similar numerical magnitude in the lower part of the matrix resulting in a much larger subtraction error that is added to the multiplication error, which is the underlying reason for the severe ill-conditioning of the Hilbert matrix. Whereas many matrices in science and engineering applications do not behave like this, the illustration it provides is quite revealing; not even small matrices can always be diagonalized properly, and double precision must be used.

It is up to the user to understand the nature of the problem, the algorithm and the program used to solve it to make the decision concerning the required accuracy of the results and to determine whether single or double precision should be used. Increasing precision capability in the hardware has a direct monetary cost. Double precision can also be implemented in software but leads to series speed degradation which may be unacceptable. Despite its higher cost it is generally true that double precision capability is best implemented as a hardware feature supported by a high-level language compiler. **DD**

How useful did you find this article? Please circle the appropriate number on the Reader Inquiry Card.

Very Useful 622
Useful 623
Somewhat Useful 624

THE MOST SIGNIFICANT BREAKTHROUGH IN VAX SYSTEM PERFORMANCE SINCE THE ARRAY PROCESSOR.



Introducing the Aptec 2400 I/O Computer – a new *class* of computer that can increase the throughput of VAX-based systems as much as 40X. Simply. And economically.

By eliminating the I/O bottlenecks that limit performance, the Aptec I/O Computer makes your peripherals work faster and more efficiently. Including disks and tapes, APs, graphics/image processors, and special purpose devices.

It lets you achieve true super-computer performance with any VAX by allowing efficient integration of multiple array processors.

And, the Aptec I/O Computer permits dramatic new levels of performance in real-time data acquisition and analysis.

Not since the array processor has any development done so much to boost the performance of minicomputer systems.


Here's how it works: The Aptec I/O Computer creates an independent, 24 MB/sec, FILES-11 I/O environment that allows VAX-shared peripherals to transfer data at full speed, free from VAX bandwidth limitations.

From 1 to 200 MB of high speed memory is directly accessible by your attached peripherals and VAX.

And, the Aptec I/O Computer provides the intelligence to control peripherals, data transfers and peripheral computations – with minimal involvement of the VAX CPU, the VMS operating system or the Unibus.

Peripheral operations become more efficient. Attached processors work at peak efficiency. And your VAX is free to provide better service to your on-line users.

Learn how the Aptec 2400 I/O Computer can unleash the performance potential of your VAX system. For the complete story on this exciting new class of computer, write or call Aptec today.



The Aptec I/O Computer will unleash the performance potential of your VAX.



Aptec Computer Systems, Inc.
10180 SW Nimbus Ave.
Portland, OR 97223
(503) 620-9840
Telex 467167

VAX, Unibus and FILES-11 are registered trademarks of Digital Equipment Corp.
© Copyright 1985 Aptec Computer Systems, Inc.

Circle 69 on Reader Inquiry Card



"I had a breadboard habit I couldn't break."

It's hard to adopt new ways.

Some people who know the advantages still resist gate arrays and standard cell ICs. Many more, however, have made the switch. They got the support they needed from a kind of Breadboards Anonymous — the semicustom group at Gould AMI.

We've spent 18 years breaking down barriers to application-specific MOS/VLSI. The old concerns

have vanished. Development takes weeks, not months. Automation wipes out risk. A thousand pieces can be cost-effective.

Credit the revolution in computer-aided design.


CAD software has made the difference. How good is it? How about successful silicon on the first try!

All we need is correct logic.

It's figured the same way as TTL on a PC board, so that's no problem. Then, Gould AMI CAD software and cell libraries will give you a double-metal gate array or standard cell design that's correct by construction. Automatically.

We can meet you halfway — or all the way.

Success doesn't depend on who does the design — you, us, or an



outside design house. In every case, you keep total control. Control of proprietary information and circuitry. Control of the time and money that goes into the design.

Whether we do the design or not, we still make your job easier. With cell libraries for popular workstations and PCs. With bridges to convert your design data to our foundry formats. With design capability through distributors.

Even with convenient design centers where Gould AMI engineers can assist you on the spot. And of course, our silicon foundry is ready when you are.

Start breaking the breadboard habit today.

For details on Gould AMI semicustom products—and how easy it is to get started—call (408) 554-2311. Or write: Breadboards

Anonymous, Semicustom Products Marketing, Gould AMI Semiconductors, 3800 Homestead Road, Santa Clara, CA 95051. See if that old breadboard habit isn't on its last legs.

Breaking The Barriers to Semicustom ICs.

 **GOULD**
AMI Semiconductors

Circle 27 on Reader Inquiry Card

Integral Array Processor Speeds Image Processing

by Aaron Boxer, Masscomp, Westford, MA

Array processors (APs) are designed to perform repetitive computations on regular structures of data at much higher speeds than general-purpose CPUs. They take advantage of this regular structure to perform several pipelined operations simultaneously. Many scientific computation and image processing problems can be performed significantly faster on an AP. Until recently, array processing hardware was available only on supercomputers, and access to the hardware was very expensive. Today, APs are sold as peripherals that attach to mainframe mini-computers.

These peripheral APs communicate with the host computer through standard buses such as Intel's Multibus or DEC's Unibus. These buses are not always the fastest ones in the computer system. Data sets to be operated on are often very large and transferring this data between the host memory and the AP memory can be a bottleneck in the host/AP system's overall performance.

An integral AP made by Masscomp for its MC-500 series computers solves this bus bottleneck. The AP-501 does DMA transfers on the MC-500 private CPU-memory bus which has a bandwidth of 8 Mbytes/sec. This is two to three times the speed of the Multibus and the Unibus, thus lowering the performance impact of DMA data transfers between AP memory and MC-500 main memory.

NMR Imaging

Nuclear magnetic resonance (NMR) is rapidly gaining acceptance in the medical community as a medical imaging technique. It can produce high quality images of bone and tissue without the use of X-rays. **Figure 1** shows an NMR brain scan performed on an MC-500 with an AP-501 array processor from NMR Imaging Inc. (Houston, TX). Producing this image from the in-




Figure 1: NMR brain scan performed on an MC-500 with an AP-501 array processor.

put data required over six million floating point calculations.

Data is digitized into the MC-500 as 16-bit integers, arranged as a 256×256 array of complex numbers in the host main memory. This array is converted to single precision floating point numbers and a two-dimensional FFT is performed on the whole array. The magnitude of each complex number in the resulting 256×256 FFT array is computed. Finally, all the magnitudes are scaled into a range between 0 and 255 and converted to bytes for display as the pixels of an image like the one in the photo.


Data Flow

Figure 2 shows the architecture of the MC-500 with its AP and the flow of data. Analog signals from the NMR hardware are sampled by a 12-bit A/D converter. The converted data is transferred as 16-bit quantities to the host memory over the Multibus. The DACP is a high speed intelligent DMA controller that transfers the data directly from the A/D converter to MC-500 main memory. The 256×256 array of complex numbers occupies a total of 256 Kbytes of main memory.

The AP DMA transfers one row of 256 complex numbers at a time from main memory into AP memory over Masscomp's high speed CPU-memory bus. In the AP, the row of data is converted to single precision floating point numbers (IEEE 754 format) and a complex FFT is performed. The AP DMA transfers the result back to the host main memory on the CPU-memory bus. This process is repeated for all 256 rows of data. This first dimension of the 2D FFT produces a result array of 512 Kbytes in main memory.

The host CPU transposes rows and columns of the result in main memory before the second FFT. The AP DMA transfers a row of 256 complex single precision numbers from the transposed result array in main memory to AP memory and another

PUT YOUR DIGITAL SIGNAL PROCESSING



LESS THAN
\$160.00
PER MEGA OPS

IN OUR HANDS

And we'll cut the cost, power and size up to 90% of your
...RADAR...SONAR...MEDICAL IMAGER...ROBOTICS IMAGER...
...SPECTRUM ANALYZER...

DSP Systems' fixed point, Digital Signal Processing boards provide cost effective array and FFT processing because they contain all the functions you need on either one or two boards. Furthermore, your design costs are minimized by easy-to-use instructions that control execution of signal processing functions. As a result, your overall costs can be as much as 90% less than other systems with similar capability.

Use of high speed, low power VLSI lowers your power requirements and equipment size by as much as 90%, compared to older generation array processors.

A new addition to our product line, the Multibus A/D Converter (MAD), contains a dual-ported, dual-buffered

RAM that can provide DMA data at a 2 megawords/sec rate.

And, for those who want to customize microcoding, there are Multibus (MAP-DS) and VMEbus (VAP-DS) development systems, whose cross-assemblers employ quasi-English, "user-friendly" commands that simplify the addition of macroinstructions.

Compared to other signal processors of similar performance, DSP Systems' boards offer the lowest cost per function, per unit time, in a fraction of the size.

All FFT and array processor boards include: 50 KHz real time processing analog bandwidth, on-board HAMMING weighting and built-in self-test.

FFT1B FFT PROCESSOR

- Multibus-compatible
- 12 Easy-to-use Instructions
- Single-board FFT
- Up to 12 Mega OPS
- 8.6 msec for 1024-PT FFT (Complex)
- FFT/IFFT and Power Magnitude Instructions

AP-4 MINI-ARRAY PROCESSOR

- Multibus-compatible
- 16+ Easy-to-use Instructions
- Single-board Array Processor
- Up to 12 Mega OPS
- 8.5 msec for 1024-PT FFT (Complex)
- Peak Pick Instruction
- On-board DMA
- Optional Block Floating Point

VAP-64 MINI-ARRAY PROCESSOR

- VMEbus-compatible (16 Bits)
- 21+ Easy-to-use Instructions
- Two-board Array Processor
- Up to 10 Mega OPS
- 10.3 msec for 1024-PT FFT (Complex)
- Up to 64K Dual-Port RAM
- Complex Demodulation
- On-board DMA
- FIR Filter and Peak Pick
- Block Floating Point

MAD-12 MULTIBUS A/D CONVERTER

- Multibus-compatible
- Dual-port, Dual-buffered 4K RAM
- On-board Anti-alias Filter
- Supports High Speed DMA
- 25 KHz to 500 KHz Sample Rate
- 12 Bits Resolution

DSP

DSP SYSTEMS CORPORATION

1081 N. SHEPARD ST., M/S-E, ANAHEIM, CA 92806 PHONE (714) 630-1330 TELEX 298615 DSPS UR

Circle 21 on Reader Inquiry Card

FFT is performed. The magnitude of each complex number in the result is then calculated according to the formula:

$$MAG = \sqrt{\text{real}[X]^2 + \text{imaginary}[X]^2}$$

where X is a complex number. The result is scaled into the range of 0 to 255 and converted to bytes before the AP DMA transfers it back to the host main memory. This process is repeated for each of the 256 rows of the transposed matrix in the host main memory.

The final result is a 256 × 256 array of bytes that is transferred from main memory over the Multibus to the raster memory of Masscomp's graphics processor (GPM). There they are displayed as a 256 × 256 array of 8-bit pixels in an image like the one in Figure 1.

Parallel Processing

The NMR application was described as if each step was performed sequentially. Significant performance improvements can be realized by performing several functions in parallel with the AP and the CPU.

A high degree of parallelism can be achieved by treating each row of 256 complex elements as a separate set of data. All the operations that can be performed on a row by the AP or the CPU are completed before the data is moved to the next piece of hardware. Figure 3 represents a "snapshot" of several pieces of the first FFT in the NMR computation occurring at once.

The AP in Figure 3 is performing DMA transfers and vector calculations simultaneously. Row 3 of the raw 16-bit integer data from main memory is being DMA transferred into the AP vector memory while the AP vector hardware is converting row 2 into floating point numbers and doing the complex FFT on it. The previously completed FFT of row 1 is also DMA transferred back to main memory.

The AP requires 1.5 msec to convert to floating point format and perform an FFT on the 256 elements in row 2. The DMA transfer from main memory of row 3 into the AP takes 0.35 msec. DMA transfer of the completed FFT of row 1 from AP memory back to main memory takes 0.4 msec. DMA hardware in the AP performs the two transfers serially rather than simultaneously. They total 0.75 msec which is less than the computation time on row 2. DMA time is not a bottleneck in the AP pro-




Figure 3: Parallel processing in NMR application.

cess since it takes less time to transfer row 1 out and row 3 in than it does to perform the computations on row 2.

The CPU transposes the FFT from row 0 in main memory into a column matrix in main memory for the next FFT concurrently with the AP activity mentioned. This takes 1.3 msec for the row of 256 complex floating point numbers. The CPU also takes 0.4 msec to issue instructions to the AP to perform the computations and the DMA transfers.

The CPU tasks take 1.7 msec which is longer than the AP tasks. The application software is designed so all the AP tasks and AP computations do not begin until the CPU has issued the current set of AP instructions and transposed a row of FFT data. The 1.7 msec of CPU tasks is repeated 256 times for a total of 425 msec for the first FFT of the NMR imaging computation.

In the second FFT, the CPU's only task is issuing instructions to the AP. The DMA transfers between the host main memory and the memory occur simultaneously with AP computations.

Each column of 256 complex floating point elements contains all the information necessary to produce one column of 256 bytes for the final image. Therefore each column of complex data is transferred from host main memory to AP memory only once, and all the computations to produce the column of bytes are performed before returning the result to the host memory. These tasks include the second FFT, the magnitude calculation scaling to a 0 to 255 range and the conversion to bytes. All computations combined require 6.9 msec per column for a total of 1.7 sec for all 256 columns.

The 256 × 256 byte pixel array is now ready for display on the MC-500 graphics display as an image. The total time to perform the 6 million floating point computations required for the photo is 2.2 seconds.

The application described took about 90 seconds on an MC-500 without an AP. NMR Imaging Inc. added a single-board AP and partitioned the problem into parallel tasks that could be divided between the AP and the host CPU. The result was a 30 times performance improvement for about a 20% higher system price.




Figure 2: Data flow path for NMR imaging application.

How useful did you find this article? Please circle the appropriate number on the Reader Inquiry Card.

| | |
|-----------------------|-----|
| Very Useful | 625 |
| Useful | 626 |
| Somewhat Useful | 627 |

Thinking of Array Processors?



Think Analogic.

The Natural Selection

There's more to throughput than megaflops.

Analogic's AP500 Array Processor delivers more real high-speed computing power per dollar than any competitive machine. Although it's convenient to rate an array processor's operation by megaflop values, claims for lots of megaflops mean little in measuring its performance when handling real data in your real-world application.

That's why we have invested tens of thousands of hours of hardware and software engineering to create this new generation array processor. *With the AP500, you get the reliable high-speed throughput you need at a price you can afford.*

Efficiency is the key.

The AP500's total system architecture combines innovative hardware and software with proven design concepts to achieve data processing efficiencies significantly better than the competition. In the AP500, activities such as high-speed computation,

DMA/PIO, and control operations can proceed at full speed, *virtually independent of one another*, so actual throughput is comparable to far more costly machines. For example, the AP500 performs 1024-pt complex FFTs in 4.68 ms, and 100-by-100 matrix inversions in 649 ms.

See for yourself.

Check out the AP500. We believe you'll find its pipelined architecture, full floating point accuracy, powerful I/O capabilities, and complete, fully supported software to be the *most cost effective answer* to your high-speed computing requirements.

We invite comparison. Run your benchmarks on the AP500. We're sure you'll agree that it's the natural selection.

For additional information, telephone (617) 246-0300 (Outside of Massachusetts 1-800-237-1011). Or write to Analogic Corporation, Computing Systems Products Group, Audubon Road, Wakefield, Massachusetts 01880.

ANALOGIC ■
COMPUTING SYSTEMS PRODUCTS GROUP

Circle 30 on Reader Inquiry Card

Modular Array Processor Features Dual Processor Design

by Robert Frisch and Barry Eisenstein, Mercury Computer Systems, Lowell, MA

There are two major problems associated with array processors: lack of compute power and difficulty of use. Although some array processors (APs) offer high throughput, they require the user to program in microcode. Other APs reduce the programming task, either by providing support in a high-level language such as Fortran or by providing the customer with a library of preprogrammed functions. However, these approaches reduce the system's performance, limit its flexibility or both.

Many APs are also optimized for a single data format and a specific type of operation, such as the FFT. Such machines fall short of advertised performance in most real-world applications. More versatile designs exist, but they pay a penalty in speed, price or both. Also, most architectures are usually "closed"; that is, there is no provision for the user to customize or enhance the hardware.

Mercury Computer's ZIP 3200 AP contains two processors: a pipeline for high-speed calculations and a control processor (CP) for data management. Each processor has its own program memory and control logic, so algorithms can be run with little or no assistance from the host computer.

To reduce further the need for service from the host, the ZIP has a 128K data memory, expandable to 16 Mbytes, and I/O ports that interface directly to external devices such as A/D and D/A converters.

Using the AP in a typical system (such as the Multibus), the pipeline resides on a separate circuit board, so that the user can change the AP's data format by changing the pipeline processor.




Figure 1: Main components of the ZIP array processor consist of the control processor, the main memory, the external ports and the host interface.

Currently, two pipelines are available: the fixed point 3216 and the floating point 3232. Future pipeline designs will support data formats up to 64 bits.

As Figure 1 shows, the main components of the ZIP are the CP, pipeline, main memory, external I/O ports and host interface. All components communicate via the main ZIP bus, which is 32 bits wide and has a 100 nsec transfer time, for a throughput of up to 40 Mbytes/sec.

The CP is a general-purpose computer based on the AMD 29116 controller. It handles functions such as passing data to and from the pipeline, computing memory addresses, controlling program sequencing in the pipeline and passing data among various parts of the system.

The presence of the CP increases performance by relieving the host computer of many data management tasks. The CP's instruction set includes such operations as rotate and merge, that can be performed in 100 nsec. It has thirty-two 16-bit general registers, sixteen of which are extended by external logic to 23 bits. The CP also features a real-time clock, 11 interrupt vectors and automatic memory refresh via cycle stealing.

The CP and the pipeline have 2048 words of program memory each. The CP has the ability to load overlays, modules of program code that are kept in the ZIP main memory until they are needed. Development software includes a linking loader and run-time executive that support programs with up to 256 overlays. Thus, the ZIP can execute complex algorithms with no need for service from the host computer.

One important feature of the ZIP is how it synchronizes data flow between the two processors. The pipeline halts when its input buffer is empty or when its output buffer is full. Similarly, the CP will halt if it tries reading from an empty buffer or writing to a full one. One of the processors will resume execution when the other clears the bottleneck by reading or writing the proper buffer. This mechanism simplifies the need to measure pipeline delays to ensure that all parts of the ZIP are properly synchronized.

At the heart of the ZIP is the arithmetic pipeline processor. Two versions are currently available: the 3232 performs floating point arithmetic on 32-bit data, and the 3216 performs fixed point arithmetic on 32- or 16-bit data.

The 3232 (Figure 2) is based on the AMD 29325 ALU chip, which is notable for its high throughput. Its design allows the result of any calculation to be immediately available as input to the next without pipeline delays. The 29325 performs fix, addition, subtraction, multiplication and float operations, operating on data in either the IEEE standard format or in DEC

An Array Processor this fast and flexible can't sell for only \$4100.

Or can it?

The imaging requirements of a geophysical research project at sea demanded intense mathematical calculations.

An array processor was the answer.

But space aboard the ship's computer was limited. Only a single Multibus* slot remained.

Marinco engineers, driven by necessity, pushed beyond the horizons of conventional array processor design.

A Single Board

They discovered how to shrink circuits to a single board—and to do so without sacrificing performance.

In fact, they enhanced it. Keeping signals within a single board actually made significant speed gains. Then they added other performance enrichments such as memory mapping and an auxiliary port for direct high speed I/O.

Easy to Program

Perhaps as important, the board is easy to program, even for someone with only high-level language experience. Standard routines may be adapted. Or new ones created. Marinco's assembler automatically generates the microcode and tracks the 48-bit control word.

Marinco makes it possible!

Imaging Productivity

The speed and flexibility of the APB-3000 series can dramatically increase your imaging productivity. Use it for coordinate transformation, hidden line removal, vector-to-raster conversion, interpolation, image enhancement and many other operations.

Very Low Price

Even with all these advantages, Marinco innovations make it possible to offer the Multibus version for only \$4100, quantity one, U.S. price.

IBM PC and PC AT versions are also available.


Can an array processor this fast and flexible really sell for such a low price?

Thanks to practical demands and Marinco innovations, it can.

Call us toll-free for details.

Specifications

Program Memory 2K X 48-bits Data Memory 8K words Data Word 24 bits long, 8-bit exponent, 16-bit mantissa (floating pt.) or 16 bits (integer).



US and foreign patents pending.
*Multibus is a trademark of Intel Corp.

MARINCO, INC.
A HELIONETICS COMPANY

Marinco Computer Products
9940 Barnes Canyon Road
San Diego, CA 92121
619-587-0461
1-800-421-4807
in Calif. 1-800-421-4808
Telex 3719117

A H E L I O N E T I C S C O M P A N Y

Circle 17 on Reader Inquiry Card

format. External circuitry provides logical AND and OR functions and formatting operations such as clearing and sign extension. A "subtract from 2" operation provides quick execution of the Newton-Raphson algorithm for computing reciprocals.

The power of the 29325 is augmented by the Weitek 1066 multiport register file. This device contains 32 words of RAM, a look-up table for reciprocals and square roots, three input ports and three output ports. Twenty-four words of RAM are used as input buffers, output buffers and temporary registers for intermediate results. The remaining eight words are dual-mode; they may be used either as input buffers or as temporaries.

Input buffer words are divided into two banks. While the pipeline is using one bank, the CP can load new data into the other. Words used as temporaries can always be accessed, regardless of which bank is in use. The output buffer is operated as a FIFO.

A useful feature of the pipeline is its ability to save the sign bit of any result in a status register. This bit can be used by conditional statements to provide an IF-THEN-ELSE function within the pipeline. This allows it to execute complex routines with no intervention by either the CP or the host computer.

The 3232 can process data at a rate of 8 MFLOPS. For more demanding applications, the ZIP can drive two pipelines for throughputs up to 16 MFLOPS. For the ultimate in performance, multiple ZIPs can be placed in a single host computer.

Users that do not require such high performance may prefer to use the 3216 fixed point pipeline. This unit can operate on integer or fractional data. Fractional data allows it to be used for block floating point operations, in which the CP manages the exponents.

The 3216 (Figure 3) has a five stage pipeline consisting of ALU, input buffers, multiplier, scaling and rounding logic and an output FIFO. All stages operate concurrently at either 20 million operations per second in 16-bit mode or 5 million per second in 32-bit mode. The pipeline can switch from one mode to the other mid-stream, with no lost cycles. This allows the programmer to freely trade precision for speed at any point in the program.

The 3216 has four accumulators for storing intermediate results. The accumulators are 48 bits wide to minimize rounding




Figure 2: Arithmetic pipeline for the ZIP 3232 which can perform floating point arithmetic on 32-bit data.




Figure 3: Arithmetic pipeline of the ZIP 3216 which can perform fixed point arithmetic on 32- or 16-bit data.

errors in long chains of calculations. Results are automatically truncated to 32 or 16 bits in the output buffer.

Many AP designs suffer from I/O bottlenecks that prevent them from achieving their advertised performance. The two most common places for such bottlenecks are transfers between the AP and the host and between the AP and the external devices such as A/D converters. Throughput in these two areas is increased by the ZIP's host interface and by its external I/O ports, respectively.

The host interface includes a programmable burst channel that transfers large blocks of data into or out of the ZIP with minimal overhead to both the ZIP and the host. The channel can transfer data at speeds of up to 400 nsec per word (5 Mbytes/sec), while using only 100 nsec of ZIP processing time. When two or more ZIPs are placed in a single host, they can use the burst channel to pass data among themselves with no intervention by the host.

The external ports may be configured by jumpers to function as separate 16-bit input and output ports or as a single 32-bit bi-directional port, with a throughput of up to 20 Mbytes/sec. On-board handshaking logic provides easy interfacing to the user's devices, and each port includes four control (output) and status (input) bits, whose functions are completely user-definable. The CP's vectored interrupts assure fast response to the ports' data needs.

How useful did you find this article? Please circle the appropriate number on the Reader Inquiry Card.

Very Useful 619
 Useful 620
 Somewhat Useful 621

An Engineer and a Scientist Agree (REMARKABLE!) on Star Technologies' Scientific Processor Computer for Satellite Image Processing

"The ST-100 was the only scientific processor in its price range that offered the reliability and processing speed needed to meet the throughput performance requirements of the Canadian government."

Alexander J. M. Baillie

Alexander Baillie
FMPS Project Manager
Canadian Astronautics Ltd.
Ottawa, Canada

The Canada Centre for Remote Sensing called on Canadian Astronautics, Ltd. to develop a system for rapid analysis of LANDSAT-5 thematic mapper images. Their objective: research into computer vision and artificial intelligence. Canadian Astronautics delivered the FAST MATHEMATICAL PROCESSOR SYSTEM (FMPS), built around the 100 MFLOPS power of the Star Technologies' ST-100 scientific processor computer.

Using FMPS, the Centre can classify a 400 Mbyte array from a 34,225 square kilometer thematic mapper image in one hour. . . **what was previously a day's processing is now handled in one hour!**

The processing handled by the ST-100 involves radiometric correction and classification of up to 21 satellite data channels and 256 classes. Another benefit of the processing speed provided by the ST-100 is that the entire process of analyzing a single image, including data I/O, accuracy assessment and other support activities, is reduced to a single day.

The exceptional computational power and dependability of the ST-100 are bringing advances in scientific research and production to many disciplines. They include geophysics, aerodynamics, cosmology, particle physics, and biology, as well as satellite and radar imaging and signal processing.

To learn how the performance, dependability, and economy of the ST-100 can benefit your computational needs, contact Star Technologies today.




STAR TECHNOLOGIES, INC.

1700 U. S. Bancorp Tower
111 SW. Fifth Avenue
Portland, Oregon 97204
503/227-2052

"We chose Canadian Astronautics and Star Technologies to provide us with the fastest processing system in the world for remote sensing image analysis involving geographic information."

David G. Goodenough

Dr. David G. Goodenough
Senior Research Scientist
Canada Centre for Remote Sensing
Ottawa, Canada



Circle 28 on Reader Inquiry Card


Parallax

GRAPHICS POWER FOR YOUR MICROCOMPUTER

Easy To Integrate

Parallax's high-performance series of graphics controllers let OEMs and system integrators add astonishing graphics power to standard microcomputers — Multibus and Q-bus controllers are available now.

These controllers are designed for easy integration and are self-hosting — just plug the Parallax controllers into a Multibus or Q-bus system, add a high-resolution color monitor, and you are



ready to begin development of powerful graphics applications.

The Parallax graphics controllers also give you the advantages of low power consumption, light weight — and with their advanced board-level designs, provide a price/performance ratio that is ideal for individual graphics workstations.

Exceptional Speed

With drawing speeds of up to 88 million pixels per second, you get

more productive interactivity between the operator and your microcomputer graphics system.

- The Series 600 single-board controllers draw at 12 million pixels per second.
- The high performance Series 1000 board-set controllers draw at 88 million pixels per second, with Block Image Transfers (BLIT) at 14 million pixels per second.

"...drawing speeds of up to 88 million pixels per second."

With immediate interactivity, applications such as animation, CAD/CAM, on-screen page make-up, and business graphics are easier to work with, simply because images and graphics appear instantly on screen — and can be changed just as quickly.

Parallax's rich instruction set provides single-instruction Polygon, Box, Circle and Vector drawing, Solid Fill, Outline, Stipple, Block Image Transfer, Opaque/Transparent, standard and user-defined Text modes, vector Dejagging — and the list goes on.


High Resolution

1024 × 1024, 60 Hz non-interlaced display is yours with Parallax's high-performance graphics controllers.

- The Series 600 provides 640 × 480 display resolution; standard 4 bit planes provide 16 colors from a palette of 4096 colors.

- The Series 1000 provides 1024 × 1024, 60 Hz non-interlaced display resolution; standard 4 bit planes with 8 bit color tables provide a palette of 16 million colors.

You can expand the Series 600 to 8 bit planes, and the



Series 1000

Series 600

Series 1000 is expandable to 24 bit planes. Other standard Parallax features include double buffering, smooth pan, and integer zoom along either axis — Parallax controllers have a long list of features that mean high performance graphics power for your microcomputer system.

Contact Parallax Graphics today. We'll be glad to draw a clear picture of all the advantages OEMs get with our graphics controllers.

Parallax

High Performance Color Graphics Controllers  GRAPHICS

1095 East Duane Avenue, Suite 215
Sunnyvale, California 94086
(408) 720-1600

Multibus is a trademark of Intel Corporation
Q-bus is a trademark of Digital Equipment Corporation

Circle 42 on Reader Inquiry Card

Maintaining Compatibility When Upgrading The 8086/87

by Jack Sterett, Al Brown and Gary Hornbuckle, Tektronix Inc., Wilsonville, OR

Intel's 16-bit microprocessor family provides a planned upgrade path with code-compatible processors that offer a range of performances. Two members of this family are the 8086 with its math coprocessor, the 8087, and the higher performance 80286 which has an 80287 coprocessor. Because of the use of the 8086 family in the IBM PC, there is a large software base of 8086-compatible software that system designers wish to protect when upgrading the performance of their existing product lines. This makes the 80286 a logical choice for product extensions and upgrades. Although the conversion from the 8086 to the 80286 is mostly a straightforward process, system designers should be aware of several details. Extending the Tektronix color graphics workstation product line from the 8086-based Tektronix 4110 Series to the 80286-based 4120 Series may prove valuable to others making the 8086/80286 conversion.

Tektronix' 4120 Series includes three color graphics workstations, the 4125 with high-resolution 2D capability, the 4128 with 3D wireframe and the 4129 with 3D shaded surface graphics. The 4120 Series provides improved performance over the 4110 Series both in terms of speed and graphics capabilities. The added functionality of 3D graphics necessitates a much larger firmware storage capability and higher computational performance to accomplish the more complex graphics calculations with comparable response time. A major design goal of the new series was to maintain complete upward compatibility for application programs originally targeted for the 4110 Series. Major engineering objectives for the new workstation hardware were to double the CPU performance, to double the EPROM available for software enhancements without reducing user RAM space, to open a system board slot for other options and to ensure complete application compatibility with the 4110 Series. Given these goals, the 80286/87 processor, math coprocessor combination was the logical choice for the new workstation.

The 80286 is a high-performance 16-bit microprocessor that is instruction-set compatible with its 8086 predecessor. Although the new processor operates at a higher clock rate, the two to three times performance improvement of the 80286 is due largely to improvements in the internal implementation. The 80286 microcode and internal logic is modified to allow most instructions to execute in fewer cycles than the 8086. It also enables a higher degree of pipelining. The philosophy of the 80286 is to decouple instruction execution as much as possible from external memory bus activity through instruction queues and bus output buffers. Although the 80286 offers built-in support for demand-paged virtual memory, the 4120 Series does not use

this feature to maintain code compatibility with the 4110 Series.

In the 4110 Series, the CPU and memory occupy two boards. One board contains an 8086 processor, self-test EPROM, an 8087 math coprocessor, an interrupt controller, keyboard and host ports and interface logic to the system backplane bus. Graphics firmware and 32K of RAM stack space are resident on the second board. The 2732 EPROM chips provide storage for firmware up to a maximum of 128 Kbytes and stack RAM is implemented with 4116 dynamic RAM chips. As a result of the two-board packaging, the CPU is required to access memory over the system backplane bus. This bus is also shared with peripheral controllers and special-purpose graphics controllers resident on other boards. A block diagram of the 4110 Series architecture is shown in **Figure 1**.

In the 4110, the system bus is a bottleneck for two reasons: the bandwidth contention among bus controllers and data sharing. The Multibus-like system bus is controlled by an Intel 8288 bus controller and the 8289 arbiter and is totally asynchronous. Because of the handshaking protocol, a memory request cycle takes a minimum of 1.2 μ sec to complete. If another bus controller has the bus, the 8086 can be held off during the other controller's activity. This is especially significant when the display controller needs the bus since it locks the bus for multiple memory cycles updating the display, keeping the 8086 from fetching instructions. Since all program instructions and stack memory are accessed over the system bus, the 8086 can become starved for instructions when bus contention is high.

The system bus is a problem, in terms of data sharing, because even to achieve a simple scheme for maintaining data integrity, the 8086 is not allowed to access critical areas of system RAM at the same time as the graphics coprocessor. As a result, the 8086 can be blocked for significant periods of time even when bus activity is low.

Using the 80286, the 80287 and some new memory parts, the two-board CPU/memory pair can be implemented on one board and can increase memory size and performance significantly (**Figure 2**). The 8288 and the 8289 parts were replaced with the 82288 and the 82289 parts to control the 4120 Series system bus. Intel's 2186 pseudostatic 8K \times 8 RAM parts allowed the entire stack to be moved to the CPU card. The entire firmware space was also moved to the CPU card using 27256 EPROMs to increase memory density eightfold and to double the total size to 256 Kbytes.

To promote system throughput, an additional 82288 system bus controller is used to establish a private, local bus. This is used exclusively by the 80286 to access RAM, EPROM and I/O

devices on the CPU board, thus bypassing the system bus for instruction fetches and stack accesses, by far the most numerous processor requests. Because this is a synchronous bus, a memory fetch can be complete in only 500 nsec. Another special synchronous bus, called the RAM bus, was added to allow the 80286 on the CPU board to directly access the graphics display list memory on a separate memory board without having to use the system bus. The dual-ported display list memory is controlled by an 8207 memory controller that provides all bus control, dynamic refresh and address decoding required by 64K dynamic RAMs. Only bus buffers are required on the CPU board. The other port of the display list memory is used by the bipolar display list processor (graphics engine) to fetch the display list created by the 80286. This list is fetched,

usually in blocks, via the system bus.

To insure the integrity of the display list data, software semaphores along with the 80286 "lock" instruction prefix are used to synchronize accesses from the 80286 and the graphics engine. The lock instruction causes a special signal from the 80286 to be asserted during a read, modify, write memory sequence. This signal is used to provide nondivisible access to a software semaphore that locks out the graphics engine at the other display memory port while the 80286 is updating the display list, preventing garbage data from appearing on the screen.

Communication between the 80286 and optional peripheral controllers takes place over the system bus, as in the 4110 Series. The new architecture and higher packaging density of the 4120 Series provide the extra space needed for the 3D graphics firmware enhancements while improving performance both through the inherent speed of the 80286 and the 80287 and through reduced bus contention.

Although the 80286 is designed to be code-compatible with





Figure 1: In the previous 4110 Series architecture, an 8086 accessed stack RAM and firmware over an external system bus shared with peripheral and graphics controllers. The asynchronous bus, implemented with the 8288 bus controller and the 8289 arbiter, required a minimum of 1.2 μ sec to complete the required handshake for each bus transfer. In addition, other controllers could become the bus master, preventing the 8086 from fetching instructions for extended periods.



When you want
a graphics terminal
that lets you move
in all directions,
we'll be there.

QVT-311GX™
MONOCHROME
TERMINAL

Tektronix 4010, 4014 and PLOT 10 are registered trademarks of Tektronix Inc. VT 125 and ReGIS are trademarks of Digital Equipment Corporation. ANSI is designed to American National Standards Institute, Inc., ANSI X3.64-1979 guidelines.
© 1984 Qume Corporation.



Now for the first time, one terminal gives you the mobility to draw on an entire universe of graphics software – both PLOT 10 and ReGIS – plus full ANSI text-editing!

Introducing Qume's new QVT 311GX™, the only monochrome graphics terminal that offers full compatibility with both Digital's VT 125 and Tektronix' 4010/4014 series... for substantially less cost than either! The QVT 311GX provides full bit-mapped graphics on a 14" non-glare white phosphor screen, with four shades of gray. There's an optional mouse device as well.

As with all Qume terminals, the QVT 311GX is engineered to the highest standards of performance and reliability, and backed by our experience and resources as an ITT company. So whatever moves you make in the years ahead, you know we'll be there with expert service and technical support.

For more information about the QVT 311GX and Qume's other graphics and alphanumeric terminals, or our full line of daisywheel printers and disk drives, call (800) 223-2479.

Or write Qume Corporation, 2350 Qume Drive, San Jose, CA 95131.

Qume®
A Subsidiary of **ITT**
Circle 35 on Reader Inquiry Card

the 8086, there are a few minor differences, documented in the Intel literature, that must be accommodated. The differences include a "divide-by-zero" interrupt that operates differently in the 80286 than in the 8086. Rather than generating an interrupt and continuing on after detecting a divide-by-zero condition, the 80286, unlike the 8086, backs up to the start of the offending instruction to enable a retry. The difference can result in an infinite loop if the software does not expect a subsequent execution of the division instruction.

Although the 80286 provides facilities for demand-paged virtual memory, it also has a "real address" mode that provides complete compatibility with the 8086. The real address mode has segmented physical addressing and does not impose a memory protect scheme. The 4120 Series uses the real address mode to maintain compatibility with existing 4110 Series application software.

The interface between the 80286 and the 80287 math coprocessor has been improved with the addition of two extra hardware synchronization signals. This allows the 80287 to take a series of instructions without the need to interpose FWAIT commands between each instruction as in the 8086. However, no functional or performance degradations have been detected when the 8086 code that includes the FWAIT is executed on the 80286/87. As a measure of code compatibility between the 4110 Series and the new workstations, application programs com-

plied with the old 8086/87 compiler also execute on the 80286/87-based 4120 Series.

Most of the compatibility problems experienced in the conversion to the 80286 were due to timing dependencies. The problems resulted from the integration of the new 80286 and its associated parts with older peripheral chips. To obtain the maximum performance, the 80286 was run at the full 6 MHz clock rate. At the same time, the peripheral chips used in the 4110 Series had to be retained to maintain application compatibility and these operate at 4.9 MHz with a separate clock. The two clocks did not present a problem as the parts are designed to be coupled asynchronously. However, each peripheral controller chip has its own inherent "recovery" time. Sending two successive commands to a peripheral chip in less than the allowed recovery time will result in erratic behavior. The time between commands is a function of the software code and the processor clock rate. Converting from the 8086 to the 80286 caused some peripheral recovery time to be violated in the prototype 4120 workstation; this violation was due to the increase in clock speed and more efficient bus transaction queuing in the 80286. Components affected included the Intel 8254 chip and the Signetics 2661 communications controller.

Recognizing the occurrence of a violation is not straightforward because the 80286 employs pipeline strategies to improve performance. This means that the instruction execution is largely decoupled from bus timing through internal instruction queues. It is not simple to determine what the output timing of peripheral commands actually is through code inspection, since multiple output instructions executed several instruc-





Figure 2: The new 4120 architecture brings all firmware and stack RAM onto the CPU board with the 80286 and the 80287. In addition, two private, synchronous buses were added to provide fast, unshared access to program memory, stack RAM and the graphics display list memory.

Quite frankly, this processor just doesn't hold water.



Or chemicals, or solvents, or anything else that makes a mess or wastes time

It's a totally dry processor for 3M Dry Silver Papers and Films. There's nothing in it that needs to be mixed or can spill or stain. Just heat. And it can process all kinds of electro-optical images in as little as four seconds.

But there's more than speed and dry instant processing to 3M's improved Dry Silver Papers and Films. Perfect for a wide range of imaging applications, 3M Dry Silver systems offer:

- Spectral sensitivity compatible with most commercially available electro-optical sources.
- Photographic quality and resolution similar to wet-process materials.
- Sufficient sensitivity to handle faster writing rates or low energy light sources.

3M Dry Silver Papers and Films hold nothing but opportunity for you

Faster access to high quality, permanent hardcopy images is an advantage anyone involved in optical recording can appreciate. And now you can have access to the time-saving proprietary technology of 3M Dry Silver processing for your own systems. We offer over 20 years of experience in dry silver media development and associated thermal processor hardware to our OEM partners. Together we can make your imaging future much brighter.

Contact us today and discover the opportunities 3M Dry Silver systems hold for you.

Imaging Systems Division/3M
223-2SW 3M Center
St. Paul, MN 55144-1000



3M hears you...

Circle 32 on Reader Inquiry Card

AMAZING NEW PRODUCT SHARPLY REDUCES CAD/CAM COSTS



SEE IT FIRST AT SIGGRAPH '85

Here's your chance to witness a highly advanced engineering marvel that significantly reduces the costs of high quality CAD/CAM.

It features 1024 × 1024 viewable resolution, displays 16 to 4096 simultaneous colors, and supports a 60 Hz noninterlaced video display. With drawing speeds of 40,000 four-hundred pixel lines per second, it provides the processing power of sophisticated CAD/CAM systems for less than what you'd pay for most workstations.

Buy No CAD/CAM System Until You See This First.

We can't tell you everything here, but we will say that this new product is unlike anything you've ever seen before. You must witness its performance for yourself.



Vectrix Corporation, 2606 Branchwood Drive
Greensboro, NC 27408 (919) 288-0520

Visit us at Siggraph '85,
Booth No. 256

Circle 36 on Reader Inquiry Card

tions apart could be queued up inside the processor to access the system bus in back-to-back requests. A simple and effective strategy to prevent violations of the peripheral timing is to follow an output instruction with a "jump to next instruction," which flushes the instruction queue, followed by the required number of "NOP" instructions to insure the minimum recovery delay. Another timing-related problem that proved difficult to detect because of its extremely intermittent nature involved the interrupt response of the 80286. Normally, if programmers want to change the interrupt mask status of an 8259A interrupt controller, they would disable the 80286 interrupt acknowledge, write to the controller and reenable interrupts. However, if there are active interrupt sources in the system when the 80286 modifies the interrupt masks, there is a finite (though very small) probability that an interrupt request will arrive after the 80286 disables interrupts but before the 8259A can respond to the new mask status. The result is a metastable state that produces a "glitch" on the 80286 interrupt input line. Under these conditions, the 8259A is not guaranteed to be stable until its "command response time" has expired, starting with the receipt of the mask command.

To insure reliable operation when there are active interrupt sources, programmers should follow this sequence when sending commands, such as interrupt mask updates, to the 8259A interrupt controller chip: 1) disable the interrupt acknowledge on the 80286, 2) write the mask to the 8259A, 3) execute a "jump to next instruction" to flush the 80286 instruction queue, followed by NOPS to establish a minimum delay equal to the controller response time (350 nsec for the 8259A) and 4) reenable interrupts on the 80286. Failure to follow this procedure allows the metastable state to affect the 80286 and cause system crashes at very infrequent, yet unacceptable intervals.

The final area of concern for any engineering team converting the 8086 to the 80286 is self-test code. Although many self-tests can, and should, be made timing independent, the very nature of self-testing makes this impossible in some cases. To accomplish a thorough fault isolation, self-test code must get very close to the hardware, and this is when timing dependencies creep in. For example, self-test code that exercises the 4110 graphics coprocessor board exhibited timing problems when executed on the 80286. During normal operation, the graphics engine fetches display list primitives under its own control and at its own rate. However, during self-test the main CPU "spoon feeds" the graphics engine one command at a time to verify basic command execution before the engine is allowed to fetch its own commands from the display list. This primitive operation gives needed feedback to service personnel about where a failure is located. The increased speed of the 80286 over the 8086 resulted in commands being sent to the graphics engine faster than it could respond, leading to false self-test failures. Code delays were employed to eliminate the problem. Any 8086 to 80286 conversion project should expect a few of these timing-related incompatibilities to surface in the self-test code. **DD**


How useful did you find this article? Please circle the appropriate number on the Reader Inquiry Card.

| | |
|-----------------------|-----|
| Very Useful | 607 |
| Useful | 608 |
| Somewhat Useful | 609 |

Speed. Resolution. Economy.

Pick any three.

High performance/
price value
for PC workstations:
It runs in the family.



Demonstrating 1280 x 1024 viewport with hardware DOS window.

Number Nine's REVOLUTION™ family of single-board graphics controllers offers a combination of features not possible before the "Revolution." An Advanced CRT Controller (ACRTC). Up to 100 MHz pixel rate. Non-interlaced, flicker-free operation. Unique memory-mapped, multi-ported 1 Megabyte display RAM. A maximum viewable resolution of 1280 x 1024, and a software selectable number of bit planes from 1 to 4.

The REVOLUTION 1280 x 4 controller is CAE/CAD for the IBM PC workstation. ACRTC hardware drawing works in tandem with the PC's own microprocessor to eliminate operational bottlenecks. Uninterrupted bus access supplements ACRTC drawing to allow for maximum flexibility in either plane or pixel access modes. BIOS emulation puts DOS functions in a hardware window to create a one-monitor system. The result: Total programming flexibility, unsurpassed read/write screen speed, unparalleled resolution, and almost universal system compatibility.

A new standard? See for yourself. The future in PC-based CAE/CAD is here today. Not someday. For all the Revolutionary information, call 617-492-0999, or write Department G3 at the address below.

Specifications:

System: IBM AT, XT, PC and compatibles, 16 and 8 bit bus.

Pixel Rate: Up to 100 MHz.

Addressable Resolution: 2048 x 4096 with 1-bit plane, 2048 x 2048 with 2-bit planes, 2048 x 1024 with 4-bit planes, software selectable.

Viewable Resolution: Factory options include 1280 x 1024, 1024 x 768, 832 x 624 and 640 x 480, all running non-interlaced.

On-board RAM: 1 Megabyte CHMOS display RAM.

Color Specs: 4096 colors, 16 simultaneously viewable, up to 4-bit planes. Three 16 x 4 R/W tables.

Display Buffer Access Modes: Multi-ported simultaneous access by host processor and ACRTC. The host processor accesses in either PLANE mode, which allows sequential access of individual bit planes, or PIXEL mode, which updates whole pixel values.

ACRTC Drawing: Absolute or relative X, Y addressing from high-level language includes vector, rectangle, polyline, polygon, circle, ellipse, random polygon fill and BIT-BLT raster operations.

Hardware Features: Zoom 1–16x independently on X or Y axis, pan and scroll, 3 horizontal split screens, one fully programmable window, clipping, cursor, fully programmable raster parameters.

Output: RGB analog or TTL.



number nine

Computer Corporation

691 Concord Avenue, Cambridge, MA 02138


Revolution is a trademark of Number Nine Computer Corporation. IBM is a registered trademark of International Business Machines, Inc.

At SIGGRAPH 85, See Us at Booth 1426

Circle 52 on Reader Inquiry Card

Thinking 3½ inches? Think **Canon.**

THE NEW SMALL STANDARD.



Shown
Actual Size

Canon is known as the master of the ultraprecise miniature mechanism. And the smaller disk drives become, the more essential such mastery becomes.

The new Canon 3½-inch microfloppy disk drives are the new small standard size. 30mm high without the bezel. 105mm wide. Weight: 550 grams.

Available now in any quantity.

Our MD350 records 135 tracks per inch, with a track-to-track access time of 3ms and an unformatted capacity of 1 Mbyte. Yet our soft read error rate is only 10^{-9} bits, and our hard read error rate a mere 10^{-12} bits.

Three critical parts designed and manufactured by Canon contribute significantly to our drives' accuracy, and to their extraordinary reliability: the extremely durable brushless drive motor; the head assembly, which uses advanced video head positioning technology; and the steel belt positioning system.

Other good reasons to use Canon's 3½-inch drives:

- Simple pushbutton operation (now industry standard, pioneered by Canon).
- Available without bezels, or with any color bezel.
- Compatible with 5¼-inch drives. Can be used in your present system without changing electronics.

Four models are available:

MD350: 135 TPI, double sided, double density, 1 Mbyte.

MD351: 135 TPI, single sided, double density, .5 Mbyte.

MD352: 67.5 TPI, double sided, double density, .5 Mbyte.

MD353: 67.5 TPI, single sided, double density, .25 Mbyte.

Canon

Call us for even more reasons why 3½-inch drives are Canon's corner. (516) 488-6700, Ext. 4958. Or write Canon U.S.A., Inc., Disk Drive Division, One Canon Plaza, Lake Success, NY 11042.

Circle 38 on Reader Inquiry Card

The Future Of Flexible Disks

by Bob Hirshon, Contributing Editor

Flexible disk technology has not exactly set the world on fire over the past decade and a half. While other mass storage technologies have improved dramatically, floppy drives have made comparatively modest gains. Micro-Winchester disk drives, for example, increased in capacity from about 5 Mbytes in 1980 to over 100 Mbytes today. During the same period, floppy drives went from 400 Kbytes to 1.6 Mbytes—a far less impressive, fourfold improvement over five years. Performance improvements have been even smaller.

The flexible disk drive technology appears to lag far behind other memory technologies because of several factors, including cost, media removability and compatibility. Floppies,

unlike Winchesters, are a removable, it is hoped, interchangeable, medium. Being removable, the diskettes are subject to extreme environmental stress during transport. Reliable reading of data under such conditions necessitates keeping recording parameters conservative.

In addition, interchangeability of media between drives from different manufacturers means standards must be set—a time-consuming and technology-stifling process. The process may be a matter of various manufacturers methodically ironing out

Bob Hirshon is Contributing Editor, Peripherals, for Digital Design and a Boston-area writer specializing in science and technology.




Figure 1: IBM's 1969 patent (left) for this early prototype floppy disk was one of the first applications for flexible disk media. One of the latest is 3M's stretched surface recording (SSR) consisting of flexible disk media stretched over a rigid plastic substance. Here (right) it is being examined for surface defects with a laser testing device.

specifications or it may be a case of IBM choosing a specification and the rest of the manufacturers following suit. But either way, once a standard is set, considerable inertia must be overcome before another can replace it. And the more established a standard becomes and the more software is available on that format, the more difficult it becomes to introduce a new format.

Cost is another key factor. Flexible disk drives compete in the intensely price-sensitive small computer market. This puts high-volume, low-cost production at a premium and makes performance advantages less important. So efficient has floppy drive production become that lower volume, advanced technology drives cannot compete. When 1.6-Mbyte drives sell for about \$100, OEMs are not willing to spend \$200 for a 3-Mbyte drive. As a result, high performance flexible disk drives have a very limited market.

Together, these factors keep the mainstream of the flexible disk industry far from the leading edge. Nonetheless, there are active efforts ongoing in the US and especially in Japan to extend the limits of flexible disk technology. Although many are limited to the laboratory or niche applications now, these technologies demonstrate the capabilities of this versatile media and indicate what we can expect from the technology in the 1990s.

Microflops Finally Emerge

One technology that has emerged from the laboratory to join the mainstream is the sub-4" microflop. It took four years of infighting over several different media formats before the industry finally settled on a modified version of the Sony 3½" format. IBM's selection of the 3½" media (over their own 3.9"-microflop media, which was discontinued early in the standards battle) for their portable JX computers in Japan, and



Figure 2: With IBM's endorsement, microflop disk drives will become increasingly popular. By 1987, the drives are expected to represent nearly one-third of all flexible disk drives shipped annually, according to Disk/Trend. (Photo courtesy Canon USA)

for another system reportedly being introduced in the US this summer, has ended the controversy for good. With Apple, Hewlett-Packard and now IBM all using the 3½" microflops, lack of software – an early difficulty with the media – will cease to be a problem.

Microflops have a number of technical advantages over larger flexible disk drives, including lower power consumption, higher reliability and smaller footprint. The hard shell media offers added durability, more precise clamping (because of the addition of a metal hub) and higher resistance to anisotropic deformation and expansion from thermal and hygroscopic effects.

Current versions of microflop drives record at 135 tracks per inch (tpi) and about 7500 bits per inch (bpi) for a capacity of 500 Kbytes per surface. Double-sided drives storing 1 Mbyte are now available in quantity and are used in IBM's JX computer. The next stage in microflop development is a 1.6-Mbyte double-sided drive. Sony demonstrated such a drive two years ago, using high-coercivity media and custom-designed heads to increase bit density from 7610 bpi to 13,340 bpi. Setting standards for the 1.6-Mbyte microflop is the next step. Nippon Telephone and Telegraph (NTT) is currently working with several Japanese manufacturers to facilitate a 1.6-Mbyte microflop standard.

Servo-Positioned Floppies

A number of companies have been working toward a high-capacity, high-performance flexible disk drive. Media for these drives look like conventional floppy disks, but may have special, high-coercivity surfaces. This allows the smaller, more tightly packed bit cells to resist demagnetization and provide a sufficiently high-amplitude signal.

Most drives in this class rely on embedding servo positioning information onto the diskette surface to keep the heads positioned properly over the densely packed data. Amlyn (San Jose, CA) and Drivetec (San Jose, CA) were two companies that developed 5¼" half-height flexible disk drives using this technique to store over 3 Mbytes on a single diskette. Both companies were forced to leave the market, primarily due to pricing pressures, but the Drivetec design was purchased by Kodak, which continues to market it.

Kodak is now working with Drivetec's engineering team to develop a 6.6-Mbyte version of the drive. Drivetec had already demonstrated such a drive last November at Comdex. Current development efforts are aimed at making the drive efficient to produce in high quantities.

An Open-Loop Design

Not all high density flexible disk drives rely on servo positioning. One technology actively sold in Japan and available on a limited basis in the US is Hitachi's (San Jose, CA) ultra-high density open-loop drive system. Without resorting to exotic technologies or servo positioning, the Hitachi drives store 6.5 Mbytes on a 5¼" disk and 9.6 Mbytes on an 8" diskette.

Hitachi pushes existing technology to the limits to squeeze higher capacity and performance out of the drives. In the process, all compatibility with standard floppies is lost. The 8" drive has a data transfer rate of 1.5 Mbits/sec and comes supplied with a modified ST-506 Winchester interface. In addition, Hitachi offers an optional SCSI controller for both drives.

Disk rotation speeds are 360 rpm for the 8" drive and 720 rpm for the 5¼" drive. Combined with high linear bit densities (20,560 bpi for the 8" drive and 29,560 bpi for the 5¼" drive), this accounts for the high transfer rates. Track density is kept

Ultra-high speed and resolution Color Film Recording Systems



CELCO CFR 4000 Color Film Recording System shown above with DEC-VAX option.

for LANDSAT, Animation and Presentation Business Graphics

| SPECIFICATIONS | CFR4000 | CFR4000-B | CFR4000-A |
|--|--|---|------------------------|
| ■ Highest Resolution | 7500 resolvable pixels | | 4200 resolvable pixels |
| ■ Fastest Recording Speed | Less than 20 seconds for a complex 35mm business graphics slide | | |
| ■ Variable Pixel Rates | From 400ns/pixel to 6.2 μ s/pixel in 400ns increments | | |
| ■ Addressability | 4096 x 8192 (pixel x pixel), 8192 x 8192 (Run length encoded) | | |
| ■ Film Format Flexibility | Variable from 16mm to 8" x 10" | Fixed, selectable from 16mm to 8" x 10" | Fixed Film Format |
| ■ Graphic Arts Workstations Interface Compatibility | Includes Autographix, Artronix, Executive Presentation Systems, Florida Computer Graphics, MAGI, Management Graphics | | |
| ■ Mainframe Compatibility | DEC-LSI-11, PDP-11 and VAX; Perkin-Elmer; IBM | | |
| ■ Device-Independent Graphics Software Compatibility | ISSCO, UNIRAS | | |



For complete details circle reader service number or call CELCO today.

CONSTANTINE ENGINEERING LABORATORIES COMPANY

70 Constantine Drive Mahwah, NJ 07430

TEL: 201-327-1123

1150 E. Eighth Street Upland, CA 91786

TEL: 714-985-9868

to a relatively conservative 96 tpi for the 8" drive and 125 tpi for the 5¼" drive. Thus it is the extremely high linear densities that result in the drives' large capacities.

To achieve these high bit densities, Hitachi incorporated narrow-gap manganese zinc ferrite heads, rather than conventional nickel zinc ferrite heads, to produce a stronger signal in a smaller bit cell. Maxell developed a high density media for use with the heads. Although coercivity, at 650 oersteds, is no higher than other high coercivity media, the Maxell disks have a thinner, smoother coating and have much lower anisotropy from thermal expansion. The thinner, smoother coating allows higher density recording, and the resistance to anisotropic effects allows accurate positioning of the heads over the densely packed data.

Although both drives have been shipped in quantity in Japan, Hitachi has not actively marketed them in the US. However, the company has provided samples to a number of US firms.

Vertical Recording

Vertical, or perpendicular, recording has numerous advantages over conventional, or longitudinal, recording. But the many logical advantages of the technology have thus far been unable to outweigh an equal number of practical disadvantages.

Vertical recording orients bit cells down into the disk surface, rather than orienting them end-to-end. Not only do the cells take up far less space when oriented in this manner, allowing more bits per inch, but they also respond favorably as bit density increases.

Longitudinally recorded bit cells deform and demagnetize each other as they are squeezed more tightly, since like-charged ends of bit cells are adjacent. Vertically recorded bit cells, however, have opposite-charged ends of cells adjacent to one another. These tend to attract each other and resist deformation and demagnetization.

Another advantage of perpendicular recording is the elimination of the need for increasingly thin media coatings. With longitudinal recording, smaller bit cells require thinner coatings to maintain optimal bit cell dimensions. This means the bit density of longitudinal recording is limited by how thinly diskette surfaces can be evenly coated. In addition, as diskette coatings become thinner, the signal amplitude of each bit cell decreases, making reading of the data more difficult and requiring higher coercivity media.

Vertical recording avoids these problems. Since the bit cell orientation is down into the disk, optimal bit cell dimensions are maintained without making the coating thinner. In fact, since longer bit cells are actually more desirable, thick film coating is preferable. Thus vertical recording allows high bit density with good recording characteristics that actually improve as density increases.

The advantages of vertical recording have been well-known for many years and have inspired numerous research efforts. To date, none have brought a product to market. The main difficulty is the media. The two preferred materials for perpendicular recording are cobalt chromium and barium ferrite, and each has its problems. Cobalt chromium must be sputtered onto the diskette, an expensive and time-consuming means of producing floppies. The diskette then requires some sort of lubricant or overcoat to reduce wear.

Barium ferrite does not require sputtering, but consistency




Figure 3: Conventional, longitudinal recording orients bit cells end-to-end along the length of the data track. Vertical, or perpendicular recording, orients the bit cells side-by-side down into the surface of the recording media.

has been a problem. Proper uniformity of the particles and the binder mix is especially crucial, and the material must be carefully oriented to achieve good recording characteristics.

Most importantly, the drives as well as the media must meet the pricing constraints of the floppy disk market. So far, the combination of technical difficulties and market concerns have prevented the introduction of a vertical recording flexible disk drive. Nonetheless, Japan-based manufacturers are still actively pursuing the technology, and some have announced plans to have a product available within a year. US efforts in flexible disk vertical recording have been reduced to comparatively small groups at the larger media and drive companies.

The one company dedicated exclusively to the technology, Vertimag (Minneapolis, MN), recently was forced to lay off most of its workforce, and is now down to only 12 full-time employees. "After January, the plug was pulled by our investors," explains Nathan Curland, vice president of engineering and acting CEO for Vertimag. "We couldn't raise enough funds by private funding, so now we're trying to sell the company." Despite Vertimag's problems, Curland remains optimistic about the future of vertical recording. "Technology will march on, densities will get higher," predicts Curland, "and eventually the market will require perpendicular recording. The only question is when."

Noncontact Recording Methods

Some technologies combine elements of flexible disk recording and Winchester technology. Bernoulli drives, for example, use flexible disk media encased in a removable cartridge. As in Winchester drives, the disks spin at high speeds, and the R/W head comes close to the surface, but never actually touches it.

Bernoulli technology takes advantage of the stabilizing action of a stationary plate just underneath a spinning disk. Rather than fluttering uncontrollably, the flexible media spins smoothly over the plate, at a distance precisely determined by the speed of rotation and the physical design of both plate and media.

This media stability allows R/W heads to be 10 μm from the media. This is close enough to allow linear bit densities of up

INTRODUCING WORKCELL SUPER-VISION.



THE S512: THE NEXT GENERATION WORKCELL/ VISION ARCHITECTURE.

Now you can control; multiple high resolution machine vision systems, multiple robots and machines from a common database, or all of the above, simultaneously. The IRI S512 Supervision System makes it all possible.

The S512 is a flexible multi-processor workcell supervisor with architecture that opens up a totally new control performance range. Now multiple high resolution color machine vision systems (512 x 512 pixels) can be configured to our S512. It's our 20 megabyte-per-second multi-processor workcell supervision system that provides concurrent factory control, database management, multi-user access and coordination of robot vision, manipulators, machine tools, and other processes—in real-time.

The S512 is a tightly-coupled multicomputer system, that acquires more than 250 million pixels per second and processes at a maximum rate of 1200 million arithmetic operations per second.

The master-system provides you with a real-time UNIX program development environment, performs data base management, and supervises the subsystems that function under their own specialized operating system. Both the master and subsystems are multiprocessor architectures designed to communicate through shared-memory via an ultra-fast 20 megabyte-per-second arbitrated memory bus.

The result? The S512 Supervision System is the world's fastest, most powerful, expandable, configurable, cost-effective workcell supervision system available today. And, it's ready to plug into your factory control world. For more information, call: Richard Carroll, V.P. Sales (619) 438-4424. International Robomation/Intelligence, 2281 Las Palmas Drive, Carlsbad, CA 92008.



THE BEST VISION INDUSTRY HAS EVER SEEN.

Circle 54 on Reader Inquiry Card

to 20 Kbits/in while avoiding head and media wear problems associated with conventional contact flexible disk recording.

IBM invented Bernoulli technology, but never incorporated it into a product. Iomega (Ogden, UT) developed the technology, and designed a line of 5 1/4" and 8" format drives around it. In addition to providing up to 10 Mbytes of removable storage on a single cartridge, the drives operate well in harsh environments and are resistant to airborne contaminants. This makes them popular for use in industrial, laboratory and military environments. Miltope (Melville, NY) makes a mil-spec version of the drive.

Ironically, Iomega's latest product is a 20-Mbyte, IBM-compatible subsystem, designed to let IBM PC/AT buyers circumvent IBM's well-publicized 20-Mbyte Winchester disk drive problems. Iomega offers free upgrade software to PC/AT buyers who purchase a stripped down, no-Winchester version of the AT, and the upgrade to a Bernoulli drive.

Stretching The Limits

Another technology that combines qualities of flexible and Winchester disk drive recording is Stretched Surface Recording (SSR). Developed by 3M (St. Paul, MN), it involves stretching flexible diskette material over a rigid circular disk between two low rims bounding the inner and outer circumference of the recording area. Stretched over the two rims, the media is taut but slightly resilient, like a drum or banjo head.

As in Bernoulli drives, the media spins rapidly, and the heads stay in close proximity to the surface, without actually touching it. Also as in Bernoulli drives, aerodynamic effects maintain the head-to-disk spacing. But in SSR, it is the dimpling effect on the surface of the disk, caused by air passing between head and disk, that creates the spacing. This space can be as small as 5 μin — half that of Bernoulli drives. Consequently, 3M engineers predict even higher capacities for their SSR disks — up to 50 Mbytes for a 5 1/4" disk.

3M recently ramped up production of SSR disks at its Wetherford, OK manufacturing facility. It expects the first drives using SSR to be fixed media drives and predicts they will be introduced this year, possibly at NCC. In the near future drives using removable SSR cartridges will be developed. These, 3M claims, will compete with removable Winchester cartridge drives, Iomega's Bernoulli drives and other high density floppy technologies.

Flexible Variations

Other new flexible disk developments range from slight variations on a theme to whole new applications for the media. Omek (Fremont, CA) is a small company trying to distinguish its product from a largely indistinguishable field. Its 5 1/4" half-height floppy drives have a unique self-testing and exercising feature that may be particularly attractive to customers who do not have their own drive test equipment. By applying jumpers to various positions on the drives' option select pins, customers can run the drives through a variety of different self-tests, the results of which are displayed by means of flashing red and green LEDs.

Another form of self-test is incorporated by Hewlett-Packard (Greely, CO) in their microfloppy drives. Their "media monitor" keeps track of disk insertions on a dedicated area of the disk and lets the user know when the disk has probably outlived its usefulness.

| Unit shipments in thousands | 1983 Shipments | Forecast | | | |
|-----------------------------|----------------|----------|----------|----------|----------|
| | | 1984 | 1985 | 1986 | 1987 |
| 8 inch drives | | | | | |
| One side | 336.4 | 227.9 | 129.7 | 68.7 | 30.9 |
| Two sides | 1,275.9 | 1,285.4 | 1,082.5 | 832.8 | 493.7 |
| 8 INCH TOTAL | 1,612.3 | 1,513.3 | 1,212.2 | 901.5 | 524.6 |
| 5 25 inch drives | | | | | |
| One side | 4,323.7 | 4,520.9 | 4,531.1 | 4,253.4 | 3,678.7 |
| Two sides | 6,165.7 | 10,126.5 | 13,412.3 | 15,891.8 | 17,681.4 |
| 5 25 INCH TOTAL | 10,489.4 | 14,647.4 | 17,943.4 | 20,145.2 | 21,360.1 |
| Microfloppy drives | 438.3 | 1,959.0 | 4,168.2 | 6,674.5 | 9,711.2 |
| TOTAL ALL DRIVES | 12,540.0 | 18,119.7 | 23,313.8 | 27,721.2 | 31,595.9 |

Figure 4: Disk/Trend predicts rapid growth for flexible disk drives in all categories except 8" drives.

Conventional flexible disk technology is increasingly finding its way into unconventional applications. Ensoniq (Malvern, PA), for example, uses microfloppy disk drives in its Mirage Digital Sampling Keyboard, a five-octave electronic synthesizer capable of reproducing sounds stored on diskettes. Chyron (Melville, NY) uses microflops in its digital character generators, which create and store alphanumeric characters for use in videotape production. And Compusonics (Denver, CO) has patented a digital floppy-disk-based audio system that stores up to an hour of music on a 5 1/4" diskette.

Market Matters

Despite the many new technologies being investigated in laboratories, no one could accuse the flexible disk drive industry of being technology driven. The successful companies have not been those who introduced the latest technologies first (in fact, most of those who did are now out of business), but those who produced the greatest number of drives at the lowest cost.

The result is that virtually all flexible disk drive production is now done overseas. Even Tandon (Chatsworth, CA), the last surviving high-volume, US-based floppy drive manufacturer, produces its drives in Singapore and India. And in every category of flexible disk drives currently undergoing growth (that is, all categories excluding 8" drives), manufacturers not based in US now dominate, according to Disk/Trend (San Jose, CA). These manufacturers now account for 66% of all single-sided 5 1/4" drives, 54% of all double-sided drives and 97% of all microfloppy drives. In the long-term, flexible disk drive technology has substantial room for innovation. However, in the near future, market concerns will continue to dominate the industry, and improvements will be measured in dollars and cents (and yen), rather than in Mbytes and msec.

How useful did you find this article? Please circle the appropriate number on the Reader Inquiry Card.

- Very Useful 604
- Useful 605
- Somewhat Useful 606

For 13 years some of the biggest names in the business have been bringing us their toughest power supply requirements.

Why? Because we work with them, beyond their specifications. Quickly. Effectively. Creatively.

How? By being highly sensitive to their needs. By working closely with them to develop the power supply that meets both their specifications and their system's requirements. By value-engineering our design before production to insure a cost-effective product. By carefully balancing materials and manpower to maintain flexibility.

PSI is committed to meeting International Safety requirements. We have developed a Safety Certification Package with all the data and specs needed to obtain approval from UL, CSA, and VDE, and other certifying organiza-


tions. And we are authorized to self-certify power supplies.

Whether your power supply requirements are simple or complex, bring them to us. Power Systems, Inc. Where powerful solutions are everyday achievements.

To find out why Power Systems, Inc. should be your power supply vendor, contact:
Power Systems, Inc., 12 Tobey Road, Bloomfield, Connecticut 06002, Tel. (203) 243-0357, TWX 710-425-8778

Power Systems, Inc.

Circle 26 on Reader Inquiry Card




NEW EL and VF DISPLAY MODULES

GRAPHICS MODULES



Electroluminescent Graphics Module with powerful drawing processor using GCI (VDI) industry standard syntax. 512 x 256 pixels.



Vacuum Fluorescent Graphics Module. Controller has dual processor pipelined architecture for fast speed. 320 x 240 pixels.




Vacuum Fluorescent Video Module accepts NTSC standard RS170 signals, has 16 gray levels, 3.75" x 5.00" screen size.




Vacuum Fluorescent Module, super fast bit mapped display. 256 x 64 pixels.


TEXT MODULES



Electroluminescent Text Module allows 24 lines by 80 characters, double wide, double high characters, many other features.



Vacuum Fluorescent Text Module allows up to 240 ASCII, ECMA and KATAKANA characters, parallel or serial input.



Vacuum Fluorescent Text Module allows 2 lines by 40 characters, same features as above. Only +5 vdc power needed.



Vacuum Fluorescent Text Module, 40 characters. Above three modules available in high brightness and extended temperature range versions also.



Vacuum Fluorescent Text Module, 2 lines by 20 characters, loaded with features!

+ MANY MORE! Over 25 standard models available!

WORLDWIDE DISTRIBUTION

THE DISPLAY INNOVATORS

DeCO T.M.

DIGITAL ELECTRONICS CORPORATION

26142 Eden Landing Road • Hayward, CA 94545 • (415) 786-0520

Telex: 172073 DIGELEC HYWD • Facsimile: (415) 786-1040


EEPROM Technologies Diversify And Find New Applications

by Dave Wilson, Executive Editor

During the 1970s, the EEPROM market was built exclusively around MNOS technology. The key companies were NCR and General Instrument, and the highest density device available was only 8 Kbits. The major uses were in consumer electronics such as tuners, in point-of-sales equipment to store prices or tax tables, in postage meters to store postal rates and in other look-up tables with a variety of applications.

In the early 1980s, the first parts using floating gate technology began to emerge from Intel and Xicor. In 1982, Seeq Technology began its first product shipments. Along the way, Advanced Micro Devices, Hughes, Motorola, National Semiconductor, Siemens and others independently developed their own EEPROM capabilities. One early idea regarding the position of the EEPROMs in the marketplace was that they would become a replacement for the UVEPROMs. The ability to reprogram the parts without having to remove them from a board brought obvious benefits to the designer. To date, however, the EPROM market has been relatively untouched by the EEPROM technology. This is primarily because of the radical difference in product cost between the two devices produced with the same design rules.

In introducing its new 64 Kbit EEPROMs, Hitachi (San Jose,



Lattice Semiconductor's GAL16V8

Intel's 2816A

CA) claims to have effectively solved the price problem. By using MNOS technology, Hitachi has built its devices (the HN58064P-25 and the P-30) with single-capacitor memory cells, as opposed to the three capacitor cells found in most of its competitors' devices designed with floating gate technology. Also, Hitachi has resisted the current trend toward putting a greater level of functionality on a single device. By moving some advanced features off the chip, Hitachi claims to have reduced the cost of the EEPROMs and made them available as a commodity product. Seeq Technology (San Jose, CA) offered EEPROM technology on-board its microcontroller (the 72710) as an alternative to the on-board UVEPROM. The part was unsuccessful because of the designers' unfamiliarity with the Texas Instruments instruction set and Seeq's delay in shipping the part. The EEPROM is, however, finding its way into many newer microcontrollers as a substitute for UVEPROM.

Another application for the technology, that of EEPROMs replacing fuses in programmable array logic devices, appears to be gaining momentum. Already, Lattice Semiconductor (Portland, OR) has announced two families of reprogrammable array logic devices. These are the Lattice Reconfigurable Array Logic (RAL) device and the Generic Array Logic (GAL) device. Both combine a CMOS process with EEPROM floating gate technology. According to Lattice, this provides designers with reconfigurable logic featuring bipolar speeds (25 nsec) at significantly reduced power levels. The GAL16V8 device is a pin-for-pin replacement for any of the standard 20-pin bipolar PAL devices and can also be configured into architectures that do not exist. Each output of the GAL can be individually set to active high or active low, with either combinational (asynchronous) or registered (synchronous) configurations. All circuit elements in the unit come fully tested. They are erased




Figure 1: Required EEPROM endurance vs. time between writes.

prior to shipment to assure a 100% programming yield. Test vectors to verify each logic pattern do not have to be generated during production testing because the programming yield is guaranteed.

In terms of density, the EEPROM has a good deal of catching up to do before it rivals the UVEPROM. Currently, the largest EE part available is the 8K × 8 (64 Kbit) device, with 256 Kbit parts promised by some suppliers later this year. On the UVEPROM side, however, Advanced Micro Devices (Sunnyvale, CA) expects to have available by the end of the summer a UV part of no less than 1 Mbit in density. This part, the AM27C1024, a 1-Mbit CMOS product, is a 5V device that features a power dissipation of 250 mW when active and 500 mW when in standby mode.

Other technologies are also continuing to challenge the EEPROM. These include the static RAM with battery backup and the shadow RAM. Two years ago Mostek (Carrollton, TX) began offering a CMOS static RAM with a built-in ten-year battery. Since then, others have jumped in. Dallas Semiconductor (Dallas, TX), for example, now offers a 64-Kbit nonvolatile RAM, the DS1225. An on-board lithium power supply and intelligent control circuitry retain data in the absence of V_{cc}.

These CMOS static RAM parts will fit into many systems that currently use other forms of nonvolatile memory because they fit into the standard 28-pin JEDEC format. They also match the pinout of the 2764 EPROM or the 2864 EEPROM to allow direct substitution. The benefits of unlimited write cycles, safeguards against corrupted data and fast read and write times (as low as 150 nsec) provide for an alternative to EEPROMs, EPROMs or shadow RAMs in some applications.

The distinction between the NVRAM and the EEPROM is that normal reading and writing occurs between the processor and the SRAM portion of the NVRAM. Writing into the EEPROM occurs only when data is to be saved, such as during a power failure. NVRAMs allow for unlimited writes and a quick store of the whole array since each system bit has a




Figure 3: Block diagram of the Exel XL-48C64.

shadow EEPROM bit. At present, however, NVRAMs are not available in densities higher than 4K, and the bulk of products shipped by manufacturers still appears to be at or below the 1K level.

In the past, EEPROM access times have been around 150 nsec, and the only available nonvolatile memory with access times below 150 nsec has been the bipolar PROM. Bipolar parts, however, can only be programmed once and consume more power than their MOS counterparts. Today, it would appear that the EEPROM is catching up, in terms of access times, to the point where it may challenge the bipolar parts. Formerly, high speed alterable nonvolatile memory systems were implemented through the use of a combination of slow EEPROMs and high-speed static RAMs. Upon power up, the system would download the EEPROM content into static RAM for fast access. Recently, however, two high-speed CMOS EEPROMs, the XL46C16 (2K × 8) and the XL46C32 (4K × 8), have broken the 100 nsec barrier and offer access times of 55 nsec. With the advent of these parts from Exel (San Jose, CA), many high-speed system designers will be able to consolidate their memory architectures by replacing their redundant combinations with the new parts. Typical applications include adaptive robotics, high-speed process controllers and programmable video pattern generators. But it is not only the access time where developments in technology continue to enhance the performance of the EEPROM.

Another area of research is focusing on the increased endurance of the parts. At present, the industry standard endurance is 10,000 cycles. (Endurance is defined as the maximum number of erase/write cycles that the entire memory can withstand before any single EEPROM cell fails.) This is sufficient for some applications but others require higher endurance.

As a result of both device technology and memory cell development, Seeq Technology now offers a family of EEPROM parts that can be reprogrammed one million times before they fail data sheet limits. The part is designed for applications with frequent data alteration (i.e., data storage portion of system memory). Figure 1 compares the one million cycle and 10,000 cycle EEPROMs. Seeq's family can be written every 6 minutes for 10 years, whereas the standard part can be written only 3 times per day for the same period.

The availability of the 64K EEPROM from a number of vendors has brought with it a new awareness among design engineers. Throughout its evolution from 16K, a number of enhancements have been made to make the EEPROM more useful to the designer. Several features are found on a variety





Figure 2: Evolution of the EEPROM in a 28-pin DIP.

No other keyboard produced test results like these.



The corners of people's mouths aren't the only things that go up with our keyboard. So does productivity. That's because our good looking keyboard makes a couple of things go down. Like mistakes. And fatigue.

We call it the ST keyboard. S for silent. T for tactile feel. People who use it, call it something else. Like terrific. So it makes sense that they liked it over other leading keyboards in a human factors test evaluating preference and productivity.

Why they preferred it has to do with fingers, wrists and ears. Fingers because of good feel and positive tactile feedback. Wrists due to the relaxing effect of its design. Ears thanks to its quiet operation.

But as much as the people who tried our keyboard liked it, you'll like it more. Especially when you keep in mind that it'll enhance the value of your product. That we deliver a keyboard to meet your requirements every time. That we offer it in enclosures with

plug and play capabilities that save you time and money. And that we have standard and custom keyboards available, including IBM and DEC compatible versions.

So if you're in the market for a low profile keyboard, remember the one that gives everyone something to smile about. The ST keyboard. For results of the test or more product information, write MICRO SWITCH, Freeport, IL 61032. Or call 815-235-6600 for the name of the branch sales office nearest you.



Together, we can find the answers.

MICRO SWITCH
a Honeywell Division

Circle 55 on Reader Inquiry Card

Stop by and see us at Booth No. 3311 during NCC-Chicago.

of chips as standard, including 5V programmability, on-chip address, data latches, timing circuitry, automatic erase before write and mechanisms to prevent inadvertent write cycles during power up and power down situations. Today, the 16K EEPROM is available in both 24-pin and 28-pin sockets, but only the 28-pin package will allow designers to directly upgrade from the 16K to the 64K density level in the same socket (Figure

2). At present, several manufacturers provide different schemes for signaling the completion of the write cycle on their 28-pin EEPROM parts. Most recommend that the designer weigh the trade offs between them before choosing the notification scheme used in their system.

The first option is to use the Ready/Busy output found on pin 1. This pin is used to notify the microprocessor in the system that a write cycle is in progress if the open drain current is low. The Ready/Busy line could be connected to an interrupt request pin of a microprocessor to interrupt the microprocessor when a write cycle is completed or to generate a status bit. If the

EEPROM CROSS REFERENCE AND SELECTION GUIDE

| General Instrument | Organization | Pins | Power Supply | Format | Size | Technology |
|---------------------------|-----------------|------|--------------|----------|-----------|------------|
| AMD | | | | | | |
| 9864 EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | NMOS |
| 2864A EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | NMOS |
| 2817A EEPROM | 2Kx8 | 28 | 5V | Parallel | 16K | NMOS |
| EXEL | | | | | | |
| XL46C16 EEPROM | 2Kx8 | 28 | 5V,12V | Parallel | 16K | CMOS |
| XL2816A EEPROM | 2Kx8 | 24 | 5V | Parallel | 16K | NMOS |
| XL2817A EEPROM | 2Kx8 | 28 | 5V | Parallel | 16K | NMOS |
| XL2865A EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | NMOS |
| XL2864A EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | NMOS |
| XL48C64 EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | CMOS |
| XL28C256 EEPROM | 32Kx8 | 28 | 5V | Parallel | 256K | CMOS |
| General Instrument | | | | | | |
| ER1451 EAROM | 50x14 | 14 | -30V,5V | Serial | 700 bits | MNOS |
| ER0082 EAROM | 82x1 | 18 | -30V,5V | Parallel | 82 bits | MNOS |
| ER1450 EAROM | 50x14 | 14 | -30V,5V | Serial | 700 bits | MNOS |
| ER1400 EAROM | 100x14 | 14 | -30V,5V | Serial | 1400 bits | MNOS |
| ER2051 EAROM | 32x16 | 28 | -28V,5V | Parallel | 512 bits | MNOS |
| ER2055 EAROM | 64x8 | 22 | -28V,5V | Parallel | 512 bits | MNOS |
| ER5901 EEPROM | 128x8 | 24 | 5V | Parallel | 1K | SNOS |
| ER5911 EEPROM | 64x16 or 128x8 | 8 | 5V | Serial | 1K | SNOS |
| ER59256 EEPROM | 16x16 | 8 | 5V | Serial | 256 bits | SNOS |
| ER3400 EAROM | 1Kx4 | 22 | -30V,-12V,5V | Parallel | 4K | MNOS |
| ER2810 EAROM | 2Kx4 | 24 | -24V,-14V,5V | Parallel | 8K | MNOS |
| PCD8572 EEPROM | 128x8 | 8 | 5V | Serial | 16K | SNOS |
| ER5904 EEPROM | 512x8 | 24 | 5V | Parallel | 4K | SNOS |
| ER5912 EEPROM | 128x16 or 256x8 | 8 | 5V | Serial | 2K | SNOS |
| PCD8582 EEPROM | 256x8 | 8 | 5V | Serial | 2K | SNOS |
| ER5902 EEPROM | 256x8 | 24 | 5V | Parallel | 2K | SNOS |
| ER5914 EEPROM | 256x16 or 512x8 | 8 | 5V | Serial | 4K | SNOS |
| HITACHI | | | | | | |
| HNS806 EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | MNOS |
| HUGHES | | | | | | |
| H0938 | 2Kx4 | 28 | 5V | Parallel | 8K | CMOS |
| H3264 | 8Kx8 | 28 | 5V | Parallel | 64K | CMOS |
| H3108A | 1Kx8 | 24 | 17V | Parallel | 8K | CMOS |
| H3104A | 512x8 | 24 | 17V | Parallel | 4K | CMOS |
| H3300 | 32x8 | 18 | 5V | Parallel | 256 bits | CMOS |
| INTEL | | | | | | |
| 2816A EEPROM | 2Kx8 | 24 | 5V | Parallel | 16K | NMOS |
| 2817A EEPROM | 2Kx8 | 28 | 5V | Parallel | 16K | NMOS |
| 2864B EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | NMOS |
| 2004 NVRAM | 512Kx8 | 28 | 5V | Parallel | 4K | NMOS |
| 2001 NVRAM | 128x8 | 18 | 5V | Parallel | 1K | NMOS |
| MITSUBISHI | | | | | | |
| M58653P | 50x14 | 14 | -30V,5V | Serial | 700 bit | MNOS |
| M58657P | 100x14 | 14 | -30V,5V | Serial | 1400 bit | MNOS |
| M58658P | 20x16 | 14 | -30V,5V | Serial | 320 bit | MNOS |
| M5G1400P | 100x14 | 14 | -35V | Serial | 1400 bit | MNOS |
| MOTOROLA | | | | | | |
| MCM2801 | 16x16 | 14 | 5/25V | Serial | 256 bit | FETMOS |

| | | | | | | |
|-------------------------------|-------|-------|-------|----------|----------|--------|
| MCM2802 | 32x32 | 14 | 5/25V | Serial | 1024 bit | FETMOS |
| MCM2833 | 4Kx8 | 28 | 5V | Parallel | 32K | FETMOS |
| MCM2864 | 8Kx8 | 28 | 5V | Parallel | 64K | FETMOS |
| NCR | | | | | | |
| 52864 EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | SNOS |
| 52801 EEPROM | 16x16 | 14 | 5V | Serial | 256 bits | SNOS |
| 52832 EEPROM | 4Kx8 | 28 | 5V | Parallel | 32K | SNOS |
| 59306 EEPROM | 16x16 | 8 | 5V | Serial | 256 bits | SNOS |
| 59308 EEPROM | 64x16 | 8 | 5V | Serial | 1K | SNOS |
| 52001 NVRAM | 128x8 | 24 | 5V | Parallel | 1K | SNOS |
| 52002 NVRAM | 256x8 | 24 | 5V | Parallel | 2K | SNOS |
| 52004 NVRAM | 512x8 | 24/28 | 5V | Parallel | 4K | SNOS |
| 52210 NVRAM | 64x4 | 18 | 5V | Parallel | 256 bits | SNOS |
| 52211 NVRAM | 128x4 | 18 | 5V | Parallel | 512 bits | SNOS |
| 52212 NVRAM | 256x4 | 18 | 5V | Parallel | 1K | SNOS |
| National Semiconductor | | | | | | |
| NMC98C64 EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | CMOS |
| NMC9817 EEPROM | 2Kx8 | 28 | 5V | Parallel | 16K | CMOS |
| NMC9346 EEPROM | 64x16 | 8 | 5V | Serial | 1K | NMOS |
| NMC9802 EEPROM | 256x8 | 18 | 5V | Parallel | 2K | NMOS |
| NMC9306 EEPROM | 16x16 | 8 | 5V | Serial | 256 bits | NMOS |
| NMC9816A EEPROM | 2Kx8 | 24 | 5V | Parallel | 16K | XMOS |
| NMC9817A EEPROM | 2Kx8 | 28 | 5V | Parallel | 16K | XMOS |
| SEEQ | | | | | | |
| 52B33 EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | NMOS |
| 52B13 EEPROM | 2Kx8 | 24 | 5V | Parallel | 16K | NMOS |
| 2816A EEPROM | 2Kx8 | 24 | 5V | Parallel | 16K | NMOS |
| 5516A EEPROM | 2Kx8 | 28 | 5V | Parallel | 16K | NMOS |
| 2817A EEPROM | 2Kx8 | 28 | 5V | Parallel | 16K | NMOS |
| 5517A EEPROM | 2Kx8 | 28 | 5V | Parallel | 16K | NMOS |
| 2864 EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | NMOS |
| SGS | | | | | | |
| M120 EEPROM | 256x4 | 18 | 5V | Parallel | 1K | NMOS |
| M9306 EEPROM | 16x16 | 8 | 5V | Serial | 256 bit | NMOS |
| XICOR | | | | | | |
| X2404 EEPROM | 512x8 | 8 | 5V | Serial | 4K | NMOS |
| X2804A EEPROM | 512x8 | 24 | 5V | Parallel | 4K | NMOS |
| X2816A EEPROM | 2Kx8 | 24 | 5V | Parallel | 16K | NMOS |
| X28C64 EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | CMOS |
| X2864A EEPROM | 8Kx8 | 28 | 5V | Parallel | 64K | NMOS |
| X28256 EEPROM | 32Kx8 | 28 | 5V | Parallel | 256K | NMOS |
| X2816B EEPROM | 2Kx8 | 24 | 5V | Parallel | 16K | NMOS |
| X2864B EEPROM | 2Kx8 | 24 | 5V | Parallel | 64K | NMOS |
| X2001 NVRAM | 128x8 | 24 | 5V | Parallel | 1K | NMOS |
| X2002 NVRAM | 256x8 | 28 | 5V | Parallel | 2K | NMOS |
| X2004 NVRAM | 512x8 | 28 | 5V | Parallel | 4K | NMOS |
| X2210 NVRAM | 64x4 | 18 | 5V | Parallel | 256 bits | NMOS |
| X2210A NVRAM | 14x4 | 18 | 5V | Parallel | 256 bits | NMOS |
| X2212 NVRAM | 256x4 | 18 | 5V | Parallel | 1K | NMOS |
| X2212A NVRAM | 256x4 | 18 | 5V | Parallel | 1K | NMOS |
| X2444 NVRAM | 16x16 | 8 | 5V | Serial | 256 bit | NMOS |



**10% OFF CABINET LIST
EFFECTIVE 7/1/85**

**Look
like
DEC*
FOR
LESS.**

Less cost.
Immediate delivery.
Just two reasons system
houses have looked to us
for DEC compatible
cabinets during the past
seven years.

Want more? Ask about our superior
quality. And our complete
physical and functional
interchangeability including
DEC compatible power sources.

Choose from our complete line of the most
popular DEC enclosures. But choose
us. We look like DEC, you'll look
like a hero.

**Everest
Electronic
Equipment, Inc.**



2100 E. Orangewood Ave.
Anaheim, California 92806
(714) 634-2200

*DEC is a trademark
of Digital Equipment Corporation

EEPROM is in a write cycle, the Ready/Busy pin is pulled low and held low until the cycle is completed. Once completed, it is pulled high indicating that valid data may be read from the EEPROM. A second notification feature available to the user is DATA polling, in which the most significant bit of the last byte is used to let the microprocessor know that a write cycle is in progress. During a write cycle, an attempted read of the EEPROM will result in a complement of the data bit. After the completion of the write cycle, true data is available. This read/compare scheme allows the EEPROM to be polled to determine if it is still in a write cycle without any external hardware.

Some manufacturers consider the Read/Busy feature an inferior solution to the problem of write cycle completion notification. This is because tying up pin 1 for the Ready/Busy function limits the progression of the device to the 256K level in a 28-pin DIP.

Another technique that most EEPROM manufacturers may soon adopt is one proposed by Exel when it introduced its XL48C64. In this part, several special user features are accessible through simple software commands. Three unique on-chip registers allow the user to select a variety of operational modes and to monitor device status. The special functions available include a software selectable 32-byte page mode, a 5V-chip erase mode, a fast write mode that allows a 5 msec write cycle time, a read only mode for inadvertent write protection and a Ready/Busy device status indicator.




Figure 4: XL48C64 status word configuration.

The three registers are accessible whenever pin 1 SW (the Status Word) is low. These are shown in Figure 3 along with their respective addresses. The status register is a read-only register which is used to indicate when the part is executing a nonvolatile write cycle. The other two control registers are write-only registers which are used to operate the special device modes.

The status read cycle (SW low) accesses information from the status register while ignoring the address lines. Status write cycles require that one of the addresses shown in Figure 4 accompany the write cycle to identify which of the two control registers is to be modified. Although the 256K version of the EEPROM will give up these modes of operation in hardware, according to industry sources, it will be retained via a sequence of three software instructions. Hence, the approach's versatility will not be sacrificed when designers need to upgrade their designs to a higher density. Higher density EEPROMs will open up new applications for program storage and data table applications, such as calibration constants and configuration parameters.

Soft-key configurations in a graphics or a character-oriented terminal is an example of functions, such as protocol, screen attributes and character fonts, which can be keyed in by the user. Calibration constants can be stored in an EEPROM with a smart interface for a robot's axis of movement. In programmable controllers and data loggers, configuration parameters for polling time, sequence and location may be stored. The EEPROM may also be used as a nonvolatile storage device inside the next generation of intelligent credit cards.

CMOS will become the preferred technology in all applications because of the reduced power requirements and the reliability of system operation. This, coupled with decreasing read and write times to the device and increasing endurance times, will continue to diversify the applications of the EEPROM.

DD


References:

1. Proceedings of the 1984 Wescon Conference.
2. Proceedings of the 1985 Electro Conference.

How useful did you find this article? Please circle the appropriate number on the Reader Inquiry Card.

Very Useful 601
 Useful 602
 Somewhat Useful 603

HIGH-SPEED INTELLIGENCE



FOUR-CHANNEL SIMULTANEOUS SAMPLING ANALOG I/O SUBSYSTEMS FOR MULTIBUS®

Designed for high-speed signal processing applications that require real-time simultaneous sampling in such fields as communications, speech, sonar and seismology. Also suitable for image processing applications including tomography, remote sensing and similar areas.

Features —

- ± 5 nanosecond aperture uncertainty
- 80K samples/sec thruput
- Fortran, Pascal, C callable subroutines
- continuous stream processing
- accuracy to within 0.04% of FSR
- 12 bits resolution

For more information contact John Amyot, Director of Marketing at (613) 226-7890.



ROY BALL ASSOCIATES LTD.

1750 Courtwood Crescent, Suite 300,
 Ottawa, Ontario K2C 2B5 Telex 053-4712

*MULTIBUS is a registered trade mark of Intel Corp.

Circle 25 on Reader Inquiry Card

THE COMPETITION GAVE UP

When it came to really tough physical design problems the others couldn't cut it. So they cut out.

Now, when companies like National Semiconductor, Motorola, Harris, Hughes and RCA—companies with challenging layout problems—need solutions, they come to the only firm that specializes in physical layout software tools, VR Systems.

Our **MERLYN-G™ Automated Gate Array Layout Software** handles chip designs up to 20,000 gates, and our **MERLYN-PCB™ Automated Printed Circuit Design System** designs 16-layer boards with up to 350 IC's per board and 2.5 equivalent 14-pin DIPs per inch density—both on a variety of popular computers and workstations, such as DEC-VAX, Apollo, Tektronix 6000, IBM, and ELXSI; and with interfaces to other CAE/CAD/CAM functions and software. And our development of other layout technologies and tools continues.

For instance, **TurnChip™** is the first "turnkey" layout product available that allows gate array logic designers to produce functionally equivalent physical designs to those of foundry design centers, without requiring mastery of physical layout issues.

VR is the layout technology leader. We have the largest engineering staff in the business, dedicated only to physi-


cal design technology for the electronic engineering market, and serious about solutions to your design problems.

In benchmark after benchmark, when the others couldn't cut it, VR technology has come through. So, bring your layout problems, no matter how easy or tough, to VR Systems.


VR is a part of the total design and test solution offered by Tektronix. For information about VR Systems' products and/or the Design & Test Solution from Tektronix, call or write us, today.

VR Information Systems, Inc.
12212-A Technology Boulevard
Austin, Texas 78727
Phone 512-331-1303
TWX 910-874-2052

The logo consists of the letters 'V' and 'R' in a bold, stylized, sans-serif font. The 'V' and 'R' are connected at the top, with the 'V' having a slightly curved top edge and the 'R' having a thick vertical stem and a curved top.



UNIBUS*




or Q-BUS

Simpact Solves Your DEC Communications Problem!

We started with DEC's MICRO/T-11 16-bit PDP-11 microprocessor so you can use your host's software development tools to write programs using the familiar PDP-11 instruction set.

Then we married the MICRO/T-11 to multiple Z8030 Serial Communications Controllers to create a family of front-end processors that can support nearly all serial protocols, standard or custom.



MICRO/T-11

All ports on our FEPs are individually programmable for baud rates, synchronous and asynchronous protocols, RS-232C, RS-449 (RS-422, RS-423), MIL-188C and MIL-188-114.

We also built in 22-bit hardware memory management so you can download sophisticated application tasks and still have plenty of room for data storage.

Finally, we added firmware for boot loading, self-test diagnostics,

and program debugging. But the hardware is only half the story...

Powerful Package of Software Tools

Because we understand what it takes to develop and support a communications system, we created a software toolkit to make our family of FEPs easy to use. Starting with our proven, memory-resident Real-Time Executive, we added a sysgen program to develop down-loadable, run-time images. We also designed efficient drivers for RSX and VMS operating systems so host applications programs can easily talk to our FEPs with simple QIO calls. To help you get started with your project we provide complete software documentation and hands-on training classes.

Standard Protocol Software

We can also provide turnkey packages for Telenet certified X.25 LAPB protocol software (CCITT 1980, Levels 1, 2, and 3) and HDLC (LAPB) frame and link level software. More standard protocols are on the way.

For the UNIBUS Model ICP1600:

Eight fully programmable comm ports
256K RAM, DMA transfers to host
Single hex-height card
Up to eight ICP1600s per UNIBUS
\$4975. (single quantity)

For the Q-BUS Model ICP1622V:

Four fully programmable comm ports
128K dual ported RAM
Single quad-height card
Up to eight ICP1622s per Q-BUS
\$3000. (single quantity)

Port Expander, Model EXC1612:

Gives the ICP1600 or the ICP1622V
twelve additional programmable
RS-232C comm ports
Optional DMA capability for two ports
Single quad-height module for UNIBUS
or Q-BUS
\$2400. (single quantity)

Software Toolkit Model QX100:

For RSX or VMS operating systems
Includes Training Class
\$5000. (one time charge)

Let us solve your DEC communications problem. Call us today at (619) 565-1865.

simpact
COMPUTER SYSTEMS

Circle 31 on Reader Inquiry Card

Simpact Associates, Inc., 5520 Ruffin Road
San Diego, CA 92123

© 1984 Simpact Associates, Inc.

* DEC, UNIBUS, Q-BUS, PDP-11, MICRO/T-11, RSX and VMS are Trademarks of Digital Equipment Corporation.

Attacking The Simulation Bottleneck

by David W. Allenbaugh,
Logic Simulation Product Manager, Zycad Corp., St. Paul, MN

PHOTO COURTESY ZYCAD CORP.

Logic simulation is a highly CPU-intensive circuit design verification task that is an essential element in the design cycle. Without logic simulation, circuit checkout and test times would be unacceptable for today's rapidly shrinking market windows. In many instances, using traditional software-based simulation techniques on LSI and VLSI designs requires an impractical amount of CPU time. A simulation demanding hundreds of hours is not unusual.

The logic simulation process can be divided into four tasks: 1) enter or define the circuit/system, 2) compile the circuit/system into a format acceptable by the simulation algorithm, 3) load the simulation algorithm and perform the simulation and 4) pass the simulation results back to the user. Prior to the introduction of hardware accelerators, executing the actual simulation proved to be the most time-consuming step. To reduce execution times, methods of improving simulation algorithms received much attention. Most attempts to increase speed focused on rewriting the algorithm in a lower level language. Although there have been some positive results, this approach has not progressed to a point where large system-level simulations or thorough regression test simulations are feasible.

An alternative way to tackle the simulation bottleneck is to implement the simulation algorithms in hardware. This approach has been taken by Zycad Corp. (St. Paul, MN) and a few other CAD/CAE companies. Zycad's solution implements an event-driven timing wheel algorithm entirely in hardware (**Figure 1**). The architecture of the hardware accelerator, or Logic Evaluator (LE), is optimized around an event driven simulation algorithm. Each of the possible 16 modules in the LE contains an independent event processing pipeline running at 1 million events/sec. There is no instruction fetching or decoding in the

event processors of the LE, so the data (events) flow from place to place concurrently. Hence, the Logic Evaluator functions like a multiprocessor dataflow machine.

In its largest configuration, the system has a random access memory bandwidth of nearly 16 billion bits/sec and processes up to 16 million events/sec. Combining several supercomputer architectural features including multiple pipelines and multiple processors results in simulation performance 1000 times that of a large mainframe. Other features of the system include the following: 12-state simulation; unidirectional, bidirectional and wired gate functions; and fault simulation with timing analysis.

Aside from actual simulation speed, another potential bottleneck is the excessive time necessary to load the algorithm. The LE attaches directly to a host computer or a workstation and is loaded via a 16-bit parallel interface with transfer rates of 1 to 2 Mbytes/sec. This translates into loading 100,000 gates into the system in approximately 9 seconds.

Zycad currently provides interfaces to Apollo-based workstations, DEC's VAX, Prime's computers, Data General's MV series and IBM or IBM plug-compatible mainframe computers through a Device Attachment Control Unit (DACU). A software-based driver to interface the LE from the host is also available for each of these configurations.

Simulation Language

With the attention removed from the actual simulation process, the focus turns to the compile time. Compilation converts a design description from a text or a graphic form to an object-code format that can be loaded into the simulation algorithm. Every simulation system must go through some type of compiling process.

Zycad Intermediate Form (ZIF) is the LE's object-code for-

mat. It consists of several 16-bit binary words, taken separately or in 32-bit pairs and collected into larger structures called packets. Each packet contains a particular type of information. Several packets may perform similar functions and thus form a packet group. There are four kinds of packets: control packets, network packets, input packets and output packets.

Control packets dictate how the LE responds to and executes simulations. Network packets describe the simulation network to the LE. All gates, fan-outs and delay values are included in the network packet. Input packets target and stimulate, or both, the pins of a simulation network, and output packets contain the data returned from a simulation run. There are five types of output packets: two that output only design verification data, two reporting fault simulation information and one providing execution statistics at the end of a simulation. Dividing the LE input

(continued on p.85)




Figure 1: Zycad's Logic Evaluator drastically increases simulation speed in comparison to traditional software simulators. The architecture of the Logic Evaluator is based on an event-driven timing wheel algorithm.

(continued from page 80)

information into independent packets allows the user to send only those packets that changed from the previous run. In the typical case, a network (the largest packet) is tested with many tests and combinations of observed outputs. These runs can be made by changing only the smaller test and output packets.

A number of current LE users integrated the LE into their existing proprietary CAD systems by developing their own compilation software. Another option is to use ZILOS, Zycad's front-end software package that permits the LE to function like a virtual turnkey system. ZILOS was developed through a joint agreement between Zycad and SimuTec (Incline Village, NV). The package functions as an interface between ZIF and SimuTec's SILOS simulation description language. Simulation input data coded in SILOS may be translated to ZIF, via ZILOS, and executed on the LE.

SILOS commands can use most of the LE's capabilities through ZIF. Conversely, the LE executes most processes that can be described by SILOS commands. ZILOS provides users with the power and flexibility of a SILOS simulator along with the speed and capacity of the LE. With ZILOS, compilation of a 20,000-gate design takes about 4 minutes; 100,000 gates can be compiled in approximately 20 minutes. ZILOS is presently available for DEC's VAX and Apollo-based workstations.

Designers currently using Tegas or workstation software from Mentor Graphics (Beaverton, OR) can also integrate a Logic Evaluator into the existing environment (Figure 2). Two interfaces currently exist for the Mentor workstations. XSIM, an interface supplied by Mentor, allows the LE to be shared on an Apollo networking ring and makes the LE transparent to the user. Zycad offers a second interface that permits Mentor users to translate Mentor's database to the ZILOS input language. A similar translator is also available for workstations from Tektronix, CAE Systems Division (Sunnyvale, CA) and Daisy (Mountain View, CA).

On mainframe computers, Tegas is the most commonly used software simulator. A translator that converts Tegas Design Language (TDL) to ZILOS is provided by Zycad. The use of a translator is often accompanied by wasted CPU time. However, this is not the case with Zycad's Tegas-to-ZILOS translator. A benchmark comparing throughput simulation times of a 20,000-gate design on DEC's VAX/780 using Tegas and the Zycad system was recently completed. To compile and link the design using Tegas required 51.5 minutes; simulating 2000 test vectors (approximately 13 million events) took 5 hours and 52 minutes. In contrast, using ZILOS and the TDL-to-ZILOS translator, the same simulation requires 2 minutes to translate, 6 minutes for ZILOS compilation and 14 seconds for LE simulation. This yields a sixfold improvement in compilation time and a 1500-fold improvement in simulation time. Total throughput time using the

Zycad system was 8 minutes and 49 seconds, compared with 6 hours and 43 minutes on the VAX/Tegas system. Table 1 highlights several other LE benchmarks.

Impact On The Design Process

Dedicated simulation engines are causing a major change in the CAE design process. Gate-level system simulation enables complete system verification prior to committing the design to hardware. Design cycles are also shortened when a hardware accelerator is used, enabling manufacturers to make product introductions within tight market windows. Moreover, the impact of hardware accelerators will become greater as the levels of integration in VLSI-based systems continues to rise. Because of these revolutionary new tools, there may also be a decline in the interest of behavioral-level simulation. Designers must often resort to the behavioral approach when there is insufficient CPU horsepower available to perform gate-level simulation. Machines such as the LE, however, offer the designer a tool that is thousands of times faster than anything previously available. DD




Figure 2: When ZILOS is used as a front-end, the Logic Evaluator (LE) functions as a standalone system. However, the system readily interfaces to a wide range of hardware and software from such vendors as DEC, IBM, Daisy, Apollo and Mentor.

How useful did you find this article? Please circle the appropriate number on the Reader Inquiry Card.

Very Useful 613
 Useful 614
 Somewhat Useful 615

| Benchmark Description | Existing System | Zycad System | Simulation Time, Existing System | Simulation Time, Zycad System |
|--|------------------------|------------------------------|----------------------------------|-------------------------------|
| 41,000 gates 41075 ZIF elements 1643 input vectors | IBM 3083 Tegas | VAX/750 LE-1002* ZILOS | 45 minutes | 35.5 second |
| 8,000 gate array 6362 ZIF elements 2770 sample times | CDC Cyber 205 Tegas | VAX/750 LE-1002 ZILOS | 10.5 minutes | 2 seconds |
| 8,000 gate array 6362 ZIF elements 2770 sample times | CRAY XMP Tegas | VAX/750 LE-1002 ZILOS | 3.9 minutes | 2 seconds |
| 3,000 gate array 6362 ZIF elements 2770 sample times | VAX/780 Tegas 5 | VAX/750 LE-1002 ZILOS | 100 minutes | 2 seconds |
| 1692 gates 8600 input vectors 2,150,000 sample times | VAX/750 Silos | VAX/750 LE-1002 ZILOS | 31.7 minutes | 7 seconds |
| 751 gates: 363 conventional 114 nodes 274 bidirectional 2560 input vectors | IBM 4341 Internal | VAX/750 LE-1002 | 21.4 minutes | 8.6 seconds |

Note: The LE-1002 is Zycad's basic model.

Table 1: Examples of simulations running on some of the world's most powerful computer systems illustrates the performance of the Logic Evaluator.

THE VQ-11 SERIES...

GET THE Q-BUS SYSTEM PACKAGE THAT YOU WANT

CUSTOM OR STANDARD – ZOLTECH DELIVERS



BUILD IT YOURSELF

- **VQ-11/Model 30:** The **INTEGRATED** system chassis includes 8x4 Q-22 card cage, quad-output power supply, full control panel, superior cooling, mounting hardware and power wiring for mass storage devices and a rear I/O connector panel that is compatible with, but more flexible than, the DEC Micro/PDP-11. Rack-mount, "Tower," and desk-top enclosures are available.
- **VQ-11/Model 20:** The **CARD CAGE ONLY** chassis – based on the Model 30, but does not provide for internal mass storage.
- **VQ-11/Model 16:** **MASS STORAGE SUBSYSTEM** chassis – based on the Model 30, but does not provide for an internal card cage.
- **VQ-11/Model 11:** The **MINIMUM** system chassis – includes only the empty metal shell of the Model 30 and the AC power input components.

Just the components that you need!


Zoltech manufactures a variety of systems and other Q-Bus related components. The VQ-11 system packages are designed to maximize reliability and versatility while minimizing cost and lead time. **Call or write** today for a quote or for our catalog of system packages, boards, drives, software and accessories available for your Q-Bus needs.

DEC and Micro/PDP-11 are trademarks of the Digital Equipment Corporation

BUY IT COMPLETE

- **CPU:** 11/23, 11/73, 68000, MicroVAX
- **MEMORY:** Up to 4 million bytes
- **MASS STORAGE:** Virtually any combination of removable and fixed devices including 5" and 8" floppies, Winchesters and tape. Capacities to 190mb. Emulations from TU58 to MSCP.
- **SERIAL I/O:** DL, DZ, DH, and DHV
- **SPECIAL PURPOSE:** Analog I/O, graphics, array processors, counter-timers...
- **SOFTWARE:** Single or multi-user, utility, development, and application.

**Your exact
configuration!**



**Call or
write today**

**ZOLTECH
CORPORATION**

7023 Valjean Avenue, Van Nuys, California 91406 USA
(818) 780-1800 Telex 755451

Representative and dealer inquiries are invited.

Circle 12 on Reader Inquiry Card

NEW PRODUCT FOCUS

S Y S T E M S

PC/AT-Based CAE Design System

The CAE Systems Division of Tektronix (Sunnyvale, CA) has upgraded the IBM PC/AT, making it a circuit design workstation. An addition to the 6000 Series family of intelligent graphics workstations, the Tekstation AT can act as a standalone system or as a multiuser system networked through Ethernet. It supports applications ranging from CAE-based design capture, design verification and physical layout to software development under the UTeK operating system. UTeK, also supported by all Series 6000 products, is Tektronix's

version of the Berkeley 4.2 UNIX-based operating system.

The Tekstation AT is also packaged with the CAE 2000 Designers' Database/Schematic Capture software and IDEAL logic simulator for compatibility with larger CAE-based systems. In addition to compatible application software from IBM and other third party vendors for tasks such as word processing and project planning, PC-DOS, which operates simultaneously with UTeK, is supported.

In hardware, CAE Systems Division has added the National Semiconductor

32016 16-bit 10 MHz coprocessor, allowing access to 16 Mbytes of virtual memory. Disk storage is increased from 85 Mbytes expandable to 280 Mbytes. It has also added a graphics card for 720 × 704 pixel resolution and increased RAM to 2.5 Mbytes expandable to 4.5 Mbytes in standard configurations.

A file server configuration is available for about \$40,000, an Ethernet interface for \$1,400. Tekstation AT prices start at \$25,000.

—Lamneck
Circle 234



S O F T W A R E

Hierarchical Design Review Speeds Throughput

Taking advantage of the high degree of hierarchy and redundancy in VLSI circuits, the DRACULA III layout verification package from ECAD Inc. (Santa Clara, CA) increases the throughput of existing superminicomputers or engineering workstations. As a result, users need not move to more expensive supercomputers or hardware accelerators as their circuits increase in size.

With circuit complexity increasing the IC's layout is constrained by the minimum chip area and the design rules. In fact, critical circuit paths become more important as the electrical parameters become closely related to the geometries. Unfortunately, many existing programs that check circuit layout can take several hours on a DEC VAX-11/780 to verify a 50,000-gate circuit. Such programs typically view the circuit as a flat homogeneous structure, so memory requirements

increase rapidly as the size of the circuit grows, as does the processing required to verify each portion of the circuit.

However, most circuit layouts can be viewed as a collection of cells with each cell containing polygons that represent the physical location of individual elements (e.g., transistors and interconnects). Individual cells can be repeated, overlapped with other cells or combined to form larger cell structures that also can be repeated many times. This collection of individual cells and combined cells forms a hierarchical tree structure describing their geometric relationships to each other.


DRACULA III analyzes intercell geometric interactions within individual cells only once or analyzes the geometric interaction between a collection of cells only once. These characteristics are then stored for future reference whenever the

package encounters a similar configuration. Since the netlist that describes the overall organization of the circuit is also saved, the verification process is analogous to compiling a subroutine and re-linking the entire program. As a consequence, the company claims performance 4× to 10× faster than packages that do not utilize such an approach. ECAD cautions that performance gains are tempered by the size of the circuit as well as the degree of overlap allowed between cells. The hierarchical approach works best with complex circuits with a minimum of overlap between cells. Small circuits, or those with highly overlapped cell structures, work better with the flat approach, according to ECAD.

The package is available on a wide variety of minicomputers including those from Data General, Digital Equipment and Gould Computer Systems. Versions are also available for the Apollo and Sun engineering workstations.

—Aseo
Circle 233

Experimental Physicists Electronics & Electro-Optical Engineers



Du Pont's R&D Programs In Electronics and Electro-Optics Are Growing Rapidly.

The groups you will be joining develop sophisticated instrumentation and measurement techniques to support new product development and existing businesses; optical disk R&D and electronic imaging are examples.

You must have a Ph.D. in physics or an M.S. or Ph.D. in electrical engineering. A strong experimental background is required, including applying lasers, video techniques or microcomputers for the development of electronic and imaging systems. Other opportunities exist for backgrounds in state-of-the-art signal processing and computer generation of algorithms for systems development. Extensive liaison required with other groups places a

premium on your communications skills, both oral and written.

You will be headquartered in one of our electronics research laboratories in the Wilmington, Delaware area, with easy access to the cultural and rural lifestyle of Delaware, Pennsylvania, and eastern Maryland.

Salary is commensurate with your training and experience. You will participate in the highly regarded Du Pont benefits program, including relocation assistance. There are significant opportunities for personal/professional advancement.

For immediate consideration, please mail your resume, in complete confidence to:

**Mr. E.W. Johnson,
Employee Relations Dept.,
Room X50085EI,
E.I. du Pont de Nemours & Co.,
Wilmington, DE 19898**



REG U.S. PAT. & TM. OFF.

An Equal Opportunity Employer M/F
U.S. Citizenship or
Permanent Visa is required.


8-Bit Graphics D/A Converter Reduces Package Size

Designed to function as a building block in graphics systems, Analog Devices' (Norwood, MA) AD9700 monolithic D/A converter can accept 8 bits of digital data at update rates as high as 125 MHz, a feature important to the spatial resolution associated with raster scan systems. Equally important is the AD9700's high settling time specified at 10 nsec to 0.4% of gray scale. The ECL-compatible device is housed in a 22-pin package and operates from a single -5.2V power supply, dissipating only 650 mW. The output is quoted to develop 1V across a 75 ohm load which will drive a graphics monitor that conforms to EIA standards RS-170 and RS-343.

Eight current switches drive a precision R2R network; the AD9700's built-in

bandgap reference controls the current switches and achieves temperature stability as well as a power supply rejection ratio of 0.1%/volt. The 8-bit inputs are gated through ECL registers within the device, providing data storage and minimizing glitches in the output signal. A glitch adjust pin is also supplied on the device. The rise and fall times of the AD9700 are specified at 2 nsec, achieving compatibility with high bandwidth CRTs and extending the capability for higher pixel density.

The AD9700 provides five composite function input controls: composite blanking, composite sync, reference white, 10% bright and setup, which allows control over the composite blanking level. In addition, the need for exter-



nal timing circuitry to integrate sync and blanking with gray scale information is eliminated.

Five versions of the AD9700 are available. The AD9700BW (nonhermetic) and AD9700BD (hermetic) are DIP units operating over a temperature range of -25°C to +85°C; the hermetic DIP AD9700SD is for use over a range of -55°C to +125°C. The AD9700BE and AD9700SE are leadless chip carrier devices for temperature ranges of -25°C to +85°C and -55°C to +125°C, respectively. The SD and SE versions are available in military requirements.


—Lamneck
Circle 231

B O A R D S

Ethernet PC Transceivers, Controllers Based On VLSI Chip

Three new products for the 3Com (Mountain View, CA) IEEE 802.3 EtherSeries IBM PC network have been designed with a VLSI transceiver IC developed by 3Com and Advanced Micro Devices (Sunnyvale, CA). The 3C101 transceiver connects all 802.3-compatible controllers to the Ethernet cable by a piercing tap. A half-card network controller for the PC, the 3C500B replaces the previous full-size board. The 3C505 is an intelligent controller designed to work in the AT for server functions, as well as in the PC and XT.

The 3C505 has dual bus connectors, so it can be used in an AT with full 16-bit I/O to create a communication, print or disk server. In addition to the AMD transceiver IC, the board uses an 80186 for protocol processing, an 82586 Ethernet coprocessor and 128 Kbytes of RAM, expandable to 256 Kbytes. Smaller or more lightly loaded networks can use the same card in an XT or PC. Both this board and the standard-performance 3C500B controller have two connectors,



one for standard Ethernet coax and an external transceiver and one for thin (Cheapernet) cable with the transceiver on-board.

The 3C500B provides a personal computer connection to Ethernet with three VLSI chips. Integration of more transceiver functions onto the AMD chip is a major factor in packing the controller onto a half-card, which eliminates the need for a card guide at installation.

Rather than the standard 500m up to 1 km of cable can be used with the 3C101 transceiver. Designed to be fully IEEE 802.3 compatible, it taps into an Ethernet cable by piercing and operates with any make of controller. The piercing tap is not a new configuration, but eases network reconfiguration and installation.

3Com has also introduced two software packages to extend the range of


EtherSeries: the Ether3270 gateway into SNA and the EtherMac products to link Macintoshes into 3Com's multifunction 3Server box. An expansion board for the 3Server provides direct connection into AppleTalk. The Port Expansion Board costs \$625, the EtherShare software is \$695 per server, EtherPrint is \$395 per server and EtherMac software is \$50 per user. Users with the \$7,995 3Server can upgrade the Share and Print software for \$125 each. Ether3270 is \$1,595 for either PCs or the 3Server.

The piercing 3C101 tap is priced at \$295, with installation toolkit and parts available. The half-card 3C500B costs \$650 and the 3C505 high-performance controller, \$1,095. All prices are suggested list and subject to OEM discounts.

—Pingry
Circle 230

COMPUTERS/SYSTEMS

In-Circuit Emulator



Supporting NMOS and CMOS 8088 μ P up to 8 MHz, this in-circuit emulator, the SBE-88, features 5 real-time breakpoints, 64 Kbytes of mappable memory and an RS-232 interface. The SBE-88 supports the minimum and maximum modes of operation for the 8088 and provides full support for the 8087 and 8089 coprocessors. The five breakpoints allow real-time program execution until an opcode fetch occurs at a specified break address. Price is \$2,495 (32K) and \$2,795 (64K). **Huntsville Microsystems**, Huntsville, AL **Circle 205**

Dual- μ P System

Based on the 68000 and the microEclipse processors, this dual-microprocessor system, the Desktop Generation Model 45, runs Desktop/UX, a native UNIX operating system based on System V. The dual architecture allows the microEclipse to offload I/O operations from the 68000, which is dedicated to UNIX applications. The basic configuration consists of 512 Kbytes of memory, a 15-Mbyte disk and one floppy diskette drive. Price is \$750. **Data General**, Westboro, MA **Circle 152**

VME-Based 32-Bit Supermicro

Designed for harsh environments, this real-time UNIX-based 32-bit supermicrocomputer, the Universe 2400, is built around the 12.5 MHz MC68000 and the VMEbus. Its 32-bit internal datapath

and 4-Kbyte cache enable the Universe 2400 to execute 1.25 MIPS with no wait-states. The 32-bit VMEbus has a bandwidth of 40M bps and optional I/O processors, each with its own MC68000. Supporting UN/System V, the firm's implementation of UNIX System V, and UNOS, the company's UNIX-compatible real-time operating system, the Universe 2400 is priced from \$9,999 to \$17,500. **Charles River Data Systems**, Framingham, MA **Circle 157**

Workstations For Designing, Programming, Testing Programmable Devices



Both of these workstations, the Universal Programming workstation and the Logic Programming workstation perform designing, programming and testing of over 125 programmable logic devices such as PALs and IFLs. They also perform logic reduction and device simulation and are hosted on a pretested IBM PC/XT setup with a 256-Kbyte RAM, 10-Mbyte hard disk and a monochrome display. The software includes MS-DOS 3.0, PROMlink and ABEL. The programmer is the 29B, set up as a logic programmer or as a universal PROM/logic programmer. Prices are \$11,250 (Logic Prog.) and \$13,750 (Universal Prog.). **Data I/O**, Redmond, WA **Circle 160**

DEC-Compatible Backplane/Mass Storage

A pair of DEC-compatible backplane/mass storage systems offer features not available with the MicroPDP-11. The Cyclone Mass storage system includes a Q-Bus backplane, mass storage controller/interface, power supply and Winchester tape and floppy drives. The controller conforms to DEC's MSCP so can be configured with the LSI-11/23 PLUS and LSI-11/73. The CSM-ST model offers 36 to 240 Mbytes of Winchester capacity and a 60 Mbyte streaming tape drive; the CSM-FL offers 36 to 88 Mbytes of hard storage and an 8" floppy drive. Price

ranges from \$9,400 to \$21,000. **Qualogy**, San Jose, CA **Circle 155**

Computer Paint System

With a full color (24-bits/pixel) mode, this computer paint system, the ArtStar II, provides 16.7M colors. With a filtering capability to output 4,000-line resolution digital camera photos, ArtStar II's panel cell animation and multiple color cycling feature (Color Palette Movies) brings animations to the screen. Other features include antialiased drawing, 99 fonts on line, with camera font compose, pans and zooms and a pen-user interface that eliminates the use of a keyboard. Price is \$94,900. **ColorGraphics Systems**, Madison, WI **Circle 161**

150 nsec Supermini

This line of 32-bit superminicomputers uses the firm's VLSI technology and 64-Kbit memory. The 9400 has a 150 nsec cycle speed and includes a 1-Mbyte 9400 processor, a 40-Mbyte Winchester drive, 3 CRTs, a 125 lpm printer and the ITX operating system. The 9400 processor module provides a micro-controlled 32-bit processor with up to 4 Mbytes of memory, up to 8 system peripherals and up to 210 RS-232 connections. Price is \$67,000. **NCR**, Dayton, OH **Circle 156**

Universal Microcomputer Development System




Supporting 8-bit CMOS and single-chip microcomputers, this microcomputer development system, the SA-1000, supports Hitachi's 6301, 6305, the HSP (signal processor) 61810, and NEC's 7810/11. The unit includes a 12" CRT, two 8" floppy disk drives, an ASCII keyboard, real-time in-circuit emulation with 64 Kbytes of no-wait state RAM and

NEW PRODUCTS

a built-in universal PROM programmer. Price is \$7,995. Emulation probes are available for \$2,495 to \$3,245 each. **Sophia Computer Systems**, Santa Clara, CA **Circle 154**

5/7 MIPS Superminis



The HCX-7 32-bit superminicomputer features 7.1 MIPS performance in UNIX and C language environments. With an instruction set of 160 that typically requires one machine cycle of 100 nsec to execute, the HCX-7 allows up to 235 terminal connections. The HI200 superminicomputer provides 5.0 MIPS and also supplies 32-bit addressing. Supporting up to 224 interactive users, the HI200 uses 100K ECL technology. **Harris**, Ft. Lauderdale, FL **Circle 151**

Data Acquisition System

An addition to the firm's data acquisition line, the 1752A data acquisition system acquires data at 1000 readings/sec with one standard analog measurement processor. Each analog measurement processor employs a 14-bit A/D converter multiplexed to 16 differential analog measurement channels. The processor offers resolution to 124 μ V in the 1V range, measurement accuracy of 0.02% and DC common mode rejection of 70 dB. The 16-bit CPU supports Macrostore floating point processor, 132K main memory, 400-Kbyte double-sided, double-density floppy disk and IEEE-488/RS-232-C interfaces. Price is \$8,390. **Fluke**, Everett, WA **Circle 159**

Enhancements For Color Workstation

A graphics processor and accompanying graphics buffer have been added to improve the speed of graphics applications on the Sun-2/160 color workstation. The graphics processor supports all of the Sun-2/160 graphics standards including the CGI standard, available with Sun System Release 2.0. With the graphics processor, the Sun-2/160 draws vectors with floating point coordinates at 1.5 MIPS,

allowing for display of 40,000 2D vectors/sec and 25,000 3D vectors/sec. The shading rate of 3D polygons is 1 MIPS with polygon fill rates of up to 35 MIPS. Both the processor and the buffer list at \$5,900. **Sun Microsystems**, Mountain View, CA **Circle 153**

In-Circuit Emulators For 6809/80186

Both of these in-circuit emulators, the ICD-178 for Motorola's 6809 and the ICD-278 for Intel's 80186, can operate in a standalone environment (controlled by a console terminal) or with a host computer. The ICD-178 8-bit emulator operates at 2 MHz with 64 Kbytes SRAM for downloading files, altering memory contents and loading future memory into a target system. The ICD-278 16-bit emulator operates from 8 to 12 MHz with 128 Kbytes SRAM. **Zax**, Irvine, CA **Circle 158**

PERIPHERALS

Desktop Test Head

Designed for the PC-based Dash family of electronic design tools, this functional testing subsystem, Dash-Test, verifies semicustom VLSI chips in the same system used for the chip's development. Dash-Test reveals functional differences and prototype errors by forcing identical test vectors into both the software models and hardware prototypes. For application-specific ICs and PCBs with up to 256 I/O pins, Dash-Test connects the device under test through a zero insertion force socket. It can be configured in increments of 16 up to 256 channels, enough capacity to handle multiple sets of ASICs if a given logic array cannot fit into a single package. Price is \$5,000. **FutureNet**, Canoga Park, CA **Circle 169**

LAN For HP 9000 Series 500s

A full implementation of the IEEE 802.3 standards for a 10 Mbyte/sec, baseband multiple-access/collision-detection LAN, the HP 9000 LAN links HP 9000 Series 500 computers to one another and to HP 3000 computers. Offering Ethernet Version 1.0 support, the LAN consists of Network Services/9000 Series 500 software (HP 5095314) and the LAN/500 link interface card (HP 27125A). **Hewlett-Packard**, Palo Alto, CA **Circle 167**


Statistical Multiplexer With Integral Modem

This 4- or 8-channel menu-driven modular multiplexer, the 7400-series statistical multiplexer, features a 2400 bps switched network internal modem option, leased-line internal modems with automatic dial back-up and restoral and an extended system control function that is accessed through a 300 bps help diagnostic modem. For leased-lines, the 7400 also offers integral 4800 and 9600 bps modems with dual-dial backup. **Racal-Vadic**, Milpitas, CA **Circle 163**

3" Floppy Disk Drives

With storage capacities from 250 Kbytes to 1 Mbyte, these 3" floppy disk drives (EME-102/202, EME-150/250, EME-130/230) are plug-compatible with 5 1/4" floppy disk drive interfaces. Measuring 90 mm wide, 150 mm deep and 40 mm high, the drives include single-button diskette ejection/insertion and direct-drive brushless motor and a steelband. Track density of the disks is 100 or 200 tpi, rotational speed is 300 rpm and disk diameter is 3". **Panasonic**, Secaucus, NJ **Circle 164**

Video Tracing System




Designed for microcomputer CAD systems, the video tracing system uses a video camera to project drawings onto a monitor. The CAD drawing screen is overlaid on top of the image to trace the drawing into the CAD system. The video tracing system can be used with AutoCAD and CADmaster; the basic system includes software, video camera, stand and scan synchronizer card for IBM PC, XT or AT and sells for \$5,000. **Brighter Images**, Lafayette, CA **Circle 166**

“The Invitational Computer Conferences bring to you the latest high-tech information you need to hear, and the major OEM products you need to see. We’ll be there!”

And you’ll find other top OEM manufacturers, such as NCR, Fujitsu, Xebec, Lear Siegler, Siemens and IBM, to name but a few.

Celebrating its 15th year, the “OEM Only” ICCs bring you, the volume buying decision makers, together with the key suppliers of computer and peripheral products. The ICCs also bring you a full day of high-tech seminars, explaining the latest in computer product technologies and what they mean to you, the systems design engineer. As an invited guest, there is no charge to attend the seminars or product displays.



Richard M. Horowitz
Vice-President, OEM Sales
Telex Computer Products, Inc.

The ICCs, a series of eleven, one-day regional conferences are convenient to where you work. The small, exclusive setting makes it easy for you to meet potential suppliers one-on-one.

Hear what the OEM manufacturers have to say, learn about new technologies, and remember, you may attend “by invitation only.”

1985/86 U.S. ICC Locations

| | |
|----------------|---------------------------------|
| Sept. 5, 1985 | Newton/Boston, MA |
| Sept. 23, 1985 | Atlanta, GA |
| Oct. 8, 1985 | Westlake Village, CA |
| Oct. 22, 1985 | Minneapolis, MN |
| Nov. 7, 1985 | Gaithersburg, MD (D.C. area) |
| Jan. 9, 1986 | Irvine, CA |
| Jan. 28, 1986 | Austin, TX |
| Jan. 30, 1986 | Dallas, TX |
| Feb. 27, 1986 | Ft. Lauderdale, FL |
| Mar. 18, 1986 | San Jose, CA |
| Apr. 2, 1986 | Nashua, NH |

Call your local OEM supplier for your invitation or fill out the coupon and mail to:

B. J. Johnson & Associates, Inc.
3151 Airway Avenue, #C-2
Costa Mesa, CA 92626
Phone: (714) 957-0171
Telex: 5101002189 BJ JOHN



Yes, I need an invitation to your “OEM Only” ICC. The nearest ICC to me is: _____

I buy in volume:

- Computers
- Disk/Tape Drives
- Controllers/Interfaces
- Terminals/Graphic Displays
- Software
- Printers
- Memory Boards
- Modems/Multiplexers
- Power Supplies

Name _____

Title _____

Company/Division _____

Address _____

City _____ State _____ Zip _____

Mail To: B. J. Johnson & Associates, Inc., 3151 Airway Avenue, #C-2, Costa Mesa, CA 92626
Phone: (714) 957-0171 Telex: 5101002189 BJ JOHN

Pen Plotters With HPGL Emulation

Designed for low-end business graphics, CAD and CAE, these two plotters, the 4550 and 4551, meet the requirements of the HPGL. Both models plot charts, graphs and drawings on paper and transparencies, and both feature removable six-pen cassettes. Ballpoint, water-based ceramic or oil-based fiber-tip pens are available in 8 to 12 colors. Both the 4550 and the 4551 contain RS-232-C Serial and Centronics Parallel interfaces. Prices are \$795 (4550) and \$995 (4551). **Facit**, Merrimack, NH

Circle 221

19.2 KBPS Compact Data Modem

Operating at 19.2 Kbps, the DSP 19200M Data Modem, packaged in a 12.4" x 15.4" x 3.5" enclosure, features a built-in eight-port data multiplexer, comprehensive diagnostic test capabilities and error correction based on trellis coding technology. The modem operates over four-wire type 3002 leased telephone lines with D1 conditioning. Price is \$12,000. **NEC America**, Melville, NY

Circle 213

1/2" Streaming Magnetic Tape Drive

With a 64-Kbyte cache memory and a MTBF of 7400 hours, this 1/2" streaming tape drive, the DMT 2520, is ANSI/IBM-compatible. Storage capacity is 46 Mbytes at 1600 bpi, 92 Mbytes at 3200 bpi (2400' reel) and up to 138 Mbytes at 3200 bpi (3600' reel). Features include automatic tape loading and threading, self-diagnostics during power up and a Pertec interface. **Anritsu America**, Oakland, NJ

Circle 162

Video Display Terminal

With an 80 or 132 x 24 display, the ADM 12plus terminal is compatible with the TeleVideo 925, 950, 912 and 920 terminals, and this firm's ADM 2, ADM 12 and the ADM 31. The terminal features programmable cursor keys, a variable format display memory, variable speed vertical scrolling and horizontal scrolling. A 4-page memory option is also available to add a 158-column x 48-line memory format. Price is \$745. **Lear Siegler**, Anaheim, CA

Circle 211

Speech Recognition And Touch Pad Keyboards

The Touch Pad keyboard and the Speech Recognition keyboard are two new products added to this firm's line of keyboards. The KB5153 touch pad keyboard allows information selection with a finger touch or a stylus. It provides three pointing modes including cursor key, mouse and absolute, and a function key mode. The KB5152V speech recognition keyboard is plug-compatible with the IBM PC and XT and allows use of a 160-word vocabulary of verbal commands. Speech recognition works through the keyboard electronics so no software modifications are necessary and no PC adder board is required. The keyboard comes with complete noise canceling microphone, foot switch, vocabulary management software and user's manual. **KeyTronic**, Spokane, WA


Circle 168

2400 BPS Modem

Bell 103, 212A and CCITT V.22 compatible, as well as internationally (CCITT V.22 BIS) compatible, Scholar, a 2400 bps modem, operates in sync/async mode. With auto dial and voice/data capabilities, Scholar offers modem options from the screen menu, rather than from switches. Also announced are five modular modems, additions to the DF100 Series. They operate at 300/1200, 2400, 4800 and 9600 bps. Price for Scholar is \$895. The DF100 Series ranges from \$595 to \$3,045. **Digital Equipment Corp.**, Maynard, MA

Circle 210

Hard-Disk Video Recorder




The Dynamic Image Store (DIS) video disk recorder is designed for real-time recording on a plated hard disk. DIS provides immediate playback of up to 500 images in real time at 60 fields/sec, as well as slow motion and single-step stop action for image-by-image analysis. **Matrix Instruments**, Orangeburg, NY

Circle 165

3 1/2 INCH DRIVE- MOUNTABLE HARD DISK CONTROLLER

ST-506/412 to SCSI/SASI



DJ 210

- LOW POWER CONSUMPTION
- LOW PARTS COUNT
- NO ADJUSTMENTS

with
**ALL THE FEATURES
AND MORE
THAT YOU HAVE COME
TO EXPECT ON A 5 1/4"
CONTROLLER**

at a
**VERY, VERY, LOW
COST TO YOU!**

CALL THE TECHNOLOGY LEADER

KONAN


The Responsive One

Tel. 602-269-2649

Telex 9109511552


Circle 63 on Reader Inquiry Card

CCSI Closes the Control Loop



For reliable performance in your STD BUS System, specify CCSI modules and card cages. Choose from our processors, memories, I/O's, controllers and support equipment. For specialized control requirements, CCSI will custom design a system to meet your most critical needs.

Write or call, today, for complete information.



Contemporary Control Systems, Inc.

2733 Curtiss Street, Downers Grove, Illinois 60515 (312) 963-7070

Circle 40 on Reader Inquiry Card

PRECISION SHAFTING?

HARD CHROME-PLATED INDUCTION HEAT-TREATED 4 to 8 SUPER-MICRO FINISH

For the Computer Peripheral Industry
Carriage Shafts
Linear Bearings
Guide Rods
Mandrels
Pins

COMPLETE IN-HOUSE SERVICE
FROM BAR STOCK
TO FINISHED
PART




Treffers Precision, Inc.

1021 N. 22nd Avenue, Phoenix, Arizona 85009 (602) 258-1554

Circle 51 on Reader Inquiry Card

NEW PRODUCTS

Photoplotter For Micro-Based CAD Systems



Designed for use with microcomputer-based PCB CAD systems, the FPI-1622 photoplotter interfaces directly to the computers via RS-232-C. The FPI can create one to one precision artwork for PCBs with line width and 12 mils spacing. The plot area is a flatbed with vacuum hold down and accommodates plots of up to 15.5" x 21.5". Currently supported by Personal CAD Systems, the FPI-1622 photoplotter is priced at \$25,000. **GTCO**, Rockville, MD


Circle 204

3 1/2" Compact Winchester Drive

With a maximum unformatted storage capacity of 19.1 Mbytes, these compact 3 1/2" Winchester disk drives (the DK301 Series) feature high density coated recording media and a low-load head. The Series adopts the ST506/412 standard interface for 5 1/4" drives, for convenient switch to 3 1/2". Price ranges from \$750 to \$920. **Hitachi**, New York, NY

Circle 206

QCR Camera




Registering film within $\pm .0002$ " without registration pins, this precision registered camera and μ P controller is designed for the Matrix Instruments QCR film recorder. The Computer Guided Optical Registration (CGOR) offers automatic operation, which electronically notches the film after 36 exposures and starts a new roll count, and manual operation for shooting long rolls of film and discretionary film notching. **Viscom Optical Products**, Costa Mesa, CA

Circle 208

NEW PRODUCTS

COMPONENTS

10-Bit ADC Low-Pass Filter Combo



The RT5640 A/D converter with on-chip antialiasing filter works as a complete analog front end for digital signal processors. Containing a fully differential 10-bit linear A/D converter with a sampling rate varying from 20 Hz to 40 kHz, the RT5640 can achieve a user-controlled AGC function through an externally supplied reference voltage. The fully differential seventh order antialiasing filter tracks the conversion rate of the A/D converter; the filter has 0.2 dB of passband ripple and a stopband rejection of more than 60 dB. Price is \$22 in 100s. **EG&G Reticon**, Sunnyvale, CA **Circle 133**

256K DRAM With Extended Page Mode

Employing triple-poly technology and laser-fuse redundancy, the MCM6256 is a 262,144-bit DRAM. Page-mode operation allows random column accesses of up to 512 bits within a selected row with page access times of 50 nsec max and page cycle times of 100 nsec max for the MCM6256-10 device. Max page access times for the MCM6256-12 are 60 nsec, and the MCM6256-15, 75 nsec. Page cycle times specify 120 nsec for the MCM6256-12 and 150 nsec for the MCM6256-15. Prices are \$26-\$36. **Motorola**, Austin, TX **Circle 182**

64K CHMOS EPROM For Military


A military-specified version of the earlier 64K 27C64 CHMOS EPROM, the M27C64 uses from 1/400 to 1/4 the power of EPROMs based on HMOS technology, such as the M2764A. The new M27C64 is pin compatible with the M2764A and can use the same programming equipment. The M27C64 also pro-

vides radiation immunity of the M2764A because of similar geometries. Available in 250 nsec and 350 nsec versions, their prices in 1,000s are \$107 and \$59, respectively. **Intel**, Santa Clara, CA **Circle 181**

Controller For Group 4 Facsimile/X.25 Communications

Handling all link-level operations of the Group 4 facsimile, as well as CCITT X.25 serial data communications standard, the WD2511F MOS/LSI device is a bit-oriented controller, which automatically manages several packet buffers, acknowledges error free packets and requests packets containing errors to be retransmitted. The device also offers built-in channel DMA, zero-bit insert and delete, auto appending and testing of FCS field and TTL compatibility. **Western Digital**, Irvine, CA **Circle 177**


Three-Port Hybrid Isolation Amplifier



Combining $\pm 2500V$ of transform-coupled isolation and $\pm 0.012\%$ max nonlinearity, this hybrid isolation amplifier uses two internal transformers to provide three-port isolation between the input, output and power supply ports. The AD295 is available in three grades: $\pm 0.05\%$, $\pm 0.025\%$ and $\pm 0.012\%$ max nonlinearity; $\pm 450 \mu V/^\circ C$, $\pm 300 \mu V/^\circ C$, and $\pm 150 \mu V/^\circ C$ max output offset voltage drift; $\pm 10 \mu V/^\circ C$, $\pm 3V/^\circ C$, $\pm 1.5V/^\circ C$ max input offset drift. Other key specs are $\pm 1.5\%$ typical gain accuracy, $\pm 60ppm/^\circ C$ max gain drift, $\pm 18 mV$ max output offset voltage, and $\pm 3 mV$ max input offset voltage. **Analog Devices**, Norwood, MA **Circle 128**

MULTIBUS* DISK and TAPE CONTROLLER for

- ST506/412 HARD DISK
- 5 1/4" or 8" FLOPPY
- FLOPPYTAPE



TAISHO 6000

- VERY HIGH PERFORMANCE
- VERSATILITY
- RELIABILITY

at

A VERY LOW PRICE!

CALL
THE TECHNOLOGY
LEADER

KONAN ^{T.M.}

The Responsive One

Tel. 602-269-2649


Telex 9109511552

*Trademark of Intel Corp.

Circle 64 on Reader Inquiry Card

BOARDS

Graphics Display Generator



Built to MIL-E-16400 requirements, this graphics display generator, CombatView, features a graphics instruction set, a dedicated Schottky μ P and a 16-bit ALU. Resolutions of either 640×512 or 1280×1024 , interlaced or noninterlaced, are available. CombatView provides black and white to multicolor displays up to 64-bit planes for configuration in any military environment. **Liacom**, Marlboro, MA **Circle 147**

3-Mbyte Memory Board For PC AT

Providing up to 3 Mbytes of RAM for the IBM PC AT, the Mega Memory is a full-size printed circuit board that fits into any of the 16-bit slots of the AT. A total of 6 banks, representing 12 rows, can be populated using either 64K or 256K chips, depending on the configuration. Standard with the board are the Wait-Less Printing and Insta-Drive Software packages. Price is \$395 to \$5,495. **Emulex**, Costa Mesa, CA **Circle 192**

Analog Input Module

An intelligent, self-contained single-board micro system, Scadar Series 10 is complete with memory, power supply and I/O. It interfaces to IBM PCs, Intel 310/A, DEC LSI-11, PDP-11, VAX, HP-3000 and other hosts through RS-232 and TTY current loop ports. Eight differential inputs are provided, each with a detection range of ± 10 VDC and over-voltage protection to ± 16 VDC. Price is \$2,500. **Burr-Brown**, Tucson, AZ **Circle 198**

16-Bit S-100 Based Slave Processor

Designed to operate with 8- and 16-bit Master CPUs, the Super 16 Slave Processor comes with an 8 MHz 80186 CPU, 256 Kbytes of RAM and 4 serial ports. Running under Turbo DOS and Network/OS, the Super 16 features Master-to-Slave, 8-bit/16-bit memory to memory communication, I/O status port, 4K/32K of EPROM, programmable baud rate generator, sync/async communications and real-time clock. Price is \$1,195. **Advanced Digital**, Huntington Beach, CA **Circle 197**

68000-Based Octal Serial Board

An addition to the firm's ModulasTen line of Multibus products, this octal serial board, the M68COM, provides eight independent full-duplex channels and contains the 16/32-bit 68000 or 68010 MPU. Running at 10 MHz with no wait states for memory reads or writes, the M68COM includes an optional 10 MHz 4-channel DMA controller. The board supports X.25, SDLC, HDLC and Bi-sync protocols. Price is \$1,595. **SBE**, Concord, CA **Circle 200**

VIDEO COORDINATE DIGITIZER


X-Y Measurements in a Standard TV Picture



- X resolution of 1,000 counts
- Y resolution of 480 counts
- Cross Hair selectable form
- RS232C or IEEE-488 (GPIB) I/O
- Optional edge decoding
- Optional full page edge enhanced characters
- Several optional manual positioners

H.E. Incorporated 2601 McLeod Drive Las Vegas, NV 89121 (702) 457-6118

VMEbus Processor With VMX Bus Port



An enhanced version of the PT-VME100 VME processor, the PT/VME103 VME/VMX processor module uses a 10 MHz 68010 virtual memory processor in conjunction with a 68451 MMU. Room for a second MMU is provided, and the module will support a 68881 floating point processor. Some features include conformance to the VMX Revision B specification, VMEbus 24-bit address and up to 128K ROM and 32K RAM or an additional 128K ROM on-board. **Performance Technologies**, East Rochester, NY **Circle 149**

NEW PRODUCTS

5 1/4" Floppy Controller For Multibus

Using the FD 1791 controller, this 5 1/4" floppy disk controller controls up to four single- or double-density floppy drives. Write data is precompensated and DMA logic is included to allow data transfers to any 16M locations in the system memory. Complete with a phase locked loop data separate and a 34-pin locking flat ribbon cable connector, its price is \$280 in 100s. **Central Data**, Champaign, IL **Circle 199**

VMEbus Board Set

Centering around a cache-based M68000/M68010 CPU board, this VMEbus product line includes a system controller board, an EPROM/SRAM board and a 512 Kbyte DRAM board. The board set is packaged on the single height VME form factor. The CPU board uses a cache scheme like the M68020 and provides 1 Kbyte on-board and cache memory, and each has an 8, 10 and 12.5 MHz M68000 or M68010. Prices begin at \$1,095 in 25s. **Microcosm**, Beaverton, OR **Circle 195**

IBM PC Quick Vector Processor

Built around the 68000, the QVP (Quick Vector Processor) accepts vector data as input and produces raster data to drive high resolution color film recorders and other hardcopy devices. Accepting data input coordinates in a 32,768 x 32,768 (15-bit) data space, the QVP comes with the SCODL (Scan Conversion Object Description Language). A total of 256 colors can be used in one image from a palette of 16M possible colors. **Matrix Instruments**, Orangeburg, NY **Circle 203**

68020 Supermicrocomputer On Multibus

Featuring the 68020, this 32-bit processor board, the MAP-2000, and the MB-2000 2-Mbyte companion memory board offers 32-bit supermini performance (VAX 11/780) on two boards. Using the dedicated 32-bit memory expansion bus, the MAP-2000 can access up to 8 Mbytes of memory. Additional on-board resources include up to 512 Kbytes of ROM, 128 Kbytes of zero wait state RAM, a real-time clock with battery backup, 16 levels of vectored interrupts, two RS-232 serial ports and bus interfaces to the Multibus, iLBX Bus and the 32-bit Matrox MX-bus. **Matrox**, Quebec, Canada **Circle 196**

HIGH RELIABILITY ACTIVE DELAY LINES




5 OR 10 TAP ACTIVE BUFFERED INPUTS AND OUTPUTS

- LOW PROFILE HERMETIC METAL 14 PIN DIP
 - HIGH RELIABILITY THICK FILM HYBRID CONSTRUCTION
 - IDEAL FOR HOSTILE ENVIRONMENTS/MILITARY GRADE COMPONENTS AVAILABLE
 - U.S. MANUFACTURED ON AUTOMATED ASSEMBLY AND TEST EQUIPMENT FOR REPEATABILITY
 - HIGH MTBF
 - COMPLETE STANDARD PRODUCT LINE AND CUSTOM DESIGNS AVAILABLE
- FOR MORE INFORMATION CONTACT...
JO-ANN RICCI (408) 395-2300 X265

HYTEK MICROSYSTEMS
980 UNIVERSITY AVENUE
LOS GATOS, CA 95030


Circle 34 on Reader Inquiry Card

The *Ultimate* Delay Line Now! Available In Two Configurations...



Auto-Insertable

- 5 Outputs, Equally Spaced
- Input and Outputs T²L Buffered Delay
- Delays—4 NS to 500 NS
- Precise and Stable Delays
- Competitively Priced
- Quick Delivery



Surface Mount

data delay devices, inc.

385 Lakeview Avenue • Clifton, New Jersey 07011 • (201) 772-1106

Circle 43 on Reader Inquiry Card

80188-Based Multibus-Compatible SBC

Based on the 80188 CPU, operating at 8 MHz, this single-board computer has 16 JEDEC 28-pin memory sockets. 96K to 128 Kbytes of RAM are available. As a system, the MP85188 includes the 80188 CPU, clock, RAM, EPROM, EEPROM, serial I/O, parallel I/O, interrupt controller, timers, watchdog security timer, user-defined board status I/O and SBX expansion. Price is \$1,495. **Burr-Brown**, Tucson, AZ **Circle 191**

IBM PC Multifunction/Display Combo Boards

Designed as IBM PC, XT, AT and compatible enhancement boards, the Persyst Mono Combo Card and Color Combo Card achieve multifunction and display on a single board. The combo boards offer up to 384K of expanded memory. Multifunction features include a parallel printer port with bidirectional capabilities. A serial port connects to any async modem. Byte parity is provided, and the boards have switch selectable starting

addresses of 128 Kbytes, 256 Kbytes and 384 Kbytes. Insta-Drive and Wait-Less Printing Software programs are included. Prices start at \$520. **Emulex**, Costa Mesa, CA **Circle 201**

SOFTWARE

Component/Semicustom IC Libraries

These three component libraries and two semicustom IC libraries are designed to work with the firm's PCB software. They include the CMOS family components library which includes 150 standard components from Motorola's 14000 series of ICs; the μ P components library containing 150 components from the Intel family of microsystem components; and the discrete device components library, drawn from various manufacturers, which has about 100 components, including resistors, capacitors, transistors and others. The semicustom IC libraries are the Motorola ALS-TTL macrocell array library and the Motorola CMOS macrocell array library. All cost \$500 each. **P-CAD**, San Jose, CA **Circle 170**

lation of MOS and CMOS circuits and is not a SPICE derivative. Written originally to simulate bipolar circuits and later adapted for MOS technology like SPICE and SPICE derivative simulators, Simon can accept existing SPICE-coded network files. The company quotes the new simulator as operating as fast as 50x the speed of SPICE and guaranteed to converge the first time it is run. **ECAD**, Santa Clara, CA **Circle 172**

Turbo Pascal 3.0 With Graphics, BCD Options

Turbo Pascal 3.0 now has added graphics, optional BCD support, I/O redirection and a memory mapped editor. The Turbo Pascal language environment includes a single-pass native code compiler, full-screen editor with Wordstar-like commands, run time error checking, commented source code and a MicroCalc spreadsheet. Requiring 35 Kbytes of memory, Turbo 3.0 is available for micros running MS/DOS, PC/DOS, CP/M 80 or CP/M 86. Price is \$69.95 **Borland International**, Scotts Valley, CA **Circle 171**

Software For IBM PC Instrumentation Systems



Designed to support the PCI-4301 series single board I/O system on the IBM PC, the PC-4901-1 software package provides subroutines which allow a user to write application software in BASIC. It consists of three parts: a BASIC callable routine package, a reference table to define I/O points and an edit program to allow users to update the reference table. The reference table is used to define such things as gain, data format and engineering units for the I/O points. **Burr-Brown**, Tucson, AZ **Circle 173**

μ P Development Tools For ULTRIX

BSO's family of μ P development tools is now available for DEC's line of VAX computers operating under the ULTRIX operating system. Full support is available for the Intel 80186, 8087 and 8051, the Motorola 68000/010 and 6809 and the Zilog Z80 and Z8000. The development tools include C, Pascal and PL/M compilers, macro assemblers, symbolic debuggers and communication packages and are available under ULTRIX or UNIX 4.2. **Boston Systems Office**, Waltham, MA **Circle 217**

SDLC PC-To-PC Communications Software

Allowing IBM PCs to communicate with each other using the SNA/SDLC protocol, the Adapt SNA PCcom software package provides complete file transfer capabilities between PCs. Files on the secondary PC can be renamed or deleted remotely via the primary PC. It runs on an IBM PC, XT, AT or compatible with 128K memory, one diskette or hard disk drive, one IBM SDLC adapter card and a synchronous modem. Price is \$475. **Network Software Associates**, Irvine, CA **Circle 220**

SPICE Circuit Simulator

The Simon Simulator is based on algorithms created specifically for the simu-

Matthey
FILTERS
means
sharper
PIXELS

IF YOU *have to* BANDLIMIT
DO IT THE MATTHEY WAY....

Matthey FILTERS ARE:

- SHARP CUT OFF ■ 75 Ω
- WIDEST BANDWIDTH
- PHASE EQUALISED
- OPTIMISED FOR LOW RINGING
- SMALL SIZE

MAX. HEIGHT — Components 9mm, Overall 12mm

ASK FOR DATA NOW

Television Equipment Associates, Inc.

BILL PEGLER, PRESIDENT
BOX 393 · SOUTH SALEM, N.Y. 10590-0393
Tel. 914-763-8893 Tlx 710-575-2600
In California phone 213-271-9570



Visit Us At SIGGRAPH Booth 1660
Circle 44 on Reader Inquiry Card

NEW PRODUCTS

Modula-2 Developers System

The Pinnacle/MOSYS Development System includes the Motorola-2 operating system and a 68000 native code compiler, a document processor, a library and utilities, and a screen editor. Standard hardware features in the developers package include 256 Kbyte RAM, a 10 Mbyte hard disk, seven serial ports and one parallel port. The Pinnacle 12 MHz 68000 executes 3 MIPS with a zero wait state RAM of up to 8 Mbytes. Price for the package is \$3,995. **Pinnacle Systems**, Dallas, TX **Circle 219**

PCB Layout Software

The Auto-Router is a collection of software tools and circuit element templates that aid in the layout and trace routing of a double-sided PCB. Currently running on most MS-DOS machines, the output of the Auto-Router is a complete definition of the PCB, including silk screen and drilling patterns, as a script file to the AutoCAD mechanical drawing program. The software can route a 20" by 20" PCB, perform traces routed on 50 mil centers,

provide for buses of variable sizes, allow for creation and use of custom parts and more. Price ranges from \$995 to \$1,499. **The Great Soft-Western Co.**, Denton, TX **Circle 218**

Data Security Software

Written in C for IBM PCs and compatibles, this menu-driven data security program, Comsafe-X, is designed for data communication and information management. In networks, it can communicate privately with another party, assure the authenticity of received data, create and verify electronic digital signatures, verify the source of a received message, implement an electronic mail system and protect data from disclosure. Price is \$500 per user. **RSA Security**, Sunnyvale, CA **Circle 216**

Symbolic Simulator For 8086/87/80186

A high-level language-oriented simulator for debugging and analyzing programs written for the Intel 8086/87/80186 μ P. SoftProbe/87 provides 8087 numerical coprocessor simulation. SoftProbe/87

can be hosted on VAX under VMS or UNIX, or any 68000-based supermicro running UNIX System III, V and BSD 4.2 operating system. Supporting Intel-compatible language processors, SoftProbe/87 accepts MCS-86 executable code module as input. License starts at \$6,750. **Systems & Software**, Costa Mesa, CA **Circle 214**

3D CAD/Drafting System

Suited for the IBM PC family, the interactive 3D CAD and drafting system, the 3-D Graphixx CADD System, is capable of 3D imaging/modeling, technical graphics, production drafting CAE, animation, slide show and more. The system includes a variety of options like 19" color workstations and A-E size plotter support. 3-D Graphixx comes with color selection per vector, menu operations, 2D and 3D editing, graphics word processing, math function graphics generation with hidden lines removed, multilayering and auto scale/auto dimensioning. Price is \$2,995 (IBM PC) and \$3,995 (PC/AT). **Universal Intergraphix**, Ontario, CA **Circle 215**

NEW LITERATURE

Military Products Designer's Reference Guide

Product Spectrum
Semiconductor
Cross-References
TEXAS INSTRUMENTS

Military Reference Guide. Over 900 devices are featured in the Military Products Designer's Reference Guide, a free 100-page manual from Texas Instruments. The guide provides four product Sections, Logic, Linear and Interface, Bipolar Memory and MOS Memory, along with a section on the SBR9989 16-bit military μ P. Product descriptions for AS, ALS, CMOS and LinCMOS are included with complete graphs and charts.

Texas Instruments **Circle 261**

The Ada Primer

An Introduction to the
Ada Language System
PHILIP I. JOHNSON

The Ada Primer. In his book, *The Ada Primer: An Introduction to the Ada Language System*, Philip I. Johnson examines Ada as a program design language that is easy to learn, lends itself to effective management and reduces costs. Assuming prior knowledge of high-level programming languages (e.g., Fortran and COBOL), Johnson introduces Ada's techniques for describing and typing data, its subprogram concepts, its approaches to parallel real-time operations and its package concept for program modules.

McGraw-Hill **Circle 256**

High Resolution Cathode-Ray Tubes



CRT Brochure. With descriptions of photorecording and projection CRTs and their applications, this six-page brochure from RCA Tube Operations presents technical data and schematic diagrams. Specifications include deflection angle anode voltages, electrode and grid voltages, line width, luminance and emission wavelength. Four-color charts and a CIE color designation chart are also provided.

RCA **Circle 263**



Digital Filtering Application Note. Dealing with digital filtering and two different structures of finite impulse response (FIR) digital filters, this application note from TRW LSI Products Division, *An Introduction To Two Different FIR Structures*, summarizes the tapped delay line signal flow structure for FIR filters. It also offers an alternative method: the Frequency-Sampling structure, which can be outlined in hardware time-multiplexed with Infinite Impulse Response (IIR) filters because of the similarity between the two forms.

TRW **Circle 254**

Photodiode/Amplifier Data Sheet. Hamamatsu has published a technical data sheet detailing characteristics, spectral response, specifications and operating instructions of its S1406 series photodiode/amplifier combination devices. These recently introduced devices incorporate a UV enhanced silicon photodiode chip and a FET input operational amplifier in a TO-5 package. The four-page data sheet is fully illustrated.

Hamamatsu **Circle 262**

APPGEN Software Directory. The APPGEN library of fourth generation UNIX software is covered in this Directory from Software Express. Included are 45 vertical market applications that run on the 50 machines to which the Software Express development environment is currently directed. They range from superminis like the IBM PC/AT to mainframes such as Amdahl. The Directory is \$10 and will be updated quarterly. **Software Express** **Circle 255**



August 1-2

Integrated Logistics Support Seminar. Washington, DC. Contact: Technical Transfer Society Seminars, c/o Technology Training Corp., Dept. ILS/LSA, PO Box 3608, 3420 Kashiwa St., Torrance, CA 90510-3608. (213) 534-3922.

August 4-8

ASME International Computers In Engineering Conference. Boston, MA. Contact: Mary Benedict, American Society of Mechanical Engineers, 345 East 47th St., New York, NY 10017. (212) 705-7100.

August 5-7

The IBM PC Seminar. Washington, DC. (four other dates and locations) Contact: Data-Tech Institute, Lakeview Plaza, PO Box 2429, Clifton, NJ 07015. (201) 478-5400.

August 5-9

Fiber Optic Communication Systems Course. Santa Barbara, CA. Contact: University of California Extension, Santa Barbara, CA 93106. (805) 961-4200.

August 5-9

Contemporary Data Communication Networks: Planning, Management And Computer-Based Design Course. Ann Arbor, MI. Contact: Dixon R. Doll, Engi-

neering Summer Conferences, 400 Chrysler Center, North Campus, University of Michigan, Ann Arbor, MI 48109. (313) 971-5234.

August 12-14

Data Communications: Network Design, Integration and Applications. Los Angeles, CA. Contact: Software Institute of America Inc., 8 Windsor St., Andover, MA 01810. (617) 470-3880.

August 13-15

Computer Graphics '85 East. Boston, MA. Contact: National Computer Graphics Association, PO Box 3412, McLean, VA 22103. (800) 225-6242.

August 13-15

Systems Network Architecture And Implementation Seminar. Boston, MA. (six other dates and locations) Contact: CSI, 992 South Saratoga-Sunnyvale Rd., San Jose, CA 95129. (408) 725-1568.

August 14-16

Structured Systems Development With 4th-Generation Languages Seminar. Denver, CO. Contact: Software Institute of America Inc., 8 Windsor St., Andover, MA 01810. (617) 470-3880.

August 20-22

Designing With Single Chip Microcom-

puters Course. Boston, MA. (Chicago, IL—Oct. 15-17) Contact: Hughes Institute, PO Box 17968, Milwaukee, WI 53217-0968. (414) 271-1266.

August 21

Applied Data Communications Seminar. Chicago, IL. (several other dates and locations) Contact: UDS Representative, Instrument Dynamics, PO Box 584, Wakefield, MA 01880. (205) 837-8100, ext. 306.

August 26-28

PC FAB Expo '85 Technical Seminar And Trade Show. Boston, MA. Contact: Julia Wilson, PC FAB Expo '85/Boston, 1790 Hembree Rd., Alpharetta, GA 30201. (404) 475-1818.

September 5

15th US Invitational Computer Conference (ICC). Newton, MA. (several other dates and locations) Contact: B.J. Johnson & Assoc., 3151 Airway Ave., #C-2, Costa Mesa, CA 92626. (714) 957-0171.

September 10-12

CADCON. Boston, MA. Contact: Steve Schuldenfrei, Morgan-Grampian Exposition Group, 1050 Commonwealth Ave., Boston, MA 02215. (617) 232-EXPO.

ADVERTISER INDEX

| | | | | | |
|---|-----|--|-------|--|-------|
| Analogic | 49 | Floating Point Systems | 6,7 | Nicolet | 34 |
| Apert-Herzog | 42 | Force Computers | 12,13 | Number Nine | 61 |
| Aptec Computer Systems | 43 | Genicom | 18 | Numerix | C4 |
| Roy Ball Associates | 76 | Gould | C2 | Omnicom | C3 |
| Canon USA | 62 | Gould AMI | 44,45 | OMTI Scientific Micro Systems | 32 |
| CELCO (Constantine Engineering Labs Co. | 65 | Graphic Strategies | 10 | Panasonic | 24 |
| Central Data | 20 | HE Inc. | 96 | Parallax Graphics | 54 |
| Cherry Display Products | 42 | Hytek Microsystems | 97 | Power Systems | 69 |
| Cherry Electrical Products | 11 | Imaging Technology | 38 | Qume | 57 |
| Contemporary Control Systems .. | 94 | INACOM International | 8 | Simfact | 78 |
| Control Data | 28 | International Robotomation | 67 | Star Technologies | 53 |
| CSPI | 26 | Invitational Computer Conferences | 92 | Television Equipment | 98 |
| Data Delay Devices | 97 | Konan | 93,95 | Treffers Precision | 94 |
| Data Translation | 9 | 3M/Imaging Systems | 59 | Vectrix | 60 |
| Datcube | 1 | Marinco | 51 | VR Information Systems | 77 |
| Digital Equipment Corp. | 2,3 | Measurement Systems | 37 | Zoltech | 86 |
| Digital Electronics | 70 | Microswitch | 73 | Zycad | 16,17 |
| DSP Systems | 47 | Mostek | 14 | | |
| Du Pont | 88 | | | | |
| dy4 | 30 | | | | |
| Eikonix | 22 | | | | |
| Everest Electronic Equipment | 75 | | | | |