

Product Type	Integrated Communication Processor
Freescale Part #	T1014, T1013
Package	T1014: 23x23 780 FC PBGA T1013: 19x19 525 FC PBGA
Crypto Hardware	SEC 5.4

Algorithms

Max Key Size (bits)

DES (ECB, CBC, OFB, CFB)	56
3DES (ECB, CBC, OFB, CFB)	168 (3-keys)
AES (ECB, CBC, CTR, CCM, CMAC, GCM, OFB, CFB, XCBC-MAC)	256
MD-5 + HMAC	(up to 512 bit keys)
SHA-1 + HMAC	(up to 512 bit keys)
SHA-224 + HMAC	(up to 512 bit keys)
SHA-256 + HMAC	(up to 512 bit keys)
SHA-384 + HMAC	(up to 512 bit keys)
SHA-512 + HMAC	(up to 512 bit keys)
Kasumi (A5/3, GEA-3, f8, f9)	128
Snow 3G	128
ZUC (EEA-1 & EIA-2)	128
RSA Digital Signature	4096-bit operands
RSA Digital Verify	4096-bit operands
ECC Digital Signature	1023-bit field or modulus size
ECC Digital Verify	1023-bit field or modulus size
FIPS compliant deterministic RNG	On chip 32-bit

Target Applications :
Control processing for Routers, Storage Arrays, Industrial Single Board Computers

Export Control Info:
Harmonized Tariff (US): 8542.31.0000
ENC Status: Restricted. US EAR part 740.17(b)(2)
ECCN: 5A002A.1
CCAT: G156463

Overview:
The T1014 and T1013 are members of the QorIQ family of integrated communications processor from Freescale Semiconductor.

The T1014 incorporates (1) 64b e5501 Power Architecture CPU core, (1) DDR3L/4 Memory Controller, up to (4) 1G Ethernet ports and (1) 10G Ethernet port, along with multiple PCIe, SATA, and USB peripheral bus controllers, and the QUICC Engine, which supports TDM/HDLC, ISDN, Industrial protocols.

The T1023 incorporates (1) 64b e5501 Power Architecture CPU core, (1) DDR3L/4 Memory Controller, up to (4) 1G Ethernet ports and (1) 10G Ethernet port, along with multiple PCIe, SATA, and USB peripheral bus controllers.

In addition to these CPUs and interfaces, the T1014 and T1013 integrate a 7Gbps Crypto Acceleration Engine (SEC 5.4). The algorithms and key lengths supported by the SEC 5.4 are listed in the table above.

In addition to crypto algorithm processing, the SEC 5.4 supports security protocol processing off-load capability, with specific support for protocol header and trailer processing for IPsec, SSL, DTLS, SRTP, MACSec, 802.16e, and 802.11e. The SEC 5.4 is expected to achieve 2500+ public key exchanges per second.

The T1014 & T1013 also provide support for secure boot and platform assurance.

NOTE 1: This authorization does not authorize the export of products designed to use the encryption functionality of these chips. Such products may require a classification and/or license from the Bureau of Industry and Security (BIS) prior to export. OEMs incorporating these chips in their products should call the BIS Encryption Export Support Line at 202-482-0707 with specific questions.

NOTE 2: Freescale Semiconductor ("Freescale") makes this export classification and regulatory information available for informational purposes only. It may not reflect the most current legal developments, and Freescale does not represent, warrant or guarantee that it is complete, accurate or up-to-date. This information is subject to change without notice. The contents of this fact sheet are not intended to constitute legal advice or to be used as a substitute for specific legal advice from a licensed attorney and or customs broker. You should not act or refrain from acting based upon information in this email without obtaining professional advice regarding your particular facts and circumstances.