



Make: Buick
 Model: Enclave
 Year: 2008-09

STANDARD/ OPTIONAL

- AM/FM in-dash multi CD Player/Navigation
- 3.5mm Aux/mp3 input
- Satellite Radio Capable
- Steering Wheel Controls
- 7 Speaker Amplified Sound System

SCOSCHE®

SPEAKER NOTES

Front Speakers

Dash:	2"
Door Tweeter:	1"
Lower Door:	6 3/4"
Speaker Adapter:	SAGMHR634
Speaker Harness:	TBA
Speaker Assembly:	TBA

Dimensions:	Dash	Tweeter	6 3/4"
	L: 0.000	L: 0.000	L: 0.000
	W: 0.000	W: 0.000	W: 0.000
	D: 0.000	D: 0.000	D: 0.000

Rear Speakers

Lower Door:	6 3/4"
Speaker Adapter:	SAGMHR634
Speaker Harness:	TBA
Speaker Assembly:	TBA

Dimensions:	Lower Door
	L: 0.000
	W: 0.000
	D: 0.000

APPLICATIONS

Dash Type:	New Custom Dash
Aftermarket Type:	Single/Double Din
Aftermarket Kit:	GM1598B
Harness:	GM21SR/GM22SR
Antenna Adapter:	CRAB/CRARB
Amplifier Location:	TBA
Auxiliary Input:	On Radio

FACTORY COLOR CODES

(+)12v Battery:	Red/White
(+)12v Accessory:	Data
(-) 12v Ground:	Black/White
(+)12v Amp Turn On:	Violet/White
Left Front Speaker (+):	Tan
Left Front Speaker (-):	Gray
Right Front Speaker (+):	Lt. Green
Right Front Speaker (-):	Dr. Green
Left Rear Speaker (+):	Brown
Left Rear Speaker (-):	Yellow
Right Rear Speaker (+):	Dr. Blue
Right Rear Speaker (-):	Lt. Blue

PRELIMINARY:

Disconnect the negative battery cable.

Make: Buick

Model: Enclave

Year: 2008-09

RADIO REMOVAL



1. With Panel Removal Tool, unclip Panel surrounding Radio, unplug and remove.
2. Extract (4) 7mm hex head screws securing Radio, unplug and remove.

FRONT DOOR SPEAKERS



1. With Panel Removal Tool, unclip inner armrest cover and extract (2) T-30 Torx head screws from behind.
2. With Panel Removal Tool, unclip inner door panel cover and extract (1) T-30 Torx head screw from behind.
3. With panel Removal Tool, unclip perimeter of door panel, lift to release, unplug and remove.
4. Extract (1) 7mm screw securing Speaker, unplug and remove.

DASH SPEAKERS

BACK DOOR SPEAKERS



1. With Panel Removal Tool, unclip screw cover behind door handle and extract (1) T-30 screw from behind.
2. With Panel Removal Tool, unclip screw cover in armrest and extract (2) T-30 Torx screws from behind.
3. With Panel Removal Tool, unclip perimeter of door panel, lift, unplug and remove.
4. Extract (1) 7mm Hex Head screw securing Speaker, unplug and remove.