



www.altec.com/treecare

DC610 6" Controlled-Feed Disc Chipper

DC610 features

- Rugged design with heavy duty 6" tubular frame
- Exclusive patented Panic Bar System
- Easy towing for lighter vehicles
- Cutter motion indicator
- Large throat opening of 6" x 10"
- "Hedge Hog" feeder design



Panic Bar is a dedicated stop mechanism for the feed system independent of the feed control bar



13 inch road tires for steady towing but soft on turf



Chute adjustment and rotation controls are easily accessible



Reliable, efficient Honda engine

New Equipment Sales

210 Inverness Center Drive • Birmingham, AL 35242
800.958.2555 Fax 205.449.4774

For more information email us at sales@altec.com

Altec DC610 standard features

- 6 in (152.4 mm) diameter chipping capacity
- Altec Exclusive Panic Bar System allows operator to instantly stop all hydraulic functions
- Disc hood safety switch prevents engine from being started with the hood open
- Time-saving one-piece disc cover
- 25 in diameter x 1.25 in thick (635 x 31.8 mm) cutting disc
- (2) double-edged, hardened knives
- 360 degree rotating discharge chute
- Disc-lock pin holds disc stationary for safe maintenance
- Adjustable chute deflector
- Hydraulic feed system with (1) horizontally mounted feed roller
- Fuel tank with gauge
- Convenient in-tank hydraulic oil filter
- Corrosion resistant powder coat finish (custom colors available)
- LED lights that conform to all applicable DOT standards
- 5000 lb (226.8 kg) trailer jack
- Corrosion resistant powder coat finish
- Steel fenders
- FeedSense[®] electronic feed control system will stop the hydraulic feed system if the RPMs drop below a certain level as to prevent stalling of the machine.



6" x 10" chipper opening to accept forked branches



Compact and easy to tow



1550 Aerial Avenue • Creedmoor, NC 27522
800.958.2555 • sales@altec.com

New Equipment Sales • 1.800.958.2555

options

- Rear jack stand
- Flag holders
- Tool box
- Spare tire/rim
- Strobe light
- Cone holder
- Debris pusher
- Caster wheel
- Rear engine cut-off
- Fuel tank gauge
- Wheel chock
- Paint color of chipper
- Paint color of Panic Bar (red or green)
- Briggs 23 HP engine
- Briggs 35 HP engine

specifications

Capacity: 6 in (152.4 mm)

Standard Engine: Honda 22 HP (16 kw)

Weight: 1900 lbs (861.8 kg)

Transport Length: 10 ft 3 in (3.1 m)

Operational Length: 12 ft 3 in (3.8 m)

Width: 5.3 in (1.6 m)

Height: 7.4 ft (2.3 m)

Infeed Chute Size:

24 h x 36 w in (609.5 x 914.4 mm)

Feed Roller Opening:

6.4 h x 10 w in (162.6 x 254 mm)

Feed Roller Diameter: 9.4 in (238.8 mm)

Feed Roller Nip Point Distance:

86.6 in (2225 mm)

Feed Rate: 125 fpm (38.1 mpm)

Feed Motor Displacement:

11.9 cu in (195 cc)

Hydraulic Tank Capacity: 7 gal (26.5 l)

Fuel Tank Capacity: 7 gal (26.5 l)

Altec reserves the right to improve products and the right to change, amend or delete specifications at any time, without notice or obligation.