

Insera DX - Order form

Step 1 - General information

Order Number _____

Date of Order _____

Dispenser Name (BLOCK CAPITALS) _____

Address _____

Patient Name (BLOCK CAPITALS) _____

(AC & BC Thresholds required for AOV)

Left

AC								dB
BC								dB
	250	500	1000	2000	3000	4000	8000	Hz

Right

AC								dB
BC								dB
	250	500	1000	2000	3000	4000	8000	Hz

AC = Air conduction thresholds BC = Bone conduction thresholds

If there is a query with your order, please list the most appropriate way(s) to contact you.

Telephone _____

Mobile _____

Email _____

Other _____

Step 2 - Performance level

☐ DX 9 ☐ DX 7 ☐ DX 5 ☐ DX 3

Step 3 - Product

DX 10A NW O DX 312 NW O DX 312 W DIR

☐ L ☐ R ☐ L ☐ R ☐ L ☐ R



Step 4 - Power level

Left

☐ M ☐ P ☐ HP ☐ SP *

Right

☐ M ☐ P ☐ HP ☐ SP *

Step 5 - Colours

Shell

☐ 19 White ☐ 21 Transparent ☐ 22 Cocoa
☐ 26 Pink ☐ 28 Brown ☐ R/B Red/Blue

* Only for DX 312 W DIR

**Only for DX 10A NW O and DX 312 NW O models

Faceplate

☐ 22 Cocoa ☐ 26 Pink ☐ 28 Brown

Step 6 - Options

Fast order ► Build this product as a standard version ☐

Legend / ☒ = Standard / ☐ = Optional

Shell size	Smallest possible	☒
	Manually selected	Style:
Vent size	AOV (enter audiogram)	☒
	Manually selected	Left : mm Right : mm
Wax system	Cerustop (CS)	☒
	Manually selected	Type:
User controls	Standard controls	☒
	Easy-t & push button	☐
	Easy-t without push button	☐
	MiniControl without push button	☐
	Volume control (VC)	☐
Removal line (RF)	T-coil **	☐
	Transparent (21)	☐
	Line extension +5 mm (RFE)	☐
Accessories (DX 312 W DIR)	TV Connector	☐
	Partner Mic™	☐
	RemoteControl	☐

Special instructions _____

Custom hearing instruments


DX 10A NW O



DX 312 NW O



DX 312 W DIR



Shell style		IIC, CIC, MC, C, HS, FS	MC, C, HS, FS	HS, FS
Push button	Standard	Push button (PM1)	No push button (PX)	Push button (PM1)
	Optional	No push button (PX)	Push button (PM1)	-
Volume control	Standard	No VC (VCX)	No VC (VCX)	No VC (VCX)
	Optional	Digital VC (VC3)	Digital VC (VC3)	Digital VC (VC3)
T-coil	Standard	No T-Coil (TX)	No T-Coil (TX)	-
	Optional	T-Coil passive (TP) (Not in combination with VC)	T-Coil passive (TP) (Not in combination with VC)	-
Magnetic switch function	Standard	Easy-t (DT4)	Easy-t (DT4)	-
	Optional	MiniControl (DT3) No Magnetic switch (RX)	No magnetic switch (RX)	-
Wax system	Standard	Cerustop (CS)	Cerustop (CS)	Cerustop (CS)
	Optional	HF3 (H3) Extended rec. tube (ER) Wax Spring (WS) Ext. Tube + Spring (WE) Wax guard not required (X)	HF3 (H3) Extended rec. tube (ER) Wax Spring (WS) Ext. Tube + Spring (WE) Wax guard not required (X)	HF3 (H3) Extended rec. tube (ER) Wax Spring (WS) Ext. Tube + Spring (WE) Wax guard not required (X)
Removal line	Standard	Removal line transparent (RF)*	-	-
	Optional	Removal line transparent (RF)*	Removal line transparent (RF)*	Removal line transparent (RF)*

*IIC & CIC will be standard equipment with removal line

01925 247 810

Unitron UK, Sonova House, Lakeside Drive, Centre Park, Warrington, WA1 1RX

SalesUK@unitron.com