



Roof Repair

RR-808

Exterior

Tough, flexible sealant ideal for waterproofing, repairing and sealing roofs.

PRODUCT DESCRIPTION

LIQUID NAILS® Roof Repair (RR-808) is a tough, flexible sealant that stops leaks fast around chimneys, flashings, roof decks, vents and other roof areas. Ideal for waterproofing, repairing and sealing roofs. RR-808 withstands even extreme temperature conditions. It works on wet roofs, and can be applied even in rain or snow. Does not freeze.

RECOMMENDED FOR repairing and sealing leaks and openings around:

- Chimneys
- Loose shingles
- Roof decks
- Roof vents
- Flashing
- Copings
- Parapet walls

NOT RECOMMENDED FOR uses other than those stated.

Please research all installation instructions and read entire label for safety, health & environmental information prior to use.

Look for other LIQUID NAILS products which are right for your specific project.

PRODUCT ADVANTAGES

- Seals leaks in all weather
- Extended outdoor durability
- Weatherproof
- Ideal for waterproofing, repairing and sealing roofs
- Tough, flexible sealant
- Works on wet roofs
- Does not freeze

SURFACE PREPARATION

Clean surface as much as possible under existing weather conditions before applying this product. Fill any deep joints with solid filler to within 1/2" of surface. Apply RR-808 at temperatures above 32°F (0°C). For easier gunning in cold weather, sealant should be conditioned to room temperature prior to use.

DANGER! COMBUSTIBLE.
HARMFUL OR FATAL IF SWALLOWED.

Read Label and Material Safety Data Sheet Prior to Use.
See other cautions on last page. MDSF5-1100





Roof Repair

APPLYING THE PRODUCT

Load RR-808 cartridge into standard caulking gun. Cut nozzle at 45° angle for desired bead size (marked on nozzle). Puncture inner seal with nail or wire. Push RR-808 sealant as far as possible into gap using firm, uniform pressure. Apply sufficient sealant to leave a bead of at least 1/4" (.64 cm) around repaired and sealed surface. Level any excess sealant with a trowel or putty knife. Let dry 24 hours.

CLEAN-UP

Use mineral spirits when wet. When dry, use *LIQUID NAILS™ Adhesive & Caulk Remover*, or scrape away.

DISPOSAL

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants. EAD-C9

LIMITED WARRANTY

Macco warrants satisfaction with this product when handled and applied according to label instructions. If this product is not as warranted, please call 1-800-634-0015 for refund or product replacement details. This warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made.** Macco shall not be liable for any special, incidental or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so the limitations may not apply. This warranty gives specific legal rights. You may also have other rights that vary from state to state.

DANGER! COMBUSTIBLE.

HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks and flame. **Do not smoke. Vapors may ignite.** Vapors may spread long distances. Extinguish all flames, burners, stoves, heaters and pilot lights and disconnect all electrical motors and appliances before use and until all vapors are gone. Do not breathe vapors. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and skin. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, **get medical attention.** **For emergency information, customer service, MSDS information or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.** MDS9-0805

RR-808

TECHNICAL INFORMATION

Base: Asphalt
Type: Solvent release
Color: Black
Appearance: Long paste
Application Temperature: 32° to 100° F
(0° to 38° C)
Service Temperature: -15° to 140° F
(-26° to 60° C)
Adhesion: Good to excellent to most common building materials
Extrudability: Good
Consistency: Smooth, buttery
Durability: Excellent
Flexibility: Excellent
Volume Shrinkage: 20%
Slump: Max 0.15"
Shore "A" Hardness: 25
Water Resistance: Excellent
Artificial Weathering: Excellent
Exterior Weathering: Excellent
Aging: Excellent
Freeze-Thaw Stable: Will not freeze
Odor: Solvent/asphalt
Tack Free Time: Tack at drying time - none
Tack at 24 hours - none
Drying Time: 24 hours
Weight Per Gallon: 10.2 pounds (4.59 kg)
Viscosity: 700,000 CPS
Solids: 84% - 87%
Flammability: Combustible
Flash Point: 105°F (40°C)
Coverage: 30 lineal feet (9.14 lineal meters) using 1/4" (.64cm) bead
Shelf Life: 12 months from date of purchase
Specifications: Federal Specification SS-C-153 Type I
Max VOC: 258 GPL



MACCO
15885 West Sprague Rd.
Strongsville, OH 44136

Division of:



Paints