

Temperature Controller

With “Sensitive Touch” Keypad



CN38S Series



CN38S-TC-R1-R2
shown actual size.

- ✓ Easy Programming
- ✓ Input for Thermocouple, RTD and Thermistor
- ✓ Resolution 0.1°C with Automatic Scale Change (Auto-Ranging)
- ✓ “Sensitive Touch” Keypad
- ✓ Switching Power Supply 100 to 240 Vac
- ✓ On/Off or PID Control with Autotuning
- ✓ Programmable Password Protection
- ✓ Soft Start or Start Up Delay
- ✓ Automatic or Stand-By Mode
- ✓ Compressor Protection Time
- ✓ Direct Access to Set-Point

Monitor and control temperature with precision using the CN38S Series controllers. The CN38S Series offers an innovative solution for programming through an ergonomic keypad which uses the technology “Sensitive Touch”. This sensor keyboard guarantees complete protection from dust and liquids in every critical environmental situation. Providing on/off control or PID control with Autotune, this controller is the solution for many applications. The CN38S series offers a soft start feature. This function makes it possible to eliminate thermal shock and mechanical stress (due to dilatation) that a system undergoes during start up. In other cases the aim is that of slowing down the increase in temperature in such a way that this can spread itself

out evenly inside the material, especially when the machine is equipped with ‘stirrers’ that cannot be started up at room temperature. The CN38S also offers a compressor protection time feature, where some actuators, compressors, and pumps cannot be turned off or turned back on too quickly for their constructive characteristics. To protect the working life of the device it therefore becomes essential to be able to activate a timer that guarantees the minimum time between the switching off of the machine and the following start up.

Specifications

Power Supply: 12 Vac/Vdc, 24 Vac/Vdc, 100 to 230 Vac/Vdc (±10%)

Power Consumption: Maximum 6VA

Device Class: Class II

Nominal Pulse Voltage: 2.5 KV

Category of Overvoltage: II

Isolation: Reinforced isolation between low voltage (input and output relay) and frontal parts; reinforced isolation between low voltage and very low voltage parts (inputs, static outputs)

Thermocouple Input

Type: J, K programmable

Resolution: 0.1°C with automatic scale change

Unit of Measurement: °C or °F programmable

Cold Junction: Automatic compensation 0 to 50°C

Cold Junction Accuracy: 0.1°C/°C @ 25°C after a warm-up (instrument switch-on) of 20 minutes

Calibration: According to EN 60584-1

Burn-Out: At the end of scale
Thermocouple Type Range:

J: -40 to 999°C (-40 to 999°F)

K: -40 to 999°C (-40 to 999°F)

RTD

Type: Pt 100 and Pt 1000, 2-wire

Resolution: 0.1°C with automatic scale change

Unit of Measurement: °C or °F programmable

Burn-Out: At the end of scale

RTD Range: -50 to 850 (-58 to 999°F)
-50.0 to 99.9 (-58.0 to 99.9°F)

Thermistor Input

Type:

PTC: 990 Ω @ 25°C

NTC: 10 kΩ @ 25°C

Unit of Measurement: °C or °F programmable

Model Range:

PTC: -50 to 150°C (-67 to 302°F),
-50.0 to 99.9°C (-67.0 to 99.9°F)

NTC: -50 to 110°C (-58 to 230°F),
-50.0 to 99.9°C (-58.0 to 99.9°F)

Outputs

Output: 1 and 2

Function: Control output

Output Action: Direct/reverse, programmable

Type: Relay output

Contact: SPDT

Contact Load: Out 1 - 8 A/250 Vac on resistive load - 3 A/250V

Relay Electric Life: 100,000 operations

DC Pulse:

Isolation: Output NOT isolated as regard the very low voltage parts

Logic State:

1: 12V ±20% @ 1 mA, 10V ±20% @ 20 mA

0: <0.5V



Mounting: Flush in panel

Dimensions: 78 x 35 mm
(3.07 x 1.38"), depth 64 mm (2.52")

Panel Cut-Out: 71 (2.8") x 29 (1.14")

Display: 3-digit single display, red,
12 mm (0.47")

Weight: 180 g (6.3 oz) approximately

Screw Terminals: 11 screw terminals
(screw M3 for cables 0.25... 2.5 mm²
or AWG 22... AWG 14)

Protection Degree:

Front Protection: IP 65 (with
gasket) according to EN60070-1
for indoor use

Screw Terminal: IP20

Operating Temperature: 0 to 50°C
(32 to 122°F)

Operating Humidity: < 95 RH%
without condensation

Storage Temperature: -25 to 60°C
(-13 to 140°F)

Overall Accuracy: ±(0.5% span ±1
digit @25 °C)

Sampling Rate: 1 s

Display Updating Time: 1 s

To Order	
Model No.	Description
CN38S-TC-R1-R2	Type J/K, thermocouple input, relay/relay
CN38S-TC-DC1-DC2	Type J/K, thermocouple input, dc pulse/dc pulse
CN38S-TC-DC1-R2	Type J/K, thermocouple input, dc pulse/relay
CN38S-RTD-R1-R2	RTD, relay/relay
CN38S-RTD-DC1-DC2	RTD, dc pulse/dc pulse
CN38S-RTD-DC1-R2	RTD, dc pulse/relay
CN38S-TH-R1-R2	Thermistor, relay/relay
CN38S-TH-DC1-DC2	Thermistor, dc pulse/dc pulse
CN38S-TH-DC1-R2	Thermistor, dc pulse/relay
Low Voltage Models	
CN38S-TC-R1-R2-12V	Type J/K, thermocouple input, relay/relay, 12V
CN38S-TC-DC1-DC2-12V	Type J/K, thermocouple input, DC pulse/DC pulse, 12V
CN38S-TC-DC1-R2-12V	Type J/K, thermocouple input, DC pulse/relay, 12V
CN38S-RTD-R1-R2-12V	RTD, relay/relay, 12V
CN38S-RTD-DC1-DC2-12V	RTD, DC pulse/DC pulse, 12V
CN38S-RTD-DC1-R2-12V	RTD, DC pulse/relay, 12V
CN38S-TH-R1-R2-12V	Thermistor, relay/relay, 12V
CN38S-TH-DC1-DC2-12V	Thermistor, DC pulse/DC pulse, 12V
CN38S-TH-DC1-R2-12V	Thermistor, DC pulse/relay, 12V
CN38S-TC-R1-R2-24V	Type J/K, thermocouple input, relay/relay, 24V
CN38S-TC-DC1-DC2-24V	Type J/K, thermocouple input, DC pulse/DC pulse, 24V
CN38S-TC-DC1-R2-24V	Type J/K, thermocouple input, DC pulse/relay, 24V
CN38S-RTD-R1-R2-24V	RTD, relay/relay, 24V
CN38S-RTD-DC1-DC2-24V	RTD, DC pulse/DC pulse, 24V
CN38S-RTD-DC1-R2-24V	RTD, DC pulse/relay, 24V
CN38S-TH-R1-R2-24V	Thermistor, relay/relay, 24V
CN38S-TH-DC1-DC2-24V	Thermistor, DC pulse/DC pulse, 24V
CN38S-TH-DC1-R2-24V	Thermistor, DC pulse/relay, 24V

Accessory (Field Installable)

Model No.	Description
CNQUENCHARC	Noise suppression kit, 110 to 230 Vac

Comes complete with operator's manual.

Ordering Example: CN38S-TC-R1-R2-12V, controller with thermocouple input, 2 relay outputs, low voltage 12V.

omega.co.uk®

Your One-Stop Source for Process Measurement and Control!

Freephone 0800 488 488 | International +44(0) 161 777 6622 | Fax +44(0) 161 777 6622 | Sales@omega.co.uk

www.omega.co.uk



UNITED STATES

www.omega.com

1-800-TC-OMEGA
Stamford, CT.

CANADA

www.omega.ca

Laval(Quebec)
1-800-TC-OMEGA

GERMANY

www.omega.de

Deckenpfronn, Germany
0800-8266342

UNITED KINGDOM

www.omega.co.uk

Manchester, England
0800-488-488
+44-(0)161-777-6611

FRANCE

www.omega.fr

0800-466-342

BENELUX

www.omega.nl

0800-099-33-44



More than 100,000 Products Available!

• Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders, Relative Humidity Measurement Instruments, PT100 Probes, PT100 Elements, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples, Thermowells and Head and Well Assemblies, Transmitters, Thermocouple Wire, RTD Probes

• Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

• pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

• Data Acquisition

Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers, Plug-in Cards, Signal Conditioners, USB, RS232, RS485, Ethernet and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Pressure Transmitters, Strain Gauges, Torque Transducers, Valves

• Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters