



SOLID COLOR WATERPROOFING STAIN & SEALER

NO. 5011



PRODUCT INFORMATION

BEHR PREMIUM® SOLID COLOR WATERPROOFING STAIN & SEALER is a 100% acrylic formula that seals out the elements, and sun's harmful UV rays, for up to 10 years on decks and up to 25 years on fences & siding. It forms a highly durable and mildew resistant finish which resists scuffing, cracking, peeling, and blistering.

RECOMMENDED USES:

Recommended for properly prepared new to moderately weathered, unsealed exterior wood surfaces such as:

- Wood
- Wood Composites

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

- No. 5011 Tintable White 124 oz.
- No. 5013 Deep Base 116 oz.

Pre-Mixed Colors:

- No. 50533 Cedar Naturaltone
- No. 50129 Chocolate
- No. 50330 Redwood
- No. 50117 Russet
- No. 50104 Cordovan Brown

Resin Type: Advanced 100% Acrylic

Weight per Gallon: 10.3 lbs

% Solids by Volume: 37.2%

% Solids by Weight: 49.2%

VOC: <100 g/L

Flash Point: N/A

Viscosity: 68-75 KU

Recommended Film Thickness:

- Wet: 7.8 Dry: 2.8 mils @ 200 Sq. Ft./Gal.
- Wet: 3.6 Dry: 1.4 mils @ 400 Sq. Ft./Gal.

Coverage: 200-400 Sq. Ft./Gal., depending on application method and substrate porosity. Does not include the loss of material from spraying.

APPLICATION:

Brush: Nylon/polyester

Roller: 3/8" nap

Pad Applicator

Airless Spray: At packaged consistency

Tip: .015"-.019"

Filter: 60 mesh

Dry Time: @ 77°F & 50% RH

To Recoat: 1-2 hours

Light Foot Traffic: 24-48 hours

Full Cure: 72 hours

- Follow spraying immediately with a pad, back brushing or back rolling for a uniform appearance.
- Work in small sections lightly saturating the surface and immediately back-brush or use pad applicator to eliminate puddling; remove excess and evenly distribute the finish. Maintain a wet edge when applying.

SURFACE PREPARATION:

The following steps and products are recommended for best results: If you use a product such as BEHR PREMIUM Wood Stain & Finish Stripper No. 64 to remove loose wood fibers, latex, oil-based and 100% acrylic coatings on new weathered wood, then you must use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to clean, brighten & neutralize wood. If you do not use a product such as BEHR PREMIUM Wood Stain & Finish Stripper No. 64, then use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to clean and brighten the wood surface and to remove light to medium stains caused by mold, mildew, algae & fungus. Rinse thoroughly and allow to dry before coating. On new wood, use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 to remove mill glaze and open the pores of the wood. Lightly sand to remove remaining wood fibers/fuzz.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

RECOMMENDED PRIMER/SYSTEMS:

Wood & Tannin/Stain-blocking:

- BEHR PREMIUM PLUS® Exterior Multi-Surface Primer & Sealer No. 436

PREVIOUSLY PAINTED SURFACES:

- Use a full coat or spot prime with BEHR PREMIUM PLUS Exterior Multi-Surface Primer & Sealer No. 436 on properly prepared surfaces.

COMPLIES WITH THE BELOW AS OF 2/1/2017

SCAQMD	YES	OTC Phase II	YES
CARB	YES	LADCO	YES
CARB SCM 2007	YES	AIM	YES
OTC	YES	MPI#	16

CLEAN UP:

Clean all tools and equipment with clean water. For proper disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing
- Do not use without the addition of tinting colorants
- Do not use if rain is expected within 24 hours
- DO NOT THIN PRODUCT
- Avoid applying stain in direct sunlight or hot surfaces
- Test product for color on a small hidden area before proceeding
- Over application of stain will lead to surface failure including peeling & cracking
- Stained surfaces may become slippery when wet.
- Shelf life under normal conditions is two years (unopened containers)
- Temperature Range: 35-90°F

GENERAL INFORMATION:



Warning! Causes eye and skin irritation. Harmful if swallowed. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Collect spillage and avoid release to the environment. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

First aid: If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. **If on skin:** Wash with plenty of soap and water. **If swallowed:** Rinse mouth and get medical attention if you feel unwell.