




## Ex-TRA 300 ANALOG

HEADSETS FOR ZONE 1



# EX-TRA300



in cooperation with

**Intradex**

## TECHNICAL DATA

### Loudspeaker

Pattern	dynamic
Impedance	150 Ohm at 1 mW / 1 kHz
Sound pressure level	max. 115 dB
Frequency range	150 Hz - 12 kHz

### Microphone

Pattern	electret
Directional	noise cancelling (NC)
Impedance	4.400 Ohm
Sensitivity	-44 dB V/Pa 1 kHz
Frequency range	300 Hz - 9 kHz

### Additional data

Ambient temperature	-20°C to +50°C
Protection class	IP54
Weight	approx. 520 g
Noise attenuation	approx. 27 dB



## CERTIFICATION

ATEX



⊕ II 2G Ex ia IIC T4

IECEx







Ex ia IIC T4 Gb





- Clear sound in noisy environments
- High attenuation
- High and excellent wearing comfort
- Big PTT-button

# Analog

The Ex-TRA 300 headsets are a series of explosion-protected headsets for use under extreme conditions. The products have been developed in conjunction with demanding users and subjected to rigorous examination. Therefore the headset will fulfill all requirements for industrial capability and reliability.


COMPATIBLE PRODUCTS			
Ex-PMR 1000	Ex-PMR 2000	Motorola GP 900	Motorola GP340-680 Ex
			
AS000260	AS000280/ 281		

## Intrinsically safe **HEARING PROTECTION** HEADSET FOR ZONE 1

ACCESSORIES	
Windscreen for microphone M995	Foam speaker cover
	
A0000428	A0000430
Headband cushion (nappa leather)	Ear cushions
	
A0000431	A0000429



# EX-TRA300



in cooperation with

**Intradex**

## TECHNICAL DATA

### Loudspeaker

Pattern	dynamic
Impedance	150 Ohm at 1 mW / 1 kHz
Sound pressure level	max. 115 dB
Frequency range	150 Hz - 12 kHz

### Microphone

Pattern	electret
Directional	noise cancelling (NC)
Impedance	4.400 Ohm
Sensitivity	-44 dB V/Pa 1 kHz
Frequency range	300 Hz - 9 kHz

### Additional data

Ambient temperature	-20°C to +50°C
Protection class	IP54
Weight	approx. 520 g
Noise attenuation	approx. 27 dB



## CERTIFICATION

**ATEX**

Ⓔ II 2G Ex ia IIC T4



**IECEX**





Ex ia IIC T4 Gb








- Clear sound in noisy environments
- High attenuation
- High and excellent wearing comfort
- Big PTT-button
- Fits to nearly all helmet variants

# Analog

The Ex-TRA 300 headsets are a series of explosion-protected headsets for use under extreme conditions. The products have been developed in conjunction with demanding users and subjected to rigorous examination. Therefore the headset will fulfill all requirements for industrial capability and reliability.

COMPATIBLE PRODUCTS			
Ex-PMR 1000	Ex-PMR 2000	Motorola GP 900	Motorola GP340-680 Ex
			
AS000260	AS000280/ 281		

## HEADSET WITH HELMET ADAPTER FOR ZONE 1

ACCESSORIES		
Windscreen for microphone M995	Helmet adaptor, types on request	
		
A0000428	A0000432 - 436	
Headband cushion (nappa leather)	Ear cushions	Foam speaker cover
		
A0000431	A0000429	A0000430

# EX-TRA300



in cooperation with



## TECHNICAL DATA

### Loudspeaker

Pattern	magnetic
Impedance	250 Ohm at 1 mW / 1 kHz
Sound pressure level	max. 115 dB
Frequency range	100 Hz - 4 kHz

### Microphone

Pattern	electret
Directional	noise cancelling (NC)
Impedance	4.400 Ohm
Sensitivity	-44 dB V/Pa 1 kHz
Frequency range	300 Hz - 10 kHz

### Additional data

Ambient temperature	-20°C to +50°C
Protection class	IP54
Weight	approx. 118 g

## CERTIFICATION

**ATEX** Ⓢ II 2G Ex ia IIC T4



**IECEX** Ex ia IIC T4 Gb



- Light weight headset
- Pressure-free comfortable wearing
- Possible with helmets and chemical splash suits

# Analog






The Ex-TRA 300 Neckband provides to you a comfortable light weight headset solution and can be used with almost every kind of helmet. Through the Open-Ear-Gain technology you are able to hear all ambient noises and also be able to have clear and loud communication even in dangerous situations.

## COMPATIBLE PRODUCTS

Ex-PMR 1000	Ex-PMR 2000	Motorola GP 900	Motorola GP340-680 Ex
			
AS000260	AS000280/ 281		


## Intrinsically Safe **NECKBAND** HEADSET FOR ZONE 1

### ACCESSORIES

Windscreen for microphone M995	Ear Mould	
		
A0000428	A0000424 - 425	
Ear bud	Acoustic ear olive	Acoustic ear tube
		
A0000421 - 423	A0000426	A0000427



# EX-TRA300



in cooperation with

**Intradex**

## TECHNICAL DATA

### Loudspeaker

Pattern	magnetic
Impedance	150 Ohm at 1 mW / 1 kHz
Sound pressure level	max. 106 dB
Frequency range	300 Hz - 4 kHz

### Microphone

Pattern	electret
Directional	noise cancelling (NC)
Impedance	2.500 Ohm
Sensitivity	-34 dB V/Pa 1 kHz
Frequency range	100 Hz - 5 kHz

### Additional data

Ambient temperature	-20°C to +50°C
Protection class	IP54
Weight	approx. 130 g



## CERTIFICATION

**ATEX**

⊕ II 2G Ex ia IIC T4



**IECEX**

Ex ia IIC T4 Gb



- Clear voice transmission and clear understanding
- Easy adaptation to helmets
- Rugged and big PTT button



# Analog

The Ex-TRA 300 Fire talk headset is designed to provide optimum communication in critical situations for fire and rescue services. The robust and rugged design and the PTT button provides to you with the highest performance in all situations. Through a large variety of helmet adaptors you can use it with almost all fire brigade standard helmets. Even changing from one helmet to another is quickly possible.

## COMPATIBLE PRODUCTS

Ex-PMR 1000	Ex-PMR 2000	Motorola GP 900	Motorola GP340-680 Ex
			
AS000260	AS000280/ 281		

## Intrinsically safe **FIRE TALK HEADSET** FOR ZONE 1

### ACCESSORIES

**Windscreen for microphone M995**



A0000428

**Helmet adaptor for Fire brigade Headset**



A0000451-461



# Ex-TRA300



The Ex-TRA 300 Fire talk supra is a special designed and very robust headset. It fits on all common fire brigade supra helmets without any additional adaption. Due to the design of the headset the rescue brigades can hear the ambient noises and have clear and loud communication to avoid mishearing commands.

## Intrinsically safe **FIRE TALK SUPRA HEADSET** FOR ZONE 1


### ACCESSORIES

Windscreen for Microphone M995



A0000428





# Analog

in cooperation with



## TECHNICAL DATA

### Loudspeaker

Pattern	magnetic
Impedance	150 Ohm at 1 mW / 1 kHz
Sound pressure level	max. 106 dB
Frequency range	300 Hz - 4 kHz

### Microphone

Pattern	electret
Directional	noise cancelling (NC)
Impedance	2.500 Ohm
Sensitivity	-34 dB V/Pa 1 kHz
Frequency range	100 Hz - 5 kHz

### Additional data

Ambient temperature	-20°C to +50°C
Protection class	IP54
Weight	approx. 130 g

## CERTIFICATION

**ATEX**

II 2G Ex ia IIC T4



**IECEx**

Ex ia IIC T4 Gb



- Perfect voice transmission even with loud ambient noises
- Special design for fire brigade helmets
- Optimum performance due to design
- Robust and big PTT button

## COMPATIBLE PRODUCTS

Ex-PMR 1000	Ex-PMR 2000	Motorola GP 900	Motorola GP340-680 Ex
			
AS000260	AS000280/ 281		

## Ex-TRA 300 DIGITAL

HEADSETS FOR ZONE 1



# EX-TRA300



in cooperation with

**Intradex**

## TECHNICAL DATA

### Loudspeaker

Pattern	dynamic
Impedance	150 Ohm at 1 mW / 1 kHz
Sound pressure level	max. 115 dB
Frequency range	150 Hz - 12 kHz

### Microphone

Pattern	electret
Directional	noise cancelling (NC)
Impedance	4.400 Ohm
Sensitivity	-44 dB V/Pa 1 kHz
Frequency range	300 Hz - 9 kHz

### Additional data

Ambient temperature	-20°C to +50°C
Protection class	IP54
Weight	approx. 520 g
Noise attenuation	approx. 27 dB



## CERTIFICATION

**ATEX**      Ⓢ II 2G Ex ia IIC T4



**IECEx**      Ex ia IIC T4 Gb







- Internal amplifier for best volume and clear sound in every situation
- High attenuation
- High and excellent wearing comfort
- Big PTT-button

# Digital

The Ex-TRA 300 headsets are a series of explosion-protected headsets for use under extreme conditions. The products have been developed in conjunction with demanding users and subjected to rigorous examination. Therefore the headset will fulfill all requirements for industrial capability and reliability.

COMPATIBLE PRODUCTS	
AIRBUS THR880i Ex	AIRBUS THR9 Ex
	

## Intrinsically safe HEARING PROTECTION HEADSET FOR ZONE 1

ACCESSORIES	
Windscreen for microphone M995	Foam speaker cover
	
A0000428	A0000430
Headband cushion (nappa leather)	Ear cushions
	
A0000431	A0000429





# EX-TRA 300



in cooperation with

**Intradex**

## TECHNICAL DATA

### Loudspeaker

Pattern	dynamic
Impedance	150 Ohm at 1 mW / 1 kHz
Sound pressure level	max. 115 dB
Frequency range	150 Hz - 12 kHz

### Microphone

Pattern	electret
Directional	noise cancelling (NC)
Impedance	4.400 Ohm
Sensitivity	-44 dB V/Pa 1 kHz
Frequency range	300 Hz - 9 kHz

### Additional data

Ambient temperature	-20°C to +50°C
Protection class	IP54
Weight	approx. 520 g
Noise attenuation	approx. 27 dB



## CERTIFICATION

**ATEX**



Ⓔ II 2G Ex ia IIC T4

**IECEx**



Ex ia IIC T4 Gb



- Internal amplifier for best volume and clear sound in every situation
- High attenuation
- High and excellent wearing comfort
- Big PTT-button
- Fits to nearly all helmet variants



# Digital






The Ex-TRA 300 headsets are a series of explosion-protected headsets for use under extreme conditions. The products have been developed in conjunction with demanding users and subjected to rigorous examination. Therefore the headset will fulfill all requirements for industrial capability and reliability.

## COMPATIBLE PRODUCTS

AIRBUS THR880i Ex	AIRBUS THR9 Ex
	

## HEADSET WITH HELMET ADAPTER FOR ZONE 1

### ACCESSORIES

Windscreen for microphone M995	Helmet adaptor, types on request	
		
A0000428	A0000432 - 436	
Headband cushion (nappa leather)	Ear cushions	Foam speaker cover
		
A0000431	A0000429	A0000430

# EX-TRA300



in cooperation with



## TECHNICAL DATA

### Loudspeaker

Pattern	magnetic
Impedance	250 Ohm at 1 mW / 1 kHz
Sound pressure level	max. 115 dB
Frequency range	100 Hz - 4 kHz

### Microphone

Pattern	electret
Directional	noise cancelling (NC)
Impedance	4.400 Ohm
Sensitivity	-44 dB V/Pa 1 kHz
Frequency range	300 Hz - 10 kHz

### Additional data

Ambient temperature	-20°C to +50°C
Protection class	IP54
Weight	approx. 118 g

## CERTIFICATION

**ATEX** Ⓢ II 2G Ex ia IIC T4



**IECEX** Ex ia IIC T4 Gb



- Internal amplifier for best volume and clear sound in every situation
- Light weight headset
- Pressure-free comfortable wearing
- Possible with helmets and chemical splash suit

# Digital

The Ex-TRA 300 Neckband provides to you a comfortable light weight headset solution and can be used with almost every kind of helmet. Through the Open-Ear-Gain technology you are able to hear all ambient noises and also be able to have clear and loud communication even in dangerous situations.

## COMPATIBLE PRODUCTS

### AIRBUS THR880i Ex



### AIRBUS THR9 Ex



## Intrinsically safe **NECKBAND** HEADSET FOR ZONE 1

## ACCESSORIES

### Windscreen for microphone M995



A0000428

### Ear Mould



A0000424 - 425

### Ear bud



A0000421 - 423

### Acoustic ear olive



A0000426

### Acoustic ear tube



A0000427

# EX-TRA300



in cooperation with

 **Intradex**

## TECHNICAL DATA

### Loudspeaker

Pattern	magnetic
Impedance	150 Ohm at 1 mW / 1 kHz
Sound pressure level	max. 106 dB
Frequency range	300 Hz - 4 kHz

### Microphone

Pattern	electret
Directional	noise cancelling (NC)
Impedance	2.500 Ohm
Sensitivity	-34 dB V/Pa 1 kHz
Frequency range	100 Hz - 5 kHz

### Additional data

Ambient temperature	-20°C to +50°C
Protection class	IP54
Weight	approx. 130 g



## CERTIFICATION

**ATEX**

Ⓔ II 2G Ex ia IIC T4



**IECEx**

Ex ia IIC T4 Gb



- Internal amplifier for best volume and clear sound in every situation
- Clear voice transmission and clear understanding
- Easy adaptation to helmets
- Rugged and big PTT button

# Digital

The Ex-TRA 300 Fire talk headset is designed to provide optimum communication in critical situations for fire and rescue services. The robust and rugged design and the PTT button provides to you with the highest performance in all situations. Through a large variety of helmet adaptors you can use it with almost all fire brigade standard helmets. Even changing from one helmet to other is quickly possible.

## COMPATIBLE PRODUCTS

### AIRBUS THR880i Ex



### AIRBUS THR9 Ex



## Intrinsically safe **FIRE TALK HEADSET** FOR ZONE 1

### ACCESSORIES

#### Windscreen for microphone M995



A0000428

#### Helmet adaptor for Fire brigade Headset



A0000451-461



# Ex-TRA300



The Ex-TRA 300 Fire talk supra is a special designed and very robust headset. It fits on all common fire brigade supra helmets without any additional adaption. Due to the design of the headset the rescue brigades can hear the ambient noises and have clear and loud communication to avoid mishearing commands.

## Intrinsically safe **FIRE TALK SUPRA HEADSET** FOR ZONE 1

### ACCESSORIES

Windscreen for Microphone M995



A0000428





# Digital

**ecom**  
MOBILE SAFETY

in cooperation with



## TECHNICAL DATA

### Loudspeaker

Pattern	magnetic
Impedance	150 Ohm at 1 mW / 1 kHz
Sound pressure level	max. 106 dB
Frequency range	300 Hz - 4 kHz

### Microphone

Pattern	electret
Directional	noise cancelling (NC)
Impedance	2.500 Ohm
Sensitivity	-34 dB V/Pa 1 kHz
Frequency range	100 Hz - 5 kHz

### Additional data

Ambient temperature	-20°C to +50°C
Protection class	IP54
Weight	approx. 130 g

## CERTIFICATION

**ATEX**



II 2G Ex ia IIC T4

**IECEx**



Ex ia IIC T4 Gb

- Internal amplifier for best volume and clear sound in every situation
- Perfect voice transmission even with loud ambient noises
- Special design for fire brigade helmets
- Optimum performance due to design
- Robust and big PTT button



## COMPATIBLE PRODUCTS

**AIRBUS THR880i Ex**



**AIRBUS THR9 Ex**





## EMEA

### Germany (Headquarters) <sup>1</sup>

ecom instruments GmbH  
Industriestraße 2  
97959 Assamstadt  
Phone +49 62 94 42 24-0  
Fax +49 62 94 42 24-100  
sales@ecom-ex.com  
<sup>1</sup> also covering Austria

### ecom Benelux <sup>2</sup>

ecom instruments BV  
Watertoren 45c  
3247 CL Dirksland, Netherlands  
Phone +31 1 87 60 59 16  
Fax +31 1 87 60 33 47  
info.nl@ecom-ex.com  
<sup>2</sup> also covering Belgium and Luxembourg

### France <sup>3</sup>

ecom Nied sarl  
4 Rue Ettore Bugatti  
67201 Eckbolsheim  
Phone +33 3 88 76 46 84  
Fax +33 3 88 76 02 85  
info.fr@ecom-ex.com  
<sup>3</sup> also covering Algeria, Egypt, Morocco,  
Tunisia and Libya

### Italy

ecom instruments srl  
Via Gandhi, 15 Galleria  
20017 Rho (MI)  
Phone +39 02 93 90 92 16  
Fax +39 02 93 90 62 97  
info.it@ecom-ex.com

### Switzerland

ecom instruments GmbH  
Merkurstraße 2  
6210 Sursee  
Phone +41 4 19 21 60 00  
Fax +41 4 19 22 00 08  
info.ch@ecom-ex.com

### United Kingdom

ecom instruments ltd  
A310, The Wilton Centre,  
Redcar, TS10 4RF,  
United Kingdom  
Phone +44 1642 46 54 00  
Fax +44 1642 46 54 02  
info.uk@ecom-ex.com

### Middle East

ecom instruments fze  
P.O. Box 8918  
Saif-Zone, Sharjah, UAE  
Phone +971 6 5 57 34 30  
Fax +971 6 5 57 34 31  
info.uae@ecom-ex.com

## Americas

### USA

ecom instruments Inc.  
1779 Westborough Drive, Suite 102  
Katy, Texas 77449  
Phone +1 281 496 59 30  
Fax +1 281 496 23 21  
info.us@ecom-ex.com

## Asia

### China

ecom instruments GmbH  
Beijing Office  
Room 11-C, CITIC Building Tower A 19  
No.19 Jianguomenwai Dajie, Choyang District  
Beijing 100004  
Phone +86 1 08 52 61 81 76 01  
Fax +86 1 08 52 61 43 6  
info.cn@ecom-ex.com

### South East Asia

Ecom Instruments (SEA) Pte Ltd  
15 Pioneer Turn  
P+F GDC Building  
Singapore 627577  
Phone +65 6779 9078  
info.sg@ecom-ex.com



Locate your nearest ecom partner on [www.ecom-ex.com](http://www.ecom-ex.com)