




EXPANSION TANKS

HYDRONIC EXPANSION TANKS



IN-LINE

American Sizing Guide	
Net Boiler Output in 1000s of Btu's	Recommended Tank(s)
25-50	AEH-2
75-150	AEH-5
175-200	AEH-7
200-400	AEH-14


Sizing based on the following operating conditions: Cold pressure 12 PSI, Relief set 30 PSI, maximum temperature 240°F. Sizes shown are for fin-tubed baseboard radiation. For systems with converters and/or unit heaters, increase tank one size. For cast-iron radiation, increase tank two sizes.

American Space Heating Expansion Tanks						
	Model Number	Gallon Capacity	Maximum Acceptable Volume (Gallons) 20 PSIG	Dimensions in Inches		Shipping Weight (lbs)
				A	B	
In-Line	AEH-2	1.96	1.53	8-1/4	10-3/16	5
	AEH-5	4.55	3.75	11	14-3/4	9
	AEH-7	7.3	4.6	11	21-1/16	14
	AEH-14	14.6	10.5	15-3/8	23-1/2	25

All Models: 100 PSIG Maximum Working Pressure, 1/2" NPTM connections

- For use with space heating boilers in closed systems — not for use with potable water heating systems
- Models up to 14.6 gallons feature in-line design for installation directly into system piping
- Field-adjustable 12 PSI pre-charge
- Drawn-steel tank
- Butyl rubber parabolic diaphragm, for permanent separation of air and water
- Maximum Working Pressure: 100 PSI
- Maximum Temperature: 240°F
- 1-Year Limited Warranty

American Expansion Tanks for closed space heating systems provide a place for expanding water to go during cycles of thermal expansion, eliminating the risk of damage to the boiler and piping in the system.



Available As Hydronic Or Potable Water Expansion Tanks

Drawn Steel Construction

Heavy Duty Butyl Rubber Parabolic Diaphragm

Maximum Working Pressure

150 PSI For Potable Water Expansion Tanks

100 PSI For Hydronic Expansion Tanks

Warranty

5-year Potable Expansion Tanks

1-year Hydronic Expansion Tanks



PO Box 4056
500 Princeton Road
Johnson City, TN 37602-4056
(800) 937-1037
(800) 581-7224 fax




POTABLE WATER EXPANSION TANKS

Thermal expansion occurs when water is heated during non-use periods. The installation of a Pressure Reducing Valve (PRV), Check Valve or Back Flow Preventer “closes” the water system, leaving water with no room for expansion. National Standard Plumbing code: 10.5.7 requires backflow prevention, to prevent backflow into the water main.

Thermal expansion in a closed plumbing system can be damaging, dangerous and costly. Its effects include damage to water heater connections, gas water heater flue tubes, pumps serving washers and dishwashers, leaking faucets, “weeping” of water through the water heater T&P Safety Valve, and noisy water hammer in the pipes.



A properly sized American Expansion Tank eliminates these problems, by giving water a place to go when thermal expansion occurs. When a water heating cycle ends, or when any fixture is opened within the system, the impact of thermal expansion is reduced, and water drains out of the expansion tank back into the system.



Expansion tanks are pre-charged with a 38 PSI air charge. If the inlet water pressure is higher than 38 PSI,the expansion tank’s air pressure must be adjusted to match that pressure but must not be higher than 80 PSI.

American Sizing Chart For Residential Water Heaters						
Inlet Water Pressure*	Water Heater Capacity in Gallons					
	30	40	50	66	82	100
40 PSI	2 gal.	2 gal.	2 gal.	2 gal.	5 gal.	5 gal.
50 PSI	2 gal.	2 gal.	2 gal.	2 gal.	5 gal.	5 gal.
60 PSI	2 gal.	2 gal.	2 gal.	2 gal.	5 gal.	5 gal.
70 PSI	2 gal.	2 gal.	2 gal.	2 gal.	5 gal.	5 gal.
80 PSI	2 gal.	5 gal.	2 gal.	5 gal.	5 gal.	5 gal.


*Highest recorded inlet water pressure in a 24-hour period of regulated water pressure. For 2 and 5 gal. sizes use TW Series models.

American Sizing Chart For Commercial Water							
Water Temperature	Water Heater Capacity in Gallons						
	30	40	50	66	82	100	120
140°	2 gal.	2 gal.	5 gal.	5 gal.	5 gal.	10 gal.	10 gal.
150°	2 gal.	2 gal.	5 gal.	5 gal.	5 gal.	10 gal.	10 gal.
160°	5 gal.	5 gal.	5 gal.	5 gal.	5 gal.	10 gal.	10 gal.
170°	5 gal.	5 gal.	10 gal.	10 gal.	10 gal.	10 gal.	10 gal.
180°	5 gal.	5 gal.	10 gal.	10 gal.	10 gal.	10 gal.	10 gal.

POTABLE WATER EXPANSION TANKS

- Maximum Working Pressure: 150 PSI
- Maximum Temperature: 140°F Residential
180°F Commercial

- For use with residential and commercial water heaters
- In-line design, with 3/4” NPTM connection: installs in cold water line of water heater
- Field-adjustable 38 PSI pre-charge
- Drawn-steel tank with powder coated interior
- Butyl rubber parabolic diaphragm, for permanent separation of air and water
- 10-Gallon (AET-10)
- IAPMO Approved
- NSF certified to NSF/ANSI 61-G and 372
- 5-Year Limited Warranty



American Water Heater Expansion Tanks						
Model Number	Gallon Capacity	Maximum Acceptable Volume (Gallons)		Dimensions in Inches		Shipping Weight (lbs)
		40 PSI	60 PSI	A	B	
AET-10	9.21	6.55	5.25	15-3/8	15-1/2	18

150 PSIG Maximum Working Pressure, 3/4” NPTM Connections

