



# **RNG-100D-SS**

## 100W Monocrystalline Solar Panel

#### **Key Features**

Sleek design and a durable frame, the Renogy 100 Watt 12 Volt Monocrystalline Panel provides you with the highest efficiency per area and is the perfect item for off-grid applications.

- High module conversion efficiency
- Top ranked PTC rating
- Quick and inexpensive mounting
- 100% EL testing on all Renogy modules
- No hot spots guaranteed

#### **Potential Uses**

The Renogy 100 Watt Monocrystalline Panel can be used in various off-grid applications that include 12 and 24 volts arrays, water pumping systems, signaling systems and other off-grid applications.



**Power Output Warranty** 



Material and Workmanship Warranty

## **RNG-100D-SS**

### 100W Monocrystalline Solar Panel

#### Electrical Data

Maximum Power at STC*	100 W
Optimum Operating Voltage (V_mp)	17.9 V
Optimum Operating Current (I)	5.72 A
Open Circuit Voltage	21.6 V
Short Circuit Current (I	6. 24 A
Cell Efficiency	21.0%
Maximum System Voltage	600 VDC UL
Maximum Series Fuse Rating	15 A

#### Thermal Characteristics

Operating Module Temperature	$-40^{\circ}$ C to $+80^{\circ}$ C
Nominal Operating Cell Temerature	(NOCT) $47 \pm 2^{\circ}$ C
Temperature Coefficient of Pmax	−0. 44%/° C
Temperature Coefficient of Voc	−0. 30%/° C
Temperature Coefficient of Isc	0. 04%/°C

#### Junction Box

IP Rating	IP 65
Diode Type	HY 10SQ050
Number of Diodes	1 Diode(s)
Output Cables	12 AWG (2.10 ft long)

#### Mechanical Data

Solar Cell Type	Monocrystalline (6.1 x 4 in)
Number of Cells	33 (3 x 11)
Dimensions 42.2 x	19.6 x 1.38in (1074 x 498 x 35mm)
Weight	1 <b>4.3</b> lbs <b>6</b> (5 kg)
Front Glass	Tempered Glass 0.13 in (3.2 mm)
Frame	Anodized Aluminium Alloy
Connectors	MC4 Connectors
Fire Rating	Class C

#### MC4 Connectors


Rated Current	30A
Maximum Voltage	1000VDC
Maximum AWG Size Range	10 AWG
Temperature Range	$-40^{\rm o}{\rm F}$ to $194^{\rm o}{\rm F}$
IP Rating	IP 67

#### Certifications






### Module Diagram



#### IV-Curve



\*All specifications and data described in this data sheet are tested undefesta@dadritions (STC - Irradiance: 1000W/m Temperature: 25 C, Air Mass: 1.5) and may deviate marginally from actual values. Renogy and any foil matter and the right to make any modifications to the information on this data sheet without notice. It is our goal to supply our customers with the most recent information regardingse adataproducts. sheets can be found in the downloads section of our website.remnwgy.com