
Commercial Stream Video Recorder (ADC-CSVR126) - Data Sheet

Important: The product or feature described on this page has not yet been released.

For more information about upcoming or newly released products and features, please see [Release Notes on the Partner Portal](#).

Stream Video Recorder

Designed specifically to work with the Alarm.com hosted video service, the ADC-CSVR126 Stream Video Recorder provides a 24x7 professional solution for commercial-grade local video storage. With the Stream Video Recorder, you can associate up to 16 Alarm.com video cameras for continuous recording.



Features

- Continuously records up to 16 Alarm.com video camera streams for local storage on two hard drives
- Rack-compatible (1U), commercial industrial design
- HDMI and VGA output
- 1080p and 4K display option
- USB mouse control
- Works with the Alarm.com website and app for remote viewing of recordings

Included accessories


- Stream Video Recorder
- Power Adapter
- Quick Start Guide
- USB Mouse





Specifications

Recording Channels	Up to 16 cameras
Video output	16 channels @ 1080p
Incoming bandwidth	160 Mbps
Outgoing bandwidth	256 Mbps
HDMI max output	4K (3840 x 2160) 60 Hz
VGA max output	Full HD (1920 x 1080) 60 Hz
Local display capabilities	Live view, playback, clip export
Compatible cameras	ADC-V522IR, ADC-V622, ADC-V722W, ADC-VC725, ADC-VC726, ADC-VC736, ADC-VC825, ADC-VC826, and ADC-VC836
Speed control	1x, 4x, 8x
Hard disk drive (HDD)	2 SATA interfaces, up to 8 TB per interface
Ethernet connection	RJ-45 10 / 100 / 1000 Mbps self-adaptive Ethernet interface
USB interface	1 x USB 2.0; 1 x USB 3.0
Power adapter	12 V DC ≤ 40 W
Dimensions (W x D x H)	15.2 x 12.4 x 2.0" (385 x 315 x 52 mm)
Operating temperature	14°F – 131°F (-10°C – 55°C)
Operating humidity	10% – 90% (non-condensing) RH
Weight (without HDD)	≤2.2 lbs. (1 kg)
Installation	Rack-mount (1U) compatible

LED guide

LED label	LED status	Description
POWER 	On	Powered on
	Off	Powered off



LED label	LED status	Description
STATUS 	Blinking	Active
	Off	Idle
NETWORK (TX / RX) 	Blinking	Active intranet connection
	Off	No active intranet connection

