

ArubaOS 8.3.0.x

aruba

a Hewlett Packard
Enterprise company

Getting Started Guide

Copyright Information

© Copyright 2018 Hewlett Packard Enterprise Development LP.

Open Source Code

This product includes code licensed under the GNU General Public License, the GNU Lesser General Public License, and/or certain other open source licenses. A complete machine-readable copy of the source code corresponding to such code is available upon request. This offer is valid to anyone in receipt of this information and shall expire three years following the date of the final distribution of this product version by Hewlett Packard Enterprise Company. To obtain such source code, send a check or money order in the amount of US \$10.00 to:

Hewlett Packard Enterprise Company
Attn: General Counsel
3000 Hanover Street
Palo Alto, CA 94304
USA

Contents	3
Revision History	4
About this Guide	5
Related Documents	5
Supported Browsers	5
Contacting Support	6
Overview	7
Installing Mobility Master and Managed Devices	7
Initial Setup	8
Configure the Managed Device to Support APs	17

Revision History

The following table lists the revisions of this document.

Table 1: *Revision History*

Revision	Change Description
Revision 01	Initial release.

This document describes the initial setup of an Aruba user-centric network that consists of an Aruba managed device and Aruba Access Points (APs).

To get started, perform the following steps:

- [Overview](#)
- [Installing Mobility Master and Managed Devices](#)
- [Initial Setup](#)
- [Configure the Managed Device to Support APs](#)

For additional information, see

- [Related Documents on page 5](#)
- [Supported Browsers on page 5](#)
- [Contacting Support on page 6](#)

Related Documents

The following guides are part of the complete documentation for the Aruba user-centric network:

- *ArubaOS 8.3.0.x Release Notes*
- *ArubaOS User Guide*
- *ArubaOS CLI Reference Guide*
- *ArubaOS Migration Guide*
- *ArubaOS API Guide*
- *Aruba Mobility Master Licensing Guide*
- *Aruba Virtual Appliance Installation Guide*
- *Aruba Mobility Master Hardware Appliance Installation Guide*
- *Aruba Wireless Access Point Installation Guide*

Supported Browsers

The following browsers are officially supported for use with the ArubaOS WebUI:

- Microsoft Internet Explorer 10 and 11 on Windows 7, Windows 8, and Windows 10
- Firefox 48 and higher on Windows 7, Windows 8, Windows 10 and Mac OS
- Apple Safari 8.0 or later on Mac OS
- Google Chrome

Contacting Support

Table 2: *Contact Information*

Main Site	arubanetworks.com
Support Site	support.arubanetworks.com
Airheads Social Forums and Knowledge Base	community.arubanetworks.com
North American Telephone	1-800-943-4526 (Toll Free) 1-408-754-1200
International Telephone	arubanetworks.com/support-services/contact-support/
Software Licensing Site	hpe.com/networking/support
End-of-life Information	arubanetworks.com/support-services/end-of-life/
Security Incident Response Team	Site: arubanetworks.com/support-services/security-bulletins/ Email: sirt@arubanetworks.com

This section provides an overview on how to install the Mobility Master and managed devices.

The installation consists of the following steps:

1. Launch the WebUI or Console Setup Wizard to configure the managed device.
2. Connect the managed device to the wired network.
3. Configure the managed device to the Mobility Master. Either Mobility Master-Managed Device topology or stand-alone controller topology is supported.
4. If it is a stand-alone controller deployment, installing the Mobility Master is not required.
5. Install and connect your APs to the network.

Installing Mobility Master and Managed Devices

Installing the Mobility Master

The Aruba Mobility Master provides a 64-bit virtualized software-based managed platform on VM architecture.

The Mobility Master is the centralized management platform for the deployment in the virtualized network infrastructure. The Mobility Master operates on the VM platforms in the VMware environment and can reside with other virtualized appliances.

Installing the Managed Devices

The WebUI Startup Wizard allows you to configure access to the managed device. The Startup Wizard is available the first time you connect to and log into the managed device or whenever the managed device is reset to its factory default configuration. The serial console setup dialog allows you to configure basic managed device settings through a serial port connection to the managed device.

After you complete the Startup Wizard or serial console setup procedure, the managed device reboots using the new configuration information you entered.

Do not connect the managed device to your network when running the Setup Wizard or serial console setup dialog. The factory-default managed device boots up with a default IP address and both DHCP server and spanning tree functions enabled. Once you have completed setup and rebooted the managed device, the managed device should appear on the Mobility Master for the management of managed device from the Mobility Master.

In addition to the traditional method mentioned above, the 7000 Series controllers running ArubaOS 8.3.0.0 can be configured without user intervention with zero touch provisioning (ZTP). This option automatically configures the managed device using Activate. For more details, see [Configure the Managed Device to Support APs](#).

You can launch the setup wizard using any PC or workstation that can run a supported Web browser.

The PC or workstation must either be configured to obtain its IP address using DHCP, or configured to have a static IP address on the 172.16.0.254/24 sub-network. The default IP address of the managed device is 172.16.0.254/24. Connect a PC or workstation to any line port on the managed device, then enter this IP address into a supported Web browser to launch the Setup Wizard.

To run the Setup Wizard:

1. Connect your PC or workstation to a line port on the managed device.
2. Make sure that the managed device is not connected to any device on your network.
3. Boot up the managed device.
4. On your PC or workstation, open a Web browser and connect to <https://172.16.0.254/24>.
5. The initial window of the **Mobility Controller Setup** Wizard asks you to select one of the following deployment modes. Select **Standalone** or **Managed** then click **Continue**.
 - **Standalone Controller:** This is the only controller on the network.
 - **Managed Controller:** This managed device will be managed by a Mobility Master.
6. If you selected **Standalone Controller** or **Managed Controller** in step 5, you will be prompted to enter the information described in the following table, which discusses options common to both stand-alone and managed controller.

Table 3: *controller Information*

Requirement	Description
System Information	
Host Name	A user-defined name by which the managed device will be referenced. You can specify a name of up to 63 characters.
Country Code	The country in which the managed device will operate. The country code determines the 802.11 wireless transmission spectrum. You cannot change the country code for managed devices designated for certain countries, such as the U.S. or Israel. Improper country code assignment can disrupt wireless transmissions. Most countries impose penalties and sanctions for operators of wireless networks with devices set to improper country codes.
Admin Password	Password of up to 32 characters for the admin user to log in to the managed device.
Clock	
Time	You can either manually set the date, time, and GMT time zone.
NTP server IP address	Enter the IP address of an NTP server from which the managed device will obtain its date and time settings.
Timezone	Enter the GMT time zone.



The default certificate installed in the managed device does not guarantee security in production networks. Aruba strongly recommends that you replace the default certificate with a custom certificate issued for your site or domain by a trusted Certificate Authority. See the ArubaOS 8.3.0.0 User Guide for more information about certificates.

- Click **Next** and the Mobility Master option is displayed and you will be prompted to enter the following information:

Table 4: Mobility Master Information

Requirement	Description
Connection to Mobility Master	Determine if the connectivity to the Mobility Master is direct or via a VPN concentrator.
Connection to Mobility Master is Direct	
Master IP address or FQDN	Specify the IP or fully qualified name of the Mobility Master.
Master IPv6 address	Optionally, specify the IP of the Mobility Master on IPv6 networks.
Master MAC address	Optionally, specify the MAC of the Mobility Master.
Redundant master MAC address	Optionally, specify the MAC of the redundant Mobility Master.
IPSec key	Security key for the IPsec tunnel between the managed device and the Mobility Master, 6 to 64 characters.
Retype IPSec key	Confirmation of the security key.
Connection to Mobility Master is Via VPN Concentrator	
Concentrator IP address	Specify the IP address of the VPN concentrator to connect to in order to reach the Mobility Master.
Concentrator MAC address	Specify the IP address of the VPN concentrator to connect to in order to reach the Mobility Master.
Redundant concentrator MAC address	Optionally, specify the MAC address of the eventual redundant VPN concentrator.
Master IP address or FQDN	Specify the IP or fully qualified name of the Mobility Master.
Authentication	Provide a choice of Factory certificate or Pre-Shared Key.
IPSec key	Security key for the IPsec tunnel between the managed device and the VPN concentrator, 6 to 64 characters.
Retype IPSec key	Confirmation of the security key.

- Click **Next**.
- Specify the Uplink settings for the managed device to reach the Mobility Master.

Table 5: Uplink Settings Information

Requirement	Description
Uplink VLAN ID	Specify the VLAN ID which is an integer. Value range- 1 to 4094.
Port	Specify the default communication interface.
Portmode	Specify the port mode as either Access or Trunk.
Uplink Type	Static IP addressing or via DHCP.
VLAN IP address	Specify the managed device's IP address.
Netmask	Specify the Netmask used to calculate the IP subnet.
Default gateway	Specify the default gateway used to setup default routes.
DNS IP address	Specify the address of the DNS server.
VLAN IPv6 address	Specify the managed device's IP address on IPv6 networks.
IPv6 gateway	Specify the default gateway on IPv6 networks.

10. Click **Next** and the Summary of the setup is displayed.

11. If you have selected **Standalone** as the option in step 5, you will be prompted to add AirWave, Connectivity, and Licensing information after you have set the basic configuration options.

Table 6: AirWave Stand-alone Controller Information

Requirement	Description
Connect to AirWave	Specify if this controller is managed via an AirWave platform or not
AirWave IP address	Specify the IP address of the AirWave platform.
SNMP version	Specify which SNMP protocol version is used (v2 or v3).
SNMP version v2	
Community string	Enter a string with 4 to 31 characters.
SNMP version v3	
Username	Enter the username with 1 to 31 characters.
Authentication password	Enter the password with 4 to 128 characters.
Retype password	Confirmation of the Authentication password.
Privacy password	Enter a privacy password with 4 to 128 characters.
Retype password	Confirmation of the Privacy password.

Requirement	Description
NTP server IP address	Specify the network time server to use. This option is available only if time is set to Set time from this machine in the controller information provided in Table 2.
Traps	Generate all traps or just the ones for AirWave.
Send system logs to AirWave	Send additional logs to AirWave for further analysis.

12. Click **Next** and enter the information for Connectivity.
13. Click **Next** and enter the licensing information.
14. Click **Next** to view the summary of the setup.

Initial Setup on a Serial Port Connection

The serial port is located on the front panel (back panel in case of 7024 and 7008 controllers) of the managed device. You can start the Initial Setup dialog when you connect a terminal, PC or workstation running a terminal emulation program to the serial port on the managed device.

The serial port connection only allows you to configure the basic configuration required to connect the managed device to the network. The recommended browser-based configuration Wizard allows you to also install software licenses and configure internal and guest WLANs. If you use the Initial Setup dialog to configure the managed device, the browser-based Setup Wizard will not be available unless you reset the managed device to its factory default configuration.

To run the Initial full setup dialog from a serial connection:

1. Configure your terminal or terminal emulation program to use the following communication settings:

Table 7: Terminal Communication Settings

Baud Rate	Data Bits	Parity	Stop Bits	Flow Control
9600	8	None	1	None

2. Connect your terminal or PC/workstation to the serial port on the managed devices using an RS-232 serial cable. RJ-45 cable and DB-9 to RJ-45 adapter is required. You may need a USB adapter to connect the serial cable to your PC.
3. Boot up the managed device. After the managed device has booted up, you should see a screen similar to the following setup dialog for managed devices:

```
Auto-provisioning is in progress. Choose one of the following options to override or debug...
```

```
'enable-debug' : Enable auto-provisioning debug logs
'disable-debug': Disable auto-provisioning debug logs
'mini-setup'   : Stop auto-provisioning and start mini setup dialog for smart-branch role
'full-setup'   : Stop auto-provisioning and start full setup dialog for any role
```

```
Enter Option (partial string is acceptable):f
Are you sure that you want to stop auto-provisioning and start full setup dialog? (yes/no):
y
Reading configuration from factory-default.cfg
```

4. (Applicable to managed devices using ZTP) enter **f** to invoke full-setup.

- The Serial Port Configuration Dialog displays the configuration prompts. The prompts may vary, depending upon the switch role you choose. Enter the required information at each prompt, then press **Enter** to continue to the next question.

Table 8: Serial Console Configuration Dialog

Console Prompt	Description
Enter System Name	Enter a name for the managed device, or press Enter to use the default system name. You can specify a name of up to 63 characters.
Enter Switch Role, (master stand-alone md)	Specify one of the following roles: Master: This device is the 7200 Series controllers running as a master controller. Stand-alone: This is the only self-managed controller on your network. md: This device will be managed by a Mobility Master. You are prompted to specify the type of authentication to be used by the managed device. If you are configuring a managed device to use pre-shared key authentication to communicate with the Mobility Master, enter the IP address of the Mobility Master and the pre-shared key. If you are configuring a managed device to use certificate authentication, specify the MAC addresses of the Mobility Master.
IP type to terminate IPsec tunnel	Specify if the IP type to which the IPsec tunnels use to terminate. The IP types are IPv4 and IPv6.
Master switch IP address or FQDN	Specify the IP or fully qualified name of the Mobility Master.
Is this a VPN concentrator for managed device to reach Master switch	Enter Yes . This is an IP address of the managed device that terminates VPN tunnels to the data center.
Master switch Authentication method	Provide a choice of PSKwithIP or PSKwithMAC. If you choose PSKwithMAC, then the peer MAC address value to be configured on a device for tunnel establishment is based on the platform type of the peer device. For more information on the type of MAC address to be configured as peer MAC address, see Peer MAC Address Configuration for PSK with MAC .
IPsec Pre-shared Key	Security key for the IPsec tunnel between the managed device and the Mobility Master, 6 to 64 characters.
Uplink Vlan ID	Specify the VLAN ID which is an integer. Value range- 1 to 4094
Uplink port	Its not value 1 or 0, value should be 1/0 or 0/0/0 or any port based on the managed device platforms.
Uplink port mode	Specify the port mode as either Access or Trunk. In trunk mode, a port can carry traffic for multiple VLANs. In access mode, the port forwards untagged packets received to the managed device and they appear on the configured access mode VLAN.
Enter Native VLAN ID [1]	Specify a particular vlan to be configured as a native vlan.
Uplink Vlan IP assignment method	Assign manually the IP addressing of the uplink or via DHCP.
Uplink Vlan Static IP address	The managed device takes its IP address from VLAN 1 and uses this IP address to communicate with other managed devices and with APs. Enter an IPv4 VLAN 1 interface IP address, or press Enter without specifying an IP address to use the default address 172.16.0.254/24.

Console Prompt	Description
Uplink Vlan Static IP netmask	Enter an IPv4 VLAN 1 interface IP subnet mask, or press Enter without specifying an IP address to use the default address 255.255.255.0.
IP default gateway	This is usually the IP address of the interface on the upstream switch or router to which you will connect the managed devices. The default gateway and the VLAN 1 IP address need to be in the same network. Enter an IPv4 gateway IP address, or press Enter to continue without specifying an IP gateway.
DNS IP address	IP address of the DNS server.
IPv6 address on vlan	IPv6 address of the managed device.
Do you want to configure port-channel (yes no) [no]	Specify if you want to configure the port-channel. LACP will be configured on port members with port-channel ID as LACP group ID.
Enter Port-channel ID [0]	Specify the port-channel ID.
Uplink Vlan Static IPv6 address	The managed device takes its IP address from VLAN 1 and uses this IP address to communicate with other managed devices and with APs. Supported subnets are: Global Unicast: 2000::/3, Unique local unicast: fc00::/7 Enter an IPv6 VLAN 1 interface IP address, or press Enter without specifying an IP address to use the default address 2000::1.
Uplink Vlan interface IPv6 prefix length	Enter a value from 0 to 128 to define an IPv6 VLAN 1 interface IP prefix length, or press Enter without specifying a prefix length to use the default value of 64.
IPv6 default gateway	This optional value is usually the IP address of the interface on the upstream switch or router to which you will connect the managed device. The default gateway and the VLAN 1 IP address need to be in the same network. Enter an IPv6 gateway IP address to configure this setting, or press Enter to continue without specifying an IP gateway.
Country code	If your managed device has a country code that restricts its usage, enter yes to confirm this code.
Time Zone	Enter the time zone for the managed device, or press Enter to select the default time zone.
Time in UTC	Enter the current time in UTC format, or press Enter to select the default time.
Date	Enter the current date, or press Enter to select the default date.
Password for admin login	Enter a password to allow the admin user to login to the WebUI, CLI and console interfaces. This password can be up to 32 alphanumeric characters long.
Re-type password for admin login	Confirmation for the admin login password

- At the end of the Initial Setup, you are asked to review and confirm your configuration changes. Enter **y** to accept the changes. The managed device reboots.



If you want to complete optional configuration options (e.g. disabling spanning tree or installing software licenses) before connecting the managed device to the network, refer to the ArubaOS 8.3.0.0 User Guide for additional information on configuration.

Peer MAC Address Configuration for PSK with MAC

The Peer MAC address configuration on a device for PSK with MAC authentication is based on the platform type of the peer device.

The following table lists the type of MAC address to be configured as the peer MAC address for different platform combinations of a Mobility Master-Managed Device pair:

Table 9: Peer MAC Address Configuration

Mobility Master Platform	Managed Device Platform	Peer MAC on the Mobility Master	Peer MAC on the Managed Device
Mobility Master Virtual Appliance	7000 Series controllers	MAC address of the VLAN 1 interface of the managed device	Management MAC address of the master device
Mobility Master Virtual Appliance	Mobility Controller Virtual Appliance	Management MAC address of the managed device	Management MAC address of the master device
Mobility Master Hardware Appliance	7000 Series controllers	MAC address of the VLAN interface	Management MAC address of the master device
Mobility Master Hardware Appliance	Mobility Controller Virtual Appliance	Management MAC address of the managed device	Management MAC address of the master device
7000 Series controllers in Master Controller Mode	7000 Series controllers	MAC address of the VLAN interface	MAC address of the VLAN 1 interface of the master device
7200 Series controllers in Master Controller Mode	Mobility Controller Virtual Appliance	Management MAC address of the managed device	MAC address of the VLAN 1 interface of the master device

Identifying the MAC Address on a Device

Execute the following command to view the Management MAC address (Applicable only for Mobility Master Virtual Appliance

or Mobility Master Hardware Appliance) or the MAC address of the VLAN1 interface for any device:

```
(host) [mynode] (config) #show switchinfo
...
...
Boot Partition: PARTITION 0
mgmt is administratively down line protocol is down
Hardware is Ethernet, address is 00:0C:29:56:33:FE
VLAN1 is up line protocol is down
Hardware is CPU Interface, Interface address is 00:0C:29:56:33:08 (bia 00:0C:29: 56:33:08)
Description: 802.1Q VLAN
...
...
```

Connect the Managed Device to the Wired Network

Once managed device setup is complete, connect a port on the managed device to the appropriately configured port on a Layer-2 switch or router. Make sure that you have the correct cables and that the port LEDs indicate proper connections and cable descriptions.

Zero Touch Provisioning

Zero touch provisioning (ZTP) makes the deployment of managed device plug-n-play. The managed device now learns all the required information from the network and provisions itself automatically.

With ZTP, a managed device automatically gets its local and global configuration and license limits from a central managed device. A managed device with factory default settings gather the required information from the network and then provision itself automatically.

The main elements for ZTP are:

- Auto discovery of Mobility Master.
- Configuration download from the Mobility Master.

Provisioning Modes

The following modes are supported:

- **auto:** In this mode, managed device provisions completely automatically. The managed device gets the local IP address and routing information from DHCP and gets the Mobility Master information and regulatory domain from one of the supported servers. Then, it downloads the entire configuration from the Mobility Master.
- **mini-setup:** In this mode, managed device gets its local IP address and routing information from DHCP server. However, user is required to provide Mobility Master information and regulatory domain. Then, it downloads the entire configuration from the Mobility Master.
- **full-setup:** In this mode, managed device gets all the basic provisioning information from user inputs. However, even in this mode, controller can download configuration from the Mobility Master if the managed device role is specified as a managed device.



In the default state, controller starts in complete auto mode. While the controller is trying to provision automatically, user are also provided an option to override the auto-mode at any time and select the desired mode. If there is "NO" ZTP provisioning in activate, then quick setup will wait for the user to provide inputs.



For auto provisioning, last physical interface port of a 7000 Series controller should be connected as uplink which will be in VLAN 4094 and act as a DHCP client.

Automatically Provisioning a Managed Device

An auto provisioning managed device acts as a DHCP client to get its local IP address, routing information, and Mobility Master information and regulatory domain from a DHCP server or Activate server. A factory-default managed device boots in auto provisioning mode. To interrupt the auto provisioning process, enter the string mini-setup or full-setup at the initial setup dialog prompt shown below:

```
Auto-provisioning is in progress. Choose one of the following options to override or debug...
```

```
'enable-debug' : Enable auto-provisioning debug logs
```

```
'disable-debug': Disable auto-provisioning debug logs
```

```
'mini-setup' : Stop auto-provisioning and start mini setup dialog for smart-branch role
```

```
'full-setup' : Stop auto-provisioning and start full setup dialog for any role
```

```
Enter Option (partial string is acceptable):_
```

If the managed device can not complete ZTP provisioning through Activate, then the initial setup process waits for the user to provide input

Activate

The managed device interacts with the activate server to get Mobility Master information. The managed device establishes HTTPS connection with the activate server and posts provision requests to it. The activate server authenticates the managed device and provides the Mobility Master information and country code to the managed device.

Activate Interface— The managed device and the Mobility Master interact with the activate server to receive information about each other. Once all the information is available in the activate server, the relationship between a Mobility Master and all the managed device managed by it is provisioned automatically.

The managed device interacts with the activate server to learn about their role, Mobility Master information, and their regulatory domain. The Mobility Master sends its own information and not managed device information. Activate reuses existing AP-information field for managed device interactions. To achieve this, the following two steps are performed:

1. Mobility Master retrieving whitelist db from activate server. The following steps are involved to get the whitelist db:
 - a. Mobility Master sends initial post with 'keep-alive' connection type with the following information:
 - Type as provision update, mode as managed device, session id, Ap-information that includes <serial number>, <mac>, <model>.
 - b. Activate responds with the following information:
 - Type as provision update, activate assigned session id, status, and connection as keep alive.
 - c. Mobility Master then sends a second POST with 'close' connection type with the following information:
 - Type as provision update, session id received from activate, Ap-information that includes <serial number>, <mac>, <model>, length of certificate, signed certificate, and device certificate.
 - d. Activate then responds with the following information:
 - Type as provision update, the same session id that activate assigned in the first response, status as success or failure, mode as master, and the list of managed devices with the whitelist db that contains <MAC address>,<Serial number>,<Model>,<Mode>,<Hostname>, and <Config group>.
2. Managed device contacting activate and retrieving the provisioning rule
The following steps are involved to retrieve the provision rule:

- a. Navigate to the device list and select a device that you want to designate as Mobility Master.
- b. Edit the selected device and set its mode to Master.
- c. Go to setup and create a folder with the managed device_to_Master rule.
- d. Populate the rule with the following information:
 - Select master device.
 - Specify IP address of the master.
 - Specify country code for managed device that will be in this folder.
 - Specify configuration group for managed device that will be in this folder.



A folder can contain only one type of managed device that have the same country code and map to the same configuration group. Different folders need to be created for each such group, if the country code or mapping to the configuration changes.

- e. Again, navigate to the device list and select a device that you intend to designate as managed device.
- f. Edit the selected device and set its name to the desired hostname. If the name is not set, it will be autogenerated.
- g. Move the selected managed device to the folder created in step c.

Configure the Managed Device to Support APs

Before you install APs in a network environment, you must ensure that the APs will be able to locate and connect to the managed device when powered on. Specifically, you need to ensure the following:

- When connected to the network, each AP is assigned a valid IP address
- APs are able to locate the managed devices

Each Aruba AP requires a unique IP address on a subnetwork that has connectivity to a managed device. Aruba recommends using the DHCP to provide IP addresses for APs; the DHCP server can be an existing network server or an Aruba managed device configured as a DHCP server.

If an AP is on the same subnetwork as the Mobility Master, you can configure the managed device as a DHCP server to assign an IP address to the AP. The managed device must be the only DHCP server for this subnetwork.

Enable DHCP Server Capability

Use the following procedure to use the WebUI to enable DHCP server capability:

1. Enter the IP address of the managed device in the URL of a browser window to access the WebUI.
2. At the WebUI login page, enter the **admin** user name and the password you entered during the Initial Setup.
3. Navigate to the **Configuration > Services** window.
4. Open the **DHCP Server** tab.
5. Select **Enable** from either **IPv4** or **IPv6 DHCP server** drop-down list.
6. In the **Pool Configuration** table, click +.
7. Enter information about the subnetwork for which IP addresses are to be assigned.
8. Click **Submit**.
9. If there are addresses that should not be assigned in the subnetwork:
 - a. Click + in the **Excluded Address Range** section.
 - b. Enter the address range in the **Add Excluded Address** section.

- c. Click **Submit**.
10. Click **Pending Changes**.
11. In the **Pending Changes** window, select the check box and click Deploy changes.

Managed Device Discovery

An Aruba AP can discover the IP address of the managed device in one of several ways. The ADP is enabled by default on all Aruba APs and managed devices. If all APs and managed devices are connected to the same Layer-2 network, APs will use ADP to discover their managed devices. If the devices are on different networks, you must configure the AP to use a Layer-3 compatible discovery mechanism such as DNS, DHCP, or IGMP forwarding after installing the AP on the network. For details, refer to the *ArubaOS 8.3.0.0 User Guide*.

With ADP, APs send out periodic multicast and broadcast queries to locate the . If the APs are in the same broadcast domain as the managed device, the managed device automatically responds to the APs' queries with its IP address. If the APs are not in the same broadcast domain as the managed device, you need to enable multicast on the network. If multicast is not an option, then the APs can be configured to use DNS or DHCP based provisioning to contact the managed device.

As APs do not terminate on the Mobility Master in ArubaOS 8.3.0.0, they are pointed to a managed device that has the configuration for the AP's **AP-group**.

Install the APs

Refer to the AP placement map generated by RF Plan to identify the locations in which to physically install your APs. You can either connect the AP directly to a port on the managed device, or connect the AP to another switch or router that has Layer-2 or Layer-3 connectivity to the managed device. If the Ethernet port on the managed device is an 802.3af PoE port, the AP automatically uses it to power up. If a PoE port is not available, contact your Aruba vendor to obtain an AC adapter for the AP.

Once an AP is connected to the network and powered up, it will automatically attempt to locate the managed device. You can view a list of all APs connected to the managed device by accessing the **Configuration > Access Points** page in the WebUI of the Mobility Master. An AP installed on the network advertises its default SSID. Wireless users can connect to this SSID, but will not have access to the network until you configure authentication policies and user roles for your wireless users. For complete details on authentication policies and user roles, refer to the *ArubaOS 8.3.x.x User Guide*.