

AMP-R2SIC51 – Two Source, 5.25" Drop Ceiling Speakers

One Speaker Package

Two source, 5.25", Drop Ceiling Amplified Speakers deliver up to 40 watts power directly to the speaker. Each powered speaker (AMP-R2SIC5) can drive three additional speakers (IC5). One line can drive up to 10 self-amplified speakers. Lower noise feature and protection from shorts and overheating. 15Volt DC Level 5 power supply included. Available in Bluetooth models.



One Speaker combination package consisting of the following:

- 1.) One (1) each (AMP-R2SIC5) 5.25" amplified speaker with (PS15VDC35AL5) 15 volts Level 5 power supply
- 2.) One (1) each Backcan enclosure
- 3.) One (1) each 5TB tile bridge

Features:

- Built onto the OWI IC5 In-Ceiling Speakers
- UL Listed, Energy Star, Energy Verified
- 2 Line Level Input/Sources
- Up to 40 Watts or Power – right at the speaker
- With Priority Override Feature
- Balanced Line level Output
- Available in models with Bluetooth Features
- With a 3.5 mm Jack Line Input
- 15 Volt DC power supply (UL rated-Level 5) included
- Protected from shorts and overheating
- Lower Noise Feature
- Fast and easy – install in the field
- Stereo/mono volume controls available
- Available in 1, 2 and 4 speaker packages

Available also in other complete install packages:

[AMP-R2SIC51SVC](#)
[AMP-R2SIC52](#)
[AMP-R2SIC52SVC](#)
[AMP-R2SIC54](#)
[AMP-R2SIC54SVC](#)

- Single speaker combination with tile bridges, backcans and volume control.
- Two speaker combination with tile bridges and backcans.
- Two speaker combination with tile bridges, backcans and volume control.
- Four speaker combination with tile bridges and backcans
- Four speaker combination with tile bridges, backcans and volume control.



OWI Incorporated * 17141 Kingsview Ave., Carson, CA 90746 * 310-515-1900 * www.owi-inc.com