

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No .:	IECEx SIR 18.0043X	Page 1 o		
Status:	Draft	Issue No	: 2	Issue 1 (2019-02-08) Issue 0 (2018-10-05)
Date of Issue:	2021-05-11			
Applicant:	TSI Incorporated 500 Cardigan Rd Shoreview, MN 55126-3996 United States of America			
Equipment:	Model SidePak AM520i Personal Aer	osol Monitor		
Optional accessory:				
Type of Protection:	Intrinsic Safety			
Marking:	Ex ia I Ma Ex ia IIC T4 Ga 0°C to +50°C			
Approved for issue o Certification Body:	n behalf of the IECEx	Neil Jones		
Position:		Certification Manager		
Signature: (for printed version)				
Date:				
This certificate is not	schedule may only be reproduced in full. t transferable and remains the property of the issu enticity of this certificate may be verified by visiting	ing body. g www.iecex.com or use of this QR Code.		
Certificate issued	l by:			
CSA Group Test Unit 6, Hawarde Hawarden, Dees United Kingdon	n Industrial Park side CH5 3US			GROUP"



GB/SIR/ExTR18.0175/00

Quality Assessment Report:

CA/CSA/QAR16.0008/02

GB/SIR/ExTR19.0027/00

GB/SIR/ExTR21.0086/00



IECEx Certificate of Conformity

Certificate No .: IECEx SIR 18.0043X

Date of issue:

Page 3 of 4

Issue No: 2

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

2021-05-11

The SidePak AM520i Personal Aerosol Monitor is a portable, battery-powered device designed to continuously measure the particle mass concentration of the ambient atmosphere. The Sidepak AM520i contains an IEC Class 1 approved laser assembly. External air is drawn through an inlet into an internal optical chamber where the scattered laser light is measured to determine particle mass concentration. The Sidepak AM520i is contained within a polymeric enclosure having an inlet and an outlet port for the ambient flow path and an external USB connection. The removable battery pack contains a barrel-type DC connector used for charging the pack outside of the hazardous area. The user interacts with the instrument through a membrane switch on the front of the enclosure. The equipment has approximate overall dimensions of 87.63 mm (W) x 129.03 mm (H) x 75.44 mm (D).

Refer to the Annexe for additional information.

SPECIFIC CONDITIONS OF USE: YES as shown below: Refer to the Annexe.



Date of issue:

IECEx Certificate of Conformity

Certificate No.: IECEx SIR 18.0043X

Page 4 of 4

Issue No: 2

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

2021-05-11

This issue, Issue 2, recognises the following changes; refer to the certificate annex to view a comprehensive history:

- 1. Recognise updates to 11 drawings (based on the original Manufacturer's Documents list), with all changes to the equipment having been assessed as maintaining compliance with the standards listed.
- 2. Recognise updates to the Manufacturer's Documents list itself, as the original list contained zip files with multiple documents; the relevant documents have been extracted, stamped, and are hereby added to the Manufacturer's Documents list.

Annex:

IECEx SIR 18.0043X Issue 2 Annexe.pdf

Annexe to:	IECEx SIR 18.0043X Issue 2
Applicant:	TSI Incorporated
Apparatus:	Model SidePak AM520i Personal Aerosol Monitor

Equipment:

The SidePak AM520i Personal Aerosol Monitor is a portable, battery-powered device designed to continuously measure the particle mass concentration of the ambient atmosphere. The Sidepak AM520i contains an IEC Class 1 approved laser assembly. External air is drawn through an inlet into an internal optical chamber where the scattered laser light is measured to determine particle mass concentration. The Sidepak AM520i is contained within a polymeric enclosure having an inlet and an outlet port for the ambient flow path and an external USB connection. The removable battery pack contains a barrel-type DC connector used for charging the pack outside of the hazardous area. The user interacts with the instrument through a membrane switch on the front of the enclosure. The equipment has approximate overall dimensions of 87.63 mm (W) x 129.03 mm (H) x 75.44 mm (D).

Data downloading while the unit is in the non-hazardous area may performed via the Micro USB 2.0 Type B port connected to a computer. The output parameters at this USB port are: Uo = +6.51V, Im = 62 mA; limited by the certified on-board 62 mA Littlefuse fuse part number 259.062 (IECEx BAS 10.0098U) and two parallel 6.51V SMBJ5341B Zener diode devices in addition to the Micro USB 2.0 Type B standard international protocol powered by the certified SELV power source.

Specific Conditions of Use:

- 1. The AM520i Personal Aerosol Monitor shall only be used in conjunction with battery pack assembly model number 803322.
- 2. For applications in the hazardous area, connection to the Micro USB 2.0 Type B port terminal shall not be made. When used outside of the hazardous area, the USB terminal may be connected to non-intrinsically safe mating Micro USB 2.0 Type B port of a computer that shall be:
 - a. Powered only by a certified safety extra low-voltage (SELV) supply (per IEC 60950) having a Um output voltage limit of [25 Vdc at 90 Watts].
- 3. The AM520i shall only be charged in the non-hazardous area using the charger specifically supplied for use with the unit approved as SELV or Class 2 equipment against IEC 60950. The maximum output voltage from the charger shall not exceed 12 Vdc.

Conditions of Manufacture:

1. Connector J201 on the Main board shall not be used as a condition of this certification.

Full Certificate Change History

Issue 1 – this Issue introduced the following changes:

- 1. Addition of Group I marking i.e. Ex ia I Ma to the product.
- 2. Modification of label drawing to accommodate new markings.
- 3. Creation of a new scheduled drawing for the membrane switch.
- 4. Creation of a new scheduled drawing with the content of the instructions manual to be controlled.
- 5. Deletion of 2 drawings from the list of manufacturer's documents.

Date: To Be Entered

IECEx SIR 18.0043X Issue 2
TSI Incorporated
Model SidePak AM520i Personal Aerosol Monitor

Issue 2 – this Issue introduced the following changes:

-

- 1. Recognise updates to 11 drawings (based on the original Manufacturer's Documents list), with all changes to the equipment having been assessed as maintaining compliance with the standards listed.
- 2. Recognise updates to the Manufacturer's Documents list itself, as the original list contained zip files with multiple documents; the relevant documents have been extracted, stamped, and are hereby added to the Manufacturer's Documents list.

Date: To Be Entered