

24 Series Exit Device Template Index Hollow Metal Door Applications

24 Series Device	Device Template
24-R, F-24-R	T-1320
24-V, F-24-V, 24-V-LBR, F-24-V-LBR	T-1328
F-24-C, F-24-C-LBR	T-1340
24-C, 24-C-LBR	T-1341

24 Series Device	700 Series Trim	Trim Template
24-R, F-24-R, 24-V-LBR, F-24-V-LBR	715DT	T-2320
	711K, 711K-BE, 711K-NL, 712L, 712L-BE, 712L-NL, 712L-DT	T-2360
	718C, 718DT, 718NL	T-2361
	710TP, 710TP-BE, 718TP, 718TP-BE	T-2325
24-V-LBR, F-24-V-LBR	719TL, 719TL-BE	T-2323
24-C, F-24-C	717DT, 718DT, 718C, 718NL	T-2362
	711K, 711K-BE, 711K-NL, 712L, 712L-BE, 712L-DT, 712L-NL	T-2363

24 Series Device	24 Series Strike	Strike Template
24-R, F-24-R	299, 299F (standard)	T-3201
	499F (optional with mullion)	T-3202
	264 (optional)	T-3203
	1439 (optional)	T-3204
	1606 (optional)	T-3205
24-V, F-24-V, 24-V-LBR, F-24-V-LBR	3788 Top Strike with 4215 angle bracket (standard)	T-3032*
24-C, F-24-C, 24-C-LBR, F-24 -C-LBR	4188 Top Strike (standard)	T-3034*
24-V, F-24-V, 24-C, F-24-C	2130 Bottom Strike (standard)	T-3053
24-V, F-24-V, 24-C	2126-A Bottom Strike (optional)	T-3050
	4155 Bottom Strike (optional)	T-3055

* For F-24-V-LBR and F-24-C-LBR applications, add template [T-5494](#) for Auxiliary Fire Latch.