封面

胶装装订，彩色印刷，93*130MM，128g铜版

英

GOOLOO ENRICH YOUR DRIVING LIFE

User Manual
Jump Starter

ELITE SERIES 1200A JUMP STARTER

Model: GP37-Plus

SUPERSAFE™ is a safety protection technology by GOOLOO®

Thank you for choosing GOOLOO jump starter. To ensure your personal safety, property security, and good user experience, please read the entire manual carefully before using this product. Please keep this manual for easy reference.

⚠Charge It First !

While reading through the manual, you can begin to charge up your GP37-Plus by connecting it to the wall charger provided and plugging into a wall socket.

Only use the charger we provided to charge the GP37-Plus!

www.gooloo.com

Scan to get more information about GOOLOO products

Parts and Functional Description



Operation Instructions

Indicator Light:

Press the power switch to check the battery level:

Indicator	1 Solid	2 Solid	3 Solid	4 Solid	5 Solid
Battery Level	20%	40%	60%	80%	100%

The indicator will flash one by one during the period of charging. Different numbers of solid indicators show different battery level of this unit. All indicators will be turned off automatically when the charging process is finished.

How to Charge the GP37-Plus

1. Charged By Wall Charger (100V~240V)

1). Plug the wall charger into the wall socket.
2). Connect the other end of wall charger to the 15V/1A input port of GP37-Plus.

2. Charged By Car Charger

1). Plug the car charger into the socket of 12V cigarette lighter.
2). Connect the other end of car charger to the 15V/1A input port of GP37-Plus.

How to Jump Start 12V Vehicles

Make sure the unit is over 60% charged (3 bars on the battery level indicator). If the unit has not used in more than two months, you should charge it first.

1. Connect the jumper cable plug into the GP37-Plus.
2. Connect red clamp to the positive (+) battery terminal and black clamp to the negative (-) battery terminal, check the indicator light on the jumper cable. Only when the indicator light turns green, can you start the vehicle.
3. Start the vehicle when the indicator light turns green.
4. Remove the jumper cable plug from the jump starter.
5. Remove the battery clamps from the vehicle's battery.

How to Use the Smart Jumper Cable

1. Connect the jumper cable plug fully seated into the host and make sure the indicator on the jumper cable is off.
2. Connect red clamp to the positive (+) battery terminal and black clamp to the negative (-) battery terminal.
3. Check the indicator light on the jumper cable and operate following the instruction as below.

GREEN LIGHT on: Indicates the connection is correct and the circuit is working, you can start the vehicle directly

RED LIGHT on with beeping: Indicates the connection is wrong. You need to correct the battery clamps as step 2 mentioned above, then wait until the GREEN LIGHT is on to start the vehicle.

GREEN LIGHT blinking with beeping: Indicates the vehicle's battery voltage is too low, press the "BOOST" button on the jumper cable, wait until GREEN LIGHT becomes solid, then start the vehicle within 30 seconds.

No Lights on, no beeping: Indicates that the vehicle's battery may be damaged. Confirm the connection of battery clamps is correct, press the "BOOST" button on the jumper cable, wait until GREEN LIGHT is on and then start the vehicle within 30s.

4. Start the vehicle when the indicator light turns green.

5. When the vehicle has been started, remove the jumper cables from the vehicle's battery and jump starter.

How to Charge Your Phone or Tablet

1. Plug the charging cable to USB output port.
2. Select the appropriate connector for your device.
3. Press the power switch, the unit can identify your device and charge it automatically. The indicators light will be lit up when charging.



LED Flashlight

Press the LED flashlight switch to start the LED light. There are 3 modes of LED light appear in order(Normal, Strobe, SOS) if you press slightly.

Package Content

#	Part Name	Quantity
1	Host	1
2	Smart Jumper Cable	1
3	USB to Type-C Quick Charge Cable	1
4	Wall Charger	1
5	Car Charger	1
6	Kit Bag	1
7	User Manual	1

Technical Specification

Input:	15V/1A
Output:	Quick Charge(5V/2.4A,9V/2A) 5V/2.1A; 12V/10A
Capacity:	66.6Wh
Start Current:	350A(3s)
Peak Current:	1200A
Size:	157*75*36(mm)
Weight:	540g
Discharge Temp & Charge Temp	-20℃～40℃/ 0℃～45℃
Lifetime	>1000 cycles
Full Charging Time:	About 5 Hours

Trouble Shooting

Finding	Cause	Remedies
It has charged for a long time, but the fifth indicator light of this unit is still blinking	Battery level recognition problem.	Battery level needs to be corrected, unplug the wall charger and discharge the device then recharge it.
No response when pressing the power switch button.	Low voltage protection is started.	Charge the device with wall charger to activate the device.
The unit can not be charged，the first indicator light of this unit blinks all the time.	The unit is over discharged	Please contact us fiona@gooloo.com
This unit is over heated or swelled	The unit is over discharged	Please contact us fiona@gooloo.com

If there is any problem with our products, please contact us directly at fiona@ gooloo.com, our customer service team will work hard to solve the problem within 24 hours.

FAQ

Q1: What is the operating temperature of this unit and how to store it?

A: This unit is Lithium polymer battery, operating temperature is -20-60 ºC/ -4-140ºF. If the ambient temperature is higher than 60ºC/140ºF, the internal construction of the Polymer Lithium-Ion cells will be changed, it may swell and will be unsafe. So DO NOT store the device in a vehicle for long periods of time, especially in hot weather.

Q2: How to jump start a vehicle with this unit?

A: Make sure the unit is over 60% charged (3 bars on the battery level indicator). If the unit has not been used for more than two months, you should charge it first.

1. Connect the jumper cable plug into the GP37-Plus.
2. Connect red clamp to the positive (+) battery terminal and black clamp to the negative (-) battery terminal, and check the indicator light on the jumper cable. Only when the indicator light on the jumper cable. Only when the indicator light turns green, can we start the vehicle. (Please refer to the use instructions above on the jumper cable).
3. Start the vehicle when the indicator light turns green.
4. Remove the jumper cable plug from the jump starter.
5. Remove the battery clamps from the vehicle's battery.

Q3: How do you know if the device is connected to the vehicle correctly?

A: With the battery clamps connected to the vehicle battery, when the jumper cable indicator light shines a steady green light, it means it's connected correctly. If the light is flashing red, it means it is connected incorrectly.

Q4: What should I do if this product cannot start a vehicle?

A: Recharge the device fully, and then try it again. Make sure to wait 30 seconds between each jump attempt. If it still does not work, contact us at: fiona@gooloo.com (Attach your order ID, it is necessary).

Q5: What should I do if this product cannot be charged?

A: Charge with 15V wall charger or car charger for a full overnight period (at least 8 hours). If it still does not work, contact us at: fiona@gooloo.com (Attach your order ID, it is necessary).

Q6: What should I do if this product cannot charge other devices?

A: Try to use another charging cable to charge it again. If it can work with another cable, the cable we provided is defective; Contact us we will provide you a new cable. If it still does not work, email us at: fiona@gooloo.com (Attach your order ID, it is necessary).

Q7: Can this product charge other devices while it is being charged?

A: Yes.

Q8: Can this product charge other devices while starting a vehicle?

A: No.

Q9: How long will the charge of the battery remain?

A: 6-12 months, however, we suggest you had better recharge it every 3 months.

Q10: Why this product cannot charge the weak current devices?

A: This product can not be able to charge the devices that needs weak current like headphone,smart watch,etc. Because it has a minimum load current(400 mA), it will be automatically off after 30 seconds if the charging current is less than 400mA.

Toxic and Harmful Substances

Composition and amount of toxic or harmful substance in this product:

Pb	Hg	Cd	Cr(VI)	PBB	PBDE
0	0	0	0	0	0

0 : Indicate that the content of harmful substances in all homogeneous materials is all lower than the prescribed limit of MCV (the standard 2002/95/EC/RoHs)

⚠Warning

1. Read this instruction manual carefully before using this unit.
2. Use caution while using this unit. Injury to self, or damage to the unit or the vehicle battery or device being charged can occur if precautions are not followed.
3. Do Not allow to use by persons who do not have proper knowledge or ability to operate the device without supervision.
4. Do Not use as a toy. Keep the unit away from children to avoid accident.
5. Jump starter is for 12V vehicles only, it would be hazardous to use for other vehicles. It is forbidden to use for other machines such as aircraft, boats, etc.
6. Do Not use this unit if any cable, clamp, or cord is damaged or if the unit is overheated or swelled or leaking fluid.
7. Do Not use in place of a vehicle battery or as a vehicle battery charger.
8. Do Not use the unit to start a vehicle while charging the internal battery.
9. Use only the jumper cable provided with this unit and charge the unit only using the charger provided with this unit.
10. Do not let this unit over-discharge (do not let the battery run to empty), please charge it regularly; we suggest you had better charge it every 3 months.

11. Make sure the blue plug of the jumper cable is plugged fully into the jumper socket; otherwise, the blue plug could melt.
12. Make sure all the battery connections are clean before jump starting, and make sure the battery clamps are well connected. If the battery terminals on the vehicle are dirty or corroded, the power of the unit will be lessened.
13. Do Not jump start more than 4 times in a row. It could damage the unit by causing it to overheat. Wait at least 30 seconds between attempts. The jumper cable can become overheated and detach as a safety measure.
14. Do Not connect the two clamps together.
15. Do Not connect the jump starter's clamps to the battery reversely while pressing the "BOOST" button to avoid accident.
16. Only use it to jump start the vehicle when the battery indicator light of the unit is more than 3 bars.
17. Do Not keep the unit connected to the vehicle battery after successfully starting the engine. Remove the product from the vehicle battery within 30 seconds after jump starting the engine. If not, it could lead to damage.
18. Do not recharge this product immediately after using it to start the vehicle, please cool it down for 30 minutes before charging.
19. Do Not allow the product to become wet and Do Not immerse in water.
20. Do Not operate the product in explosive atmospheres, such as in the presence of flammable liquids, gases, or dust.

21. Do Not modify or disassemble the unit. Only a repair technician may repair this unit.
22. Do Not expose product to extreme heat or fire.
23. Do Not drop or crush the unit. If the unit has received a sharp blow or is damaged in any other way, a qualified battery technician should check it.
24. Do Not store in locations where the temperature may exceed 70ºC/ 158ºF.
25. Charge only at ambient temperature between -20~60ºC / -4~140ºF.
26. Under extreme conditions, the battery may leak. If a liquid is leaking from the unit, Do Not handle with bare hands. In case of skin contact wash with soap and water immediately. If the liquid contacts to eyes, rinse eyes with cold running water for at least 10 minutes and get medical treatment immediately.
27. The unit contains the lithium-based batteries. At end of the product life, or if the unit is leaking liquid, dispose the unit according to local regulation.

Your Warranty Inclues

- 30 Days Money Back Guaranty
  Within the first 30 days after your purchase, you can apply return for it through Amazon when you have any issue.
- 30 Days to 3 Months (9 Months)
  We will replace the defective unit due to manufacturer issues with a new one. (you will receive extra 6 months warranty if you register member on our website.)
- 3 Months to 24 Months
  Within 24 months, we will provide timely and effective online after- sales service after your purchase.

Scan to be our member for extending more 6 months warranty

Disclaimer

A. The warranty is valid upon presentation of the original receipt (Order ID by the original purchaser with the product need to be repaired or replaced.
B. The warranty does not cover damage or product failure resulting from normal wear and tear, physical abuse, improper installation, misuse, modification or repairs by unauthorized third parties.
C. We are not liable for any incidental or consequential damage that arises from incorrect use or misuse of this product.
D. All warranty claims are limited to repair or replacement of the defective product and at the sole discretion of GOOLOO.

⚠Attention

- Do Not Submerge In Water
- Do Not Disassemble
- Do Not Drop
- Avoid Extreme Temperatures
- Do Not Place Near or Into Fire

Overcharge/discharge Protection | Fuse Protection | Against-reverse Plug

CONFORMS TO UL STD.2743

Customer Service

- 24-Months Online After- Sales Service
- Lifetime Technical Service
- Feel Free to Contact Us **fiona@gooloo.com**
- For FAQ and More Information **www.gooloo.com**

@gooloofans
@+Gooloofans
@gooloo-tech
@GoolooOfficial
@mygooloo
gooloo

GOOLOO

Thank You for Choosing

Made in China

德语

GOOLOO ENRICH YOUR DRIVING LIFE

Willkommen zu Anleitung

ELITE SERIES 1200A JUMP STARTER

www.gooloo.com

Bitte lesen Sie vor dem Gebrauch diese Anleitung aufmerksam und bewahren Sie sie auf, falls Sie später etwas nachlesen möchten.



Produktstruktur



Betriebshandbuch

Anzeigelichter

Drücken Sie den Stromschalter, um die Speicherungsebene zu überprüfen.

Anzeigelichter	1 Stetig	2 Stetig	3 Stetig	4 Stetig	5 Stetig
Speicherungsebene	20%	40%	60%	80%	100%

Bei dem Aufladen der Starthilfe blinken die Anzeigelichter eins nach dem anderen. Verschiedene Anzahl der stetig leuchtenden Anzeigelichterzeigt jeweils verschiedene Speicherungsebene von das Produkt.Alle Anzeigelichter leuchten nicht mehr, wenn das Aufladen beendet oder fertig ist.

Wie lädt man die Starthilfe auf ?

1. Aufgeladen durch Hausadapter(Wandadapter)
1). Stecken Sie den Hausadapter in die Universaldose.
2). Schließen Sie das andere Ende des Hausadapters an den 15V/1A Eingangsanschluss vom das Produkt an.

2. Aufgeladen durch Auto
1). Stecken Sie den Autoadapter in die Steckdose des Zigarettenanzünders.
2). Schließen Sie das andere Ende des Autoadapters an den 15V/1A Eingangsanschluss an.

Wie startet man ein Fahrzeug mit der Starthilfe ?

Stellen Sie sicher, dass das Gerät über mehr als 60% Batterie verfügt. Wenn das Gerät mehr als zwei Monate nicht benutzt wird, sollte es zuerst aufgeladen werden.

1. Schließen Sie den Stecker des Starthilfekabels an die Starthilfe an.
2. Rote Klemme sollte mit "+", schwarze Klemme mit "-" verbunden werden.
3. Starten Sie das Fahrzeug.
4. Entfernen Sie den Stecker aus der Starthilfe.
5. Entfernen Sie die Klemmen aus der Batterie.

Wie benutzt man das Starthilfekabel ?

Stecken Sie den blauen Stecker vollständig in die Starthilfesteckdose, und stellen Sie sicher, dass die Kabelanzeige ausgeschaltet ist.

Bitte benutzen Sie das Starthilfekabel nach der Kabelanzeige:

1. Das Grüne Licht leuchtet: Die Verbindung ist korrekt und die Schaltung funktioniert, man kann den Motor einschalten, um direkt zu starten.

2. Das Rote Licht leuchtet mit Summen: Die Verbindung ist falsch, bitte starten Sie den Motor NICHT. Verbinden Sie die Klemmen wieder, rote Klemme mit "+" und schwarze Klemme mit "-", bis das Grüne Licht leuchtet.

3. Das Grüne Licht blinkt mit Summen: Die Batterie des Fahrzeugs ist niedrig, bitte drücken Sie die Taste "BOOST", warten Sie darauf, dass das grüne Licht stetig leuchtet, und starten Sie dann den Motor innerhalb von 30s.

4. Keine Lichter an, kein Summen Die Batterie des Fahrzeugs kann beschädigt werden. Bitte überprüfen Sie die Klemmenverbindung, drücken Sie die Taste "BOOST", warten Sie darauf, dass das grüne Licht stetig leuchtet, und starten Sie dann den Motor innerhalb von 30s.

Wie schaltet man das LED-Licht

Drücken Sie den LED-Schalter, um es einzuschalten. Drücken Sie leicht, um 3 Beleuchtungsmodi zu ändern: Taschenlampe, Blitzlicht, SOS Signalblitz. Schalten Sie das Licht auch mit diesem Schalter aus.

Lieferumfang

#	Teilname	Menge
1	Starthilfe	1
2	ntelligentes Starthilfekabel	1
3	USB to Type-C Kabel	1
4	Hausadapter	1
5	Autoadapter	1
6	Bewahrungstasche	1
7	Bedienungsanleitung	1

Technische Spezifikationen

Eingang	15V/1A;
Ausgang	Schnellladung (5V/2.4A,9V/2A) 5V/2.1A;12V/10A
Kapazität	66.6Wh
Startstrom	350A(3s)
Spitzenstrom	1200A
Größe	157*75*36(mm)
Gewicht	540g
Betriebstemperatur Ladetemperatur	-20℃～40℃/ 0℃～45℃
Lebensdauer	>1000 Zyklen
Volle Ladezeit	5Stunden

Achtung:

Finding	Cause	Remedies
Keine Reaktion beim Drücken des Stromschalters.	Der Niederspannungsschutz schützt das Gerät.	Stecken Sie den Adapter in den 15V/1A Eingangsanschluss, um das Gerät zu aktivieren.

Antworten

Q1: Wie startet man ein Auto mit dem Starthilfe?
A: 1). Stellen Sie sicher, dass dir Starthilfe über 60% Batterie verfügt. Wenn das Gerät mehr als zwei Monate nicht verwendet wird, sollte es zuerst aufgeladen werden.
2). Schalten Sie es ein und verbinden Sie die rote Klemme mit "+", die schwarze Klemme mit "-" Ende der Autobatterie.
3). Wenn das Grüne Licht des Intelligenten Starthilfekabels leuchtet, starten Sie Ihr Auto.
4). Wenn das Grüne Licht nicht leuchtet, schalten Sie den Autoscheinwerfer ein und warten Sie, bis das Grüne Licht leuchtet. Versuchen Sie dann, das Auto zu starten.
5). Ziehen Sie das Starthilfekabel aus der Starthilfe innerhalb von 30 Sekunden heraus und trennen Sie die Klemmen von der Autobatterie.

Q2: Wie sieht die korrekte Verbindung zwischen dem Produkt und dem Auto aus?
A: Wenn die Klemmen an die Autobatterie richtig angeschlossen sind, leuchtet das Grüne Licht des Starthilfekabels stetig. Das zeigt die richtige Verbindung.

Wenn das Licht blinkt oder das rote Licht leuchtet, ist es falsch angeschlossen.

Q3: Was soll ich machen, wenn das Produkt das Auto nicht starten kann?
A: Laden Sie die Starthilfe wieder und vollständig, versuchen Sie wieder. Stellen Sie sicher, 10 Sekunden zwischen jedem Startsversuch zu warten. Wenn es noch nicht funktioniert,
mailen Sie uns: devon@gooloo.co,
innerhalb von 12-Monatiger Garantiezeit (Teilen Sie bitte Ihre Bestell-ID auch mit, es ist notwendig).

Q4: Was soll ich machen, wenn das Produkt sich nicht aufladen lässt?
A: Laden Sie es jeweils mit einem 15V Wand-Ladegerät und Auto-Ladegerät für etwa eine ganze Nacht. Wenn es noch nicht funktioniert,
mailen Sie uns: devon@gooloo.co, innerhalb von 12-Monatiger Garantiezeit (Teilen Sie bitte Ihre Bestell-ID auch mit, es ist notwendig)

Q5: Was soll ich machen, wenn das Produkt andere Geräte nicht aufladen kann?
A: Versuchen Sie mit einem anderen Ladekabel, wenn es funktioniert, muss das Kabel defekt sein. Mailen Sie uns und wir würden Ihnen ein neues Kabel zur Verfügung stellen. Wenn es noch nicht funktioniert,
mailen Sie uns: devon@gooloo.co,
innerhalb von 12-Monatiger Garantiezeit (Teilen Sie bitte Ihre Bestell-ID auch mit, es ist notwendig).

Q6: Kann das Produkt andere Geräte aufladen, während es aufgeladen wird?
A: Ja.

Q7: Kann das Produkt beim Start eines Autos andere Geräte aufladen?
A: Nein.

Q8: Wenn es keine Reaktion beim Drücken der Schalttaste von das Produkt gibt, was soll ich machen?
A: Vielleicht ist es durch den Niederspannungsschutz verursacht. Stecken Sie den Adapter in den 15V/1A-Eingang, um ihn zu aktivieren.

Q9: Wie lange bleibt die Speicherung der Batterie?
A: 6-12 Monate, aber wir schlagen Ihnen vor, es jede 3 Monate aufzuladen.

Giftige und schädliche Stoffe

Zusammensetzung und Menge von giftiger oder schädlicher Substanz in das Produkt.

Pb	Hg	Cd	Cr(VI)	PBB	PBDE
0	0	0	0	0	0

"0" bedeutet, dass der Gehalt von Schadstoffen in allen homogenen Stoffen niedriger ist als die vorgeschriebene Grenze von MCV (der Standard 2002/95/EC/RoHs).

⚠Warnung

1. Lesen Sie die Bedienungsanleitung aufmerksam durch, bevor Sie das Gerät benutzen.
2. Starthilfe nur für 12V Fahrzeuge. Es wäre gefährlich, wenn Sie mit diesem Gerät andere nicht-12V Fahrzeuge starten. Bitte benutzen Sie es nicht für andere Maschinen wie Flugzeuge, Schiffe usw..
3. Seien Sie vorsichtig bei der Benutzung dieses Gerätes.
4. Benutzen Sie dieses Gerät nicht, wenn eine Kabelklemme oder ein Kabel beschädigt ist.
5. Benutzen Sie es nicht als Ersatz einer Fahrzeugbatterie.
6. Benutzen Sie es nicht als Akkuladegerät.
7. Ziehen Sie das Gerät sofort aus der Autobatterie aus nach dem erfolgreichen Anlassen des Autos.

8. Benutzen Sie nur das mitgelieferte Starthilfekabel.
9. Stellen Sie sicher, dass der blaue Stecker des Starthilfekabels vollständig in die Starthilfesteckdose gesteckt ist, sonst wird der blaue Stecker geschmolzen.
10. Stellen Sie sicher, dass alle Batterieanschlüsse vor dem Starten sauber sind und die Batterieklemmen gut angeschlossen sind. Wenn die Batterieklemmen am Fahrzeug verschmutzt oder korrodiert sind, wird die Leistung des Gerätes verringert.
11. Starten Sie Ihr Auto nicht mehr als 3 Mal in Folge. Das Gerät kann durch Überhitzung beschädigt werden. Das Starthilfekabel kann überhitzt und als Sicherheitsmaßnahme abgetrennt werden. Warten Sie bitte zwei Minuten zwischen den Versuchen.
12. Entfernen Sie das Produkt aus der Fahrzeugbatterie innerhalb von 30 Sekunden nach dem Start des Motors. Sonst könnte es zu Schäden führen.
13. Schließen Sie die beiden Klemmen nicht zusammen.
14. Wir schlagen Ihnen vor, den Motor zu starten, wenn es über 60% Batterie gibt.
15. Kinder oder kranke Leute sollten ohne Aufsicht das Produkt nicht benutzen.
16. Bitte benutzen Sie es nicht als Spielzeug.
17. Lassen Sie es nicht, dass das Produkt nass wird.
18. Lassen Sie das Produkt nicht im Wasser eintauchen.
19. Benutzen Sie das Produkt nicht in explosionsgefährdeten Bereichen, z.B. bei brennbaren Flüssigkeiten, Gasen oder Staub.
20. Das Produkt darf nicht modifiziert oder demontiert

werden. Nur ein Reparaturtechniker darf dieses Gerät reparieren.
21. Setzen Sie das Produkt keiner extremen Hitze oder Feuer aus.
22. Stellen Sie sicher, dass jemand in Reichweite Ihrer Stimme oder nahe genug sein sollte, um Ihnen helfen zu können, wenn Sie mit Batterien arbeiten.
23. Entfernen Sie Ihre persönlichen Metallgegenstände wie Ringe, Armbänder, Halsketten, u.a., wenn Sie die Starthilfe benutzen.
24. Lassen Sie es nicht fallen. Wenn das Produkt einen scharfen Schlag bekommt oder auf andere Weise beschädigt wird, sollte es durch einen qualifizierten Batterietechniker überprüft werden.
25. Bewahren Sie es nicht in Orten, wo die Temperatur 80℃ überschreiten kann.
26. Betriebstemperatur: -20℃ - 40℃, Ladetemperatur: 0℃ – 45℃
27. Lasen Sie es nur mit den mitgelieferten Ladegeräten auf.
28. Benutzen Sie das Gerät nicht zum Starten eines Fahrzeuges, während die interne Batterie aufgeladen wird.
29. Wenn das Produkt leckflüssig ist, sollte das Produkt recycelt werden.
30. Unter extremen Bedingungen kann die Batterie austreten. Wenn eine Flüssigkeit aus dem Gerät austritt, berühren Sie nicht mit bloßen Händen. Bei Hautkontakt soll man sofort mit Seife und Wasser

abwaschen. Wenn die Flüssigkeit mit den Augen in Berührung kommt, spülen Sie die Augen mit kaltem fließendem Wasser für mindestens 10 Minuten aus und suchen Sie sofort nach ärztlicher Behandlung.
31. Das Produkt enthält die Lithiumbatterien. Entsorgen Sie bitte das Produkt gemäß den lokalen Vorschriften am Ende der Produktlebensdauer.

Garantieinformationen

1. Wir bieten Ihnen eine begrenzte Garantie für dieses Produkt gegen jeglichen Material- und Verarbeitungsdefekt für einen Zeitraum von 12 Monaten ab dem Kaufdatum durch den Endverbraucher/ Konsument. Die Garantiebedingungen gelten wie folgt:
2. Die Garantie gilt, nur wenn der originale Käufer über das originale Beleg (vom Händler/Halter) und das zu reparierende oder zu ersetzende Produkt verfügt.
3. Die Garantie gilt nicht, wenn die Seriennummer, das Kaufdatum und das Etikett entfernt worden sind.
4. Die Garantie deckt keine Beschädigung oder Mängel ab, die durch normale Abnutzung, körperlichen Missbrauch, unsachgemäße Installation, Missbrauch, Modifikation oder Reparaturen durch nicht-autorisierte Dritte verursacht wird.
5. Wir übernehmen keine Verantwortung für Verluste oder Beschädigung, die während des Transports oder wegen höherer Gewalt entstanden sind.

6. Wir haften nicht für zufällige oder entsprechende Beschädigung, die wegen des Missbrauchsch dieses Produktes entstehen.
7. Alle Garantieansprüche sind auf Reparatur oder Ersatz des defekten Produktes und nach alleinigem Ermessen von uns beschränkt.
8. Wenn wir das Produkt reparieren oder ersetzen, wird das Produkt für die verbleibende Zeit der originalen Garantiezeit abgedeckt. Ersetzter Teil oder ersetztes Produkt gehört zum Eigentum von uns.
9. Verbrauchskomponenten wie Batterien sind nicht mit der Garantie abgedeckt.

⚠Achtung

- Tauchen Sie es nicht im Wasser
- Zerlegen Sie es nicht
- Lassen Sie es nicht fallen
- Vermeiden Sie extreme Temperaturen
- Legen Sie es nicht in die Nähe vom oder ins Feuer

Überlade-und Entladeschutz | Elektrische Absicherung | Verpolungsschutz

Kunden Service

- 12-monatige begrenzte Garantie
- Technischer Service für Lebensdauer
- Fühlen Sie sich frei uns zu kontaktieren devon@gooloo.co
- Für FAQ und mehr Informationen www.gooloo.com

@gooloofans
@+Gooloofans
@gooloo-tech
@GoolooOfficial
@mygooloo
gooloo

GOOLOO

Vielen Dank für Ihren Einkauf!

In China hergestellt

日语

GOOLOO ENRICH YOUR DRIVING LIFE

取扱説明書

カージャンプスターター

1200A

www.gooloo.com

〈お客様へ〉
・ご使用前、安全に正しくお使いいただく為に必ず「取扱・取付説明書」をよくお読みになってください。
・パッケージからだして、最初にお使いになる時は、充電がされていない状態なので満充電にしてから、使用するようにしてください。



製品ライアウト:



残量インジケータ:

インジケータ
スイッチを押して、本製品のストレージレベルを確認します。

インジケータ	1ソリッド	2ソリッド	3ソリッド	4ソリッド	5ソリッド
ストレージレベル	20%	40%	60%	80%	100%

受電している時、インジケーターは一つずつ点滅します、ソリッドインジケーターの数が異なるのは、異なる本製品のストレージレビルを示します。充電が一時停止または完了すると、全てのインジケータは消灯します。

本製品の充電方法:

1、家庭用コンセントによると充電
ホームアダプタをユニバーサルソケットに接続します。
本製品の15V 1A入力ポートをホームアダプタの他端に接続します

2、車内充電（DC12V車専用）によると充電:
シガーライターのソケットに車のアダプタを差し込みます。本製品の15V 1A入力ポートをカーアダプターの他端に接続します。

本製品の使い方:

①体のスイッチを押して、インジケーターが60%残量以上を確認します。
②ジャンプスターターケーブルのクリック（赤色）を車載バッテリー（＋）端子に接続します。
③ジャンプスターターケーブルのクリップ（黒色）を車載バッテリー（－）端子に接続する。
④端子カバーを開けてジャンプスタートケーブルのコネクター（青色）を本体（DC12V出力端子）に接続する。
⑤セルモーターを回しエンジンを始動する。
・エンジンが始動しなかった場合は、1 分以上待ってから再度セルモーターを回してください。
・3 回程度始動してもエンジンがかからない場合は、使用をちゅうしてください。



⑥エンジンが始動したら、本体からジャンプスタートケーブルを外し、30秒以内に車載バッテリーに接続されたクリップを外す。
・マイナス（－）端子側のクリップ（黒色）を外してから、
・プラス（＋）端子側のクリップ（赤色）を外してください。

＊緑色LED点灯；接続が正しくされています。エンジン始動してください。

＊赤色LED点灯＆ブザー音：接続が間違っています。②③から接続し直してください。

＊緑色LED点滅＆ブザー音：車両バッテリー電圧が低いです。BOOSTキーを押して、緑色LEDが点灯したことを確認後、30秒以内にエンジンを始動してください。

＊全てLED消灯＆ブザー音無：過熱などの異常検出による保護が働いています。時間を置いて再度に接続してください。

LEDライトの使用方法:
①スイッチボタンを 3 秒間長押しすることでLEDランプが点灯します。
②LEDランプが点灯してる状態でスイッチを 1 回押すと点滅し、