

IMPORTANT SAFETY INSTRUCTIONS

- Read all installation instructions before installing. It is important to save these instructions.
- Observe and follow all label information and instructions regarding dry, damp and wet location listings, proper lamp type and wattage, warnings of installation near combustible materials and/or insulation.
- Turn off power at circuit breaker before attempting to install or perform maintenance on the fixtures.
- Wear rubber-soled shoes and work on a sturdy wooden ladder
- The product must be installed in a manner consistent with the intended use and in compliance with the national electrical codes and local codes.
- Ground fixture to avoid potential electrical shock.
- Do not install any fixture assembly closer than 6 inches from any curtain, or similar combustible material.
- **WARNING:** Lamp may be hot, allow lamp to cool before attempting to replace lamp (Do not use bar hand to replace lamp in fixture)
- Fluorescent and HID lamps contain a small amount of mercury as indicated by the **Hg** mark. Follow disposal laws. See www.lamprecycle.org. (LED fixtures do not contain mercury).
- **WARNING: RISK OF FIRE.** Minimum of 90°C supply conductors. Consult a qualified electrician before installation.

WARNING: Fixtures can only be mounted vertically and are not to be mounted horizontally.

INSTALLATION INSTRUCTIONS

1. Turn off circuit breaker before doing any of the work.
2. Connect universal junction box plate to junction box with the screws provided.
3. Connect black wire from fixture to black (**HOT**) supply wire, white wire from fixture to white (**NEUTRAL**) supply wire and connect the ground from fixture to green (**GROUND**) supply wire. Use UL listed connectors or wire nuts to make the connections (not included).
4. Place wires inside junction box and attach fixture with the screws provided to the universal plate.
5. Once all fixtures have been installed, power at the breaker can be restored.

