

RTX 4022 DECT Repeater



Product Name: RTX 4022 DECT Repeater

Manufacturer: -

Model Number: RTX4022

Please Note: This product has been discontinued. Please see the Snom Wireless VoIP Phones for an alternative.

RTX 4022 DECT Repeater

A RTX 4022 DECT Repeater can be deployed when a need to extend the range of a DECT telephone arises. The repeater can also be utilized wherever there is a need to increase limited coverage or improve reception in remote areas.

RTX 4022 Key Features

- RTX is the world leading supplier of repeaters and an obvious choice as your future supplier.

- Technically superior at the best price on the market.

- Double the range of a DECT base station – or achieve up to 2.4 km range with the Professional edition.

- Possibility to register multiple repeaters.

- Superior audio quality – both narrow band and wide band.

RTX 4022 - Technical Specifications

GENERAL FEATURES

- Worldwide DECT support

- Extending the DECT coverage

- Supports automatic handover of calls between cells

- Handling of 2 active calls simultaneously

- Up to 6 repeaters per base station

- Automatic registration method

- Environmental conditions: temp range, from -10°C to +50°C

DESIGN/SIZE

- Indoor cabinet

- Manual mounting kit

- Easily mounted on walls

- Size: 120(W) x 35(D) x 135(H)mm

POWER SUPPLY

- 230 VAC and 110 VAC versions available

FREQUENCY/COVERAGE

- Frequency bands coverage: EU/AU/NZ, US/CA, LATAM, TW

- Up to 50m indoor and 300m outdoor

- Receiver sensitivity: -92dBm

- 2 internal omni-directional antennas

STANDARDS/APPROVALS

- The DECT repeater is designed in accordance with the Digital Enhanced Cordless Telecommunications (DECT) standard

RTX 4022 DECT Repeater

The DECT repeater is compliant with: - TBR6, TBR22 (Generic Access Profile, GAP) - ETS 300 700 - ETSI Wireless Relay Station Specification

LED INDICATOR

Radio link quality indication

Price: £84.75
