

CINELIFE+™ SERIES

From boutique cinemas to premium large format auditoriums

Advance cinema storytelling to the next level by bringing the biggest and brightest visual content to life













Key features:

- > Quick and easy setup The autoconfigure feature automatically adjusts settings for optimal playback when you connect different sources
- > Advanced format cinema HFR support for 2K and 4K 120fps, native 3D playback
- > Remote UI Use a web browser to access the interface anywhere
- > Hyperrealism New system architecture displays content without motion blur or artifacts
- > Ultra-fast processing HDMI 2.0 and 4x 12GB SDI inputs for 1.06G pixels per second

- > Electronic Color Convergence -Provides perfect alignment throughout the entire image
- > Long-lasting light source For more than 50,000 hours of optimal performance

Real laser 🖸

Advanced laser light source for accurate reproduction of DCI content





Adds ultra high frame rate providing each eye 2K 120fps, 4K 120fps, 4K 3D 60fps

DIGITAL CINEMA CONFIGURATOR

Help find the right lens for your projector on our website





CP4415-RGB





Small-screen auditoriums | Boutique cinema Post production | Screening rooms Operational efficiency: 9.4 lumens per watt

Specifications: Up to 6000:1 contrast | >95% of REC 2020 color gamut |

Up to 15,000 lumens

Power consumption: 1430W, max DCI brightness,

@25°C 4880 BTU/hr

Dimensions: 37.2 x 28.0 x 20.7" (944 x 711 x 525mm)

Weight: 285lbs max (130kg)



CP4420-RGB







Medium-screen auditoriums | Event cinema Post production | Screening rooms

Operational efficiency: 10.6 lumens per watt

Specifications: Up to 6000:1 contrast | >95% of REC 2020 color gamut |

Up to 20,000 lumens

Power consumption: 1890W, max DCI brightness,

@25°C 6448 BTU/hr

Dimensions: 37.2 x 28.0 x 20.7" (944 x 711 x 525mm)

Weight: 285lbs max (130kg)



CP4430-RGB







Large-screen auditoriums | Post production | Screening rooms

Operational efficiency: 12.3 lumens per watt

Specifications: Up to 6000:1 contrast | >95% of REC 2020 color gamut |

Up to 28,000 lumens

Power consumption: 2295W, max DCI brightness,

@25°C 7830 BTU/hr

Dimensions: $37.2 \times 28.0 \times 20.7$ " (944 x 711 x 525mm)

Weight: 285lbs max (130kg)



CP4440-RGB









Premium large format auditoriums | Advanced format cinema | Event cinema Operational efficiency: 8.9 lumens per watt

Specifications: Up to 6000:1 contrast | >95% of REC 2020 color gamut | Up to 45,000 lumens with HB lens,

35,000 lumens with UHC lens

Power consumption: 5300W including chiller, max DCI

brightness, @25°C 18,085 BTU/hr

Dimensions •61.1x28.0x22.0" (1551.1x710.6x559.6mm)

Weight
• 385lbs (175kg)

Chiller • 26.38x18.5x35.0"

(670x470x890mm); 202lbs (92kg)



CP4450-RGB









Premium large format auditoriums | Advanced format cinema | Event cinema Operational efficiency: 10.5 lumens per watt

Specifications: Up to 6000:1 contrast | >95% of REC 2020 color gamut | Up to 55,000 lumens with HB lens, 42,000 lumens with UHC lens

Power consumption: 5450W including chiller, max

DCI brightness, @25°C 18,600 BTU/hr

Dimensions •61.1x28.0x22.0" (1551.1x710.6x559.6mm)

Weight Chiller • 26.38x18.5x35.0"
• 385lbs (175kg) (670x470x890mm); 202lbs (92kg)

Corporate offices

Christie Digital Systems USA, Inc.

ph: 714 236 8610 Christie Digital Systems Canada Inc. Kitchener ph: 519 744 8005

Worldwide offices

Australia ph: +61 (0) 7 3624 4888 Brazil ph: +55 (11) 2548 4753 China (Beijing) ph: +86 10 6561 0240 China (Shanghai) ph: +86 21 6030 0500

Colombia ph: +57 (318) 477-3179

India ph: +91 (080) 6708 9999 Mexico ph: +52 55 4744 1790 Singapore ph: +65 6877 8790

Germany ph: +49 221 99 512-0

South Korea ph: +82 2 702 1601 Spain ph: +34 91 633 9990 United Arab Emirates

ph: +971 (0) 4 503 6800 United Kingdom ph: +44 (0) 118 977 8000 United States (Arizona) ph: 602 943 5700

Independent sales consultant offices

ph: +39 (0) 2 9902 1161 Russia ph: +7 (495) 930 8961

For the most current specification information, please visit christiedigital.com

Copyright 2021 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD2034_Christie CineLife+ Series_Line Card_June-21_EN





