



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK



Video Cameras:



SES is a proud distributor of Hitachi Cable America
Complete offering of high quality Category and Fiber Optic Cable



Ganz GenStar Outdoor IP Cameras

CHU ZN8B4NVF56
Outdoor IR Bullet w/ 2.8-12mm Varifocal lens, WDR, PoE, 12VDC, 1080P

CHU ZN8F7NTFN10L
6MP Outdoor Fisheye Dome w/ 6 IR LEDs, WDR, PoE, 12VDC



CHU ZN8M4NTFN4L
Outdoor Mini IR dome w/ 3.6mm fixed lens, WDR, PoE, 12VDC, 1080P

PixelPro Series H.264 IP Cameras: Optimized for HD
1080p, 720p, and VGA models available - 1 / 2.5" Progressive Scan CMOS - True Day/Night performance - Triple Power 12VDC/24VAC/PoE - Dual Streaming Video - Micro SDHC Card Slot - External Alarm I/O - Bi-directional audio support - ONVIF Compliant



PixelPro Dome Cameras
Built-in 3.3-12mm Varifocal Lens-IP66 Rated

CHU ZNDT2MTP
H.264 HD Optimized Outdoor IP Dome Camera (HD 1080p)

- ProSet system lets you zoom and focus directly from your PC
- 1/2.5" Progressive Scan CMOS
- Built-in 3.3-12mm Varifocal Lens
- Dual Streaming Video
- True Day/Night Performance
- Triple Power (12VDC/24VAC, PoE)
- MicroSDHC Card Slot
- Service Monitor Output
- External Alarm I/O
- Bi-directional Audio Support
- ONVIF Compliant
- Plug and Play with PixelMaster Embedded NVR with no configuration required



CHU ZNDT2MTP
H.264 Outdoor IP Dome (1080p) w/ IR

- 1080p Model (720p Model also available)
- ProSet system lets you zoom and focus directly from your PC
- 1/2.8" Progressive Scan CMOS
- Built-in 3-9mm Varifocal Lens
- 18 IR LEDs
- Improved low-light performance
- Improved picture quality
- Dual Streaming Video
- True Day/Night Performance
- DPC (Defective Picture Correction)
- Triple Power (12VDC/24VAC, PoE)
- Service Monitor Output
- External Alarm I/O



- Bi-directional Audio Support
- IP66 for outdoor use
- ONVIF Compliant
- Plug and Play with PixelMaster Embedded NVR with no configuration required

CHU ZND2MTP

H.264 Indoor IP Dome (1080p)

- 1080p (720p and VGA Models also available)
- ProSet system lets you zoom and focus directly from your PC
- 1/2.8" Progressive Scan CMOS
- Built-in 3-9mm Varifocal Lens
- Better low-light performance
- Improved picture quality
- Dual Streaming Video
- True Day/Night Performance
- DPC (Defective Picture Correction)
- Triple Power (12VDC/24VAC, PoE)
- Service Monitor Output
- External Alarm I/O
- Bi-directional Audio Support
- ONVIF Compliant

CHU ZND2MTPIR

H.264 Indoor IP Dome (1080p) w/ IR

- 1080p Model (720p Model also available)
- ProSet system lets you zoom and focus directly from your PC
- 1/2.8" Progressive Scan CMOS
- Built-in 3-9mm Varifocal Lens
- 18 IR LEDs
- Better low-light performance
- Improved picture quality
- Dual Streaming Video
- True Day/Night Performance
- DPC (Defective Picture Correction)
- Triple Power (12VDC/24VAC, PoE)
- Service Monitor Output
- External Alarm I/O
- Bi-directional Audio Support
- ONVIF Compliant
- Outdoor & Bullet models also available

CHU ZNMD1243MIR

1080p Indoor IP Mini IR Dome w/ 4.3mm Lens

- 1080p HD Resolution
- 1/2.8" CMOS Sensor
- H.264 & MJPEG
- 4.3mm Fixed Lens
- True Day/Night
- Privacy Masking
- PoE Power supply (802.3af Class 2)
- Motion Triggered Alarm
- ONVIF Profile S Compliant
- Dual Streaming Video
- Service Monitor Output
- DPC (Defective Pixel Correction)
- Plug and Play with PixelMaster Embedded NVR with no configuration required

CHU ZNMD221M

PixelPro H.264 HD Optimized Outdoor IP Mini Dome (1080p)

- 1/2.8" CMOS Sensor
- H.264 & MJPEG
- 2.1mm Fixed Lens
- PoE

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.



Smart Homes open up a world of opportunity.

It starts with a proven partner like Interlogix.

By 2020, the Smart Home industry is expected to be worth \$58 billion.* With Interlogix as your partner, you'll have the proven products and support you need to succeed in this evolving security market. **Our UltraSync™ SmartHome system** gives your customers the enhanced security and lifestyle connectivity they want and provides your business with the long-term growth opportunity it needs.

Visit interlogix.com/ultrasync-smarthome to learn how UltraSync SmartHome technology can help grow your business.



*MarketsandMarkets, Smart Homes Market, Global Forecast to 2020



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK



CHU ZNMB243M

- CHU ZNMD243M**
Ganz PixelPro H.264 1080p HD Indoor IP Mini Dome w/ 4.3mm Lens
- 1080p HD Resolution
 - 1/2.8" CMOS Sensor
 - H.264 & MJPEG
 - 4.3mm Fixed Lens
 - PoE Power supply. 802.3af Class 2
 - Motion Triggered Alarm
 - Dual Streaming Video
 - Service Monitor Output
 - Digital Day/Night
 - DPC (Defective Pixel Correction)
 - IP66 rated for all weather conditions



AME ADCI800FB521

- Pixel-Pro Bullet Camera**
CHU ZNB2MTP
H.264 HD Optimized Outdoor IP Bullet Camera (HD 1080p)
- ProSet system lets you zoom and focus directly from your PC
 - P-Iris feature (Precise iris)
 - 1/2.5" Progressive Scan CMOS, 3.3-12mm varifocal lens
 - Dual Streaming Video
 - True Day/Night Performance
 - 42 IR LEDs provide over 100' illumination range
 - Triple power (12VDC/24VAC, PoE)
 - MicroSDHC card slot
 - External alarm I/O
 - ONVIF Compliant
 - Setup and recording software included
 - IP66 rated for all weather performance
 - Mounting bracket and sunshield included
 - Plug and Play with PixelMaster Embedded NVR with no configuration required



VIV CC8130

- VIVOTEK**
VIV CC8130
1MP Panoramic View Compact Size Compact Cube Network Camera
- 1-megapixel CMOS Sensor
 - 180° Horizontal Panoramic View
 - Compact, Elegant Design
 - Real-time H.264 and MJPEG compression (Dual Codec)
 - 30 fps @ 1280x800
 - Built-in IEEE 802.3af Compliant PoE
 - Flat Mount/ Tilt Mount Available



VIV CC8370HV

- CHU ZNMB243M**
H.264 Outdoor IP Bullet Mini Camera (1080p)
- 1080p HD Resolution
 - 4.3mm Lens
 - True Day/Night
 - Privacy Masking
 - PoE Power supply (802.3af Class 2)
 - Motion Triggered Alarm
 - ONVIF Profile S Compliant
 - Dual Streaming Video
 - Service Monitor Output
 - DPC (Defective Pixel Correction)
 - Plug and Play with PixelMaster Embedded NVR with no configuration required
 - IP66 rated for all weather conditions
 - 18 IR LEDs provide over 26' illumination
 - Sunshield and mounting bracket included



VIV FE8174



- Illustra-Flex IP Cameras**
 Illustra Flex cameras provide affordable high quality megapixel video at a fraction of the cost. True Day/Night and 3D Dynamic Noise Reduction technology improves video quality and reduces storage requirements in low light conditions. The Wide Dynamic Range feature increases the image quality of objects dimly lit by bright backgrounds, such as a person entering an outside door. The cameras offer indoor and outdoor enclosure options and varifocal lenses on most models to customize the field-of-view.



VIV FD8365EHV



GST GSIP715BC

The 1MP wireless Cube reduces cabling and installation costs for fast, flexible deployments.

- AME ADCI600FD021**
 Illustra Flex 1MP Indoor/Outdoor Dome, Vandal Resistant, Varifocal 3-9mm, IR
- AME ADCI600FD111**
 Illustra Flex 1MP Indoor Dome, Varifocal 3-9mm
- AME ADCI800FB521**
 Illustra Flex 3MP Bullet, Varifocal 9-22mm
- AME ADCI800FD021**
 Illustra Flex 3MP Indoor/Outdoor Dome, Vandal Resistant, Varifocal 3-9mm, IR
- AME ADCI800FD111**
 Illustra Flex 3MP Indoor Dome, Varifocal 3-9mm
- AME ADCI600M111**
 Compact Indoor, 720p 2.83 mm fixed, vandal resistant, PoE, white, clear
- AME ADCI610M111**
 Compact Indoor, 1080p, 2.8 mm fixed, vandal resistant, PoE, white, clear
- AME IES01D10CWIY**
 Illustra Essentials 1MP Dome, 2.8-12mm, outdoor, vandal, clear, white, TDN w/IR, WDR.



- VIV CC8130**
1MP Panoramic View Compact Size Compact Cube Network Camera
- 1-megapixel CMOS Sensor
 - 180° Horizontal Panoramic View
 - Compact, Elegant Design
 - Real-time H.264 and MJPEG compression (Dual Codec)
 - 30 fps @ 1280x800
 - Built-in IEEE 802.3af Compliant PoE
 - Flat Mount/ Tilt Mount Available

- VIV CC8370HV**
3MP Outdoor Anti-Ligature Fisheye Network Camera, Compact Vandal-proof, 1.6MM Lens
- 3-Megapixel CMOS Sensor
 - 30fps @ 2048x1536
 - Anti-Ligature Design
 - Weather-proof IP66-rated and Vandal-proof IK10-rated Housing
 - 180° Horizontal Panoramic View
 - ±25° Tilt Lens
 - WDR Pro (100dB) to Provide Extreme Visibility in High Light Contrast Scenes
 - Video Rotation
 - Built-in Microphone
 - SNV (Supreme Night Visibility)
 - 3D Noise Reduction for Low-light Conditions
 - Real-time H.264 and MJPEG Compression (Dual Codec)
 - Built-in IEEE 802.3af Compliant PoE
 - Built-in MicroSD/SDHC/SDXC card slot

- NEW VIV FD836BHVF2**
Fixed Dome Network Camera
- 2-Megapixel CMOS Sensor
 - 30 fps @ 1920x1080
 - 2.8 ~ 12 mm, Vari-focal, Remote Focus, P-iris Lens (FD836B-HTV/EHTV)
 - Built-in IR Illuminators, Effective up to 30 Meters

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

- WDR for Unparalleled Visibility in Extremely Bright and Dark Environments
- SNV (Supreme Night Visibility) for Low-light Conditions
- 3D Noise Reduction
- Two-way Audio
- Video Rotation for Corridor View
- Weather-proof IP66-rated and Vandal-proof IK10-rated Housing
- Support Installation with AM-713 Outdoor Conduit Box
- Extreme Weather Support with PoE (FD836B-EHVF2/EHTV)
- VIVOTEK VCA (Video Content Analysis) Support

NEW VIV FD8167A

Fixed Dome Network Camera

- 2-Megapixel CMOS Sensor
- 30 fps @ 1920x1080
- Real-time H.264, MJPEG Compression (Dual Codec)
- Removable IR-cut Filter for Day & Night Function
- Built-in IR Illuminators, Effective up to 20 Meters
- Built-in 802.3af Compliant PoE
- Built-in MicroSD/SDHC/SDXC Card Slot for On-board Storage
- Supports ONVIF Standard to Simplify Integration and Enhance Interoperability
- SNV (Supreme Night Visibility)
- Smart Stream II to Optimize Bandwidth Efficiency

NEW VIV FD8367AV

Fixed Dome Network Camera

- 2-Megapixel CMOS Sensor
- 30 fps @ 1920x1080
- Real-time H.264, MJPEG Compression (Dual Codec)
- Removable IR-cut Filter for Day & Night Function
- Built-in IR Illuminators, Effective up to 30 Meters
- Built-in 802.3af Compliant PoE
- Built-in MicroSD/SDHC/SDXC Card Slot for On-board Storage
- Supports ONVIF Standard to Simplify Integration and Enhance Interoperability
- Weather-proof IP66-rated and Vandal-proof IK10-rated Housing
- Smart Stream II to Optimize Bandwidth Efficiency

VIV FE8174

5MP 360° Surround View Pixel Calculator Local Dewarp Fisheye Fixed Dome Network Camera

- 5-Megapixel CMOS Sensor
- 30 fps @ 1080p Full HD
- 1.5 mm Fisheye Lens for 180° Panoramic View and 360° Surround View
- Removable IR-cut Filter for Day & Night Function
- Real-time H.264, MPEG-4, and MJPEG Compression (Triple Codec)
- WDR Enhancement for Unparalleled Visibility in Extremely Bright or Dark Environments
- ePTZ for Data Efficiency
- Built-in 802.3af Compliant PoE

- Built-in MicroSD/SDHC/SDXC Card Slot for On-board Storage
- Pixel Calculator for Image Clarity Measurement
- Support Local or Client Side Dewarping

VIV FD8169

2MP Indoor IP Dome Camera

- 2-Megapixel CMOS Sensor
- 30 fps @ 1920x1080
- Real-time H.264, MJPEG Compression (Dual Codec)
- Removable IR-cut Filter for Day & Night Function
- Built-in IR Illuminators, Effective up to 15 Meters
- Built-in 802.3af Compliant PoE
- Built-in MicroSD/SDHC/SDXC Card Slot for On-board Storage
- Supports ONVIF Standard to Simplify Integration and Enhance Interoperability
- 3D Noise Reduction
- Smart IR Technology to Avoid Overexposure
- WDR Enhancement for Unparalleled Visibility in Extremely Bright and Dark Environments

VIV FD8365EHV

2MP 30 FPS H264 WDR PRO IP6 RF1.3-F2.5 VF

- 2-Megapixel CMOS Sensor, 30 fps @ 1920x1080
- Motorized, P-iris Lens & DC-iris
- Removable IR-cut Filter for Day & Night Function
- Built-in IR Illuminators, Effective up to 20 Meters, Smart IR Technology to Avoid Overexposure
- 3D Noise Reduction for Low-light Conditions
- WDR Pro (100dB) to Provide Improved Visibility in Extremely Bright or Dark Environments
- Smart Focus System for Remote and Precise Focus Adjustment
- Two-way Audio
- Weather-proof IP66-rated and Vandal-proof IK10-rated Housing
- Video Rotation for Corridor Format
- EIS (Electronic Image Stabilization) to Control Image Stability

VIV FE8174V

5 MP Outdoor Fisheye Vandal Proof Camera

- 5-Megapixel CMOS Sensor
- 30 fps @ 1080p Full HD
- 1.5 mm Fisheye Lens for 180° Panoramic View and 360° Surround View
- Removable IR-cut Filter for Day & Night Function
- EN50155 Compliance for Professional Mobile Surveillance
- Real-time H.264, MPEG-4, and MJPEG Compression (Triple Codec)
- WDR Enhancement for Unparalleled Visibility in Extremely Bright or Dark Environments
- Vandal-proof IK10-rated and Weather-proof IP66-rated Housing
- ePTZ for Data Efficiency
- Built-in 802.3af Compliant PoE
- Built-in MicroSD/SDHC/SDXC Card Slot for

- On-board Storage
- Pixel Calculator for Image Clarity Measurement
- Support Local or Client Side Dewarping
- VCA Supported

NEW VIV IB8367A

Bullet Network Camera

- 2-Megapixel CMOS Sensor
- 30 fps @ 1920x1080
- Real-time H.264, MJPEG Compression (Dual Codec)
- Removable IR-cut Filter for Day & Night Function
- Built-in IR Illuminators, Effective up to 30 Meters
- Built-in 802.3af Compliant PoE
- Built-in MicroSD/SDHC/SDXC Card Slot for On-board Storage
- Supports ONVIF Standard to Simplify Integration and Enhance Interoperability
- Weather-proof IP66-rated and Vandal-proof IK10-rated Metal Housing

VIV IP8365EH

2MP Bullet Network Camera, 30 FPS, H264, MJPEG, WDR PRO, F1.2-F2.3VF

- 2-Megapixel CMOS Sensor
- 30 fps @ 1920x1080
- Motorized P-iris Lens
- Removable IR-cut Filter for Day & Night Function
- Built-in IR Illuminators, Effective up to 30 Meters
- Smart IR Technology to Avoid Overexposure
- 3D Noise Reduction for Low-light Conditions
- WDR Pro (100dB) to Provide Improved Visibility in Extremely Bright or Dark Environments
- Smart Focus System for Remote and Precise Focus Adjustment
- Two-way Audio
- Weather-proof IP67-rated Housing
- Video Rotation for Corridor Format
- EIS (Electronic Image Stabilization) to Control Image Stability



2.3MP IP Cameras with Built-in PoE now available in 2.8-12MM Varifocal Bullet and Ball Dome

- 2.3 MP VariFocal allows seem-less plug and play with GSI PoE NVR's
- 2.8-12MM MP Vari-focal Lens
- 36 IR LED's (up to 60' Illumination)
- IP66 Weather Rating Bullet Camera, IP66 Weather Rating and Vandal Resistant Ball Dome
- True Day/Night ICR
- 12VDC or PoE Support
- ONVIF and PSIA Conformant

GST GSIP714BD

Ball Dome

GST GSIP715BC

Bullet Camera



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK




GST GSIP804BD




GST GSIP814BD




GST GSIP815BC




FLR N233VE




FLR N237VE




FLR T4325BN




FLR T4325BN

IR LED 4MPx IP Cameras, 3.6mm Fixed Megapixel Lens D/N Color

- 1/3" OV HDR Megapixel CMOS Sensor
- Plug and Play with GSI PoE NVRs 8/16/24
- 4 Megapixel 2592 x 1520 Resolution at 30FPS
- Versatile 3-Axis Camera Mount
- 3.6mm MP Fixed Lens
- 24 IR LEDs (Up to 50ft Illumination)
- Aesthetically Pleasing Housing for Indoor/Outdoor Use
- IP66 Weather Rating
- Vandal Resistant Dome or Bullet
- True Day/Night ICR
- H264 / H265 Compression
- PoE or 12VDC Input
- Web interface and Mobile App Support
- Solid and compact Aluminum construction

GST GSIP804BD Vandal Ball Dome
GST GSIP805BC Bullet Camera

NEW GST GSIP814BD Vandal Ball Dome 2.8-12mm V/F Megapixel Lens 4 MP Day/Night Color IP Camera

- 1/3" OV HDR Megapixel CMOS Sensor
- Solid and compact Aluminum construction
- Plug and Play with GSI PoE NVRs 8/16/24
- 4 Megapixel 2592 x 1520 Resolution at 20FPS
- Versatile 3-Axis Camera Mount
- 2.8-12 mm V/F Megapixel Lens
- 30 IR LEDs (Up to 80ft Illumination)
- Aesthetically Pleasing Housing for Indoor/Outdoor Use
- ONVIF and PSIA Conformant

NEW GST GSIP815BC Vandal Bullet 2.8-12mm V/F Megapixel Lens 4 MP Day/Night Color IP Camera

- 1/3" OV HDR Megapixel CMOS Sensor
- Plug and Play with GSI POE NVRs 8/16/24
- 4 Megapixel 2592 x 1520 Resolution at 20FPS
- Versatile 3-Axis Camera Mount
- 2.8-12 mm V/F Megapixel Lens
- 30 IR LEDs (Up to 80ft Illumination)
- Aesthetically Pleasing Housing for Indoor/Outdoor Use

IP Weatherproof Cameras

GST GSIP705BC
 IP Weatherproof Bullet Camera, 3.6MM Lens



FLIR IP: Dome Cameras

Built rugged, the FLIR Dome IP Camera offers HD picture quality in real time with outstanding night vision capabilities. Installation is made easy with PoE operation included.

Dome Cameras

FLR N233VE
 Mini Vandal Dome, 3MP, 3MP@20fps, 2.8mm, IR LED's, PoE / 12V, ONVIF, Micro SD, dual streaming

FLR N237VE
 Motorized Varifocal Vandal Dome, 3MP, 3MP@20fps, 2.8-12mm, IR LED's, PoE / 12V, ONVIF, dual streaming

NEW FLR PE133E

- 3MP Fixed HD IP Eyeball Camera
- PoE (Class 3) support for simplified cabling
 - 12V DC / PoE (802.3af) operation
 - Tamper detection
 - ONVIF Profile S conformance
 - Rugged construction for all weather conditions
 - Cold climate capability (-22°F / -30°C)
 - IP66 weatherproof rating
 - Simple wall / ceiling installation
 - Remote access via iOS, Android™, PC & Mac when connected to a FLIR NVR
 - Centralized viewing and control of up to 64 cameras on each screen with PC & Mac
 - Access live or recorded video at any time on your iPad®, iPhone® or Android™ device
 - Advanced mobile app features including remote playback, push notifications for motion/alarm, E-map, manual record/snapshot to device

NEW FLR PE133F

- 4MP Fixed HD IP Cameras
- Outstanding image detail, both day and night
 - PB133F/P – 4MP HD @ 20fps, 1/3" CMOS, 2.8mm lens, 90ft (27m) IR range
 - PoE (Class 3) support for simplified cabling
 - ONVIF Profile S conformance
 - 12V DC / PoE (802.3af) operation
 - Simple wall / ceiling installation
 - Rugged construction with advanced video correction features
 - True Wide Dynamic Range (up to 100dB @ 3MP) provides more accurate detail in high contrast scenes
 - Intelligent compression coupled with Region of Interest (ROI) optimizes video performance based on available bandwidth
 - IP66 weatherproof rating with cold climate capability (-22°F / -30°C)
 - Remote access via iOS, Android™, PC & Mac when connected to a FLIR NVR
 - Centralized viewing and control of up to 64 cameras on each screen with PC & Mac
 - Access live or recorded video at any time on your iPad®, iPhone® or Android™ device
 - Advanced mobile app features including remote playback, push notifications for motion/alarm, E-map, manual record/snapshot to device

FLIR Thermal Security Cameras: The next level of security.

FLIR Thermal Security Cameras can see as well at night as they can during the day. Cameras dependent on visible light are useless at night or in poor visibility without supplementary illumination from lights or lasers.

FLR T4325BN
 Thermal Mini Bullet 25°, Tri-Mode IP/MPX/Analog

FLR T4350BN
 Thermal Mini Bullet 50°, Tri-Mode IP/MPX/Analog

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.



THE NEXT LEVEL OF PHYSICAL & VIDEO SECURITY

Gateway Unified Solutions.

The NLSS Gateway is a completely unique IP security solution. It combines video management, access control, video analytics and more onto a single networked platform that can be accessed through the Web browser. Data from these subsystems is automatically correlated into a sophisticated event management system, providing users with a comprehensive view of security operations. Video, access, intrusion, system health events and more can be linked to specific actions or automatically send email notifications. Because there is no software to install, the NLSS Gateway is a true browser-based solution that can be accessed from any Web-enabled device.

The NLSS Gateway is available in a variety of different models - NLSS Gateway 500-3, NLSS Gateway 3000 and NLSS Gateway 6100. The NLSS Gateways are fully integrated with ATV IP cameras for seamless API camera programming.

To learn more, contact us today at **888.288.7644** or visit www.atvideo.com/support-center/request-info.



ADVANCED
TECHNOLOGY
VIDEO

Security without compromise



[www.atvideo.com/
support-center/request-info](http://www.atvideo.com/support-center/request-info)



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK

speco technologies



CSI O2IB3M

speco technologies



CSI O2ID4M

speco technologies



CSI O2IMD1

speco technologies



CSI O2B16

interlogix
United Technologies



ILX TVB3105

interlogix
United Technologies



ILX TVD3106

interlogix
United Technologies



ILX TVW3107



CSI O2FB3M
Flexible Intensifier® Technology 1080p Indoor/Outdoor IP Bullet Camera, 2.8-12mm lens, Dark Grey Housing

- Flexible Intensifier® Technology fits any lighting application – color in low light, monochrome with IR in almost complete darkness, and monochrome without IR in low light
- Adaptive IR LEDs
- IR Range: 98' (depending on scene reflection)
- Motorized lens with auto focus
- Supports up to Full HD resolution @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- Wide dynamic range (WDR) operation
- Supports H.264 and MJPEG codecs
- 2-way audio communication
- Micro SD card slot (card not included)
- Sensor input and relay output
- Built-in heater and anti-fog glass reduces condensation under any weather condition
- IP66 compliant
- Conformant with ONVIF profile S
- 2 year warranty

CSI O2FD4M
Flexible Intensifier® Technology 1080p Indoor/Outdoor IP Dome Camera, 2.8-12mm lens, Dark Grey Housing

- Flexible Intensifier® Technology fits any lighting application – color in low light, monochrome with IR in almost complete darkness, and monochrome without IR in low light
- Adaptive IR LEDs
- IR Range: 50' (depending on scene reflection)
- Motorized lens with auto focus
- Supports up to Full HD resolution @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- Wide dynamic range (WDR) operation
- Supports H.264 and MJPEG codecs
- 2-way audio communication
- Micro SD card slot (card not included)
- Sensor input and relay output
- Built-in heater and anti-fog glass reduces condensation under any weather condition
- IP66 compliant
- Conformant with ONVIF profile S
- 2 year warranty

CSI O2IB3M
Intensifier IP Full HD 2MP Bullet, 2.8-11mm motorized lens, grey housing

CSI O2ID4M
Intensifier IP Full HD 2MP Vandal Dome, 2.8-11mm motorized lens, grey housing

CSI O2IMD1
Intensifier IP Full HD 2MP Outdoor Miniature dome, 2.9mm Lens, Grey Housing

NEW CSI O2B6
Full HD 1080p Indoor/Outdoor Bullet IP Camera, 3.6mm fixed lens, Dark Grey Housing

- 3.6mm fixed lens
- Supports up to Full HD 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- Smart IR function provides vivid image with no saturation in darkness

- True Day/Night operation (IR cut filter)
- IR Range: 50' (depending on scene reflection)
- Supports H.264 and MJPEG codecs
- Micro SD slot
- 2-way audio communication
- Sensor input and relay output
- Built-in heater reduces condensation under any weather condition
- IP66 compliant
- Conformant with ONVIF Profile S
- 2 year warranty

NEW CSI O2C1
1080p H.265 Wi-Fi IP Camera, 2.9mm fixed lens, Black Housing

- Dual-band Wi-Fi camera (2T2R 802.11n)
- Perfect for residential applications
- Easy setup through mobile app – no need to log into camera through a web viewer to connect it to an access point
- Flexible recording options – record to SecureGuard® VMS, NS/HS/HT recorders, edge recording on micro SD cards, and local PC recording through web browser
- Supports up to full HD 1080p @ 30fps
- Triple-codec operation – H.265/H.264/MJPEG
- H.265 compression saves approximately 40% in storage and bandwidth compared to H.264
- Built-in speaker and microphone for 2-way audio communication

NEW CSI O2CP2
1080p H.265 Wi-Fi Pan/Tilt IP Camera, 3.6mm fixed lens, White Housing

- Dual-band Wi-Fi camera (2T2R 802.11n)
- Remote pan & tilt control
- Perfect for residential applications
- Easy setup through mobile app – no need to log into camera through a web viewer to connect it to an access point
- Flexible recording options – record to SecureGuard® VMS, NS/HS/HT recorders, edge recording on micro SD cards, and local PC recording through web browser
- Supports up to full HD 1080p @ 30fps
- Triple-codec operation – H.265/H.264/MJPEG
- H.265 compression saves approximately 40% in storage and bandwidth compared to H.264
- Built-in speaker and microphone for 2-way audio communication

NEW CSI O2D5M
Full HD 1080p 2MP Indoor/Outdoor Dome IP Camera, 3.3-10mm Lens, Dark Grey Housing

- 3.3-10mm auto iris varifocal motorized lens
- Supports up to Full HD 1080p @ 30fps
- Motorized lens with auto focus
- Built-in standard PoE (IEEE 802.3af)
- Smart IR function provides vivid image with no saturation in darkness
- True Day/Night operation (IR cut filter)
- IR Range: 65' (depending on scene reflection)
- Supports H.264 and MJPEG codecs
- 2-way audio communication
- Micro SD card slot (card not included)
- Sensor input and relay output
- Built-in heater reduces condensation under any weather condition
- IP66 compliant
- Conformant with ONVIF profile S
- 2 year warranty

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

NEW CSI O2VLB5**2MP 1080p Indoor/Outdoor Bullet IP Camera, 3.6mm Fixed Lens, White Housing**

- Supports up to Full HD 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- Built-in IR LEDs
- IR Range: 50' (depending on scene reflection)
- Supports H.264 and MJPEG codecs
- IP66 compliant
- Conformant with ONVIF Profile S
- 2 year warranty

NEW CSI O2VLD5**2MP 1080p Indoor/Outdoor Dome IP Camera, 3.6mm Fixed Lens White Housing**

- Supports up to Full HD 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- Built-in IR LEDs
- IR Range: 50' (depending on scene reflection)
- Supports H.264 and MJPEG codecs
- IP66 compliant
- Conformant with ONVIF Profile S
- 2 year warranty

NEW CSI O5D4M**5MP H.265 Indoor/Outdoor Dome IP Camera, 3.6-10mm motorized lens, Dark Grey Housing**

- Supports up to 5MP resolution @ 30fps
- Triple-codec operation – H.265/H.264/MJPEG
- H.265 compression saves approximately 40% in storage and bandwidth compared to H.264
- Adaptive IR LEDs
- IR Range: 50' (depending on scene reflection)
- Chameleon Cover™: snaps on and can be painted to match any décor!*
- Motorized lens with auto focus
- Built-in standard PoE (IEEE 802.3af)
- Wide dynamic range (WDR) operation
- 2-way audio communication
- Micro SD card slot (card not included)
- Sensor input and relay output
- IP66 compliant
- Conformant with ONVIF profile S
- 2 year warranty

CSI O2B16**Full HD 1080p 2MP Bullet IP Camera, 3-9mm Lens, Dark Grey Housing**

- EZ Focus: Motorized 3x zoom lens with auto focus for completely hassle-free remote focusing
- Supports up to Full HD 1080p @ 60fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- Built-in IR LEDs
- IR Range: 98 ft. (depending on scene reflection)
- Wide dynamic range (WDR) operation
- 2-way audio communication
- Micro SD card slot (card not included)
- IP66 compliant
- ONVIF Profile S listed
- 2 year warranty

NEW CSI O2D11M**2MP H.265 Dome IP Camera, 2.8-12mm Lens, Dark Grey Housing**

- 2.8-12mm auto iris varifocal motorized lens EZ Focus: motorized 3-axis & optical zoom lens
- with auto focus for hassle-free remote focusing
- Supports up to Full HD 1080p @ 60fps
- Triple-codec operation - H.265/H.264/MJPEG
- True Day/Night operation (IR cut filter)
- Smart IR function provides vivid image with no saturation in darkness
- IR Range: 65' (depending on scene reflection)
- Built-in standard PoE (IEEE 802.3af)
- Wide dynamic range (WDR) operation
- 2-way audio communication
- Micro SD card slot (card not included)
- IP66 compliant, weather resistant
- IK10 compliant, vandal resistant
- Conformant with ONVIF profile S
- 2 year warranty

CSI O2DP9**Full HD 1080p 2MP Indoor Miniature Dome IP Camera, 3.7mm Fixed Lens, White Housing**

- Free Apps with support for view on most smart devices
- 3.7mm fixed lens
- Supports up to Full HD 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- Built-in IR LEDs
- IR Range: 30' (depending on scene reflection)
- Wide dynamic range (WDR) operation
- Supports H.264 and MJPEG codecs
- ONVIF Profile S listed
- 2 year warranty

CSI O3VLB3**3MP Indoor/Outdoor Bullet IP Camera, 2.8mm fixed lens, dark grey housing**

- Supports 3MP @ 20fps and 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR Range: 98' (depending on scene reflection)
- Supports H.264 and MJPEG codecs
- IP67 compliant

CSI O3VLD1**3MP Indoor/Outdoor Vandal Resistant Dome IP Camera, 2.8mm fixed lens, white housing**

- Supports 3MP @ 20fps and 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR Range: 98' (depending on scene reflection)
- Supports H.264 and MJPEG codecs
- IP67 and IK10 compliant

CSI O5MDP1**5MP 360° Panoramic Indoor/Outdoor Miniature Dome IP Camera, 0.98-1.12mm panomorph lens, Dark Grey Housing**

- 360° field of view
- Various panoramic viewing features

- 5MP resolution
- Built-in standard PoE (IEEE 802.3af)
- Supports H.264 and MJPEG codecs
- 2-Way audio communication
- Micro SD card slot (card not included)
- IP66 compliant
- ONVIF Profile S
- 2 year warranty

**TruVision® IP Cameras****ILX TVB3105**

TruVision® IP bullet camera, 3.0MPX, 2.8~12mm VF lens, true D/N, DWDR, 30m IR, alarm, SD/SHDC slot, PoE (803.af) /12VDC, IP66, NTSC

ILX TVB3203

TruVision IP Bullet Camera, 3MPx, 8~32mm Motorized Lens, WDR, True D/N, 50m IR, Alarm, SD/SHDC Slot, Intelligence, PoE (802.3-af) /12VDC, Heater, IP66, NTSC

ILX TVD3105

TruVision® IP mini dome, 1.3MPX, true D/N, 2.8mm fixed lens, DWDR, 10m IR, IP66, PoE (803.af) / 12VDC, BNC, NTSC

ILX TVD3106

TruVision® IP mini dome, 3.0MPX, true D/N, 2.8mm fixed lens, DWDR, 10m IR, IP66, PoE (803.af) / 12VDC, BNC, NTSC

ILX TVW3103

TruVision® IP Wedge Camera, 1.3MPx, Wi-Fi, 2.8mm fixed lens, DWDR, True D/N, 10M IR, SD/SHDC slot, PoE (802.3-af)/12VDC, corrosion resistant, IP66, IK8, audio, gray housing, NTSC

ILX TVW3104

TruVision® IP Wedge Camera, 1.3MPx, Wi-Fi, 2.8mm fixed lens, DWDR, True D/N, 10M IR, SD/SHDC slot, PoE (802.3-af)/12VDC, corrosion resistant, IP66, IK8, audio, white housing, NTSC

ILX TVW3105

TruVision® IP Wedge Camera, 3.0MPx, Wi-Fi, 2.8mm fixed lens, DWDR, True D/N, 10M IR, SD/SHDC slot, PoE (802.3-af)/12VDC, corrosion resistant, IP66, IK8, audio, gray housing, NTSC

ILX TVW3106

TruVision® IP Wedge Camera, 3.0MPx, Wi-Fi, 2.8mm fixed lens, DWDR, True D/N, 10M IR, SD/SHDC slot, PoE (802.3-af)/12VDC, corrosion resistant, IP66, IK8, audio, white housing, NTSC

ILX TVW3107

TruVision® 1.3MPx Open Standards, Progressive Scan CMOS Low Profile Wedge Vandal Dome Camera, Elec D/N, 2.0mm Fixed Lens, ONVIF/PSIA, PoE/12VDC, IP66, NTSC, Gray

ILX TVW3108

TruVision® 1.3MPx Open Standards, Progressive Scan CMOS Low Profile Wedge Vandal Dome Camera, Elec D/N, 2.0mm Fixed Lens, ONVIF/PSIA, PoE/12VDC, IP66, NTSC, White



INTERACTIVE | CENTRAL VAS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK



ILX TVF3101

ILX TVW3109

TruVision® 1.3MPx Open Standards, Progressive Scan CMOS Low Profile Wedge Vandal Dome Camera, Elec D/N, 2.0mm Fixed Lens, ONVIF/PSIA, PoE/12VDC, IP66, NTSC, Black

ILX TVW3116

TruVision® IP Wedge Camera, 3.0MPx, Wi-Fi, 6mm fixed lens, DWDR, True D/N, 10M IR, SD/SHDC slot, PoE (802.3-af)/12VDC, corrosion resistant, IP66, IK8, audio, white housing, NTSC



IDV BUF364MP

ILX TVB3101

TruVision® 1.3MPx Open Standards, Progressive Scan CMOS, Outdoor Bullet, True D/N, DWDR, 6mm Fixed Lens, 25m IR, ONVIF/PSIA, PoE/12VDC, IP66, NTSC

ILX TVB3102

TruVision® 3.0MPx Open Standards, Progressive Scan CMOS, Outdoor Bullet, True D/N, DWDR, 6mm Fixed Lens, 25m IR, ONVIF/PSIA, PoE/12VDC, IP66, NTSC



IDV DEF284MP

ILX TVD3101

TruVision® 1.3MPx Open Standards, Progressive Scan CMOS, Indoor Mini-dome, DDN, DWDR, 2.8mm Fixed Lens, BNC Out, ONVIF/PSIA, PoE Only, NTSC

ILX TVD3102

TruVision® 3.0MPx Open Std, Progressive Scan CMOS, Indoor Mini Dome, DDN, DWDR, 2.8mm Fixed Lens, BNC out, ONVIF/PSIA, PoE only, NTSC

ILX TVD3103

TruVision® 1.3MPx Open Standards, Progressive Scan CMOS, Outdoor Vandal Dome, True D/N, DWDR, 2.8-12mm VF Lens, 15m IR, Micro SD Slot, ONVIF/PSIA, PoE/12VDC, NTSC

ILX TVD3104

TruVision® 3.0MPx Open Standards, Progressive Scan CMOS, Outdoor Vandal Dome, True D/N, DWDR, 2.8-12mm VF Lens, 15m IR, Micro SD Slot, ONVIF/PSIA, PoE/12VDC, NTSC



VIT VTCTNB42R3F



VIT VTCTNT30R3F

ILX TVW3101

TruVision® 1.3MPx Open Standards, Progressive Scan CMOS Low Profile Mini-dome Camera, True D/N, DWDR, 2.8mm Fixed Lens, 10m IR, Micro SD Slot, ONVIF/PSIA, PoE/12VDC, IP66, NTSC

ILX TVW3102

TruVision® 3.0MPx Open Standards, Progressive Scan CMOS Low Profile Mini-dome Camera, True D/N, DWDR, 2.8mm Fixed Lens, 10m IR, Micro SD Slot, ONVIF/PSIA, PoE/12VDC, IP66, NTSC



VIT VTCTNT30R3V

ILX TVF3101

TruVision® 360° Indoor Dome Camera, 3MPx, WDR, 1.19mm Fisheye Lens, True D/N, 10m IR, 2-Way Audio (built-in mic & speaker), SD/SHDC Slot, PoE (802.3af) /12VDC, NTSC

ILX TVF3102

TruVision® 360° Outdoor Dome Camera, 3MPx, WDR, 1.19mm Fisheye Lens, True D/N, 10m IR, 2-Way Audio (built-in mic & speaker), SD/SHDC Slot, PoE (802.3af) /12VDC, IP66, IK10, NTSC

ILX TVF3103

TruVision® 360° Indoor Dome Camera, 6MPx, DWDR, 1.27mm Fisheye Lens, True D/N, 10m IR, 2-Way Audio (built-in mic & speaker), SD/SHDC Slot, PoE (802.3af) /12VDC, NTSC



TOS IKSWR7022

ILX TVF3104

TruVision® 360° Outdoor Dome Camera, 6MPx, DWDR, 1.27mm Fisheye Lens, True D/N, 10m IR, 2-Way Audio (built-in mic & speaker), SD/SHDC Slot, PoE (802.3af) /12VDC, IP66, IK10, NTSC



IDV BUF363MP

3 Megapixel IR Bullet, 1/3" Aptina CMOS, 2048 x 1536, fixed lens 3.6mm, 0.1 Lux/F1.4 (0 Lux IR on), H.264/JPEG Snapshot, Day/Night, DWDR, Day/Night, 3DNR, AWB, AGC, BLC, IR Distance 60ft, IP66, DC12V /PoE, 14°F ~ 140°F, 3.5" x 2.5" x 9", 0.85 lbs

IDV BUF362MP

2MP IP IR Bullet Camera 3.6MM, 12VDC/ PoE -IP66-DWDR

IDV DEF363MP

3 Megapixel Eyeball Dome camera, 1/3" Aptina CMOS, 2048 x 1536, fixed lens 3.6mm, H.264/JPEG Snapshot, 0.1 Lux/ F1.4 (0 Lux IR on), DWDR, Day/Night, BLC, AGC, AWB, 3DNR, IR distance IP66, DC 12V/PoE, 14 °F ~ 140 °F, 3.8" x 3.2", 0.75 lbs

IDV DEF362MP

2MP IP IR Turret Camera DWDR 12VDC/ PoE -3.6MM Lens

IDV DF362MP

2MP IP IR Mini-Dome Camera, 3.6MM-12VDC/ PoE -DWDR-IP66

IDV DF363MP

3MP IP IR Mini-Dome Camera, 3.6MM-12VDC/ PoE -DWDR-IP66

IDV DP362MP

2MP IP IR Pancake Dome Camera, 3.6MM-12VDC/ PoE -DWDR-IP66

IDV DP363MP

3MP IP IR Pancake Dome Camera, 3.6MM-12VDC/ PoE -DWDR-IP66

NEW IDV BUF364MP

4MP IP IR Bullet Camera 3.6mm Lens

NEW IDV DEF284MP

4MP IP Turret Camera 2.8mm Lens

NEW IDV DEF364MPG

4MP Turret Camera 3.6mm Lens Gray

NEW IDV DEF364MPW

4MP IP Turret Camera 3.6mm Lens White



Transcendent Series Megapixel Cameras

VIT VTCTNB36R3V

3MP IP IR Outdoor WDR Bullet Camera, 2.8-12mm Lens, 12VDC/PoE

- Up to 30fps live view @ 1920x1080 (2MP) / 15fps live view @ 2048x1536 (3MP)
- 36 Infrared LED's with 120' IR Range
- H.264/MJPEG Dual Streaming
- ONVIF Compliance
- IP66 Weather Resistance

VIT VTCTNB42R3F

3MP IP IR Outdoor WDR Bullet Camera, 3.6mm Lens, 12VDC/PoE

- Up to 30fps live view @ 1920x1080 (2MP) / 15fps live view @ 2048x1536 (3MP)
- 42 Infrared LED's with 150' IR Range
- H.264/MJPEG Dual Streaming
- ONVIF Compliance
- IP66 Weather Resistance

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

VIT VTCTNT30R3F**3MP IP IR Indoor/Outdoor WDR Turret Camera, 3.6mm Lens-12VDC/PoE**

- Up to 30fps live view @ 1920x1080 (2MP) / 15fps live view @ 2048x1536 (3MP)
- 30 Infrared LED's with 100' IR Range
- H.264/MJPEG Dual Streaming
- ONVIF Compliance
- IP66 Weather Resistance

VIT VTCTNT30R3V**3MP IP IR Indoor/Outdoor WDR Turret Camera, 2.8-12mm Lens-12VDC/PoE**

- Up to 30fps live view @ 1920x1080 (2MP) / 15fps live view @ 2048x1536 (3MP)
- 30 Infrared LED's with 100' IR Range
- H.264/MJPEG Dual Streaming
- ONVIF Compliance
- IP66 Weather Resistance

VIT VTDTND30R3V**3MP IP IR Vandal Resistant Dome Camera, 2.8-12mm Lens, 12VDC/PoE**

- Up to 30fps live view @ 1920x1080 (2MP) / 15fps live view @ 2048x1536 (3MP)
- 30 Infrared LED's with 100' IR Range
- H.264/MJPEG Dual Streaming
- ONVIF Compliance
- IP66 Weather Resistance

VIT VTCIR302FNP**ENVI 2.1 MegaPixel WDR Day/Night IR Bullet Camera with 120' Range, 3.6mm Fixed Lens**

- 1/2.9" Sony® Exmor™ Progressive Scan CMOS Sensor

- Up to 30fps live view @ 1920x1080p
- 30 850nm Infrared LEDs with 120' IR Range
- Auto True Day Night (TDN) with Dual Filter Switch for no focus shift at night
- WDR (Wide Dynamic Range)
- 3D-DNR Noise Reduction
- 16:9 Video format
- H.264/MJPEG Dual Streaming
- Minimal Latency w/Max 16 User Connections
- ONVIF Profile S Compatibility
- MicroSD Card Slot supporting up to 64GB cards for Onboard EDGE Recording and Playback
- Motion Detection, Privacy Masking & Highlight Masking
- Gasket Sealed with an IP66 Weather Resistance Rating
- 12VDC & PoE (Power over Ethernet) Operation

VIT VTCAR2B4FN**2.4 MP Bullet Camera with 3.6mm Fixed Iris Lens**

- 1/2.7" Progressive Scan CMOS
- 2.4 MegaPixel With full 1080p/720p Output
- Up to 30fps live view @ 1920x1080 (1080p)
- Automatic True Day/Night
- H.264/MJPEG Dual Streaming
- 24 IR LEDs with up to 60' Range
- Micro SD memory card slot for Local recording

- Advanced OSD Functions: Motion Detection & Privacy Masking
- Heavy Duty IP66 rated weather/vandal resistant aluminum construction
- 12VDC & PoE (Power over Ethernet) Operation

TOSHIBA

Leading Innovation >>>

TOS IKSWR7022**1080P Light Duty PTZ Camera with WDR, Day/Night, IP66 and ONVIF**

This 1080p PTZ camera is suitable for both indoor and outdoor applications where panning and tilting functions are required. Full HD resolution, 350° pan, and 90° tilt provides full coverage for any large area. ONVIF compliant and 802.3af Power over Ethernet ensure compatibility with virtually any system.

TOS IKWB82A**3MP Outdoor Bullet with IR, Adaptive IR LEDs, Hallway View and Remote Auto Focus**

Powerful 3MP resolution, 4x optical remote zoom and remote focus make monitoring large areas easy, while H.264 Smart Codec reduces network bandwidth. Adaptive IR LEDs and Hallway view give extra versatility for almost any application. It comes complete and ready for installation without the need for any accessories.

THE INDUSTRY'S ENTERPRISING STAND-ALONE**H.265****VT-TNR3216P**

Transcendent Series 32 Channel 5 MegaPixel H.265 Real Time Network Video Recorder with 4K HDMI Output & Integrated 16 Port PoE Switch Supporting up to 48TB Internal Storage + eSATA

VT-TNR6480

Transcendent Series 64 Channel 5 MegaPixel H.265 Real Time Network Video Recorder with 4K HDMI Output & Dual Ethernet Ports Supporting up to 48TB Internal Storage + eSATA



COMPANY - WIDE HOURS
MONDAY - FRIDAY, 7:30AM - 5:30PM



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK

TOSHIBA

Leading Innovation >>>



TOS IKSWD6112

TOSHIBA

Leading Innovation >>>



TOS IKSWP816R

TOSHIBA

Leading Innovation >>>



TOS IKSWP806

inaxsys



INA INSBO2IRWA

inaxsys



INA INSDO2IRV

inaxsys



INA INSDO3IRA

AV



ATV N04P2

TOS IKSWD6112

1080p indoor low profile dome, 3.6mm, ONVIF, H.264, PoE, SD Card, WDR

TOS IKSWP816R

1080p outdoor PTZ, 4.7-84.6mm, 18x optical zoom, IP66, ONVIF, H.264, WDR

TOS IKSWP806

IKS-WP806 is an 18x 1080p HD PTZ IP camera designed for indoor applications. Full HD resolution, 18x optical zoom and pattern tour provides full coverage for any large area. ONVIF compliant and 802.3at Power over Ethernet Plus ensure compatibility with any system.

Features:

- 18x optical zoom
- 1080p HD video high resolution video image capture
- Pattern tour
- True Day/Night
- ONVIF compliant for maximum compatibility
- Power over Ethernet Plus (802.3at)
- Digital Wide Dynamic Range

TOS IKWD04A

1MP Varifocal Indoor Mini-Dome

- 720p HD video high resolution image capture
- Wide dynamic range enables use in locations with difficult lighting conditions
- Varifocal 3mm - 12mm lens
- ONVIF compliant for maximum compatibility
- Dual power; PoE (802.3af) and 12VDC
- MicroSD card for edge recording

TOS IKWR04A

Outdoor IP Network Mini-Dome Camera

- 720p HD video high resolution image capture
- Wide dynamic range enables use in multiple locations
- Varifocal 3mm - 12mm optical zoom
- ONVIF compliant for maximum compatibility
- Power over Ethernet (802.3af)
- MicroSD card for edge recording
- IP66 rated housing
- IK10 vandal proof rating
- Works great with the following recording solutions: ESV series, DVSe, XVSe, NVSe, IPSe, NVSPRO

TOS IKWD05A

Wide Angle Indoor IP Mini-dome

- 110 degree horizontal viewing angle captures a wide area
- 1080p HD video image capture
- True Day/Night with IR LEDs
- Pre-focused lens for objects at close range up to infinity
- ONVIF for maximum compatibility
- Power over Ethernet (802.3af)
- MicroSD card for edge recording

TOS IKWR05A

Wide Angle Outdoor IP Mini-dome

- 110 degree horizontal viewing angle
- 1080p HD video image capture
- True Day/Night with IR LEDs
- Pre-focused lens for objects at close range up to infinity
- ONVIF for maximum compatibility
- Power over Ethernet (802.3af)
- MicroSD card for edge recording
- IP66 rated housing

TOS IKWD14A

Indoor IP Mini-Dome Camera, 2MP

- Full HD 1080p streaming resolution (1920 x 1080) @ 30 fps
- H.264/MPEG4/JPEG quad streaming compression maintains low network bandwidth and maximum versatility
- Wide dynamic range for challenging lighting environments
- Advanced SR LED IR illuminators
- ONVIF compliant
- Day/night imaging
- Simple installation and deployment
- Two year warranty

TOS IKWR14A

Outdoor HD IP Vandal Dome Camera, 2MP

- Remote optical zoom and one-touch remote auto focus for faster installation
- Full 1080p HD video high resolution image capture (1920 x 1080)
- Advanced SRLED technology for edge to edge lighting down to 0 lux
- Wide dynamic range optimizes visibility in difficult lighting conditions
- Vandal resistant IP66 housing
- ONVIF compliant interface for maximum compatibility
- Improved cable management

TOS IKWB81A

1080p HD Bullet IP Camera

- Remote optical zoom and one-touch remote auto focus for faster installation
- Full 1080p HD video high resolution image capture
- Advanced SRLED technology providing 53° illumination angle for edge to edge lighting
- Split glass design eliminates IR back reflection
- Wide dynamic range optimizes visibility in difficult lighting conditions
- Weatherproof IP66 housing
- ONVIF compliant
- SD card slot for edge recording



Storm MP IP Cameras

INA INSBO2IRWA

Storm 2.1MP IR Bullet Camera Auto-Focus, WDR, 2.7-12mm Lens

INA INSDO2IRV

Storm 2.1MP IR Outdoor Dome Camera-2.7-12mm Lens-12VDC/PoE

INA INSDO2IRWA

Storm 2.1MP IR Outdoor Dome Camera Auto-Focus, WDR, 2.7-12mm

INA INSDO3IRV

Storm 3.1MP Vari-Focal Outdoor Dome Camera, 2.7-12mm lens, 12VDC, PoE

- 1/3" Megapixel progressive scan CMOS
- H.264 & MJPEG dual-stream encoding
- Max 20fps@ 3M (2148 x 1536)
- DWDR, Day/Night(ICR), AWB, AGC, BLC
- 2.7mm-12mm vari focal, IP66, IK10, PoE

INA INSDO3IRA

Storm 3.1MP IR Outdoor Dome Camera -2.7-12mm, 12VDC/PoE

INA INSMDO2F

Storm 2.1MP Outdoor Dome Camera 3.6mm, 12VDC/PoE

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.



ATV IPB3TI IP Bullet, 3MP, TDN, DWDR, Corridor, 2.8-12mm, 3X, Micro-SD, 36-IR, IP66, 12VDC/PoE

ATV IPFD3TI IP Int Surface/Flush Dome, 3MP, TDN, DWDR, Corridor, 2.8-12mm, 3X, Micro-SD, 30-IR, IP66, 12VDC/PoE

ATV IPV3TI IP Vandal, 3MP, TDN, DWDR, Corridor, 2.8-12mm, 3X, Micro-SD, 36-IR, IP66, 12VDC/PoE

ATV IPCH2M43PB
Covert Mega-Pixel IP Height Strip Camera, 2MP, 4.3mm, Black

- Covert IP Camera in Height Strip Housing
- Brilliant Video Quality with 2 Mega-Pixel Full HD, 1920 x 1080 Resolution
- Highly efficient H.264 Video Compression
- Wide Dynamic Range for High Contrast Lighting Conditions
- Swivel Bracket for Horizontal and 5° Tilt Lever for Vertical Camera Adjustments
- Supports Micro-SD Memory Card Slot for Local Recording Storage
- ONVIF Compliant for Network Video Interoperability
- 12 VDC/PoE Power Options

ATV IPMB2FI

2MP True Day/Night, On-Board Storage, IR, Mini-Bullet Camera

- Superior 2MP Full HD, 1920 x 1080 Resolution
- TRUE Day/Night Functionality for Low-light Conditions
- Highly Efficient H.264 Video Compression which Drastically Reduces Bandwidth and Storage Requirements
- Progressive Scanning for Sharper Video Motion Images
- 3.7 Wide Angle, Fixed Lens
- Triple Video Streams Simultaneously, up to 30-ips, at 1080p Resolution using H.264 and MJPEG Compression
- Powerful IR LED Lights for 0Lux Night-time Operation up to 60ft
- Supports a Micro-SD Memory Card Slot for Local, Event Detection Recording
- Backlight Compensation and Auto White Balance
- Motion Detection (Windows 8), Privacy Masking (Windows 8) and FTP Image Upload
- Up to 10 Simultaneous Connections through Remote Monitoring
- View and Record up to 64 Cameras or View and Manage up to 64 NVR's, with included ATVision IP Remote Management Software
- ONVIF Compliant for Network Video Interoperability
- PoE & 12VDC Power Options
- IP67 Rated Weather Resistant Housing

ATV IPMD2FI

2MP True Day/Night, On-Board Storage, IR, Interior Mini-Dome Camera

- Superior 2MP Full HD, 1920 x 1080 Resolution
- TRUE Day/Night Functionality for Low-light Conditions
- Highly Efficient H.264 Video Compression which Drastically Reduces Bandwidth and Storage Requirements
- Progressive Scanning for Sharper Video Motion Images
- 3.7 Wide Angle, Fixed Lens
- Triple Video Streams Simultaneously, up to 30-ips, at 1080p Resolution using H.264 and MJPEG Compression
- Powerful IR LED Lights for 0Lux Night-time Operation up to 60ft
- Supports a Micro-SD Memory Card Slot for Local, Event Detection Recording
- Backlight Compensation and Auto White Balance
- Motion Detection (Windows 8), Privacy Masking (Windows 8) and FTP Image Upload
- Up to 10 Simultaneous Connections through Remote Monitoring
- View and Record up to 64 Cameras or View and Manage up to 64 NVR's, with included
- ATVision IP Remote Management Software
- ONVIF Compliant for Network Video Interoperability
- PoE & 12VDC Power Options

NVR/Streaming Video Recorders:



NVR-E Series with Built In POE Switches

ATV N04P2

NVR w/ 4 PoE HDMI e-SATA 1HDD 2TB

- 4CH PoE, 2MP Recording
- Automatic Device Discovery and Display
- IR Remote and Mouse Incl.
- License Free ATVision Software Incl.
- 1TB and 2TB models, ONVIF

ATV N08P4

NVR w/ 8 PoE HDMI e-SATA 2HDD 4TB

- 8CH PoE, 2MP Recording
- Automatic Device Discovery and Display
- IR Remote and Mouse Incl.
- License Free ATVision Software Incl.
- 2TB and 4TB models, ONVIF

ATV N16P2

NVR w/ 16 PoE HDMI e-SATA 2HDD 2TB

- 16CH PoE, 2MP Recording
- Automatic Device Discovery and Display
- IR Remote and Mouse Incl.
- License Free ATVision Software Incl.
- ONVIF

ATV N16P4

NVR w/ 16 PoE HDMI e-SATA 2HDD 4TB

- Same features as above

ATV N4P1B4

Plug-N-Play Kit: NVR 4CH, PoE, HDMI, 1TB, and (4) 2MP IR Bullet Cameras

ATV N4P1T4

Plug-N-Play Kit: NVR 4CH, PoE, HDMI, 1TB, (4) 2MP Turret Cameras

ATV N8P2B4

Plug-N-Play Kit: NVR 8CH, PoE, HDMI, 2TB, (4) 2MP IR Bullet Cameras

ATV N8P2T4

Plug-N-Play Kit: NVR 8CH, PoE, HDMI, 2TB, (4) 2MP IR Turret Cameras



TruVision® NVR 10

The TruVision® NVR 10 (TVN 10) is a cost effective, network video recorder with up to 8 built-in PoE ports designed to support video streams from IP video cameras. With a total of 20/40/80Mbps of total bandwidth available, the NVR 10 can support up to 16 cameras at HD resolution in real-time (30fps) and many other configurations. Flexible bandwidth allocation per channel allows users to maximize recording performance. In addition to browser, software and mobile device management tools, the familiar front panel controls allow for easy operation. On-board PoE ports support up to 120 watts for ease of installation.

ILX TVN1004CS1T

TruVision® NVR 10, 4 channels, 4 channel PoE switch, 12 Mbps, 1TB

ILX TVN1004CS2T

TruVision® NVR 10, 4 channels, 4 channel PoE switch, 12 Mbps, 2TB

ILX TVN1008S2T

TruVision® NVR 10, 8 channels, 8 channel PoE switch, 24 Mbps, 2TB

ILX TVN1008S4T

TruVision® NVR 10, 8 channels, 8 channel PoE switch, 24 Mbps, 4TB

ILX TVN1016S3T

TruVision® NVR 10, 16 channels, 8 channel PoE switch, 80 Mbps, 3TB

ILX TVN1016S6T

TruVision® NVR 10, 16 channels, 8 channel PoE switch, 80 Mbps, 6TB

TruVision® Plug-N-Play IP Video Bundle

TruVision® NVR 10 Plug and Play Kits

ILX TVN1004KB1

4-Channel Kit w/4 Bullet Cameras Kit

- 1 x TVN-1004cS-1TB
 - 4-Channel NVR 10 Compact w/Built-in 4-Port PoE Switch, 1TB Storage
- 4 x TVB-3101
 - 1.3MPx Open Standards IR Bullet Cameras



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK




ILX TVN1004KW1

ILX TVN1004KW1
4-Channel Kit w/4 Wedge Cameras Kit

- 1 x TVN-1004CS-1TB
 - 4-Channel NVR 10 Compact w/Built-in 4-Port PoE Switch, 1TB Storage
- 4 x TVW-3101
 - 1.3MPx Open Standards Low-profile Mini Dome IR Wedge Cameras




ILX TVN2116P8T

ILX TVN1008KB1
8-Channel Kit w/4 Bullet Cameras Kit

- 1 x TVN-1008S-2TB
 - 8-Channel NVR 10 w/Built-in 8-Port PoE Switch, 2TB Storage
- 4 x TVB-3101
 - 1.3MPx Open Standards IR Bullet Cameras




INA INS88NVR2T

ILX TVN1008KW1
8-Channel Kit w/4 Wedge Cameras Kit

- 1 x TVN-1008S-2TB
 - 8-Channel NVR 10 w/Built-in 8-Port PoE Switch, 2TB Storage
- 4 x TVW-3101
 - 1.3MPx Open Standards Low-profile Mini Dome IR Wedge Cameras

TruVision® NVR 21
 The TruVision® NVR 21 (TVN 21) is a high-performance network video recorder designed to support video streams from IP video cameras. With a total of 40/80 Mbps of total bandwidth available, the TVN 21 can support up to 16 cameras at HD resolution in real-time (30fps) and many other configurations. Flexible bandwidth allocation per channel allows users to maximize recording performance. In addition to browser, software and mobile device management tools, the NVR 21's familiar front panel controls allow for easy operation.




CHU NR816M742TB

ILX TVN21082T 8-Channels, 2TB Storage
ILX TVN21084T 8-Channels, 4TB Storage
ILX TVN21162T 16-Channels, 2TB Storage
ILX TVN21164T 16-Channels, 4TB Storage
ILX TVN21168T 16-Channels, 8TB Storage




VIV ND8322P2TB4IB69

TruVision® NVR 21Plus
 The TruVision® NVR 21Plus (TVN 21P) is a high-performance network video recorder designed to support video streams from IP video cameras. With a total of 40/80/160 Mbps of total bandwidth available, the NVR 21Plus can support up to 32 cameras at HD resolution in real-time (30fps) and many other configurations. Flexible bandwidth allocation per channel allows users to maximize recording performance. In addition to browser, software and mobile device management tools, the familiar front panel controls allow for easy operation.




KAN INTEVOADV3TB

ILX TVN2108P4T
 TruVision® NVR 21Plus, 8-Channels, IP H.264 ONVIF/PSIA 40Mbps Bandwidth, eSATA, 4TB Storage




CSI ZIPL84B2

ILX TVN2116P8T
 TruVision® NVR 21Plus, 16-Channels, IP H.264 ONVIF/PSIA, 80Mbps Bandwidth, eSATA, 8TB Storage

ILX TVN2132P12T
 TruVision® NVR 21Plus, 32-Channels, IP H.264 ONVIF/PSIA, 160Mbps Bandwidth, eSATA, 12TB Storage

ILX TVN2132P16T
 TruVision® NVR 21Plus, 32-Channels, IP H.264 ONVIF/PSIA, 160Mbps Bandwidth, eSATA, 16TB Storage

TruVision® NVR 21S Series
ILX TVN2108S2T
 TruVision® NVR 21S, 8-Channel, IP H.264 ONVIF/PSIA, 8-Port PoE Switch, 40Mbps Bandwidth, eSATA, 2TB Storage

ILX TVN2108S4T
 TruVision® NVR 21S, 8-Channel, IP H.264 ONVIF/PSIA, 8-Port PoE Switch, 40Mbps Bandwidth, eSATA, 4TB Storage

ILX TVN2108S8T
 TruVision® NVR 21S, 8-Channel, IP H.264 ONVIF/PSIA, 8-Port PoE Switch, 40Mbps Bandwidth, eSATA, 8TB Storage

ILX TVN2116S2T
 TruVision® NVR 21S, 16-Channel, IP H.264 ONVIF/PSIA, 16-Port PoE Switch, 80Mbps Bandwidth, eSATA, 2TB Storage

ILX TVN2116S4T
 TruVision NVR 21S, 16-Channel, IP H.264 ONVIF/PSIA, 16-Port PoE Switch, 80Mbps Bandwidth, eSATA, 4TB Storage

ILX TVN2116S8T
 TruVision® NVR 21S, 16-Channel, IP H.264 ONVIF/PSIA, 16-Port PoE Switch, 80Mbps Bandwidth, eSATA, 8TB Storage



Storm Mini NVR's
INA INS44NVR2T
 Storm 4CH Mini NVR, 2TB HDD

INA INS88NVR2T
 Storm 8CH Mini NVR, 2TB HDD

INA INS88NVR4T
 Storm 8CH Mini NVR, 4TB HDD

INA INS1616NVR4T
 Storm 16CH Mini NVR, 4TB HDD

INA INS1616NVR6T
 Storm 16CH Mini NVR, 6TB HDD

IVTVision IP Servers
INX 2UIPS4000
 The IVTVision® 2U Rackmount IP Server is a system that provides complete video management utilizing today's latest IP video surveillance cameras on an enterprise-class chassis. The system comes pre-configured with the IVTVision VMS Server and client software. The powerful, yet easy-to-operate client user interface installs on any standard computer running Windows, Linux or Mac OS X and can connect to multiple IVTVision Hybrid (analog and IP cameras) and IP Camera Servers creating a virtually unlimited amount of cameras and protection. Video from all IVTVision systems can also be accessed with web browsers and mobile devices with access to the internet. Each 2U Rackmount IP Server can be easily expanded from 1 to up to 64 IP cameras.

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

INX DTIPS2000

The IRTVision® Desktop IP Server is a system that provides recording of today's latest IP video surveillance cameras on a space-saving desktop chassis. The powerful, yet easy-to-operate client user interface installs on any standard computer running Windows, Linux or Mac OS X and can connect to multiple IRTVision Hybrid (analog and IP cameras) and IP Camera Servers creating a virtually unlimited amount of cameras and protection. Video from all IRTVision systems can also be accessed with web browsers and mobile devices with access to the internet. Each Desktop IP Camera NVR server can be easily expanded from 1 to up to 64 IP cameras.



Ganz GenStar Embedded NVRs

CHU NR84M711TB

4CH, up to 4MP Recording Res, 30fps @ 1080p, 1 SATA HDD, 1 HDMI & VGA, 4 PoE ports, 2 USB, 1TB, 1080P

CHU NR88M722TB

8CH, up to 4MP Rec. Res, 2 SATA HDD, 1 HDMI & VGA, Two-way audio, 2CH I/O, 8 PoE ports, 2 USB, 2TB, 1080P

CHU NR816M742TB

16CH, Up to 4MP Rec. Res, 4 SATA HDD, 1 HDMI & VGA, Two-way audio, 2CH I/O, 16 PoE Ports, 3 USB, 2TB, 1080P



EXQ EVIP01

Professional IP Camera License

Includes 1 year of software updates, or 3 years when purchased with an exacqVision server.

EXQ START01

Start IP Camera License Download

- Low-Cost, VMS Software, Simple Surveillance Solution for Stand-Alone Applications
- Software Updates Included (exacqVision Servers): 3 Years
- Software Updates Included (3rd Party Servers): 90 Days

EXQ ACEVIP01

Activation card with one exacqVision Professional IP camera license. Includes one year of software updates.



VIV ND8322P2TB4FD69

8CH PNP Kit w/2TB HDD + (4) FD8169 2MP Indoor Dome Camera

VIV ND8322P2TB4IB69

8CH PNP Kit w/2TB HDD + (4) IB8369 2MP Bullet Cameras

KANTECH

All in one NVR/Access Control

INTEVO represents the evolution of integration. Now with the addition of new INTEVO Compact, the platform offers the ability to grow the system to meet organizational needs over time. Designed exclusively for security applications, INTEVO is an easy to deploy integrated security platform, designed to be up and running in minimal time with out-of-the-box ease. INTEVO is simple to configure and includes a customized dashboard for easy system management.

- Simple to configure, easy to deploy
- Supports EntraPass Corporate Edition features such as:

- EntraPass Go mobile application
- EntraPass Web client
- EntraPass Workstation client
- DSC PowerSeries alarm panel Integration
- DSC MAXSYS alarm panel Integration

- Compatible with all Kantech controllers
- Connect up to 32 IP cameras
- Optimized for use with American Dynamics Illustra Series IP Cameras
- Supports H.264, MPEG-4, MJPEG and a wide variety of IP cameras including Megapixel
- Seamlessly integrate American Dynamics VideoEdge NVR, Intellex, HDVR and ADTVR into one solution
- Video storage

KAN INTEVOADV3TB

INTEVO Integrated Security Platform

- All-in-One NVR/Access Control
- With single IP camera license included
- 32CH, 3TB HDD

KAN INTEVOCMP1TB

Access Control and IP Video - All in One, 1TB

- Preloaded with:
 - EntraPass Corporate Edition
 - IP video (up to 16 cameras, 1 license included)
 - EntraPass Web and EntraPass Go Mobile
- First boot wizard for easy configuration
- 1 TB Storage

Network Servers with Built-In PoE Switches



NSF Series NVR's with built-in 16 Port PoE Switch

- 16 channel plug & play network video recorder with 16 channel built-in PoE
- Plug & play feature with Speco's OnSIP/VIP/ZIP cameras
- Dual network ports for isolating IP camera network and remote network traffic
- Network video recorder with free Speco DDNS server
- 2-way audio communication
- Built-in S.M.A.R.T. Technology (Self-Monitoring, Analysis and Reporting Technology for HDD)
- PC and MAC® compatible
- Free Apps with support for view on most smart devices
- ONVIF support
- 3 year warranty

CSI N16NSF2TB 16 Channel, 2TB HDD

CSI N16NSF3TB 16 Channel, 3TB HDD

CSI N16NSF4TB 16 Channel, 4TB HDD

CSI N16NSF6TB 16 Channel, 6TB HDD

CSI N16NSF8TB 16 Channel, 8TB HDD

NSL Series NVRs

- Full HD (1920 x 1080) recording and playback
- Video Out: 1 HDMI, 1 VGA, 1 CVBS
- Built-in PoE provides power to IP cameras
- Remote monitoring / recording / playback / configuration/software upgrades and PTZ control via internet
- Network accessible via SpecoTech Multi-Client Software, SecureGuard® CMS and Speco Player Mobile Viewer
- PC and MAC® compatible
- 3 year warranty

CSI N4NSL1TB

4CH 1080P NVR w/1TB HDD

- 4 Channel NVR with 4 Channel Built-In PoE

CSI N8NSL2TB

8CH NVR 2TB HDD w/ Built-in 8 CH PoE

- 8 Channel NVR with 8 Channel Built-In PoE

4 Channel

ZIP kits with new NSL NVR's

CSI ZIPL84B2

8CH Plug-and-Play NVR 1080p, 240FPS, 2TB w/4 Outdoor IR Bullet 3.7mm lens

CSI ZIPL84D2

8CH Plug-and-Play NVR 1080p, 240FPS, 2TB w/4 Outdoor IR Dome 3.7mm lens

CSI ZIPL88B2

8CH Plug-and-Play NVR 1080p, 240FPS, 2TB w/4 Outdoor IR Bullet 3.7mm lens



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUD. | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK

speco technologies



CSI N4WNSP1TB

CSI ZIPL88D2

8CH Plug-and-Play NVR 1080p, 240FPS, 2TB w/8 Outdoor IR Dome 3.7mm lens

CSI ZIPL8BD2

8CH Plug-and-Play NVR 1080p, 240FPS, 2TB w/4 Outdoor IR Bullet and 4 Outdoor IR Dome 3.7mm lens

NSP Plug & Play Network Video Recorders

- Plug & play feature with Speco's OnSIP/VIP cameras
- ONVIF support
- Dual network ports for isolating IP camera network traffic and remote network
- Supports all H.264 compression profiles (baseline, main and high)
- A patented DVR solution that easily mounts in equipment closets or electrical rooms for covert installations
- Network video recorder with free DDNS server
- Easy and simple graphical user interface
- Digital Deterrent® for triggering audio message via motion detection or sensor
- 2-Way audio communication
- Programmable recording on motion detection, sensor, schedule, continuous and manual
- Full HD (1920 x 1080) recording and playback
- Supports wireless access point for viewing and configuration
- Built-in S.M.A.R.T. Technology (Self-Monitoring, Analysis and Reporting, Technology for HDD)
- 4/8/16 channel selectable local or IP camera audio recording
- Covert camera operation provides enhanced security and administrator control



IDV K404BU2MPWIFI1TB



IDV K404BU13MPOE1TB

4CH PoE NVR/1.3MP Camera Bundle -- 1TB HDD, (4) IR Bullet Cameras, 3.6mm Fixed Lens

IDV K404ED13MPOE1TB

4CH PoE NVR/1.3MP Camera Bundle -- 1TB HDD, (4) IR Turret Cameras, 3.6mm Fixed Lens

IDV K804BU13MPOE2TB

8CH PoE NVR/1.3MP Camera Bundle -- 2TB HDD, (4) IR Bullet Cameras, 3.6mm Fixed Lens

IDV K804ED13MPOE2TB

8CH PoE NVR/1.3MP Camera Bundle -- 2TB HDD, (4) IR Turret Cameras, 3.6mm Fixed Lens

NEW IDV K404BU2MPWIFI1TB

4CH 1080P HD Wi-Fi NVR W/1TB HD + (4) 2MP Wi-Fi Bullet Cameras

NEW IDV K404BU2MPWIFI2TB

4CH 1080P Wi-Fi NVR KIT W/2TBB HD + (4) Bullet Cams 4mm Fixed Lens

NEW IDV K808BU13WIFI2TB

8CH 960P Wi-Fi NVR KIT W/2TBB HD + (8) 960P Bullet Cam 4mm Lens

inaxsys



INA INSK1688N2TB



INA INSK1688N2TB

16CH All in One STORM Series NVR Camera Bundle, 2TB NVR with 8 x 2.1MP (1080P) Bullet Cameras

- Up to 16 IP camera input channels
- H.264/MJPEG dual codec decoding
- Maximum 200Mbps of incoming bandwidth
- Up to 5MP resolution for preview & playback
- HDMI/VGA/TV simultaneous video outputs
- 16 channel synchronized real-time playback, GRID interface
- Supports multiple brands of network cameras
- Conforms to ONVIF Version 2.4
- 3D intelligent positioning
- Supports 4 SATA HDDs (up to 16TB), 1 eSATA port and 2 USB ports (1 USB 3.0)
- Supports IP cameras UPnP and 16 PoE ports
- Multiple network monitoring
- IP Camera Features:
 - 1/2.7" 2 megapixel CMOS
 - H.264 & MJPEG dual-stream encoding
 - 25/30 fps @1080P
 - DWDR, Day/Night (ICR), AWB, AGC, BLC
 - 2.8mm fixed lens
 - Maximum length of IR LEDs: 30m, Smart IR
 - IP67 rated, DC 12V, Poe (802.3af)

Wall Mounts

CSI N4WNS2TB 4 CH, 2TB HDD

CSI N4WNSP1TB 4CH Wall Mount NVR w/ 1TB HDD and Power Supply

CSI N8WNSP2TB 8 CH Wall Mount NVR w/ 2TB HDD and Power Supply

CSI N8WNSP4TB 8 CH, 4TB HDD, PoE

CSI N16WNS6TB 16 CH, 6TB HDD

CSI N16WNSP6TB 16 CH, 6TB HDD, PoE

Stand Alone Units

CSI N4NSP1TB 1TB HDD, PoE

CSI N4NSP2TB 2TB HDD, PoE

8 Channel

CSI N8NSP1TB 1TB HDD, PoE

CSI N8NSP2TB 2TB HDD, PoE

CSI N8NSP3TB 3TB HDD, PoE

CSI N8NSP4TB 4TB HDD, PoE

NVR Plug 'N' Play ZIP Kits

CSI N8NSP2KT4D

8CH NVR/4ea MP Dome Camera Kit with PoE

CSI N8NSP2KT4B

8CH NVR/4ea MP Bullet Camera Kit with PoE

FLIR



FLR DN1142E43



FLIR IP: Bundles and NVRs

- FLIR's HD IP Security Bundles go several steps further to offer the most competitive bundled solution at unprecedented value.

FLIR



FLR DNR516R2

EverFocus



EVE ENVR8304D1T

VITEK



VIT TNR16282T

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

- FLIR NVRs further accelerate high definition recording, offering higher capacity 200 Mbps processing for real-time recording with cameras up to 5MP.

Bundles

NEW FLR DN1142E43

Full HD PoE NVR System

- 80Mbps network bit rate processing
- Supports high definition recording up to 4MP
- Pentaplex operation – simultaneous viewing, recording, playback, backup & remote monitoring
- Integrated PoE inputs for quick, convenient connection
- 4 integrated PoE ports with PoE+ support
- 50W total PoE (up to 25W per channel)
- Auto-discovery of FLIR IP cameras with no programming
- 3mp cameras included
- 3MP HD recording for superior image detail
- PE133E/P – 3MP (2048x1536) @ 25fps, 75° (H) field of view, 75ft (23m) IR night vision range
- 3-axis design for easy wall / ceiling mounting
- IP66 weatherproof rated & cold climate capable (-22°F / -30°C)
- Remote access via iOS, Android, PC & Mac with FLIR Cloud™
- Set up remote viewing in 3 easy steps: install FLIR Cloud™ app, scan QR code on NVR, and start viewing live video
- Multisite viewing with FLIR Cloud™ CMS for PC & Mac

NEW FLR DN4163E12

Full HD PoE+ NVR System

- 200Mbps network bit rate
- Supports high definition recording with cameras up to 4MP
- Intelligent compression coupled with Region of Interest (ROI) optimizes video performance based on available bandwidth*
- Integrated PoE inputs for quick, convenient connection
- 16 integrated PoE ports with PoE+ support
- 120W total PoE (up to 25W per channel)
- Auto-discovery of FLIR IP cameras with no programming
- 4mp dome cameras included
- Outstanding 4MP recording provides evidentiary level of detail
- PE133F – 4MP (2688x1520) @ up to 20fps, 90° (H) field of view, 85ft (25m) IR night vision range
- True Wide Dynamic Range (up to 100dB @ 3MP) provides more accurate detail in high contrast scenes
- IP66 weatherproof rated & cold climate capable (-22°F / -30°C)
- Remote access via iOS, Android, PC & Mac with FLIR Cloud™
- Set up remote viewing in 3 easy steps: install FLIR Cloud™ app, scan QR code on DVR, and start viewing live video
- Multisite viewing with FLIR Cloud™ CMS for PC & Mac

FLR DN408P28

8CH NVR with 8 PoE, 240fps@1080p, 480fps@720p, 2TB HDD with 8x mini bullet 2.1MP, 3.6mm, Cloud connectivity

NVRs

Flir IP PoE High Definition NVR

- Supports HD recording with cameras up to 5MP
- Pentaplex operation - simultaneous View, Record, Playback, Backup & Remote Monitoring
- 80Mbps network bit rate processing
- 4/8 integrated PoE ports
- 50Watt total PoE (up to 25W per channel)
- Auto-discovery of FLIR IP Cameras with no programming
- Supports SATA HDD up to 4TB
- Back-up via 2x USB 2.0 ports
- Set up remote viewing in three easy steps: install FLIR Cloud app, scan QR code on DVR, view live video
- Multisite viewing on FLIR Cloud CMS for PC / Mac

NEW FLR DNR1141

4CH, 1TB HDD

NEW FLR DNR1181

8CH, 1TB HDD

NEW FLR DNR1182

8CH, 2TB HDD

NEW FLR DNR416R2

16 channels (NTSC) 2TB HDD

- Turbo 200Mbps network bit rate
- Supports high definition recording with cameras up to 4MP
- Pentaplex Operation – simultaneous view, record, playback, backup & remote monitoring
- 8/16 integrated PoE ports with PoE+ support
- ONVIF 2.3 conformance
- Auto-discovery of FLIR IP Cameras with no programming
- Drive mirroring to second internal HDD
- Supports 2x SATA HDDs up to 6TB (12TB total)
- Instant back-up via 2x USB 2.0 port
- Set up remote viewing in three easy step: install FLIR Cloud™ app, scan QR code on NVR, view live video
- Multisite viewing on FLIR Cloud™ CMS for PC / Mac
- Premium services coming soon

NEW FLR DNR516R2

DNR500R Series NVR 16 Channels, 16 PoE+ Support, 200Mbps, 2TB HDD

- Turbo 200Mbps network bit rate
- Supports HD real-time recording with cameras up to 4MP
- Pentaplex operation – simultaneous View, Record, Playback, Backup & Remote Monitoring
- 16 integrated PoE ports with PoE+ support
- 150W total PoE (up to 25W per channel)
- Auto-discovery of FLIR IP Cameras with no programming
- Drive mirroring between up to 4 internal HDDs

- Supports 4x SATA HDDs up to 6TB (24TB total)
- eSATA support for 4 external drives
- Set up remote viewing in 3 easy steps: install FLIR Cloud app, scan QR code on NVR, view live video
- Multisite viewing on FLIR Cloud CMS for PC / Mac

NEW FLR DNR532R2

32CH NVR with 16 PoE, HDMI, 960fps@1080p, up to 4MP cameras, 2TB HDD, Mobile, PC/MAC, Cloud Connectivity



Plug'N'Play NVR

EVE ENVR8304D1T

8CH Plug and Play NVR, 1TB

EVE ENVR8304D2T

8CH Plug and Play NVR, 2TB

EVE ENVR8304E/1T

8CH Plug & Play NVR with Embedded 8 Channel PoE Switch with 1TB Storage

EVE ENVR8304E/2T

8CH Plug & Play NVR with Embedded 8 Channel PoE Switch with 2TB Storage



VIT VTNV400S1TB

4 Channel Real Time 1080P Network Video Recorder, 1TB HDD

- Stand-alone Real-time IP Network Video Recorders with Real Time Recording on all channels at 1080P and share the same local and remote software platform as our award winning On Cue HD-SDI recorders.
- The Advanced On Cue Central Monitoring software (CMS) is capable of connecting multiple On Cue NVRs and HD-SDI/EX-SDI recorders.

NVR Kits

VIT TNKT81TA

8CH NVR/Camera Kit w/1TB HDD + (4) 3MP IP Turret Cameras

VIT TNKT81TB

8CH NVR/Camera Kit w/1TB HDD + (4) 3MP IR Bullet Cameras

Transcendent 8/16 Channel Real Time Network Video Recorders

VIT TNR16282T

16CH NVR w/2TB HDD w/8 PoE Outputs

VIT TNR16283T

16CH NVR w/3TB HDD w/8 PoE Outputs

VIT TNR8141T

8CH 1TB NVR w/1TB HDD and 4 PoE Outputs

VIT TNR8142T

8CH NVR w/2TB HDD and 4 PoE Outputs



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK



VIT VTTNR3216P-12T



NAP ISEIVR250/12



TOS ENV4P1T



VIT TNKT81TA



GST GS4CHPOEPK1



TAT TS55M4



VWZ VZ19CME

VIT TNKT84TB

Complete Transcendent Series 8CH 3MP IP Surveillance Package, w/ Bullet Cameras, and 4TB IP NVR

- Network Video Recorder (NVR):
 - o Transcendent 8 Channel Network Video Recorder Supporting Real Time (240fps) Recording of up to eight 3.0 MegaPixel IP Cameras.

o Internal storage options of up to 6TB are available. (VT-TNR814)

- 3.0 MegaPixel Bullet Cameras:
 - o Transcendent Series 3.0 Megapixel Indoor/Outdoor IP Bullet Cameras with 42 IR LED Illumination Delivering an IR Range of over 150' with Included 3.6mm Lens. (VTC-TNB42R3F)

NEW VIT VTTNR3216P-12T

32 Channel 5 Megapixel H.265 Real Time Network Video Recorder with 4K Output & 16 Port PoE Switch – 12TB

- Full 5 Megapixel Real-time recording (960fps) with 16 Channel (480fps) playback
- 4K HDMI & VGA Video Outputs
- H.265 / H.264 Video Compression
- Plug and Play & Auto configuration for many leading ONVIF compliant IP Camera models
- Internal 16-Port PoE Switch
- 1 Gigabit LAN Port
- Pentaplex: Live Display / Record / Playback / Backup / Remote Access
- 16 Local Alarm Inputs / 4 Alarm Outputs
- 8 Internal SATA2/SATA3 HDD Slots supporting up to
- 48TB (8 x 6TB HDD) Internal Storage + 1 eSATA Port for External Expansion
- RS485 & Network Based PTZ Control
- Applications for iOS & Android™
- Remote Viewing over the Internet via Web Browser or LAN
- Mac OS® Client & CMS Central Management Software Included
- Supports both Dynamic and Static IP Addresses
- Web-based remote configuration
- Control locally via Front Panel Controls, USB Mouse, or with the Included IR Remote control
- Heavy duty rack ears included

NEW VIT VTTNR3216P-4T

32 Channel 5 Megapixel H.265 Real Time Network Video Recorder with 4K Output & 16 Port PoE Switch – 4TB

- Full 5 Megapixel Real-time recording (960fps) with 16 Channel (480fps) playback
- 4K HDMI & VGA Video Outputs
- H.265 / H.264 Video Compression
- Plug and Play & Auto configuration for many leading ONVIF compliant IP Camera models
- Internal 16-Port PoE Switch
- 1 Gigabit LAN Port
- Pentaplex: Live Display / Record / Playback / Backup / Remote Access
- 16 Local Alarm Inputs / 4 Alarm Outputs
- 8 Internal SATA2/SATA3 HDD Slots supporting up to 48TB (8 x 6TB HDD) Internal Storage + 1 eSATA Port for External Expansion
- RS485 & Network Based PTZ Control
- Applications for iOS & Android™
- Remote Viewing over the Internet via Web Browser or LAN

- Mac OS® Client & CMS Central Management Software Included
- Supports both Dynamic and Static IP Addresses
- Web-based remote configuration
- Control locally via Front Panel Controls, USB Mouse, or with the Included IR Remote control
- Heavy duty rack ears included

NEW VIT VTTNR3216P-8T

32 Channel 5 Megapixel H.265 Real Time Network Video Recorder with 4K Output & 16 Port PoE Switch – 8TB

- Full 5 Megapixel Real-time recording (960fps) with 16 Channel (480fps) playback
- 4K HDMI & VGA Video Outputs
- H.265 / H.264 Video Compression
- Plug and Play & Auto configuration for many leading ONVIF compliant IP Camera models
- Internal 16-Port PoE Switch
- 1 Gigabit LAN Port
- Pentaplex: Live Display / Record / Playback / Backup / Remote Access
- 16 Local Alarm Inputs / 4 Alarm Outputs
- 8 Internal SATA2/SATA3 HDD Slots supporting up to
- 48TB (8 x 6TB HDD) Internal Storage + 1 eSATA Port for External Expansion
- RS485 & Network Based PTZ Control
- Applications for iOS & Android™
- Remote Viewing over the Internet via Web Browser or LAN
- Mac OS® Client & CMS Central Management Software Included
- Supports both Dynamic and Static IP Addresses
- Web-based remote configuration
- Control locally via Front Panel Controls, USB Mouse, or with the Included IR Remote control
- Heavy duty rack ears included

NEW VIT VTTNR818P-4T

8 Channel 5 Megapixel H.265 Real Time Network Video Recorder with 4K Output & 8 Port PoE Switch – 4TB

- Full 5 Megapixel Real-time recording (240fps) with 240fps playback
- 4K HDMI & VGA Video Outputs
- H.265 / H.264 Video Compression
- Plug and Play & Auto configuration for many leading ONVIF compliant IP Camera models
- Internal 8-Port PoE Switch
- 1 Gigabit LAN Port
- Pentaplex: Live Display / Record / Playback / Backup / Remote Access
- 1 Internal SATA2/SATA3 HDD Slot supporting up to 6TB (1 x 6TB HDD) Internal Storage
- Network Based PTZ Control
- Applications for iOS & Android™
- Remote Viewing over the Internet via Web Browser or LAN
- Mac OS® Client & CMS Central Management Software Included
- Supports both Dynamic and Static IP Addresses
- Web-based remote configuration
- Control locally via USB Mouse or with the Included IR Remote control

NEW VIT VTTNR818P-6T

8 Channel 5 Megapixel H.265 Real Time Network Video Recorder with 4K Output & 8 Port PoE Switch – 6TB

- 8 Channel Stand-alone Real-time IP Network Video Recorder
- Full 5 Megapixel Real-time recording (240fps)

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

- with 240fps playback
- 4K HDMI & VGA Video Outputs
- H.265 / H.264 Video Compression
- Plug and Play & Auto configuration for many leading ONVIF compliant IP Camera models
- Internal 8-Port PoE Switch
- 1 Gigabit LAN Port
- Pentaplex: Live Display / Record / Playback / Backup / Remote Access
- 1 Internal SATA2/SATA3 HDD Slot supporting up to 6TB (1 x 6TB HDD) Internal Storage
- Network Based PTZ Control
- Applications for iOS & Android™
- Remote Viewing over the Internet via Web Browser or LAN
- Mac OS® Client & CMS Central Management Software Included
- Supports both Dynamic and Static IP Addresses



NAP ISEEIVR250/12

Internet Video Recorder (IVR) with 12 months of service



TOS ENV4P1T

4 Channel Embedded Network Recorder with Built-in PoE

Records 2048 x 1536 video from up to 4 channels at up to 120 fps. It supports two internal HDDs with each bay supporting storage of up to 4TB. It also supports one eSATA drive. Compatible with Surveillix SCS video management software. SCS enables you to monitor, search, and archive surveillance video from multiple remote locations. It also allows you to manage and configure recorders from a single platform. Customizable user screens, intuitive search capabilities and advanced mapping features make SCS powerful and efficient for all video surveillance requirements.



NVR Kits

VIT TNKT81TA

8CH NVR/Camera Kit w/1TB HDD + (4) 3MP IP Turret Cameras

VIT TNKT81TB

8CH NVR/Camera Kit w/1TB HDD + (4) 3MP IR Bullet Cameras

Transcendent 8/16 Channel Real Time Network Video Recorders

VIT TNR16282T

16CH NVR w/2TB HDD w/8 PoE Outputs

VIT TNR16283T

16CH NVR w/3TB HDD w/8 PoE Outputs

VIT TNR8141T

8CH 1TB NVR w/1TB HDD and 4 PoE Outputs

VIT TNR8142T

8CH NVR w/2TB HDD and 4 PoE Outputs



GST GS16CHNVRPOE2TB

16CH PoE NVR Built-in 2TB HD + USB Mouse

GST GS16CHNVRPOE4TB

16CH PoE NVR Built-in 4TB HD + USB Mouse

GST GS16CHNVRPOE8TB

16CH PoE NVR Built-in 8TB HD + USB Mouse

NEW GST GS8CHNVRPOE2TB

8CH NVR W/PoE +2TB HDD Plug-n-Play & Built in GSI "Auto Connect" feature. Full HD 1080P 1920x1080 Resolution

NEW GST GS8CHNVRPOE4TB

8CH NVR W/PoE + 4TB HDD Plug-n-Play & Built in GSI "Auto Connect" feature. Full HD 1080P 1920x1080 Resolution

4 and 8 Channel PoE NVR Plug & Play Megapixel Dome Camera Kits

- Easy Plug and Play Set up
- Makes IP systems easy to upgrade & install
- Built-in individual PoE Ports for each NVR (4 an 8 port)
- Power and video over a single Cat5 Cable – saves installation time & costs
- Built-in GSI "Auto connect" feature – Plug the camera into any port and the NVR automatically recognizes that channel with that camera. Easy no hassle IP installation.
- 1080p Resolution – 30FPS
- 2TB Hard drive included with each NVR
- Each kit Includes 4 pieces of Outdoor Rated 2.3 Megapixel IR Fixed Lens Cameras

GST GS4CHPOEPK1

4CH Plug-n-Play PoE Kit w/4 IP Dome Cameras

GST GS4CHPOEPK2

4CH Plug-n-Play PoE IP Kit w/4 Bullet Cameras

NEW GST GS4CHNVRPOEPK14M

4CH NVR 2TB HDD/PoE + (4) 4MP GSIP804BD Cameras 3.6MM Fixed Lens, Vandal Resistant, IP66 Rated Ball Dome

GST GS8CHPOEPK1

8CH Plug-n-Play PoE Kit w/4 Outdoor IR Dome Cameras

GST GS8CHPOEPK2

8CH Plug-n-Play PoE IP Kit w/4 Outdoor IR Bullet Cameras

NEW GST GS8CHPOEPK14M

8CH Plug & Play PoE NVR w/2TB & (4) 4MP GSIP804BD Cameras 3.6MM Fixed Lens, Vandal Resistant, IP66 Rated Ball Dome

NEW GST GS8CHPOEPK24M

8 CH Plug & Play PoE NVR w/2TB+(4) 4MP GSIP805BC Cameras 3.6MM Fixed Lens, IP66 Rated Bullet

LED Interactive Displays:



Multi-Touch Interactive LED Displays

Primary markets include Education, Presentation and any application that requires collaborative learning and information sharing. Features and benefits include:

- Surface Light Wave Technology (one of the most advanced multi-touch technologies)
- Touch Screen Response under ambient and bright lighting
- Protective Tempered Glass
- Built-in Speakers
- VGA, USB, HDMI, Composite AV inputs
- Supports Windows 7 & 8, Mac OS and Linux operating systems
- 60,000 hours panel lifespan
- 3 year warranty with 3 year advance replacement
- Annotation Software Included

TAT TS55M4

55" Full Hi-Definition Multi-Touch Interactive Display with 4 touch points (multiple personnel can work on the screen simultaneously).

TAT TS65M10

65" Full Hi-Definition Multi-Touch Interactive Display with 10 touch points (multiple personnel can work on the screen simultaneously).

TAT TS70M10

70" Full Hi-Definition Multi-Touch Interactive Display with 10 touch points (multiple personnel can work on the screen simultaneously).

IP LED Monitors:



HD Resolution Commercial Grade Desktop Security Monitors

- Eco-Friendly - 40% Lower Power Consumption
- HDMI, DVI, VGA
- Built-in Speakers
- 3-Year Warranty

VWZ VZ19CME

19.5" HD Resolution

VWZ VZ22CME

21.5" Full HD Resolution

VWZ VZ24CME

23.6" Full HD Resolution



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PADEST. AUD. | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK

EverFocus®



EVE ESK1000

TRIPLETT Test Equipment & Tools



TRP 8071

EverFocus®



EVE PALUN01

VIGITRON



VIG VI0021

VIGITRON



VIG VI2001

DSC



DSC TL150

DSC



DSC TL250

IP Camera Test Monitors:



IP/Analog Camera Test Monitor

NEW GST IPLCDTST7HD

Super Charged LCD Test Monitor IP Camera ONVIF Device Manager and AHD/TVI/CVI & Analog CVBS

- IP, AHD, TVI, CVI and Analog CVBS Capable
- Composite Video Input and RS485 PTZ Controls
- Bright 7" Capacitive LCD Touchscreen
- ONVIF Device Manager & 3rd Party IP Camera Apps
- Wi-Fi Connectivity Support, Web Browser Function
- UTP Continuity Tester
- Built-in Monitor Stand
- 12VDC 1A Output, PoE Injector or Pass Through
- Rechargeable Lithium Battery



EVE ESK1000

IP Sidekick, multi-functional IP utility tool; PoE, 12VDC, and USB power output

- Provides the ability to troubleshoot camera lens and display on installation site
- Streamline the process of a new IP camera installation
- Small and compact for portability
- High capacity power with lithium batteries (18650 type)
- Equipped with external Wi-Fi router with a built-in DHCP server
- Supports EF Sidekick mobile app for iOS
- Multi-function use: smart phone charger (USB output) or wireless AP provider
- LED indicators for Power, PoE and charging status
- PoE and DC Power Supply



TRP 8071

CamView™ IP Pro+, Ruggedized IP & Analog NTSC/PAL, AHD, and HD-TVI Camera Tester with Built-In DHCP Server

- Works with the most popular IP* & NTSC/PAL, AHD, and HD-TVI Analog cameras
- Works with or without a network. Built-in DHCP server allows you to:
 - Set & Assign IP addresses to cameras
 - Auto-detect IP settings on networks
 - Ping, Sniff, List Subnet Powers IP cameras—no need for external PoE
- No need to download Apps or manufacturer-specific software
- IP camera tests including: discover the camera, view camera's video, configure camera's parameters, etc.
- Record, save, and export full IP camera reports
- Ethernet Tests including:

- 10M/100M/1G Ethernet Link Test
- Packet Loss Test
- Ethernet Loop Detection, etc.

- Powers Analog cameras—12 VDC @ <2A
- Analog Camera Test & RS485 PTZ Control Test
- TDR cable tests
- Intuitive user interface
- Compact, lightweight, & ruggedized for real-world use



TAT TOM0431P

4.3" Universal OLED Test Monitor for IP/Analog Cameras, PoE

- Tests for wire runs
- Internal battery with charger included
- Works with multiple IP camera brands
- USB 2.0 for upload of additional brands via the Tatum website as they become available
- 4.3" OLED Daylight viewable display with touchscreen
- Includes:
 - Velcro wrist strap for hands free operation and leather carrying case
 - MicroSD Card Slot & 8 gig SD card & USB port for storage of snapshot and video
 - Internal battery with charger included
 - 3 year warranty

Processing Equipment:



EVE PALUN01

PoE-Powered video balun

- No external power required
- No re-wiring necessary: Implement IP cameras with existing Coax cables
- Flexible and secure installation: two eyelets for screws offer a stable mounting platform
- Easy Installation: slim and compact design provide simple integration
- Rugged design with splash-proof casing
- End-to-end connection of up to 1148ft/350m



Ethernet over 2-wire/Coax Systems (Eo2)

Ethernet over 2-Wire Eo2™ Transceiver is a compact media converter capable of transmitting 10/100 Base T Full Duplex Ethernet up to 1,000ft (305m) over 4-pair Cat5 UTP, 750ft (228m) over 18/2, or similar; 500ft (150m) over Shielded Twisted Pair. One NVT Eo2™ transceiver at the network-end can support up to four remote Eo2 transceivers and their connected IP network devices.

- NVT EC1701UK1H** 1 Camera Kit
- NVT EC1701UK2H** 2 Camera Kit
- NVT EC1701UK3H** 3 Camera Kit
- NVT EC1701UK4H** 4 Camera Kit

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.



VIG VI0021

ViewMate PoE Camera Setup Tool

- Provides a simple way to setup PoE powered IP cameras
- Maintains PoE power to the IP camera while making a local Ethernet connection to a laptop to view the camera image
- Measures and displays PoE voltage and power at the camera
- 10/100BASE-T compliant with integrated network crossover
- Compatible with IEEE 802.af/at and most non-standard solutions up to 30W
- Does not require external power source, uses PoE power from the network
- Speeds up the IP camera installation
- Limited lifetime warranty

VIG VI2001

Ethernet Surge Protector

- Innovative direct in line port plug in module saving valuable equipment space
- Ability to choose only ports that require extra protection
- The best protection for standard and extended UTP Ethernet runs
- Provides additional port protection for cameras, DVRs and NVRs
- Compatible with 10/100/1000 BaseT port
- Does not require extra ground cable
- Compatible with PoE 802.3af and 802.3at
- Tested and certified to EN61000-4-5 and EN55024 surge standards



Camera Encoders

ILX TVE400

TruVision® Encoder 4-channel analog to IP

ILX TVE800

TruVision® Encoder 8-channel analog to IP

ILX TVE1600

TruVision® Encoder 16-channel analog to IP



CSI AP300M

300Mbps, 5.85 Ghz Outdoor Point-to-Point AP with DIP Function

- Point to point direct networking between camera and recorder/viewer
- Signal up to 7000' line of sight
- Includes ball joint mount with wall and pole mount attachments
- Sold each, used in pairs
- Each access point requires PoE powered by AC adapter (included)

NEW CSI APRPT

300Mbps, 2.4Ghz Outdoor Wi-Fi Access Point or Repeater

- Extends the range of Wi-Fi ready

equipment beyond typical performance range with a signal up to 300'

- Includes ball joint mount with wall and pole mount attachments
- Sold individually
- Each access point requires PoE powered by AC adaptor (included)

NEW CSI WIFIMOD

Wi-Fi Adaptor for IP Camera

- Converts Speco IP cameras to Wi-Fi
- Dual-band Wi-Fi (2T2R 802.11n)
- Easy setup through mobile app – no need to log into the camera through a web viewer to connect it to an access point
- PoE for providing power to the camera
- Works with Speco Connect
- 2 year warranty

CSI OS102

Dual-Codec H.264 & MJPEG 1 CH. Video Server

- Dual-codec (H.264 & MJPEG)
- Multi-profile streaming
- Small form factor
- Ultra-compact design
- ONVIF support
- 2 year warranty

CSI DSWFUSB

USB Wireless Access Point

- Wireless access point for viewing and configuration of Speco DVRs and NVRs
- Compatible with DS and NS series DVRs



MIC ENC

MiniLinkVideo server/Encoder

- Encode CIF to D1 video up to 30fps MPEG 4 Compression
- Compatible with MiniLink wireless Ethernet System
- Dual stream video via LAN and WAN ports
- PoE and DDNS supported
- 2 Alarm I/O ports
- Plug and Play

MIC DEC

MiniLink Decoder

- Decodes CIF to D1 up 30fps from paired ENC Encoder
- LAN and WAN ports
- PoE and DDNS supported
- Plug and Play

Alarm Signaling Equipment:



BOS C900V2

Universal IP Dialer capture module



T-LINK IP Communicator Series

DSC TL150

Residential IP Communicator for PC1555/PC5010/PC1616/PC1832 controls

DSC TL250

Commercial IP Communicator for Power Series 864/1864 and Maxsys

DSC TL255NA

T-Link Internet Alarm Communicator – IMPASSA

- Compatible with IMPASSA control panel
- Panel remote uploading & downloading via internet/intranet using DLS 5
- Programmable using DLS 5 or keypad
- Supervision heartbeat via internet/intranet
- 128 Bit AES Encryption
- Full event format
- SIA and Contact ID protocol

DSC TL2603GRUSA

Dual Path IP/Cell Communicator for Power Series

DSC TL260RNA

Internet Communicator for Power Series

DSC TL265

T-Link Internet/Intranet Alarm Communicator for ALEXOR

- Compatible with ALEXOR Wireless Panel
- Fully redundant Internet/Intranet alarm communication
- Integrated call routing
- Panel remote uploading/downloading support
- Supervision heartbeats via Internet/Intranet
- 128-bit AES encryption via Internet/Intranet
- Full event reporting
- SIA or Contact ID format
- PC-Link connection
- Approvals: UL, ULC, CE

NEW DSC TL2803GREUSA

PowerSeries Neo Internet and HSPA Dual-path Alarm Communicator

- Fully redundant Internet and Cellular dual-path alarm communication
- Integrated call routing
- Panel remote uploading/downloading support via Cellular and Internet
- Supervision heartbeats via Cellular or Internet
- 128-bit AES encryption via Cellular and Internet
- Full event reporting
- SIA and Contact ID protocol
- SIM Card (included)
- Remote activating and programming through C24 Communications
- Programmable via DLS or keypad
- UL standard & encrypted line security
- ULC passive or active line security levels
- Active Cellular account is required to use Internet function
- Signal strength and trouble display
- PC-Link connection

COMPANY - WIDE HOURS
MONDAY - FRIDAY, 7:30AM - 5:30PM





INTERACTIVE | CENTRAL VAS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK



IPD BATCDMA

- Visual verification over Cellular or Internet
- Communicator can be housed in separate cabinet using PCL-422 Communicator Remote Mounting Module
- Command and Control via SMS
- Supports 3rd party integration via IP
- R model supports 3rd party integration option via RS232 serial connection

NEW DSC TL280E

Internet Security Alarm Communicator

- Panel remote uploading/downloading via Internet
- Programmable using DLS 5 or keypad
- Supervision heartbeat via Internet
- 128 Bit AES Encryption
- Full event reporting
- SIA and Contact ID protocol
- Visual verification over Internet
- Communicator can be housed in separate cabinet using PCL-422 Communicator Remote Mounting Module
- E model provides expanded user support and up to 4 Ethernet integrations with PowerSeries Neo panels V1.2 and higher



IPD BATCDMAWIFI



IPD BATWIFI



IPD GATEWAY30



EYZ EVL-4CG

NEW DSC TL280RE

Internet Security Alarm Communicator

- Panel remote uploading/downloading via Internet
- Programmable using DLS 5 or keypad
- Supervision heartbeat via Internet
- 128 Bit AES Encryption
- Full event reporting
- SIA and Contact ID protocol
- Visual verification over Internet
- Communicator can be housed in separate cabinet using PCL-422 Communicator Remote Mounting Module
- R model includes RS232 serial integration option
- E model provides expanded user support and up to 4 Ethernet integrations with PowerSeries Neo panels V1.2 and higher
- Refer to www.dsc.com for complete integration options

DSC TL300

Universal IP Communicator

DSC TL300CF

Commercial Fire Universal IP Communicator

DSC SG-System I

Multi-Format Receivers are a perfect fit for smaller central stations and proprietary application. They have a small foot-print and can be rack mounted.

- Two POTS line connections
- Patented ANI and DNIS reception, Automatic Handshake Selection, Caller ID capability, and virtual configurations
- Up to 63 different profiles and up to 8 different handshakes per profile
- Continuous verification of computer/receiver links
- Integrated scheduled receiver line card testing via the SG-Systems Console
- Optional support for 512 IP communicators
- Flash download software upgrades
- Optional rack-mount in standard 19" rack with the SG SIIRMK

DSC SGSYSTEMI POTS version



NAP NLMOD



FL IPGSM4G

DSC System II Single

Single Line IP Receiver Remote monitoring solution ideal for proprietary applications

- 128 bit AES encryption
- Supports 1024 TLink accounts (TL150, 250, 300) 512 can be supervised
- TCP/IP, USB, or serial outputs to automation software
- Menu driven, 40 character, 2 line LCD display with blue backlighting for manual mode
- 4 buttons for manual programming and acknowledgements
- Onboard flash memory and DSP for future upgrades

DSC SGSYSTEMIIP IP Version



IPD BAT

Broadband Alarm Transmitter

ipDatatel, Inc. Broadband Alarm Transmitter (BAT) provides signaling to your central monitoring station, your alarm company's office, and to your customer, automating many central station functions, such as the routing of open/close, trouble, supervisory, and test signals. Connects a Honeywell Vista® or the DSC PowerSeries alarm panel to your monitoring station via broadband Internet

- No Telephone Lines Needed
- Arm/Disarm Alarm via Internet Keypad
- Remote Programmable
- Transmits Contact ID to Any Central Station
- Transmits SIA/FSK Databurst to Any Central Station
- Telephone Notification (automated voice)
- Text & email messaging To Users
- Super-Fast Transmission Speed
- Easy to Install and Set-up
- Automatically Acquires IP Address
- Very Affordable

APPLICATIONS:

- Alarm Signal Reporting
- Open/Close Signal Reporting
 - Monitor employees by user code
- Latch-Key Reporting
 - Monitor when your child arrives home
- Polling Loss Notification
- Supervisory by Zone
 - Monitor a liquor or gun cabinet in your home and many more uses.

IPD BATCDMA

Dual Path Cellular/Broadband Communicator with Interactive services and Zig Bee control.

The Cellular BAT replaces outdated conventional phone lines to provide high-speed dual path of IP Internet and Cellular alarm transmission. Alarm transmissions are made using Contact ID format, and this format can be sent to your Central Station via the PSTN to your alarm receiver or can be transmitted directly by IP. Alarm signals such as open/close, trouble, supervisory, latch-key, and monitoring of special devices, can be routed directly to your Central Station or to the customer. Transmissions such as open/close signals can be filtered to the Central Station reducing costs on monitoring fees.

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

IPD BATCDMAWIFI

Communicates all alarm events over the Internet and Verizon CDMA cellular network to any CS in full Contact ID. Sends Instant notifications of all events. Offers a full featured Virtual Keypad. Runs through Wi-Fi Network or Ethernet cable from panel to router/modem for Internet connectivity. Provides dual path for alarm signals and Interactive Services. Can be used on CDMA and/or Internet only.

IPD BATWIFI

Wi-Fi Broadband Alarm Transceiver

ipDatatel's Wi-Fi Broadband Alarm Transceiver provides secure and cost-effective IP alarm transmissions through your customers Wi-Fi router, full featured virtual keypad, smart device automation, and notifications.

IPD GATEWAY30

Gateway with Power Supply, Ethernet Cable, and Plastic Box.

- This is a hub which connects to IP cameras with API and wireless smart devices (Thermostats, Lighting, Appliance, and Lock Controls).
- 100-125 ft Range.
- Supports both Z-Wave.



Take Control. The new EnvisaLink 3 is a powerful TCP-IP based bus-level interface to DSC PowerSeries panels and Honeywell Vista panels. It allows your customer to view the status of and even control their alarm panel through a standard web-browser or smart-phone. VOIP Friendly.

EYZ EVL4CG

Envisalink 3 IP Communicator for DSC and Honeywell Controls

- No Network Setup. Little or No Programming and No Monthly Fees!



NAP NLMOD

Net Link Internet/Intranet Alarm Reporting Module - Interfaces with the P816, P1632, P3200, P9600, and X255 panels. Provides primary and/or backup reporting of alarms over TCIP/IP network and/or telephone lines. No dedicated central station receiver required. Dynamic IP addressing and encryption. Supports network based automation routines. Easy archiving and review of event histories by account - Download panel programs



FL IPGSM4G

IP Internet & GSM (4G/3G/2G) Dual Path Communicator



SIL SKIP2UD

Fire IP Up/Down Loadable Communicator

Use the IP Communicator to save money and increase response time. Monitor your fire alarm systems over the internet by connecting the Silent Knight IP Communicator to any Silent Knight FACP or dialer

- Listed to UL Standard 864.
- SKIP2UD allows up/downloading of the IntelliKnight™ 5820XL and 5808 addressable fire alarm control panels.
- UL 864 Ninth Edition prohibits downloading to a panel without entering a local panel password. Uploading is permitted at any time without entering a password.
- Eliminates the cost of two dedicated phone lines. Only the customer's shared IP equipment is required.
- Can use newer low-cost, non-analog, digital telephone services such as cable or fiber optics.
- Increases connection supervision to the central station from the once-a-day test signal to once every 30 – 90 seconds.
- Requires no change to the existing panel configuration.
- The IP Communicator connects directly to the primary and secondary analog panel telephone ports.
- Fast alarm transmission (less than 10 second transmission time).

SIL IPDACT2

IPDACT Communicator

- Listed to UL Standard 864 for Silent Knight fire alarm control panels
- Eliminates the cost of two dedicated phone lines
- Can use newer low-cost, non-analog, digital telephone services such as cable or fiber optics
- Includes IPENC enclosure

SIL SKIP2

IP Communicator Kit

- Listed to UL Standard 864 for Silent Knight fire alarm control panels
- Eliminates the cost of two dedicated phone lines
- Can use newer low-cost, non-analog, digital telephone services such as cable or fiber optics
- Allows remote up/downloading of 5820XL and 5808 FACP's
- Includes IPENC enclosure

SIL SKF485C

SBUS Wire to Fiber Converter Module

- Fiber solution allows one fire alarm control panel to protect multi-building applications eliminating the monitoring costs of multiple phone lines
- Eliminates the risk of lightning damage caused by running copper wire between buildings
- SK-F485C does not take up an SBUS address and allows for long distance location of SBUS accessories
- UL listed

IP Access Control:



TruPortal™ Access Control:

TruPortal™ access control solutions have been engineered and designed to install quickly and easily right out of the box. These units are ideal for small- to mid-size applications, with a user-friendly Install Wizard™ feature to assist with each step. Interlogix made configuring TruPortal™ solutions simple and efficient for you and intuitive and convenient for your customers.

ILX TPADD2D

2-Door Add-on Kit TruPortal™ 2-Door Expansion Board (UL-listed enclosure with integrated 12V 4A power supply, 120VAC)

ILX TPADD2D2R

2-Door Add-on Kit with Two (2) Readers TruPortal™ 2-Door Expansion Board (UL-listed enclosure with integrated 12V 4A power supply, 120VAC, includes two (2) T-100 series Readers)

ILX TPADDIO

TruPortal™ I/O Expansion Add-on Kit. Consists of a TruPortal™ 16 input, 8 output I/O Expansion Module installed in a UL listed enclosure w/4 AMP power supply.

ILX TPRDR100A

TruPortal™ T-100 Series Reader (minimullion mount, ProxLite/HID,® 3 covers, 18"/45.7cm pigtail wire, Wiegand output)

ILX TPRDRLRN

Dual-Frequency Enrollment Reader

2-Door Base Systems

ILX TPSYS2D

TruPortal™ 2-Door Base system. Consists of a TruPortal™ System Controller installed in UL listed enclosure w/ integrated power supply / standby battery charger.

ILX TPSYS2D2R

TruPortal™ 2-Door Base system with readers. Consists of a TP-SYS-2D bundled w/ (2) T-100 readers and (5) HID Prox keyfobs.

ILX TPADD1DIP

TruPortal™ IP-Based Single-Door Add-on Kit. Consists of TruPortal™ 1-door interface module installed in a UL listed enclosure.

ILX TPADD2DBRD

TruPortal™ 2-Door Interface Module. Board only. For installation into an existing TP-ADD-2D, TP-ADD-2D2R or TP-ADD-4D.

ILX TPADD4D

TruPortal™ 4-Door Add-on Kit. Consists of large TruPortal™ enclosure (TP-CTX6 w/6 AMP Power Supply) prepopulated with two 2-door add-on boards (TP-ADD-2D-BRD). Note this enclosure can support up to 4 other Add-on Boards, TP-ADD-IO-BRD or TP-ADD-2D-BRD).

INTERACTIVE | CENTRAL VACS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUD. | STRUCT. WIRE | TOOLS | INFO

IP NETWORK IP NETWORK



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK

Linear



IEI MAX3SYS

Credentials 125 KHz - Cards & Keyfobs

ILX TPRXCLAM50PK

TruPortal™ Credential - Hid Proxcard II Clamshell Design Cards - 50 Pack

ILX TPRXKF50PK

TruPortal™ Credential-Hid Prox Keyfobs - 50 Pack

ILX TPRXISO50PK

TruPortal™ Credential-Hid Prox Iso Cards - 50 Pack

Linear



IEI MAX3MOD

NOVA.16 Radio Key Dual Technology Access Kits

Secura Key offers SK-NET™ with NOVA.16 control panels in a variety of specially-priced 4-door access control kits, which include the SK-NET basic software and manual, a NOVA.16-LE control panel, a power supply, and four smart readers. The kits include everything you need to control access to four doors except for cabling and door locking devices.

SKC SKMRCP4RKDTM

Includes four ET8-SR-X-M Mullion Readers (black)

Linear



IEI SEGM

Linear

BOSCH
Invented for life



BOS APCAEC21UPS1

eMerge Browser Managed Security Platform from IEI.

IEI EM50P

Network control module with power supply and enclosure

- Controls up to 32 readers
- 5000 users
- Email/SMS
- NAS backup
- Burglary interface
- Enterprise capable

infinias
Simple. Scalable. Secure.
POWERED BY I3+LOGIC



INF SEIDC32

IEI EMACM

Access control module for 2 readers, 4 inputs and 4 outputs

IEI EMIN

Supervised Input Module with 8 inputs

IEI EMOUT

Relay output module with 8 outputs

infinias
Simple. Scalable. Secure.
POWERED BY I3+LOGIC



INF SDOORKITWHST

IEI EMEXN

Expansion node card in an enclosure with power supply

eMerge E3-Series

eMerge Essential and Essential Plus - Affordable and Scalable Browser-Based Access Control

Represents the next step in the evolution of Linear's access control technologies, delivering faster set-up, enhanced features, and industry-leading scalability that outperforms the competition and provides best-in-class value and lowest cost of ownership. The eMerge Essential and Essential Plus embedded browser-based network appliances make advanced security technology reliable and affordable for any entry-level access control application.

LIN ES1C

Emerge Essential 1 door access system

suprema
ENTERTECH SYSTEMS



ENT FSM

LIN ES1CB

Emerge Essential, 1 Door Access Control w/ Prox Reader

LIN ES4C

Emerge Essential 4 door access system

LIN ES1M

Emerge Essential Plus 1 door access system

LIN ES1MB

Emerge Essential Plus IP Access Control w/Prox Reader

LIN ES4M

Emerge Essential Plus 4 door access system

LIN ES4MB

eMerge Essential Plus 4-Door 4-Reader Access Control Platform Bundle

- eMerge Essential Plus 4-door system bundle, includes four P-300HA proximity readers,
- Up to 1,000 cardholders with up to 8,000 cards, up to 8 readers,
- Upgradable up to 4 doors and 8 readers with license keys,
- UL294 Listed 5-amp supervised power supply (backup battery not included),
- Optional PoE power with E3-PoE module,
- Housed in a locking metal cabinet with integrated tamper switch

LIN ACM4D

eMerge Elite 4-Door Access Control Module

- eMerge Elite Expansion Access Control Module, adds 4 readers, 8 inputs, and 8 outputs to system, plugs-into eMerge Elite-36 systems mounted in large or extra large cabinet.

LIN ES1DL

Single door Add License

LIN ES1DLB

eMerge Essential 1-Door License with one Reader Bundle

eMerge Essential 1-door license upgrade, includes one P-300HA proximity reader, and adds one additional door and two additional readers to eMerge Essential system.

Controls in Compact Cabinets

LIN EL362C eMerge Elite-36, 2-Door Access Control Platform

LIN EL364C eMerge Elite-36, 4-Door Access Control Platform

Controls in Standard Cabinets

LIN EL362M eMerge Elite-36, 2-Door Access Control Platform

LIN EL364M eMerge Elite-36, 4-Door Access Control Platform

NEW LIN EL364MB

Elite-36 4-door system w/4-reader bundle, metal

eMerge Elite-36 4-door system bundle, includes four P-300HA proximity readers, up to 20,000 cardholders with up to 80,000 cards, up to 8 readers, browser-based management via embedded Web server, upgradable up to 36 doors and 72 readers with license keys and plug-in modules or expansion nodes, easy setup wizard, optional PoE power with E3-POE module, housed in a locking metal cabinet with integrated tamper switch.

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

NEW LIN EXN4MB

eMerge Elite 4-Door 4-Reader Expansion Node Bundle

eMerge Elite Expansion Node bundle, includes four P-300HA proximity readers, 4 Reader ports, 8 Inputs, 8 Output relays, and optional POE, housed in a locking metal cabinet with integrated tamper switch.

LIN E3POE E3 PoE Module

LIN P300HAS Mullion multi-tech reader for Emerge Essential

LIN P500HAS Single Gang multi-tech reader for Emerge Essential

LIN P640HAS Single Gang multi-tech reader w/keypad for Emerge Essential

LIN PIP12V60W

Plug-in 12VDC 60 watt power supply

IEI SEG1

Security Ethernet Gateway

- LAN/WAN (TCP/IP to serial) Interface Manage IEI access system from any PC on an enterprise network
- Efficient remote site management
- Utilizes existing network infrastructure
- 128 bit secure encryption
- Uses IEI's HUBSWR software v5.0 or higher

Max 3 Access Systems:

Updated version of the Max II with support for both in and out readers connected directly to the module

- Supports any Wiegand format up to 39 bits
- Supports LED and Sounder control
- Communicates in 1/3 less time as the Max II
- Added panel diagnostics for faster installation and improved trouble shooting. Expandable to 64 doors per site and unlimited number of sites.

IEI MAX3SYS

Max 3 Complete single door access control system kit. Contains Max 3 Door control and backplane to support 3 additional control modules in an oversized metal cabinet with cam lock. Includes XF1050 Proximity reader that is AWID, HID, xCreedID and Casi/Prox lite compatible; Hub Manager Professional access control software; 12/24VDC board power supply; AC transformer.

IEI MINIMAX3SYS

MiniMax 3 complete single door access control system kit. Includes; Metal locking cabinet, AC transformer, 12VDC 1 amp power supply, Max 3 door control module, Hub Manager Professional access control software, programming keypad, and XF1050 Proximity reader that is AWID, HID, xCreedID and Casi/Prox lite compatible.

IEI MAX3MOD

Max 3 Module single door access control module. MAX3MOD plugs into Max 3 backplane to expand system capacity one door at a time.

IEI SEGM

Secure Ethernet Gateway converts Ethernet to serial which enables IEI access systems to use existing corporate network infrastructures. It plugs in easily into Max3, HubMax II, MiniMax 3 and Hub Mini Max II backplanes.



BOSCH

Access Easy Controller

- 4 door expandable to 16 doors with options for up to 32 four state supervised inputs and 32 relay outputs
- No dedicated computer required
- Monitor, manage, and control from any computer regardless of operating system
- No software installation required
- Web based user interface via standard web browser
- Events, alarms, and power failure notification via E-mail or SMS - Remote access via Internet or serial modem dial-in.

BOS APCAEC21UPS1

Four door IP access control with CPU, enclosure, power supply, 4 door board, and software

BOS APIAEC214WR

AEC 2.1 Controller with 4 Wiegand readers + 8 I/O board

BOS APIAEC218180

8 In/Output Board for AEC 2.1 Controller



Infinias is now 3X Logic

Integrated PoE Access Control feature Intelli-M control

INF SEIDC32

Intelli-M PoE network single door controller with up to 2 reader control

INF SBASEKIT

Intelli-M Base software kit for up to 32 doors

INF SDOORKITWHST

Intelli-M Single Door Add Kit with Wiegand HID prox reader with Strike and Sensors

Simplified ordering and successful installation...One kit per door, with or without electric door strike plus one Intelli-M Access (S-BASE-KIT).

Intelli-M Single Door Kit includes following components:

- One S-EIDC32 eIDC - PoE network door controller
- One S-SMB-5075 Surface Mount Box
- One A-CRS-6005-GRY HID ProxPoint reader (Gray)
- One S-STRK-2400-05 electric door strike
- One GRI flush mount door sensor
- One GRI metal mount door sensor



ENT FSM

Suprema – FaceStation - Smart Face Recognition Terminal

Perfect combination of beauty and performance. Using Suprema's proprietary algorithms combined with state-of-the-art hardware, FaceStation provides near real-time template matching results. FaceStation comes with a wide array of features & functions, which can be accessed through an intuitive user friendly GUI. It can be used in both standalone or network environments.

ENT ACM2

BioStar ACM Third Party Access Control Integration Software

- Enroll up to 10 templates per user to ensure success
- Manage biometrics, PINs and cards effectively in one user profile
- 1:1 and 1:N verification tests
- View live enrollment feedback and scores
- Customizable Wiegand outputs/inputs up to 64 bit Wiegand
- Programmable Wiegand output for failed access
- Connect and configure up to 512 devices
- Manage authentication modes and options based on time and user
- Control matching types on a device basis, utilizing 1:N, 1:1, Template on Card and Server Matching
- Simple firmware management tools
- Real-time monitoring of biometric devices
- Exportable log lists
- Drill down reporting for system diagnostics
- Single/dual line LED controls
- Programmable buzzer control
- Programmable LED device indicators

ENT BEPHOC

BioEntry Plus Fingerprint IP Reader/Controller

BioEntry Plus is an IP based fingerprint access control device featuring easy installation and user friendly operations. Integrated with both fingerprint and proximity card, BioEntry Plus covers a full range of access control applications from a simple standalone door control to complex networked access control systems

ENT BEWHOC

BioEntry W Indoor/Outdoor Fingerprint IP Reader

The Suprema BioEntry Plus/W exquisitely blends the benefits of a next generation distributed IP system with the high level security provided by biometrics. Engineered by the World's leading biometric experts, the BioEntry Series offers unrivaled quality with exceptional engineering. BioEntry W takes the series one step further by encasing a world renowned product into an IP65 vandal resistance housing and adding PoE (Power over Ethernet) capabilities. It is truly the ultimate for outdoor biometric access control systems.



INTERACTIVE | CENTRAL VANS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK




ENT BIOMINI




ENT BSSE2




PAX 345-220-US




NET2 PAXLOCKS




PDK PM01ACP




PDK PM07EDCW




PDK PP08DRM

ENT BIOCON-PX

Biometric Integration Software License for Paxton
BioConnect from Entertech Systems allows for Suprema's biometric readers to be integrated with access control systems. Instead of having to manage badge records in two different systems (one for the access control panel and another for the biometric templates), BioConnect seamlessly syncs users between these two systems. Using a simple enrollment window, users can search for a user/badge and add biometric templates.

ENT BIOMINI

High Performance PC Fingerprint Solution

- World's best performing fingerprint algorithm: Top results in NIST MINEX tests and FVC
- FIPS 201 certified template extractor and matcher
- NIST certified interoperable template format standards (ANSI-378/ISO19794-2)
- Image Compression Standard (WSQ)
- Fast matching speed: 100,000 match within a second Multi-threaded code design fully utilizing multi-core CPU power
- Plug and play USB 2.0 high speed interface
- Supports multiple device handling
- 500 dpi optical fingerprint sensor
- Scratch free sensor surface
- BioMini SDK for easy application software development
- Supports MS Windows and Linux
- Supports multiple programming languages

ENT BSSE2

BioStar SE IP based Distributed Access Control
The BioStar system goes a step beyond conventional access control systems, by combining unique biometric identification with configurable access card capabilities. With its intuitive easy-to-use GUI and wizard type settings, BioStar provides comprehensive access control security for enterprise-level systems to small-to-medium sized systems.



Key benefits of Paxton Access systems

- Reliable, high quality systems: They are confident of their quality and back their components with a 5-year guarantee.
- Systems that are incredibly easy to use: Minimal training required for administrators.
- Systems that are designed to grow with your customer's needs: You can add doors as and when needed.
- Net2 Software: No hidden/unexpected costs or per seat licenses. Software can be installed on as many workstations as required.
- Free software upgrades..

Paxton BLU

Paxton BLU is a unique technology to deliver access control services in the cloud. Hosted software is ideal for those projects that require central configuration and managed services of multiple customers, sites, doors and users. Paxton's BLU access controller provides a more secure environment. Customer elects a primary communication to the panel by choosing Ethernet or GSM. Sites can be managed from any device, anywhere in the world. Innovation and simplicity with Paxton BLU.

PAX 838-501-US

Paxton BLU Master Controller In Enclosure

PAX 838-601-US

Paxton BLU 2 Door Master Control

PAX 838-605-US

Paxton BLU GSM Modem Kit

PAX 838-621-US

Paxton BLU 2 Door Slave Control

Net2 Entry

Paxton combines video, access control and intercom into one simple totally IP solution!

- Just 3 components simply plug together
- IPv6 auto detect – all devices find each other on a network
- PoE enabled – one Cat5-6 cable for data and power
- Handset or hands free at monitor station
- Touchscreen monitor
- Weather proof video intercom station with embedded prox reader
- Easy integration with Net2 access control

PAX 333-110-US

P38 Prox Reader Small Mullion, Includes: Gray & Off White Covers

PAX 337-286-US

NET2 Entry Monitor PoE Only

PAX 337-727-US

NET2 Entry Access Control Unit, Includes: 4PT PoE Switch

PAX 337-837-US

NET2 Entry Intercom Panel, PoE

PAX 337-900-US

NET2 Entry Single Door Kit, Includes: Panel/Control/Monitor

PAX 337-952-US

NET2 Entry Flush Vandal Resistant Single Door Kit

PAX 337-957-US

NET2 Entry Flush Vandal Resistant Intercom Panel

PAX 345-110-US

P50M PROX Reader Mullion Mount, Includes: Gray & Off White Covers

PAX 373-110-US

P75 PROX Reader Wall Mount, Includes: Gray & Off White Covers

PAX 514-326-US

NET2 Desktop Enrollment Reader USB

PAX 682-230-US

1 Door Expansion Kit PoE; Includes

- (1) 682-721-US; Net2 Plus with PoE Power Supply in Metal Cabinet
- (1) 345-110-US; P50M Reader

PAX 682-290-US

2 Reader System Start Kit w/PoE PS NET2+/ENR Reader/P50 Card Software

PAX 682-493-US

NET2 PLUS Controller PCB Only

PAX 682-721-US

NET2PLUS Controller in Cabinet w/PoE Power Supply/Outputs

PAX 682-810-US

NET2 PLUS Controller Cabinet with Power In/Outputs

PAX 682-825-US

2 Reader System Start Kit w/PS NET2PLUS/ENR Reader/P50 Reader/Card

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.



BRI ACS5000S

Brivo - Eight Door/Ten Floor Controller

A flexible solution to control numerous doors from a central location. With enough mounting space for a second Eight Door Controller you can connect a total of sixteen doors or twenty elevator floors.

NEW PDK PP08CPC

Eight io Door Controller – Ethernet

NEW PDK PM07EIOEE

Eight io Door Expander – Ethernet

NEW PDK PM07EIOEW

Eight io Door Expander - Wireless

NEW PDK PM07EIOW

Eight io Door Controller – Wireless



brivo®

Brivo System produces IP solutions for your access control needs. Their line-up features the Online Access Control System (ACS). This system is expandable to up to 30 doors, up to 5000 credentials per control panel, 50,000 event buffer, up to 14 expansion door boards or Input/Output boards, 128 bit encryption, 8 supervised inputs expandable to a maximum of 120 per panel, and 6 outputs expandable to 118 maximum per panel. All programming and system management is done via an easy to use browser interface. The system can provide up to the minute event notification via email, pager, or cell phone.

BRI ACS5000S

Main control with two reader control board, power supply, transformer, battery

BRI ACS5000EXP

Expansion chassis to accommodate 2 expansion boards in an enclosure with power supply, transformer and battery

BRI ACS5000DB

Two reader expansion door board

BRI ACS5000IO

Input/Output expansion board with 8 inputs and 8 outputs



THE EDGE SOLO - Network based interface and standalone access control. Give your customers access to their doors from anywhere using a standard web browser. A 1000 card capacity and 5000 event buffer fits most applications.

HID 83000CKE

EDGE Plus Solo IP Based stand-alone single door access control solution - interfaces with any Wiegand reader.

HID 83120

EDGE Solo IP Based stand-alone single door access control solution with integrated RP40 iClass smart card reader.

HID K83000BKEPC

EDGE SOLO Kit w/Multi-Class Reader

Package includes:

- ES400 IP Single door controller,
- RP15 Multiclass reader and 20 iClass cards.
- The Multiclass reader can read both iClass and standard HID proximity cards

HID K83000BKERC

IP Access Control reader kit

Kit includes:

- (1) Edge Solo - ES400,
- (1) R15 iClass reader,
- (20) iClass 2k cards programmed w/ 37bit H10302 format



KAN KT400

Ethernet-Ready Four Door Controller

- Supports four readers and expand inputs, outputs, and relays with the addition of expansion modules
- Onboard Ethernet 128-bit AES-encrypted communication with the EntraPass system ensures a high degree of network security
- Anti-Passback feature
- 100,000 card capacity and up to 20,000 concurrent events in stand-alone mode
- Removable terminal blocks
- 256 Inputs and Outputs
- Verify and configure IP setting with built-in web configuration page
- Supervised door lock outputs with internal or external power supply

KAN SKSE402

KT400, 4-Door Access Control Starter Kit

- Includes: EntraPass Special Edition Software USB Key
- KT-400 Controller
- (3) P225XSF Readers
- (1) P225KPXS Reader
- USB-485 Communication Interface
- TR1675 16VAC/75 VA Transformer
- KT-BATT-12 12V 7 AH Battery
- (5) P40KEY Keyfobs

KAN EK400

4-Door Expansion Kit

- Includes: KT-400 Controller
- TR1675 16VAC/75 VA Transformer
- KT-BATT-12 12V 7 AH Battery

KAN EK402

4-Door Expansion Kit

- Includes: KT-400 Controller
- (4) P225XSF Readers
- TR1675 16VAC/75 VA Transformer
- KT-BATT-12 12V 7 AH Battery

KAN KT1

One Door IP Controller

The KT-1 single door controller provides simplicity at the edge of an IP network. With its single button programming and on-board Ethernet port for direct network connection, the KT-1 controller is up and running in just a few easy steps.



AIP ISDVF

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

KAN KT1M

Ethernet-ready one door controller (KT-1-PCB) and metal cabinet (KT-1-CAB-M), 12VDC/PoE

KAN EK1RDR

Expansion Kit

KT-1 and ioProx reader (P225XSF).



KER NetXtreme

TCP/IP Based Access Control Solution - This fully scalable IP Access Control solution features SQL Compliant software with Thin Client/Server Architecture for easy software transportability. It can be used by multiple concurrent operators across multiple concurrent sites. Each Node can have 50,000 cards and thousands of doors. It can be wired into an existing LAN or a parallel CAT 5 network.

KER NXT2D

2 Door System controller includes enclosure and software

KER NXT2D-MS

2 Door/4 Reader NXT Controller with Mercury Powered Option

Manages 2 doors access and egress (4 readers) when used with NXT prox readers, or 2 doors (2 doors access or 1 door access + egress) when used with MS or Wiegand reader types, with enclosure **KER NXT4D** 4 Door System controller includes enclosure and software

KER NXT4X4

Optional local door controller with 4 supervised inputs and 4 general purpose form C outputs

KER NXT4KIT

Complete 4-Door Access Control System

- (1) NXT Software CD w/ one Client
- (1) NXT-4D-X, Four Door Controller
- (1) NXT Power Supply
- (4) NXT-3R Mullion Readers
- (4) NXT-C Clamshell Prox Cards
- (4) NXT-I ISO Prox Cards w/o Mag
- (4) NXT-K Proximity Keytags
- One Lot Enclosure and Hardware

KER NXT4D-MS

4 Door/8 Reader NXT Controller with Mercury Powered Option

Manages 4 doors access and egress (8 readers) when used with NXT prox readers, or 4 doors (4 doors access or 2 door access + egress) when used with MS or Wiegand

reader types, with enclosure **KER NXTS Multi Technology Card**

- ISO Thin, just 0.031" (0.8 mm)
- Designed for photo ID printing
- With Magnetic Stripe
- Can also print Bar Codes
- Unique, non-duplicated ID codes
- 128 bit Encryption

KER NXTRM3

Reader interface module for adding standard Wiegand reader to NetXtreme system

KER NXT3R Mullion Style NetXtreme prox reader

KER NXT5R Wall Switch Style NetXtreme prox reader

KER NXT1R Euro Mount Style NetXtreme prox reader

Credentials for NetXtreme prox readers:

KER NXTC Clamshell card

KER NXTK Key tag

KER DNET500UP15

Licenses for upgrading PXL500 to Doors. Net (from Doors32). Software for 1 to 5 controllers.

- Upsell your existing customers by showing them how to get more from their system and extend its life by upgrading to Doors. NET Software.

KER LAN520AES

LAN port RS232 to Ethernet Converter, Encrypted

This small option board plugs into any PXL-500, PXL-510 or Time and Attendance providing an interface to a customer's Ethernet backbone. The unit acts as a 100baseT gateway from the master of any PXL-500 based system to the rest of the RS485 network.

Call SES today to learn more about this highly flexible IP Access Control Solution.



KEY CIM

Computer Interlink Module

The Keyscan CIM establishes communication links for each control panel with CAN Bus communication protocol using one twisted pair cable for server to ACU communication and another twisted pair for global communication, all standard CAT5 cabling

KEY NETCOM2P

Network Communication Board

- This plug on TCP/IP communication adapter provides network connectivity for the CB485 communication board
- Delivers multiple ACU communication to PC over a LAN/WAN (TCP/IP)
- Plugs into socket on CB-485
- Suitable for 10/100 Ethernet/Fast Ethernet applications
- Uses static IP address
- Encrypted version available (NETCOM6P)

KEY NETCOM2

Network Communication Interface

- Ideal for providing TCP/IP LAN/WAN connectivity for a single ACU
- Uses a Static IP
- Suitable for 10/100 Ethernet/Fast Ethernet applications



SES is a proud distributor for RBH Access Technologies. RBH offers a complete line of access control systems.

Their Integra 32™ software features:

- Up to 10 Simultaneous full function clients
- Up to 99 System operators
- Up to 64 Integra 32™ Controllers
- Up to 128 Access Points
- Up to 512 inputs and outputs
- Up to 5000 cards per panel, expandable to 8000 cards
- 32 Schedules with 8 time zones each
- Integra 32™ Software offers complete network flexibility: TCP/IP, LAN, WAN

Integra 32™ Software is available in a variety of "one box" kit solutions such as:

RBH URC2008

Elevator Control for up to 8 floors

RBH LIF200

Network module connects up to 16 panels

IP Addressable Video Intercoms:



IS Series - IP Security Intercom

Features:

- Unlock doors & communicate remotely from anywhere on the network and communicate easily between stations
- Program daily bulletins & bell schedules on or off site making it ideal for schools and school districts
- Broadcast emergency announcements
- Install up to 20 doors -20 masters -120 rooms together using a Cat 5e/6 cable

AIP ISDV

Wide angle, digital Pan Tilt/Zoom camera door station, zinc die cast, surface mount

AIP ISDVF

Wide angle, digital Pan Tilt/Zoom camera door station, stainless steel, flush mount

AIP ISSS

Audio only door/substation, stainless steel, flush mount

AIP ISMV Video master station

AIP ISRS Audio only room/substation

AIP ISCCU Central Control Unit for 4 doors-4 masters

AIP ISSCU Add-on Control Unit for 8 doors-8 masters

AIP ISRCU Room Sub Control Unit for 30 rooms

AIP ISPUUL Power supply

Expand to up to 160 doors-160 masters-960 rooms per system with up to 32 systems total globally and 1,024 IP Addressable devices. Bring the IS Series onto a LAN/WAN network



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK



AIPHONE
AIP ISIPDV



Paxton
PAX 337-405-US



ring
RING 88LP000CH000



ring
RING VIDEO DOORBELLS



ALARM.COM
ALM ADCVDB101



interlogix
United Technologies
ILX TPWEM01



WINLAND ELECTRONICS, INC.
WIN EA800IP

All-in-One Box Solution IS-IP Series IP Video Intercom Kits

- All-in-one communication system to control video entry, public address, access control, and scheduled bell systems
- Uses new or existing CAT-5e / 6 network infrastructure (multicast must be enabled on the network)
- Program system functions via browser
- For Local IP and Local Hardwired - Basic conversation plus full range of exchange functions including time based call forwarding, scan monitoring, emergency call, priority call, and unit paging
- IP addressable stations available for easy network communication
- PC master station records audio/video directly to PC

AIP ISIPDV - IP addressable, wide angle, digital PanTilt/Zoom camera door station, zinc die cast, surface mount

AIP ISIPMV - IP Addressable video master station Control units



Paxton

Net2 Entry IP Video Intercom

- Now with Genuine HID Technology
- Fully integrated access control and PoE video intercom connected via a single Cat5
- IP video intercom made easy and scalable using IPv6 plug and play architecture
- SIP compatible door panel for IP phone and mobile app communication
- Includes Paxton's industry high 5 year warranty

PAX 337-405-US

Net2 Entry IP Video Intercom, Flush Mount

PAX 337-425-US

Net2 Entry IP Video Intercom, Surface Mount

PAX 337-505-US

Net2 Entry IP Video Intercom, Flush Mount, Vandal Resistant

PAX 337-525-US

Net2 Entry IP Video Intercom, Surface Mount, Vandal Resistant



Comelit
Passion. Technology. Design.

COM 8513HIM

Single-Family Kit w/iKall Metal and Master Gateway. ViP H264

The kit consists of:

- (1) external video door entry unit for ViP system (4894IM)
- (1) 33VDC power supply unit (1595)
- (1) 30W power supply unit (1441B)
- (1) Master gateway (1456)
- The kit is pre-programmed and ready to use, except for 1456 gateway configuration which must be carried out via internal web server.
- The kit can be expanded with other products from the VIP catalogue.



RNG 88LP000CH000

1080p Ring Pro Video Doorbell w/ 4 Covers

- Ultra slim design with advanced features
- Requires an existing hardwired doorbell
- Advanced Motion Detection
- Interchangeable Faceplates
- 2.4 or 5 GHz Wi-Fi Connection
- Lifetime Purchase Protection
- Night Vision
- Two-Way Audio
- Works with iOS, Android™ & Windows 10

Ring Video Doorbells

- Works on every home – with or without a doorbell.
- Quick and easy install.
- 720p HD Video
- Motion Detection
- Built-in Rechargeable Battery
- 2.4 or 5 GHz Wi-Fi Connection
- Lifetime Purchase Protection
- Night Vision
- Two-Way Audio
- Works with iOS, Android™ & Windows 10

RNG 88RG000FC000

Ring Video Doorbell, 502 Satin Nickel Finish

RNG 88RG001FC100

Ring Video Doorbell, 503 Polished Brass Finish

RNG 88RG002FC100

Ring Video Doorbell, 504 Venetian Bronze Finish

RNG 88RG003FC100

Ring Video Doorbell, 505 Antique Brass Finish

RNG 88SC000FC100

Ring Stick-Up Camera, Black

- Weather-resistant and wire-free, mount Stick Up Cam anywhere to see, hear, and speak with your visitors.
- Motion Detection – Customize motion zones and sensitivity to activate Stick Up Cam and trigger Ring App alerts
- Two-Way Audio
- Night Vision
- Cloud Video Recording

RNG 88CH000FC000

Ring Chime

- Chime plugs into any standard power outlet and works with your Ring Video Doorbell to let you know when you have a visitor even if your phone is in the other room.
- Set up as many Chimes as you want, and never miss a ding



ALARM.COM

Alarm.com Wi-Fi Doorbell Camera

- Skybell HD Edition enables homeowners to hear, see and speak to visitors, and also works with other sensors and devices in the home to extend awareness and control to the front door.

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

- The smart entry solution lets homeowners securely manage access by seamlessly unlocking the door from the video call screen in the Alarm.com mobile app.

ALM ADCVDB101

Wi-Fi Doorbell Camera, Satin Nickel Finish

ALM ADCVDB102

Wi-Fi Doorbell Camera, Bronze Finish

ALM ADCVACDBDA

Digital Doorbell Adapter

IP Environmental Monitors:



Carrier Branded CoR Wi-Fi Thermostat

ILX TPWEM01

CoR Wi-Fi Smart Thermostat

- Wi-Fi enabled for remote access via Internet with Apple® or Android™ smartphone and tablet devices
- Designed to save energy with smart setback and energy reporting features
- Wide range of HVAC system and brand compatibility

WINLAND ELECTRONICS, INC.

WIN EA800IP

EnviroAlert IP based environmental control 4-wireless and 4 hardwire zones

- IP Networking Monitoring Console
- 12-24VDC
- RMR Generating device

Wireless Transmitters and Sensors

All Wireless sensors feature 1000' line of sight range - Estimated 3 year battery life on 2 AA alkaline batteries.

WIN WTS

Wireless temperature sensor

WIN WHS

Wireless humidity sensor

WIN WMFS

Wireless multi-function sensor

Hardwire Sensors for EA800IP

WIN TEMPHS

New Stainless Steel Hi Temp Probe (M-001-0081)

WIN TEMPLW

Temp Sensor, Low Temp, Waterproof (Blue) -58 to 158°F (-50 to 70°C)

WIN WSS

Standard water surface sensor – Supervised (Will alarm if wire is severed.)

WIN WUCU

Under carpet sensor for WB-200

WIN HA3 (HAIII+)

Electronic Humidity Sensor (Not Compatible with EA-WMFS)

(5-95% RH ±5% @ 10-90% RH, 77°)

WIN PS110

Power-Out Alert (1022) Plugs into any outlet - Adjustable time set from 1-6 minutes for power outage before alert

PoE Power Supplies:



Netway Midspan PoE Power Injectors

ALT NETWAY1

Single Port Injector (Midspan)

- UL/CUL Listed for Information Technology Equipment (UL 60950-1)
- UL Listed for Access Control Systems (UL 294)
- CUL Listed – CSA Standard, Signal Equipment
- One (1) port of video over Ethernet (CAT5) cable up to a distance of up to 100m (328 ft.) per port
- 24VAC/VDC input
- IEEE 802.3af compliant port provides up to 15.4W max. power per channel
- Trigger input feature allows for PoE shutdown
- Lifetime Warranty

TRENDNET®

Rugged Industrial Switches



TI-PG80

8-Port Hardened Industrial Gigabit PoE+ DIN-Rail Switch

- 8 x Gigabit PoE+ Ethernet ports
- Up to a 200 Watt full PoE+ power budget
- Hardened IP30 rated metal switch
- Limited Lifetime Warranty



TI-G50

5-Port Hardened Industrial Gigabit DIN-Rail Switch

- 5 x Gigabit Ethernet ports
- Hardened IP30 rated metal switch
- Includes DIN-rail and wall mounts
- Limited Lifetime Warranty

PoE Solutions



TI-PG80

28-Port Gigabit Web Smart PoE+ Switch

- 4 x Gigabit PoE+ ports
- 20 x Gigabit PoE ports
- 4 x SFP slots
- 185 Watt PoE budget



TPE-TG160g

16-Port Gigabit PoE+ Switch

- 16 x Gigabit PoE+ ports
- 246 W PoE budget
- 32 Gbps switching capacity
- Limited Lifetime Warranty

www.trendnet.com

COMPANY - WIDE HOURS
MONDAY - FRIDAY, 7:30AM - 5:30PM



INTERACTIVE | CENTRAL VAS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK



Altronix
ALT NETWAY1512
15W adapter for conventional IP cameras

- UL/CUL Listed for Information Technology Equipment (UL 60950-1).
- 12VDC/15W adapter for non-PoE compliant IP cameras.
- Lifetime Warranty.



Altronix
ALT NETWAY3012
30W adaptor for conventional IP cameras

- UL/CUL Listed for Information Technology Equipment (UL 60950-1)
- 12VDC/30W adapter for non-PoE compliant IP cameras
- Lifetime Warranty



Altronix
ALT NETWAY8M
Eight (8) Port PoE Managed Midspan

- UL/CUL Listed for Information Technology Equipment (UL 60950-1)
- Repeater module extends data range 100m (328 ft.) each
- No external power required
- Compatible with NetWay1, NetWay8/8M and NetWay16/16M
- Lifetime Warranty



Altronix
ALT EBRIDGE1PCRT
IP over Coax Solution - eBRIDGE Kit

- UL/CUL Listed for Information Technology Equipment (UL 60950-1)
- Sixteen (16) ports of video over Ethernet (CAT5) cable up to a distance of up to 100m (328 ft.) per port
- Four (4) ports are selectable for 30W to accommodate IP PTZ cameras (requires NetWay3012 adaptor for each camera port)
- Unit provides up to 15.4W max. power per channel
- IEEE 802.3af compliant
- Individual port status LEDs
- Auto detection and protection of legacy non-PoE cameras



NAPCO
NAP IREMOTEMOD/12
Remote PoE Injector

- IEEE 802.3af compliant
- Individual port status LEDs
- Auto detection and protection of legacy non-PoE cameras
- Unit can be rack, shelf or wall mounted
- 1U EIA 19" rack mount chassis
- Lifetime Warranty



legrand
ONQ DA1015V1
Netway Midspan PoE Power Injectors

- UL/CUL Listed for Information Technology Equipment (UL 60950-1)
- Eight (8) ports of video over Ethernet (CAT5) cable up to a distance of up to 100m (328 ft.) per port
- Two (2) ports are selectable for 30W to accommodate IP PTZ cameras (requires NetWay3012 adaptor for each camera port)
- Unit provides up to 15.4W max. power per channel
- IEEE 802.3af compliant
- Individual port status LEDs
- Auto detection and protection of legacy non-PoE cameras
- Unit can be rack, shelf or wall mounted
- 1U EIA 19" rack mount chassis
- Lifetime Warranty



DITEK
DTK MRJPOE
Sixteen (16) Port PoE Managed Midspan

- UL/CUL Listed for Information Technology Equipment (UL 60950-1)
- UL Listed for Access Control Systems (UL 294)

- CUL Listed – CSA Standard, Signal Equipment
- Sixteen (16) ports of cameras/edge devices over Ethernet (CAT5) cable up to a distance of 100m (328 ft.) per port
- Unit provides up to 30W max. full power per port. Total power: 300W
- IEEE 802.3af (PoE) and IEEE 802.3at compliant (PoE+)
- Short circuit protection
- Programmable PoE shutdown for each port. Utilized to reset cameras/edge devices
- Auto detection and protection of legacy non-PoE cameras/edge devices
- LAN or laptop connection enables programming of PoE shutdown and port monitoring
- Lifetime Warranty

- UL/CUL Listed for Information Technology Equipment (UL 60950-1)
- UL Listed for Access Control Systems (UL 294)
- CUL Listed – CSA Standard, Signal Equipment
- Eight (8) ports of cameras/edge devices over Ethernet (CAT5) cable up to a distance of 100m (328 ft.) per port
- Unit provides up to 30W max. full power per port. Total power: 150W
- IEEE 802.3af (PoE) and IEEE 802.3at compliant (PoE+)
- Short circuit protection
- Programmable PoE shutdown for each port. Utilized to reset cameras/edge devices
- Auto detection and protection of legacy non-PoE cameras/edge devices
- LAN or laptop connection enables programming of PoE shutdown and port monitoring
- Lifetime Warranty

- Interfaces with HubWay and HubSat UTP Transceiver Hubs for 24VAC/12VDC fixed or PTZ cameras (based on power supply selection)
- Used to pass through video/data and power

- HubWay Series provides centralized UTP Video, RS422/RS485 data and distributed camera power over a single CAT 5e or higher to simplify CCTV installation for distances up to 1000 feet. This provides eight individually selectable power outputs. Includes 8ea HUBWAYAV Video Balun/Combiners

- One (1) eBridge1CR Receiver and one (1) eBridge1CT Transceiver

- High-performance and cost effective solution to transmit IP video/data and power over coax cable up to 1500ft
- Allows easy upgrade of legacy coax infrastructure
- Supports IEEE 802.3af (PoE) cameras and access control devices
- Eliminates labor and costs of deploying new cable
- Auto detection and protection of legacy non-PoE cameras/devices

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

ALT EBRIDGE100RMT

Ethernet over Coax/CAT5e Adapter Kits for Extended Distances

- Replace legacy analog products with new IP devices over existing coax or CAT5e cable
- Works with Megapixel, HD720, HD1080 and VGA (SD) cameras
- Extend Network link distance in an industrial environment
- Upgrade deployed CCTV Coax to a digital network in Retail, Casinos, Airports, Schools, Hospitals, etc

ALT NETWAY1D

Single Port Hi-PoE Injector for Standard & Enhanced Power Network Infrastructure

NetWay1D is an indoor single port midspan injector that provides Hi-PoE (60W), PoE+ (30W), and PoE (15W). The unit is also equipped with a 56VDC Class 2 rated power-limited output for use with Altronix eBridge™ Plus receivers. NetWay1D operates at 115VAC or 230VAC input.

ALT NETWAY1DWP

Outdoor Single Port Hi-PoE Midspan Injector

NetWay1DWP is an outdoor single port midspan injector that provides Hi-PoE (60W), PoE+ (30W), and PoE (15W). The unit is ideal for use with outdoor IP cameras and PTZs, WiMAX modems and WLAN access points. NetWay1DWP features a lightweight NEMA 4/4X IP66-11 rated enclosure that can be wall or pole mounted. The unit operates at 115VAC or 230VAC input.

ALT PACE1PRMT

IP and PoE+ over extended distance UTP or CAT5e

Pace1PRMT is a long range Ethernet adapter kit which transmits data at 100Mbps full duplex and power via a single twisted pair (UTP) or Cat5e or higher cable in a PoE(+) compliant format. The Pace1PRM receiver is powered via a PoE midspan such as the Altronix Netway series or by an endspan. The receiver passes the PoE(+) compliant power over the cable to the Pace1PTM transceiver which in turn passes this power to an enabled IP camera/device. These plug and play units facilitate cost effective solutions for IP devices that need to be installed at distances greater than 100m. They also provide a simple way to replace legacy analog products with new IP devices over single twisted pair (UTP) or structured cable.

- Extend Network link distance in an industrial environment over 150m (UTP) or 500m (CAT5e or higher)
- Retrofit digital IP cameras in an analog CCTV CAT5 wired installations.
- Works with Megapixel, HD720, HD1080 and VGA (SD) cameras. With proper head end equipment.



Structured Cabling CCTV Power Supply Solutions

NVT 16PS10PVD

16 Channel Power Supply Cable Integrator HUB - provides power 24V to 28 VAC to cameras and pan/tilt control over a single CAT5E or CAT6 cable - 568B compliant - Individual Channel diagnostic LEDs and 3 position power switch.

NVT 8PS13PVD

8 Channel Power Supply Passive Receiver HUB - same features as the 16PS10PVD with an integral passive twisted pair receiver HUB.

NVT 16PS13PVD

16 Channel version of the 8PS13PVD

Passive/Active Hardware Modules:



NAP IREMOTEMOD/12

iRemote control internet module for use with iPhone® to control Gemini series control panels. Includes 12 months of service.



ONQ DA1015V1

Desktop 5-Port Gigabit Ethernet Switch

The Desktop 5-port Gigabit Ethernet Switch is a high performance, low cost, and easy to use switch. Easily upgrade to improve your old network to Gigabit speeds (1000Mbps).

ONQ DA1101

In Ceiling/In-Wall Wireless Access Point 802.11

ONQ DA2131V1

Outdoor Wireless Access Point

The Legrand 802.11n Outdoor Wireless Access Point extends the range of the home network to back-yards, porches, decks and patios. Weather resistant with IP 55 casing protection, the Outdoor WAP is suitable to be installed in outdoor environments and exposed locations as well as indoors, and will operate normally under conditions including rain and wind. With connection speeds of up to 150Mbps, this Outdoor WAP supports wireless applications such as streaming video services and web browsing

Gigabit 1 and 4 port Powerline Adapters

ONQ DA2301V1

1-Port Powerline Network Adapter

With the On-Q/Legrand 1-Port Powerline Network Adapter, you can set up a second Ethernet (wired Internet) connection in your home, thereby expanding your home

network to an additional location. This allows you to connect Internet-enabled devices (gaming systems, Blu-ray players, PCs, TVs, etc.) directly to the Internet.

- Expands a home network to locations without an Ethernet connection
- Works in conjunction with the Four-Port Powerline Adapter
- Delivers Internet connection over existing power lines in the home
- Offers high speeds up to 500Mbps

ONQ DA2304V1

4-Port Network Powerline Adapter

Plug the On-Q/Legrand 4-Port Powerline Adapter into any standard power outlet in your home for an easy, retrofit high-speed Internet connection. With four ports to support four devices, the adapter offers an affordable solution for streaming online video through your TV, setting up online gaming for your Xbox®, and implementing any other entertainment networking possibilities. The Powerline Adapter offers speeds up to 500Mbps for reliable streaming no matter the content.

- Connects four internet-capable devices using existing power cable
- Enables streaming of HD content throughout your home
- Offers Internet speeds up to 500Mbps
- Plugs into any standard power outlet



DTK MRJPOE

Power over Ethernet Power/Data Surge Protection

- Protects all 4 pairs
- RJ45 connection with external grounding screw
- Multi-stage hybrid design provides the best possible protection
- Complies with IEEE Std. 802.3af for Power over Ethernet
- Ten Year Limited Warranty



ELK IP232

Serial to Ethernet Converter

- Supports both UDP and TCP protocols
- Allows up to twelve (12) simultaneous TCP-IP network connections
- Outgoing connections may be initiated upon power up or when serial activity is detected. They may remain connected indefinitely or for a set time period
- Integrated 802.3 compliant 10/100 Mbit network interface
- RS232, DB9M 9-pin serial port connection
- Connects to the M1 RS-232 Serial port (Port 0)
- RJ45 8-pin Network Jack
- 2.1mm barrel type power connector (center positive)
- LED Indicators for Power, Link, and Data



INTERACTIVE | CENTRAL VMS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK



INA IN81POE

ELK M1XEP
Ethernet port interface makes M1 controls accessible via LAN/WAN or Internet - Built-in web server.

Switches/Routers/Access Points




LUX ABR4400

INA IN41POE
4 Port 10M/100M Desktop PoE Fast Ethernet Switch

INA IN81POE
8 Port 10M/100M Desktop Fast Ethernet Switch

INA IN242POEWM
Full Power 24 Port 10M/100M, PoE + 2 Gigabit Copper 1000M




LUX XWR3100

LUX ABR4400
AV Series (Ports on the Back) Multi-WAN Gigabit Router

- 1 Dedicated WAN, 1 Dedicated LAN, 3 LAN/WAN Configurable Ports
- 1 USB 2.0 Port
- Auto Failover between WAN ports
- Load Balancing
- Virtual Private Network (VPN): PPTP, L2TP, IPsec



LUX XWS1310

LUX AGS1016
AV Series 16-Port Gigabit Switch

- 16 Gigabit RJ45 Ports
- 32Gbps Switching Capacity
- Non-Blocking and Full-Duplex for Optimal Network Performance
- Auto Uplink (MDI/MDI-X)
- Plug-and-Play



SMX 065-1100

LUX AGS1024
AV Series 24-Port Gigabit Switch

- 24 Gigabit RJ45 Ports
- 48Gbps Switching Capacity
- Non-Blocking and Full-Duplex for Optimal Network Performance
- Auto Uplink (MDI/MDI-X)
- Plug-and-Play Setup



SMX 065-7861POE-EP

NEW LUX XRMDTZ1
Domotz Pro Remote Management

- Processor: Intel Celeron N2807 (up to 2.16GHz)
- RAM: 1GB DDR3L
- Storage: 4GB eMMC
- Network Connectivity: Gigabit Ethernet
- Additional Connectivity: 1x USB 2.0, 1x USB 3.0, 1x HDMI
- Power supply: 5V/3A micro USB type connector with US, EU and UK plugs
- Other Highlights: Premium Enclosure, Open Architecture, Automatic software upgrades, Multi-VLAN support
- In The Box: Power supply (110/220V), Flat Gigabit Ethernet cable



TNT TE100S50G

NEW LUX XWR1200
Dual-Band Wireless AC1200 Gigabit Router

- 802.11ac Wi-Fi (up to 1200Mbps)
- Seamless Roaming with Luxul Roam Assist™
- 2x2 MIMO
- High Power for Extended Signal Range
- Wireless Data Transfers of up to 1200Mbps
- Concurrent Dual-Band (2.4 GHz and 5GHz)
- 5Ghz Beamforming Technology
- Virtual Private Network (VPN)
- Secure Guest Networking
- Quality of Service (QoS)
- Network Security and Firewall
- 1 WAN and 4 LAN Gigabit Ports
- USB 2.0 Port
- Three Year Limited Warranty

NEW LUX XWR3100
XWR-3100 Empowered Wireless Gigabit Router

- 802.11ac Wi-Fi (data transfers up to 3100Mbps)
- Easily Expands Wi-Fi Network with up to 2 Additional APs
- Seamless Roaming with Luxul Roam Assist™
- 4x4 MU-MIMO (Wave 2)
- High Power for Extended Signal Range
- Concurrent Dual-Band Wireless AC
- 2.4 and 5GHz Beamforming
- Quality of Service (QoS)
- VPN Remote Access
- Secure Guest Networking
- Network Security and Firewall
- 1 WAN and 4 LAN Gigabit Ports
- USB 3.0 Port
- Three Year Limited Warranty

LUX XAP1240
High Power Wireless 300N Outdoor Access Point

- High Output Power for Maximum Coverage
- Compatible with the Luxul XWC-1000 Wireless Controller
- Patented Signal Propagation Technology
- VLAN Support for Creating a Secure Guest Network
- Up to 4 SSIDs
- Single Cable Installation with PoE (Injector included)

LUX XAP1410
High Power AC1200 Dual-Band Wireless AP

- High Performance 802.11ac Wi-Fi (up to 1200Mbps)
- High Output Power for Maximum Coverage
- Concurrent Dual-Band (2.4 GHz and 5GHz)
- 5Ghz Beamforming Technology
- Compatible with the Luxul XWC-1000 Wireless Controller
- VLAN Support for Creating a Secure Guest Network
- Up to 4 SSIDs per Band (8 Total)
- Single-Cable Installation with PoE (Injector included)
- Installs on Ceiling or Wall; or Use as a Desktop AP
- Simple and Discreet Installation
- Three-Year Limited Warranty

LUX XBR4400
The Luxul Commercial Grade Multi-WAN Router (XBR-4400) is a critical building block of your IP network. With Gigabit performance across all ports, it provides an optimal platform for setting up the ultimate residential or commercial network. This commercial grade router allows for up to 512

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

concurrent device routing entries. It features advanced management, as well as firewall, QoS, VLAN, VPN and other capabilities that ensure optimal performance, scalability and security of your network.

LUX XFS1084P

The Luxul 8-Port Fast Ethernet PoE Switch (XFS-1084P) provides exceptional performance, quality and reliability. It is an affordable choice for expanding your network when using PoE-enabled devices such as VoIP, IP cameras and Wireless Access Points. This 8-port switch lets you use standard Ethernet cable to deliver power and data to up to four 802.3af-compliant devices, while also attaching up to four more Ethernet-enabled devices at full duplex speeds of up to 200Mbps.

LUX XGS1024S

The Luxul 24-Port Gigabit Flex Mount Switch (XGS-1024S) provides exceptional performance, quality and reliability. It offers all the benefits of a full-sized 19" rack mount switch in a smaller footprint and is a great choice for expanding your wired network or setting up a VoIP, multimedia or extreme gaming environment. With a 48Gbps backplane, this 24-port switch lets you network up to twenty-four Ethernet-enabled devices at full-duplex, non-blocking Gigabit speeds. It can easily be mounted on a wall, desktop or in a 19" rack using the included mounting hardware.

LUX XMS1024

It is an excellent choice for expanding your wired network or setting up a high performance VoIP, multimedia or extreme gaming environment. This 24-port Gigabit Switch also features advanced management and security capabilities to ensure optimal benefit from your home or office network.

LUX AGS1008M

8 Port Gigabit Switch w/Magnetic Mount

LUX AGS1016

AV Series 16 Port Gigabit Rack Mount Switch

LUX AMS1208P

AV Series 12 PORT/8 PoE+ Gigabit Managed Switch (130W)

- 10, Gigabit RJ45 Ports
- 2, Gigabit SFP ports
- 8 Ports Support 802.3af/at PoE+ with 130 Watt Power Budget
- 24Gbps Switching Capacity
- Layer 3 Static Routing
- 802.1Q VLAN (with Trunking) and QoS Support
- Plug-and-Play Installation with Intuitive Management
- Simple Power Management of PoE-Enabled Devices
- User Selectable Green or Blue Front facing LEDs
- Fanless for Silent Operations
- Standard 19" Rack-Mount
- Three Year Limited Warranty

LUX AMS2616P

26PT/16PT PoE+ Gigabit Switch w/Rear Facing Ports

LUX AMS4424P

AV Series 26 Port Gigabit Stackable PoE + L2/L3 Switch

LUX XAP310

Wireless 300N Low Profile Access Point

LUX XMS1010P

10 Port/8 PoE+Gigabit Managed Switch

LUX XMS2624P

26 Port/24 PoE+ Gigabit Manage Switch

LUX XPE2500

PoE Injector

LUX XSF1816P

18 Port/16PoE+/2 Gigabit Uplink Switch

LUX XVSF5

5-Port 10/100 Mbps Fast Ethernet Switch

LUX XVWP30

Wireless Range Extender/Bridge

Luxul's XVW-P30 Wireless 300N Range Extender/Bridge offers a simple option for extending the reach of your network wirelessly. It can be used either as a bridge link for directly connecting Ethernet devices to your network or as a range extender for providing Wi-Fi coverage to those hard to reach dead spots.

LUX XWC1000

Wireless Controller

- Seamlessly Roam Between Multiple Access Points
- Simply Configure up to 16 Luxul Access Points
- Create a Secure Guest Network with Broad Coverage
- Cost-Effectively Deliver Centralized WLAN Configuration and Control

LUX XWS1310

300N Wireless Controller Kit



SMX 065-1100

10/100BaseT/TX to 100BaseFX Media Converter ST Multimode, 2 km Span

SMX 065-1110

10/100BaseT/TX to 100BaseFX Media Converter SC Multimode, 2 km Span

SMX 065-7012G

8-Port 10/100/1000 Compact Unmanaged Switch

SMX 065-7305GPOEP

5-Port 10/100/1000BaseT/TX PoE/PoE+ Switch with 4 PoE/PoE+ Ports.

SMX 065-7309POEP

9-Port 10/100BaseT/TX PoE+ Switch with 8 PoE/PoE+ Ports plus 1 Gigabit Dual Media Port

SMX 065-7331GPOEP

18-Port 10/100/1000BaseT/TX PoE+ Switch with 16 PoE/PoE+ Ports plus 2 Gigabit SFP Ports

SMX 065-7308POE-FP

8-Port 10/100BaseT/TX Full-Power PoE Switch with 8 PoE Ports

SMX 065-7861POE

26-Port 10/100/1000 Stackable PoE/PoE+ Managed Switch with 4 SFP Dual Media Ports + 2 SFP Ports; 185 watts PoE power.

SMX 065-7861POE-FP

26-Port 10/100/1000 Stackable PoE/PoE+ Managed Switch with 4 SFP DualMedia Ports + 2 SFP Ports; 370 watts PoE power.

SMX 065-POEINJ-GA

1-Port 10/100/1000 PoE/PoE+ Power Injector

SMX 12458M-C5E

12-Port Category 5e Mini Panel w/89D Bracket, T568A/B Wiring

SMX 24458MD-C5E

24-Port Category 5e Patch Panel, T568A/B Wiring, 1.75"-High

SMX 24458MD-C6C

24-Port Category 6+ Patch Panel, T568A/B Wiring

SMX 24U-HDMMP

24 Port Hi-Density Uploaded Multi-Media Panel 1.75"H

SMX 48458MD-C5E

48-Port Category 5e Patch Panel, T568A/B Wiring, 3.50"-High

SMX 48458MD-C6C

48-Port Category 6+ Patch Panel, T568A/B Wiring

SMX 48U-HDMMP

48 Port Hi-Density Unloaded Multi-Media Panel 3.5"H

SMX CMP-175-A

Panel with (5) 1.75" x 3" Horizontal Distribution Rings, 1 RMS

SMX FPC-LC05

LC, 50-µm MM (OM2), for 250- and 900-µm buffered fibers, 2- and 3-mm jacketed cables, black

SMX FPC-ST05

ST, 50-µm MM (OM2), for 250- and 900-µm buffered fibers, black

SMX HWB-175

1-RMS Hinged Wall Mount Bracket, 1.75"H x 6"D

SMX HWB-350

2-RMS Hinged Wall Mount Bracket, 3.50"H x 6"D

SMX HWB-700

4-RMS Hinged Wall Mount Bracket, 7.00"H x 6"Dw

Switches

TNT TE100S50G

5-Port 10/100 GREENnet Switch (Metal)

- GREENnet technology reduces power consumption by up to 40%*
- 5 x 10/100Mbps Auto-Negotiation RJ-45 ports
- Build an energy efficient network in minutes
- Plug and Play this sturdy metal switch



TNT TEG160WS



TNT TPET80H.



TNT TEW653AP.



VIG VI3026



VGX IPSW1



ILX NS20514P/1T



ILX NS2503-8P/2C

TNT TE100S5**5-Port 10/100Mbps Fast Ethernet Switch (Version v1.3R)**

- Build a reliable Fast Ethernet network in minutes
- Easy Plug and Play installation
- Auto-Negotiation optimizes networking speeds for all 5 ports
- 5 x 10/100Mbps Auto-Negotiation, Auto-MDIX Fast Ethernet RJ-45 ports
- Compliant with Windows, Linux, and Mac Operating Systems.
- Store-and-Forward Switching method

TNT TE100S8**8-port 10/100Mbps Switch****TNT TE100S80G****8-Port 10/100Mbps GREENnet Switch**

- 8 x 10/100Mbps Auto-Negotiation, Auto-MDIX Ethernet Ports
- 1.6Gbps switching fabric
- Store-and-Forward switching architecture with non-blocking wire-speed performance
- Compliant with Windows, Linux, and Mac Operating Systems
- Sturdy metal housing
- Diagnostic LEDs

TNT TEG160WS**16-port Gigabit Web Smart Switch w/ 2 Shared Mini-GBIC Slots (Version C2.0R)**

- Provides SNMP (v1), IEEE 802.1X and STP Support
- 32 Gbps switching capacity
- 16 x Gigabit Auto-MDIX ports
- 2 x shared mini-GBIC slots
- Supports IEEE 802.1Q VLAN, Asymmetric VLAN, QoS, IGMP, Trunking and Mirroring

TNT TEGS16G**16-Port Gigabit GREENnet Switch (Version v1.0R)**

- GREENnet technology reduces power consumption by up to 70%
- 16 x Gigabit Auto-MDIX RJ-45 ports
- Sturdy rackmount metal switch with Built-in power supply
- 32Gbps forwarding capacity

TNT TEGS24G**24-Port Gigabit GREENnet Switch (Version v1.0R)**

- GREENnet technology reduces power consumption by up to 70%
- 24 x Gigabit Auto-MDIX RJ-45 ports
- Sturdy metal rackmount switch with Built-in power supply
- 48Gbps forwarding capacity

TNT TEGS50G**5-Port Gigabit GREENnet Switch (Version v3.0R)**

- GREENnet technology reduces power consumption by up to 70%
- 5 x Gigabit Auto-Negotiation ports
- Build a high performance energy efficient Gigabit network in minutes
- Sturdy metal switch with a simple Plug and Play installation

TNT TEGS80G**8-Port Gigabit GREENnet Switch (Metal)**

- GREENnet technology reduces power consumption by up to 70%
- 8 x Gigabit Auto-Negotiation ports
- Build a high performance energy efficient Gigabit network in minutes

TNT TPE1620WS**16-Port Gigabit Web Smart PoE+ Switch**

- 16 x PoE+ Gigabit ports
- 2 Shared SFP slots
- Up to 30 W per port with a 185 W total power budget
- 32 Gbps switching capacity
- Rack mountable

TNT TPE224WS**24-Port 10/100Mbps Web Smart PoE Switch with 4 Gigabit Ports and 2 Mini-GBIC Slots (Version B1.11R)**

- Reduces equipment cost by delivering data and power over existing network cables
- 24 x PoE 10/100Mbps ports, 4 x Gigabit Auto-MDIX ports and 2 x shared Mini-GBIC slots
- 12.8Gbps switching capacity with SNMP v1, 802.1X and STP support
- Features 802.1Q VLAN, Asymmetric VLAN, QoS, IGMP, Trunking and Mirroring

TNT TPET160H**16-Port 10/100 Mbps PoE+ Switch**

- 16 x 10/100 Mbps PoE+ ports
- Up to 30 Watts per port with a 250 Watt total power budget
- 3.2 Gbps switching capacity
- Rack mount kit included

TNT TPES44**8-Port (4 10/100, 4 PoE) PoE Switch**

- Reduces equipment cost by delivering data and power over existing network cables
- 4 PoE and 4 standard 10/100Mbps ports
- Flow Control for Full-Duplex mode

TNT TPET80H**8-Port 10/100 Mbps PoE+ Switch**

- 8 x 10/100 Mbps PoE+ ports
- Up to 30 Watts per port with a 125 W total power budget
- 1.6 Gbps switching capacity
- Rack mount kit included
- Use with TRENDnet's PoE Splitter to network and power non-PoE devices

TNT TPETG81G**8-Port Gigabit GREENnet PoE+ Switch (Version v1.xR)**

- 8 x Gigabit PoE+ ports (up to 30 watts per PoE+ port)
- Internal power supply
- Up to 30 W per port with 105 W total power budget
- Reduces equipment cost by delivering data and power over existing network cables
- 16 Gbps switching capacity
- Sturdy rack mountable metal case
- Up to 75% GREENnet power savings

Wireless Routers and Access Points**TNT TEW653AP****N300 Wireless PoE Access Point**

- Features Access Point, WDS, and Repeater modes
- No need to install the device near a power source using PoE technology
- Assign individual VLANs for up to four separate SSIDs
- Advanced encryption, WMM® QoS and SNMP support
- High-speed data rates up to 300Mbps using 802.11n connection

TNT TEW731BR

N300 Wireless Home Router

- High performance 300Mbps wireless N router
- Stream video, download files, talk online and play games wirelessly
- Connect computers with one-touch Wi-Fi Protected Setup (WPS)
- Up to 50% energy savings with GREENnet technology

TNT TEW733GR

N300 Wireless Gigabit Router

- Proven 300 Mbps Wireless N
- Pre-encrypted for your security
- Create an isolated guest network
- One touch network connection with the WPS button
- All Gigabit wired ports

Energy savings GREENnet technology

TNT TEW735AP

N300 High Power PoE Access Point

TNT TEW738APBO

10 dBi Outdoor PoE Access Point

- Wireless N300 building-to-building networking (2.4 GHz)
- Supports Access Point (AP), Wireless Distribution System (WDS), Repeater, and CPE + AP modes
- IP67 rated aluminum housing
- Built-in 10 dBi directional sector antenna

TNT TEW812DRU

AC1750 Dual Band Wireless Router

- 1750 Mbps total wireless: 1300 Mbps AC + 450 Mbps N bands
- Share music and videos with the USB share port
- Create an isolated guest network
- One touch network connection with the WPS button
- All Gigabit wired ports
- High power amplifiers extend wireless coverage

TNT TK407K

4-port USB KVM Switch Kit (Include 4 x KVM Cables)

TNT TPL406E2K

500 AV Compact Powerline Ethernet Adapter kit



NEW VIG VI3026

High power, High bandwidth network switch designed for IP security applications

- Provides 26GB Ethernet ports, with 24 PoE ports and 6 Fiber ports
- 24 ports provide full 802.3af power at 15.4 watts and 12 ports at 802.3at at 30 watts
- High bandwidth 52 Gbytes for handling largest Megapixel cameras
- Automatic port monitoring and unattended reconnection to avoid service calls

VIG VI3010

MaxiiNet 10-port Gigabit Ethernet L2 Plus Managed PoE Switch

- All 10 Ethernet ports are 1Gbps - 8 PoE and 2 SFP ports
- 8 ports at 802.3af PoE and up to 6-ports at 802.3at (30W)
- SNMP for communicating error messaging to local computers
- Automatic IP and PoE connection and reconnection
- Automatic MAC identification for all connected devices
- Individual IP Source Guard for protecting ports
- Supports Jumbo Frames up to 9600 bytes
- High Bandwidth 20Gbyte switching fabric
- Virtual Network Switch Stacking
- Lifetime Warranty



VGX IP1STD

iPulse Automatic Network Reboot Device

Features:

- Universal
- Compact and easy to use, and simple to install
- Connects directly to any modem or device
- No dedicated power source needed
- Instantly detects failed transmission and reboots the device
- Benefits:
 - Prevents disturbing a covert deployment
 - ◆ Eliminates the need for human intervention
 - ◆ Flexible and proven in many government applications

VGX IPSW1

uSwitch Browser Based Remote Switch Controller

Whether you are right next door or halfway across the world, YOU have control over any device on a network through any web browser.

Features and Benefits:

- No programming required! Control uSwitch using a standard web browser, or CGI
- Automatically reboots any modem or networking device that locks up without and human intervention or any additional software
- Control uSwitch via the Internet or a local intranet.
- Up to 15Amp and 2 relays up to 220V
- Removable terminal connectors for simple wiring (included)
- Coupled with an iPulse, you'll have the most reliable, fault tolerant solution available in the market.
- Can be controlled from iPhone®, iPad®, Android™, Laptop or any web enabled device



IFS PoE Switches

The new line of IFS network switches provides enterprise-class features and is engineered with high bandwidth, isolated PoE ports, integrated SFP fiber ports and browser-based Web Services that deliver powerful performance that's easy to use.

ILX DSSG244POE

24-Port 10/100/1000+ GigE SFP PoE Stackable Managed Switch

ILX DSH82POE

8-Port 10/100+2 GigE TP/SFP Industrial Full PoE Managed Switch

- For 24VAC/12VDC fixed cameras (based on power supply selection)
- Use only with HubWayH16 Passive UTP Transceiver Hub
- Lifetime Warranty
- For 24VAC/12VDC fixed cameras (based on power supply selection)
- Use only with HubWayH16 Passive UTP Transceiver Hub
- Lifetime Warranty

ILX NS20514P/1T

5-Port PoE Unmanaged Industrial Ethernet Switch

The IFS® 5-port PoE Unmanaged Industrial Ethernet Switch provides four 10/100Mbps Ethernet ports with IEEE802.3-af PoE and one 10/100Mbps non-PoE Ethernet port.

ILX NS2503-8P/2C

8-Port Fast Ethernet Layer 2 Managed Switches

For fast and efficient connectivity from the network edge to a backbone switch or server, the IFS® 8-port Fast Ethernet Managed Switch Series features eight 10/100Mbps Fast Ethernet ports with 2 Gigabit TP/SFP combo ports. The 2 Gigabit TP/SFP combo ports can support either 10/100/1000Mbps (RJ45) or (1000Base-SX/LX/BX) through an SFP (Small Form-factor Pluggable) GBIC interface. This series is also available with PoE and PoE+ capabilities.

ILX PS48VDC100DIN


48VDC DIN-Rail Industrial Power Supplies

- 5VDC, 12VDC or 24VAC
- 48VDC and 56VDC for PoE Devices
- Wall-mount
- Desktop (in-line brick)
- DIN-Rail Mount
- For Use w/IFS Transmission Fiber Modules, Network Switches and Media Converters
- Commercial or Industrial-grade
- Models for Meeting World-wide Power Requirements
- UL Approved
- CSA Approved
- Level IV and V International Efficiency Compliant
- Two-year Warranty



INTERACTIVE | CENTRAL VANS | IP NETWORK | CCTV | BURGLARY | DETECTION | WIRELESS | FIRE | TRANSMISSION | ENVIRONMENTAL | PERS | ACCESS | COMMUNICATIONS | HOME ENT. | PA/DIST. AUDIO | STRUCT. WIRE | TOOLS | INFO

IP SOLUTIONS IP NETWORK



ILX S202MLC2



QTI NLJ5501



QTI HPSE10A



VAN 820524



VAN 280444



DAM RRA19084-3MU



VMP ERS1

Mini-GBIC SFP Transceivers

Small Form-factor Pluggable Transceiver Modules

- Design: Plug-and-play capability for easy installation
- Hot-swappable
- Low power dissipation
- Optical Performance: Available in wide-temperature versions for harsh industrial applications
- Data rates of 100Mbps or 1.25Gbps
- Single mode or multi-mode fiber
- 1 or 2 fiber configurations
- RJ-45 1.25Gbps SFP available
- Standards Compliance: Mini-GBIC Interface compliant
- Multi-source Agreement (MSA) compliant
- Class 1 laser safety standard IEC 60825 compliant
- Warranty: 3-year warranty

ILX S202MLC2

SFP-Port Fast 2 Fiber Mini GBIC Module SM 1310nm - 20km

ILX S302MLC

SFP-Port Gigabit 2 Fiber Mini GBIC Module MM 850nm - 550m

ILX S302MLC2

SFP-Port Gigabit 2 Fiber Mini GBIC Module MM 1310nm - 2km

ILX S302SLC10

SFP-Port Gigabit 2 Fiber Mini GBIC Module SM 1310nm - 10km

Network Equipment Racks/ Patch Panels/ Cables/ Modular Plugs/ Tools/ Testers



Loc-Jack System

- QTI NLJ0045** Locjack RJ45 Security Key
- QTI NLJ5501** CAT5E Locjack Jack, Black
- QTI NLJ5502** CAT5E Locjack Jack, Blue
- QTI NLJ5508** CAT5E Locjack Jack, White
- QTI NLJ6501** CAT6 Locjack Jack, Black
- QTI NLJ6502** CAT6 Locjack Jack, Blue
- QTI NLJ6508** CAT6 Locjack Jack, White

Rack Mountable Cat5e/6 Patch Panels

- QTI NPP5024** 24 Port Cat5E
- QTI NPP5012** 12 Port Cat5E
- QTI NPP5048** 48 Port Cat5E
- QTI NPP6012** 12 Port Cat6
- QTI NPP6024** 24 Port Cat6
- QTI WB190206H** Hinged 19" Wall Mount Bracket
- QTI NMP8225** Cat5e modular plug
- QTI NMP8725** Cat6 modular plug

Cat5e Patch Cables

- QTI NPC1201** 1' Blue
- QTI NPC1203** 3' Blue
- QTI NPC1907** 7' Gray
- QTI NPC1610** 10' Green
- QTI NPC1825** 25' White

Rack Mount Surge Protectors/Power Strips

QTI HPSE12P

Horizontal Rack Mount Power Strip

- 12 Outlets
- Includes: 6' AC power cord with NEMA 5-15P plug

QTI HPSE10A

Horizontal Rack Mount Power Strip

- 10 Outlets
- Includes: 6' AC power cord with NEMA 5-15P plug

WM1000 Series wall mount enclosure racks

The features of the 100 Series WM1019 Locking Wall mount enclosures are:

- Ships Fully Assembled and is UPS Shippable
- 19" Mounting Format with 11" - 22" External Heights
- Vented Side Panels and Front Door
- Complete with One Pre-Installed 80cfm Fan
- Constructed of 22AWG Cold Rolled Steel
- Available in Black or Ivory Electrostatic Microfinish
- Mounting Hardware Included
- Meets or Exceeds EIA-310D Standards

QTI WM1019-05-02 5RU

QTI WM1019-07-02 7RU

QTI WM1019-09-02 9RU



Slimline CAT6 Patch Cables

- VAN SCAT61BK** 1' Superslim CAT6 Patch Cable, Black
- VAN SCAT61BU** 1' Superslim CAT6 Patch Cable, Blue
- VAN SCAT61GY** 1' Superslim CAT6 Patch Cable, Gray
- VAN SCAT61WH** 1' Superslim CAT6 Patch Cable, White
- VAN SCAT63BK** 3' Superslim CAT6 Patch Cable, Black
- VAN SCAT63BU** 3' Superslim CAT6 Patch Cable, Blue
- VAN SCAT63GY** 3' Superslim CAT6 Patch Cable, Gray
- VAN SCAT63WH** 3' Superslim CAT6 Patch Cable, White
- VAN SCAT67BK** 7' Superslim CAT6 Patch Cable, Black
- VAN SCAT67BU** 7' Superslim CAT6 Patch Cable, Blue

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

VAN SCAT67GY

7' Superslim CAT6 Patch Cable, Gray

VAN SCAT67WH

7' Superslim CAT6 Patch Cable, White

Category 5e Patch Panels

VAN 820524

24 Port Cat5e Patch Panel, 1U

- Meets Category 5e Standards
- Meets EIA/TIA 568B.1
- IDC Compatible for 110 and Krone tools
- Color-coded labels for T568A and T568B Universal Wiring
- 50 Microns Gold Plating
- ETL Listed

VAN 820548 48 Port Cat5e Patch Panel, 2U

VAN 820582 12 Port Cat5e Patch Panel, 1U

Category 6 Patch Panels

- Meets Category 6 Standards
- Meets EIA/TIA 568B.2
- IDC Compatible for 110 and Krone tools
- Color-coded labels for T568A and T568B Universal Wiring
- 50 Microns Gold Plating
- ETL Listed

VAN 820662 12 Port Cat6 Patch Panel, 1U

VAN 820664 24 Port Cat6 Patch Panel, 1U

VAN 820668 48 Port Cat6 Patch Panel, 2U

Brackets

VAN 820587 1U Wall Mount Bracket 19"

VAN 820588 2U Wall Mount Bracket 19"

VAN 280444

S-VGA 1x4 Splitter with Audio

- Use to Duplicate and Amplify VGA and Audio Signals from a Single Source to Four Monitors or other Display Devices
- Enhances Video Signals for Long Distance Broadcast up to 164 ft (50m)
- Supports VGA, SVGA, XGA, SXGA, UXGA and Multi-Sync Compliant Monitors
- Supports Video Resolutions up to 1920x1200 at 60 Hz
- Supports 500 MHz Video Bandwidth for Each Port
- Supports Two Channel Stereo Audio, Bandwidth: 30 KHz
- (1) Input Connector: HD-DB15 (15 Pin) Female Jack and 3.5mm Female Jack, (4) Output Connectors: HD-DB15 (15 Pin) Female Jacks and 3.5mm Female Jacks
- Includes 6ft VGA Male/Female Cable
- Power Supply: 5VDC, UL Listed
- Dimensions: 6.5" W x 1.8" H x 3.6" D

Equipment Racks and Accessories:



DAM ATFK2L

2pk Low Noise Fan Kit 120VAC

DAM MRC084W-3

84" Vertical Cable Manager Cover 6" Wide

DAM MRD084W-3

84" Vertical Cable Manager Rack 6" Wide

DAM PLAEC

2pk End Caps For Ladder Style Cable Rack

DAM PLB12RS-3

12" Ladder to Rack Mounting Kit

DAM PLBE00-3

2pk Ladder Style Runway Butt Splice Bracket

DAM PLBJT-3

2pk Ladder Style Runway Junction Tee Bracket

DAM PLBWA12-3

Ladder Runway Wall Angle Bracket Support Kit

DAM PLBWT12-3

Ladder Runway Triangle Wall Support Bracket Kit

DAM PLR1210-3

1'x10' Ladder Cable Runway Black

DAM R4A19084B-3MU

84" Dual 19" Equipment Rack 45u-29" Depth-Black

DAM RRA19084-3MU

84" 2 Post 19" Equip. Rack 45u-Black

DAM WLR24AKP1VVV3

24" Wall Mount 12u Vented Rack-Plexi Door-Fully Assemble

DAM WLR36AKP1VVV3

36" Wall Mount 18u Vented Rack-Plexi Door-Fully Assemble

DAM WLR48AKP1VVV3

48" Wall Mount 26u Vented Rack-Plexi Door-Fully Assemble

DAM WR24C-3

24" Swing-Out Wall Rack 12u Black

DAM WR36C-3

36" Swing-Out Wall Mount 18u-Black

DAM WR48C-3

48" Swing-Out Wall Rack 24u-Black



Racks and Post Kits:

VMP ER1

19" Head end Equipment Rack-71" High-40 rack spaces-EIA compliant-Black static resistant powder coat finish-includes 32 rack screws-400lbs capacity

VMP ER14PKIT

2 Post Expansion kit for ER1-converts ER1 from 2 post to 4 post rack-includes side stabilizing bars

VMP ER184

19" Head end Equipment Rack-84" High-45 rack spaces-EIA compliant-Black static resistant powder coat finish-includes 32 rack screws-400lbs capacity

VMP ER1844PKIT

2 Post Expansion kit for ER184-converts ER184 from 2 post to 4 post rack-includes side stabilizing bars

VMP ER148

19" Head end Equipment Rack-84" High-45 rack spaces-EIA compliant-Black static resistant powder coat finish-includes 32 rack screws-400lbs capacity

VMP ERWEN12E

19" Hinged Wall Equipment Rack Enclosure, 12U Wall Mount (MUST SHIP VIA TRUCK)

- Adjustable front and rear rails, Vented top and bottom, Top and bottom cable routing knockouts, Reversible hinged tempered glass front door, Removable hinged back panel, Lockable, removable side panels (Locks not included), Welded steel construction, Ships assembled, Load capacity - 120lbs, Black powder coat finish

VMP ERWEN15E

19" Hinged Wall Equipment Rack Enclosure - 15 spaces

- Adjustable front and rear rails, Vented top and bottom, Top and bottom cable routing knockouts, Reversible hinged tempered glass front door, Removable hinged back panel, Lockable, removable side panels (Locks not included), Welded steel construction Ships assembled, Load capacity - 120lbs, Black powder coat finish

VMP ERW24

19" Swing Gate Wall Rack-24" high-13 rack spaces- Black static resistant powder coat finish-innovative lift-off design for populated rack-swing open design-EIA Compliant-19" usable depth

Rack Accessories:

VMP ERS1

Economy Rack Shelf-2 space racking height (2.6")-17" usable width-12.5" shelf depth-40lbs capacity-power coat finish

VMP ERS1UV

1U Vented Rack Shelf

- Fits components up to 17.375" wide
- One space rack height (1.75")
- Tray depth - 14.75"
- Convenient tie down slots in rear of tray
- Includes 10-32 and 12-24 rack screws
- Load capacity - 50lbs
- Black static resistant powder coat finish

VMP ERS2U

Two Space Rack Shelf- up to 17.375" equipment width-14.75" depth-50lbs capacity-black static resistant powder coat finish

VMP ERS2UV

Vented version of the ERS2U

VMP ERSS1U

Sliding Keyboard shelf 1U





INTERACTIVE | CENTRAL VMS

IP NETWORK

CTV

BURGLARY

DETECTION

WIRELESS

FILE

TRANSMISSION

ENVIRONMENTAL

PERIS

ACCESS

COMMUNICATIONS

HOME ENT.

PAVIST. AUD.

STRUCT. WIRE

TOOLS

INFO

IP SOLUTIONS IP NETWORK



VMP ERLCD1017

VMP ERLCD1017

LCD Monitor Rack Mount- for 10-17" LCD monitors-inverted up to 23" LCD Monitor-50lbs capacity-9 space racking height-accommodates VESA 75mm or 100mm



VMP ERCASTERS

VMP ERCASTERS

4 pack of heavy duty casters that attach to ER1, ER148, and ER184 racks-400lbs capacity

Blank Filler Plates

VMP ER1B Single Space Filler Plate

VMP ER2B Two Space Filler Plate

VMP ER4B Four Space Filler Plate

VMP ER8B Eight Space Filler Plate



BW RACKFC

Indoor/Outdoor Enclosures with 19" Rack Mounts

Each enclosure is completely assembled and ready to use. Because of size and weight these enclosures must be drop shipped from Mier via truck.

BW RACKFC

NEMA3R Outdoor Enclosure with 12RU rack, fan, rain shroud, filters, and lock.

BW RACKAcht


NEMA4 Outdoor Environmental Enclosure with 12RU rack, 2000 BTU AC, heater, filters, and lock

BW RACKCART

NEMA1 Indoor Enclosure with 12RU rack, fan, louvers, lock, and wheels.

BW 3RU

3RU rack mount open face shelf for enclosures above or any standard 19" rack



BW 3RU



TRP 9625

Network Test Equipment:



TRP 9625

PoE Bug Power over Ethernet Detector

- Detects 802.3af, 802.3at - Determines Mid & End Span
- Tests RJ45 Ethernet ports for the presence of DC power

TRP 3290

Firefly Kit – WireMaster Rapid LAN Mapping Tool

- Works with any wired RJ-45 installation
- Flashing green LED identifies cable
- Works with CAT5, CAT5e, CAT6, CAT6a, CAT6e, CAT7 (GG45), & CAT7a (GG45) installations
- Includes short & continuity tester
- Magnetic back for easy mounting
- Pays for itself on first use
- Patent Pending
- 3 year warranty



TRP 3290



PLA TNC950AR



NEW PLA TNC950AR

Net Chaser™ Ethernet Speed Certifier & Network Tester

- Port Discovery
- Detects PoE per IEEE 802.3af/at with load test for voltage drop and which pairs the PoE is located on (class)
- IPV4 Support
- Ping to a specific IP or URL address
- Ping up to 8 IP targets at a time
- Link light to identify location on a hub/switch/router port
- Verifies DHCP connectivity and DNS
- Discovers CDP and LLDP Protocols
- VLAN Discovery
- Traceroute
- Bit Error Rate Test (BERT), Signal to Noise Ratio (SNR), SKEW
- BERT only test 100Mbps & 1Gbps
- Measures and displays length for each pair in feet or meters
- Improperly terminated cables are clearly displayed on a color graphical wire-mapping display
- Detects Length to Opens & Shorts
- Verifies Continuity for RJ45, and Coax cables
- Saves test results and easily uploaded to a computer
- Tone Generation
- ID Only remotes (Network and Coax) - up to 20 available
- Testing and ID Remotes - up to 8 available

FOR FULL, UP-TO-DATE PRICING VISIT US ONLINE AT WWW.SESONLINE.COM

Due to space limitations, we are unable to list every product from every manufacturer which we carry in stock. If you can't find the product you're looking for or if you have a specific need, please call us toll free for more information about our inventory.

GROW your business with SES Up-Sell and RMR

At **SES**, we're always looking for new ways to **help your business grow**. We study the market, analyze what works and what doesn't, and peer into the future to see what new products and opportunities are coming so you can be prepared. But in this tough economy, we knew we had to look deeper. What are the trends telling us? What are the common business practices that help businesses thrive and make good companies great?

What we discovered were two simple, yet incredibly valuable traits shared by all the great companies; the art of the **Up-Sell**, and the benefits of **Recurring Monthly Revenue (RMR)**.

Up-Selling is a sales technique that can work for any business, because the products you are "adding" to the order complement (or are related to) the products your customer is already buying. Successful fast food restaurants do it everyday, and look how it's worked for them. Give Up-Selling a try today, and see how it can grow your business and increase your revenue every time you use it!

You can also easily add **RMR** to your business model. For example, monthly service subscriptions are a great way to earn a regular monthly income from existing customers with little to no additional work on your part. The revenue simply flows in while you're out in the field acquiring new customers.

We're confident that just by implementing these two simple practices into your business plan, **your business will be better prepared to profit throughout the coming year**. And, as always, SES stands ready to help with any questions you may have.

