

Switch Start MH Std 400W/640 Mog ED28 CL

Product family description Range of Switch Start quartz metal halide lamps for long life and high efficiency.

Features/Benefits

- Long life up to 20,000 hours.
- Up to 100 lumens per watt.

Applications

• Ideal for industrial and retail high/low bays, and parking lots.

Notes

- Color characteristics may vary somewhat from one lamp type to another. Time should be allowed for the lamp to stabilize in color when it is turned on for the first time or if for any reason its operating position is changed. This may require several hours' operation, with more than one start. Lamp color and output may change temporarily if the lamp is subjected to excess vibration or shock. Lamp color characteristics may change after long accumulate operating time. (372)
- Rated average life is the life obtained, on the average, from large representative groups of lamps in laboratory tests under controlled conditions at 10 or more operating hours per start. It is based on survival of at least 50% of the lamps and allows for individual lamps or groups of lamps to vary considerably from the average. For lamps with a rated average life of 24,000 hours, life is based on survival of 67% of the lamps. (351)
- Rated average life hours for universal lamps is based on vertical operating position. Operating these lamps in other position will reduce the life by approximately 25% of the rated average life hours.
- Approximate lumen values listed are for vertical operation of the lamp. (352)
- Means Lumens is the approximate lumen output at 40% of lamp rated average life. (353)
- · Heat resisting glass bulb.


Product data		
Product Number	278622	
Full product name	Switch Start MH Std 400W/640 Mog ED28 CL	
Ordering Code	MH400/U/ED28	
Pack type	1 Sleeve Open End	
Pieces per Sku	1	
Skus/Case	12	
Pack UPC	046677278625	



Product data		
EAN2US		
Case Bar Code	50046677278620	
Successor Product number		
Base	Mogul [Single Contact Mogul Screw]	
Base Information	Brass [Brass Base]	
Bulb	ED28	
Bulb Material	Hard Glass	
Bulb Finish	Clear	
Operating Position	Universal [Any or Universal (U)]	
Packing Type	1SL [1 Sleeve Open End]	
Packing Configuration	12	
RatedAvgLife(See Family Notes)	20000 hr	
Ordering Code	MH400/U/ED28	
Pack UPC	046677278625	
Case Bar Code	50046677278620	
Energy Saving	Not Applicable	
ANSI Code HID	M59/E	
Watts	400W	
Lamp Voltage	135 V	
Mercury (Hg) Content	52 mg	
Color Code	640 [CCT of 4000K]	
Color Rendering Index	65 Ra8	
Color Designation	Cool White	
Color Temperature	4000 K	
Initial Lumens	36000 Lm	
Design Mean Lumens	24000 Lm	
Light Center Length L	5 in	
Max Overall Length (MOL) - C	8.313 in	
Diameter D	3.5 in	
Product Number	278622	





SS MH Std ED28 CL



Cap-Base E39







SS MH Std ED28

Operating Position any

