

Power Management Software

PowerPanel[®] Business Management

Rev. 4

SAVE THESE INSTRUCTIONS

Please read this manual and follow the instructions for installation and use.

CyberPower Software License Agreement

PLEASE READ THIS LICENSE AGREEMENT ("LICENSE") CAREFULLY BEFORE USING THIS SOFTWARE. BY DOWNLOADING, INSTALLING, OR USING THIS SOFTWARE, YOU ACCEPT ALL TERMS AND CONDITIONS OF THE LICENSE AGREEMENT. IF YOU DO NOT AGREE TO THE TERMS OF THIS LICENSE, YOU MUST DELETE OR DISABLE ANY COPY IN YOUR POSSESSION OR CONTROL.

1. General.

- a. The term "Software" will include any upgrades, modified versions or updates of the Software licensed to you by Cyber Power Systems, Inc. unless such upgrades, modified versions or updates is accompanied by a separate license in which case the terms of that license will govern.
- b. Title and intellectual property rights in and to any content displayed by or accessed through the Software belongs to the respective content owner. Such content may be protected by copyright or other intellectual property laws and treaties, and may be subject to terms of use of the third party providing such content. This License does not grant you any rights to use such content.

2. Use of the Software. Subject to the terms of this License, you are granted a limited nontransferable license to install and use this Software on any compatible computer or device that you own or control.

3. License Grant. You are hereby granted a personal, non-transferable and non-sublicenseable, non-exclusive license to use the Software. Except for the license aforesaid, you are granted no other rights or licenses, by implication, or estoppel, or otherwise, under any patents or other intellectual property rights.

4. Restrictions.

- a. You agree not to: (i) remove any copyright, trademark or other proprietary notices from any portion of the Software; (ii) copy, reproduce, modify, adapt, translate, reverse engineer, decompile, disassemble, decrypt or create derivative works of the Software or otherwise attempt to discover the source code of the Software or any part thereof; (iv) link to, mirror or frame any portion of the Software; (v) cause or launch any programs or scripts for the purpose of scraping, indexing, surveying, or otherwise data mining any portion of the Software or unduly burdening or hindering the operation and/or functionality of any aspect of the Software; or (vi) attempt to gain unauthorized access to or impair any aspect of the Software or its related systems or network; (vii) distribute or make the Software available over a network where it could be used by multiple devices at the same time; and (viii) publish, rent, lease, lend, sell, redistribute or sublicense the Software.
- b. The Software was designed for systems that do not require fail-safe performance. You may not use the Software in any device or system in which a malfunction of the Software would result in foreseeable risk of injury or death to any person. This includes operation of nuclear facilities, aircraft navigation or communication systems and air traffic control.
- c. Any attempt to do so is a violation of License. If you breach this

restriction, you may be subject to prosecution and damages.

- 5. Consent to Use of Data.** You agree that Cyber Power Systems, Inc. and its subsidiaries may collect and use technical and related information, including but not limited to technical information about your computer, mobile device, system and application software, and peripherals, that is gathered periodically to facilitate the provision of Software updates, product support and other Softwares to you (if any) related to the Software. Cyber Power Systems, Inc. may use this information, as long as it is in a form that does not personally identify you, to improve our products or to provide Softwares or technologies to you. At all times your information will be treated in accordance with Cyber Power Systems, Inc. Privacy Policy, which can be viewed on our website.
- 6. Intellectual Property Rights.** The Software is owned by Cyber Power Systems, Inc. and its suppliers, and its structure, organization and code are the valuable trade secrets of Cyber Power Systems, Inc. and its suppliers. All title and intellectual property rights in and to any third party content that is contained in the Software or may be accessed through the use of the Software, is the property of the respective content owners and may be protected by applicable intellectual property related laws and treaties.
- 7. Disclaimer.** The Software is being provided to you AS IS and Cyber Power Systems, Inc., its subsidiaries and their supplier makes no warranty as to its use or performance. THE ENTIRE RISK OF USE AND PERFORMANCE REMAINS WITH YOU. CYBER POWER SYSTEMS, INC., ITS SUBSIDIARIES AND THEIR SUPPLIERS DO NOT AND CANNOT WARRANT THE PERFORMANCE OR RESULTS YOU MAY OBTAIN BY USING THE SOFTWARE. CYBER POWER SYSTEMS, INC., ITS SUBSIDIARIES AND THEIR SUPPLIERS MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AS TO NONINFRINGEMENT OF THIRD PARTY RIGHTS, MERCHANTABILITY, OR FITNESS FOR ANY PARTICULAR PURPOSE. IN ADDITION, CYBER POWER SYSTEMS, INC., ITS SUBSIDIARIES AND THEIR SUPPLIERS MAKES NO REPRESENTATION, WARRANTY, OR GUARANTEE REGARDING THE RELIABILITY, TIMELINESS, QUALITY, SUITABILITY, OR AVAILABILITY OF THE SOFTWARES OR ANY SOFTWARES OR GOODS REQUESTED THROUGH THE USE OF THE SOFTWARES, OR THAT THE SOFTWARES WILL BE UNINTERRUPTED OR ERROR-FREE. YOU FURTHER ACKNOWLEDGE THAT THE SOFTWARE ARE NOT INTENDED OR SUITABLE FOR USE IN SITUATIONS OR ENVIRONMENTS WHERE THE FAILURE OR TIME DELAYS OF, OR ERRORS OR INACCURACIES IN THE CONTENT, DATA OR INFORMATION PROVIDED BY, THE SOFTWARE COULD LEAD TO DEATH, PERSONAL INJURY, OR SEVERE PHYSICAL OR ENVIRONMENTAL DAMAGE, INCLUDING WITHOUT LIMITATION THE OPERATION OF NUCLEAR FACILITIES, AIRCRAFT NAVIGATION OR COMMUNICATION SYSTEMS, AIR TRAFFIC CONTROL, LIFE SUPPORT OR WEAPONS SYSTEMS.
- 8. Limitation of Liability.** IN NO EVENT WILL CYBER POWER SYSTEMS, INC., ITS SUBSIDIARIES AND THEIR SUPPLIERS OR ANY OF THEIR RESPECTIVE OFFICERS, DIRECTORS, EMPLOYEES, LOCALS OR AFFILIATES BE LIABLE TO YOU FOR ANY CONSEQUENTIAL, INCIDENTAL, SPECIAL OR PUNITIVE

DAMAGES, INCLUDING BUT NOT LIMITED TO ANY LOST PROFITS, LOST DATA, OR COST TO PROCURE SUBSTITUTE SOFTWARES, EVEN IF CYBER POWER SYSTEMS, INC., ITS SUBSIDIARIES AND THEIR SUPPLIERS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, OR FOR ANY CLAIM BY ANY THIRD PARTY. Cyber Power Systems, Inc. ,its subsidiaries and their suppliers shall not be responsible for any incorrect or inaccurate information, caused by the internet user or for any of the equipment or programming associated with or utilized in this Software, or for any technical error, or any combination thereof that may occur in the course of the administration of this Software including any omission, interruption, deletion, defect, delay in operation or transmission, communications line or telephone, mobile or satellite network failure, technical problems or traffic congestion on the internet or website, software failure, theft or destruction or unauthorized access to or alteration of entries and any injury or damage to your computer related to or resulting from participating in or downloading any materials in this Software.

Some states or jurisdictions do not allow the exclusion or limitation of incidental, consequential or special damages, or the exclusion of implied warranties or limitations on how long an implied warranty may last, so the above limitations may not apply to you.

9. Compliance with Law; Export Control. You will comply with all national and international laws, rules and regulations that apply to the Software and your use of the Software as well as end-user, end-use and destination restrictions issued by the United States or other governments. You agree that the Software will not be shipped, transferred, exported or re-exported into any country or used in any manner prohibited by the United States Export Administration Act or any other export laws, restrictions or regulations. In particular, but without limitation, the Software may not be exported or re-exported (a) into any U.S. embargoed countries or (b) to anyone on the U.S. Treasury Department's list of Specially Designated Nationals or the U.S. Department of Commerce Denied Person's List or Entity List. By using the Software, you represent and warrant that you are not located in any such country or on any such list. You also agree that you will not use the Software for any purposes prohibited by United States law and the applicable laws you located, including, without limitation, the development, design, manufacture or production of missiles or nuclear, chemical or biological weapons.

10. Trademark. This License does not grant to you any rights in connection with any trademarks or service marks of Cyber Power Systems, Inc. or of its licensors or suppliers.

11. Termination. This License is effective until terminated. Your rights under this License will terminate automatically or otherwise cease to be effective without notice from Cyber Power Systems, Inc. if you fail to comply with any term(s) of this License. Upon the termination of this License, you shall cease all use of the Software and destroy all copies, full or partial, of the Software. Sections 5, 6, 7, 8, 9, 10, 12 and 13 of this License shall survive any such termination.

12. Governing Law and General Provisions.

This License will not be governed by the United Nations Convention on Contracts for the International Sale of Goods, the application of which is expressly excluded.

- a. **North and South America.** If you acquired the Software in North or South America, this License will be governed by the laws of the State of Minnesota, U.S.A., excluding the application of its conflicts of law rules. You irrevocably agree to the exclusive jurisdiction and venue of the courts in Minneapolis, Minnesota, U.S.A. for any disputes arising out of or in connection with this License. If applicable law prevents jurisdiction and venue in Minneapolis and you live outside the United States, then to the maximum extent permitted by applicable law you irrevocably agree that for any disputes arising out of or relating to this License exclusive jurisdiction and venue will be in the courts in the largest city in your country within 200 miles of where you live.
- b. **Europe.** If you acquired the Software in Europe, this License will be governed by the laws of France, excluding the application of its conflicts of law rules. You irrevocably agree to the exclusive jurisdiction and venue of the courts in Paris, France for any disputes arising out of or in connection with this License. If applicable law prevents jurisdiction and venue in Paris, then to the maximum extent permitted by applicable law you irrevocably agree that for any disputes arising out of or relating to this License exclusive jurisdiction and venue will be in the courts in the largest city in your country within 200 miles of where you live.
- c. **Outside the United States and Europe.** If you acquired the Software in any country other than in North America, South America or Europe, this License will be governed by the laws of Taiwan and the court of first instance will be Taiwan Shilin District Court, excluding the application of its conflicts of law rules. If applicable law prevents the designation of the Taiwan Shilin District Court as the court of first instance, then to the maximum extent permitted by applicable law you irrevocably agree that for any disputes arising out of or relating to this License exclusive jurisdiction and venue will be in the courts in the largest city in your country within 200 miles of where you live.

13. Others.

- a. If any part of this License is found void and unenforceable under applicable laws, it will not affect the validity of the rest of the License, which shall remain valid and enforceable according to its terms. This License shall automatically terminate upon failure by you to comply with its terms. This License may only be modified in writing signed by an authorized officer of Cyber Power Systems, Inc.
- b. These terms expressly supersede prior agreements or arrangements with you. We may amend the Terms from time to time. Amendments will be effective upon Cyber Power Systems, Inc. posting of such updated terms at this location or in the amended policies or supplemental terms on the applicable Software(s). Your continued access or use of the Software after such posting confirms your consent to be bound by the Terms, as amended.


Table of Contents

CyberPower Software License Agreement	i
1 Introduction.....	1
2 Getting Started	2
2.1 Prerequisites	2
2.1.1 Hardware Limitation	2
2.1.2 Operating System.....	2
2.1.3 Web Browser.....	3
2.2 Installation	3
2.2.1 Installation on Windows.....	3
2.2.2 Installation on Linux.....	6
2.3 Accessing PowerPanel® Business Management	11
2.3.1 Login	11
3 Using PowerPanel® Business Management	13
3.1 DASHBOARD.....	13
3.1.1 Toolbar.....	13
3.1.2 Node Components	14
3.1.3 Power Device Management.....	17
3.1.4 Power Device Details	18
3.1.5 Power Device Operations.....	21
3.1.6 IT Equipment Management.....	24
3.1.7 IT Equipment Details	25
3.1.8 IT Equipment Operations	25
3.1.9 Infrastructure Management	26
3.1.10 Infrastructure Details.....	28
3.1.11 Infrastructure Setting Wizard	29

3.1.12	Group Management	34
3.1.13	Group Details.....	35
3.1.14	Group Operations	37
3.2	SETTING	39
3.2.1	Shutdown Events.....	39
3.2.2	Notifications.....	39
3.2.3	Notification Channels	40
3.2.4	Recipients	45
3.2.5	Auto-Discover Range.....	46
3.2.6	Security.....	47
3.2.7	Advanced.....	52
3.2.8	Event Details.....	56
3.3	REPORTING	58
3.3.1	System Logs	58
3.3.2	Event Logs.....	59
3.3.3	Energy Use	61
3.4	HELP	62
3.4.1	PowerPanel® Business.....	62
3.4.2	Content	63
4	Technical Support.....	64
4.1	Troubleshooting	64
4.2	FAQ	66
5	Glossary.....	71

1 Introduction

PowerPanel® Business Management software simultaneously monitors and controls multiple UPS/PDU/ATS units and computers which have Local or Remote (modules from PowerPanel® Business) installed via the local network. It also logs events and results about commands for power management.



PowerPanel® Business structure

PowerPanel® Business Management provides users the following functions:

- Simultaneous monitoring of multiple UPS/PDU/ATS units, equipment and computers which have Local or Remote installed.
- Control access to all monitored UPS, PDU, computers and equipment.
- Detailed load management between UPS/PDU/ATS and all powered computers/equipment.
- Equipment groups for easy monitoring or individual access.
- Viewing additional information and status of monitored UPS, PDU, computers and equipment.
- Historical logs for events and results about demands to power management.

2 Getting Started

2.1 Prerequisites

2.1.1 Hardware Limitation

- Minimum Core 2 – Compatible CPU.
- 1 gigabytes (GB) of RAM recommended minimum; more memory generally improves responsiveness.
- Minimum of 1 GB of free space of hard disk.
- Serial port or USB port. (Required by the Local)
- Network interface.

2.1.2 Operating System

PowerPanel® Business software can be installed and is supported on the following operating systems:

- **32-Bit Versions:**
 - Windows 10
 - Windows 8
 - Windows 7
 - Centos 7+
 - Ubuntu 18.04 LTS
 - VMware ESXi 6.0+ (ESXi Free Edition is not supported)
- **64-Bit Versions:**
 - Windows Server 2012
 - Windows Server 2012 R2
 - Windows Server 2016
 - Windows Hyper-V Server 2012
 - Windows Hyper-V Server 2012 R2
 - Windows 10
 - Windows 8
 - Windows 7
 - Centos 7+
 - Ubuntu 18.04 LTS
 - VMware ESXi 6+ (ESXi Free Edition is not supported)

Note: Because of the abundance of different Linux builds, not all builds are tested with PowerPanel® Business but most builds will be able to run the program.

2.1.3 Web Browser

PowerPanel® Business software is accessed using a web browser and is compatible with the following browsers:

- Microsoft Internet Explorer 11 or above
- Firefox
- Google Chrome

2.2 Installation


2.2.1 Installation on Windows

After you have downloaded PowerPanel® Business from CyberPower Systems' website (www.cyberpower.com) follow the setup installation wizard as described below.


- Click the **Next** button to start an installation.




- Accept the license agreement.




- Select the destination directory.



- Choose the component. PowerPanel® Business Management only contains one module. In this step, only Management can be selected.



- Click the **Finish** button to complete the installation.




2.2.2 Installation on Linux


After you have downloaded ® Business from CyberPower Systems' website (www.cyberpower.com) follow the setup installation wizard as described below. The installer is used to install the software and requires root permission. The installation wizard will guide users in completing the installation. Initiate the wizard by running the `./ppb-linux-x86.sh` command or double clicking `ppb-linux-x86.sh` on 32-bit systems or by running the `./ppb-linux-x86_64.sh` command or double clicking `ppb-linux-x86_64.sh` on 64-bit systems.

To install, follow below steps:


- Click the **Next** button to start an installation.




- Accept the license agreement.




- Choose the destination directory.



- Choose the component. PowerPanel® Business Management only contains one module. In this step, only Management can be selected.



- Click the **Finish** button to complete the installation.



2.2.2.1 Installation in Text Mode

When the system does not support graphic mode, the Linux installation needs to be initiated in the terminal by using the `./ppb-linux-x86.sh -c` command on 32-bit systems or use `./ppb-linux-x86_64.sh -c` command on 64-bit systems.

The installation procedure will be initiated as following steps:

- Press **Enter** to start an installation.

```
Unpacking JRE ...
Starting Installer ...
This will install CyberPower PowerPanel Business on your computer.
OK [o, Enter], Cancel [c]
```

- Accept the license agreement.

```

of law rules. You irrevocably agree to the exclusive jurisdiction and venue
of the courts in Paris, France for any disputes arising out of or in
connection with this License. If applicable law prevents jurisdiction and
venue in Paris, then to the maximum extent permitted by applicable law you
irrevocably agree that for any disputes arising out of or relating to this
License exclusive jurisdiction and venue will be in the courts in the
largest city in your country within 200 miles of where you live.
c. Outside the United States and Europe. If you acquired the Software in any
country other than in North America, South America or Europe, this License
will be governed by the laws of Taiwan and the court of first instance will
be Taiwan Shilin District Court, excluding the application of its conflicts
of law rules. If applicable law prevents the designation of the Taiwan
Shilin District Court as the court of first instance, then to the maximum
extent permitted by applicable law you irrevocably agree that for any
disputes arising out of or relating to this License exclusive jurisdiction
and venue will be in the courts in the largest city in your country within
200 miles of where you live.

13. Others.
[Enter]

a. If any part of this License is found void and unenforceable under
applicable laws, it will not affect the validity of the rest of the License,
which shall remain valid and enforceable according to its terms. This
License shall automatically terminate upon failure by you to comply with its
terms. This License may only be modified in writing signed by an authorized
officer of Cyber Power Systems, Inc.
b. These terms expressly supersede prior agreements or arrangements with
you. We may amend the Terms from time to time. Amendments will be effective
upon Cyber Power Systems, Inc. posting of such updated terms at this
location or in the amended policies or supplemental terms on the applicable
Software(s). Your continued access or use of the Software after such posting
confirms your consent to be bound by the Terms, as amended.

I accept the agreement
Yes [1], No [2]

```

- Choose the destination location.

```

Select the folder where you would like CyberPower PowerPanel Business to be
installed, then click Next.
Where should CyberPower PowerPanel Business be installed?
[/usr/local/PPB]

```

- Choose the component. If one single computer is connected to the UPS directly via a USB or serial connection, Local should be installed. If the computer is powered by a UPS already connected to a Local, has a remote management card installed or is connected to a PDU, Remote should be installed.

Note: Local and Remote cannot be installed on the same computer.

```

Which components should be installed?
1: Local
2: Remote
Please enter a comma-separated list of the selected values or [Enter] for the default selection:
1

```

- Installation procedure starts to process until the installation is complete.


```

Extracting files ...
ling CyberPower PowerPanel Business on your
computer.
Finishing installation ...
Setup has finished instal

```

2.3 Accessing PowerPanel® Business Management

The PowerPanel® Business Management web interface can be accessed following the directions below. To access the web interface on a local computer, select **Start > All Programs > CyberPower PowerPanel® Business > PowerPanel Business Management** in the Windows Desktop or enter the **http://localhost:3052/management** as the URL in the browser.




Launching PowerPanel® Business software

On Linux, users can enter **http://localhost:3052/management** in the address of the web browser to access the interface. Users can also enter the URL, **http://localhost:3052/management** in the local computer or **http://hosted_computer_ip_address:3052/management** in the remote computer, to the address field of the web browser to access the PowerPanel® Business software web interface. **hosted_computer_ip_address** is the IP address of the computer which has the PowerPanel® Business software installed. For vMA on the ESX or ESXi, **hosted_computer_ip_address** is the IP address of the vMA (**Note: hosted_computer_ip_address** is the IP address of the host computer on ESX).

2.3.1 Login

The default username is **admin** and the password is **admin**. For security, it is recommended to change the username and password on the **SETTING/Security/User** page after the initial login.



Selecting the **Remember Me** option on the login page allows the credentials to be remembered for automatic logon at the next session. To terminate the session, click the **Logout** button on the page. The session will timeout and you will be logged out if no activity takes place during the time of **Session Timeout**. The **Session Timeout** can be configured on the **SETTING/Security/User** page.

3 Using PowerPanel® Business Management

3.1 DASHBOARD

DASHBOARD page provides the management of power equipment and infrastructures such as VMware virtualization. Below are the capabilities user can find in **DASHBOARD** page.

- Monitor status and events from a connected UPS/PDU/ATS.
- Issue commands to the UPS/PDU/ATs such as a power off, power cycle or power restore.
- Request that the UPS perform a battery test, sound its alarm or mute the audible alarms.
- Manage equipment and computers which are powered by UPS units and PDUs, and order connected computers to shut down or a reboot.
- Manage grouped UPS/PDU/ATs.
- Monitor the operating status from the infrastructures.
- Define detailed action setting for each event of the infrastructure's power source.
- Manage the service infrastructures.

Device	Status	Message	Summary
PDU1SSW10ATNET	Normal	Battery has fully charged. Normal.	112V, 100%, 59%RH, 24.5°C, 14%
RMCARD205	Normal	Normal. Battery test is complete and was successful.	112V, 100%, 59%RH, 24.5°C, 14%
PDU30SWT17ATNET	Normal	Bank #3 becomes no load. Normal.	112V, 100%, 59%RH, 24.5°C, 14%
ERP Server	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
localhost.localdomain	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
VMware vCenter Server	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
datastore1	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
datastore1 (1)	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
Test	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
Cluster	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
192.168.208.230	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
192.168.208.231	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
vApp1	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
ppb400-local	Power off	Power off.	112V, 100%, 59%RH, 24.5°C, 14%
win10	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
test	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%
PowerChute Network Shutdown...	Power off	Power off.	112V, 100%, 59%RH, 24.5°C, 14%
win7	Normal	Normal.	112V, 100%, 59%RH, 24.5°C, 14%

DASHBOARD page

3.1.1 Toolbar

The Toolbar provides information about the status of monitored devices and options to expand, add group or device.

Toolbar of DASHBOARD

These three buttons will allow users to add devices, expand or collapse all groups and device outlets.

	Add Device. Click this button then the <i>Add Device</i> dialogue box will appear.
	Expand All. This button will expand all groups and device outlets.
	Collapse All. This button will collapse all groups and device outlets.

The refresh button on the right side of the tool bar allows user to refresh DASHBOARD page.

	Refresh. Click this button to refresh DASHBOARD page.
---	--

The other four icons indicate the amount of monitored devices that have had severe-level or warning-level events occur, the numbers of devices that have lost communication with Management and the number of devices that are normal.

	Indicates severe-level power events such as <i>Runtime is insufficient</i> .
	Indicates warning-level power events such as <i>Utility power failure</i> .
	Indicates the devices which have lost communication with Management. Management cannot monitor or control computers and equipment when communication is lost.
	Indicates that there are no problems with these devices.

System will change the state according to the current power consumption of the entire system in past hour.

	Indicates the total power consumption of the entire system falls in a normal range.
	Indicates the total power consumption of the entire system exceeds the high threshold.
	Indicates the total power consumption of the entire system violates the low threshold.


System will change the state according to the current load of the entire system in past hour.

	Indicates the total load of the entire system is zero.
	Indicates the total load of the entire system falls in a normal range.
	Indicates the total load of the entire system is overload.

3.1.2 Node Components

Each node has a name and an icon indicating what type it is. A UPS/PDU/ATS node provides detailed information about what power events have occurred and what the current status is.

The detail information for each node is available by clicking information icon , and a context menu for each node is available by clicking setting icon . This allows users to view detailed information such as *Summary* or *Status*, or request operations such as *Shutdown* or *Restart*. A menu item becomes disabled when this operation is in progress or is not supported.



A context menu appears by accessing a device node.

Each node can be one of the following types:

	A Group.
	A UPS. This UPS may have an RMCARD or is connected to a computer which is controlled by Local.
	A UPS. A VMware vCenter server or VMware ESXi host is connected with this UPS.
	A PDU. This PDU may be set to connect to a monitored UPS.
	An ATS. This ATS may be set to connect with the UPS which could be monitored by Management.
	IT Equipment. A computer which has Local installed.
	IT Equipment. A computer which has Remote installed.
	IT Equipment. Equipment which may be a computer or powered equipment.
	Indicates the computer connected with the UPS is a VMware ESXi host.
	Indicates that this outlet is not being using by any IT equipment.
	Indicates that is a VMware vCenter server.
	Indicates that is a storage in a vCenter.
	Indicates that is a Cluster. The Cluster is included in a vCenter.
	Indicates that is a VMware ESXi host. The ESXi host may be included by a vCenter server.
	Indicates that is a vApp. A vApp is a group of virtual machines.
	Indicates that is a virtual machine running on the VMware ESXi server.

Each node also has a column that indicates what the current state is and what power events have occurred. The column in a UPS node displays power events such as *Utility power failure* or *Runtime is insufficient* event while the column in a PDU node displays power events such as *Input is low load* or *Input is overload*.

The UPS/PDU/ATS nodes display a brief operating status consisting of schedules, utility power, batteries, support load and outlets. The brief status column displays in gray when local or network communication has failed.

A UPS can have the following states:

	Normal. The UPS is working normally.
	Power Failure. There is no utility power supplied to UPS.
	Bypass. The UPS has switched to bypass mode and is supplying direct utility power.
	Boost. The utility voltage is below the regular voltage and UPS is increasing the utility voltage.
	Buck. The utility voltage is beyond the regular voltage and UPS is decreasing the utility voltage.
	Test. A battery test is processing.

Batteries can have the following states when UPS is operating:

	Not Present. Batteries are absent and there is no battery power.
	Normal. Batteries are not being using.
	Charging. Batteries stops discharging due to a power event and are being charged.
	Discharging. The UPS is supplying battery power to its load.
	Fully Charged. Batteries are at 100% capacity.

UPS/PDU/ATs have the following states according to their current load:

	No Load. There is no output load.
	Low Load. The PDU is in a low load condition.
	Normal. The output power is normal.
	Near Overload. The PDU is near the overload condition.
	Overload. Output consumption of equipment exceeds the rating load on UPS or the PDU is in an overload condition.

ATS have the following states on functioning:

	ATS uses this input source as current source, and this source is normal.
	ATS uses this input source as redundant source, but this source is normal.
	This power source of ATS is power failure.

The sensor on the UPS/PDU/ATS has the following states according to the environment temperature:

	Normal. Indicates the temperature measured by the sensor is in a predefined normal range.
	Overheated. Indicates the current temperature exceeds the high temperature threshold.
	Undercooled. Indicates the current temperature violates the low temperature threshold.

The sensor on the UPS/PDU/ATS has the following states according to the relative humidity:

	Normal. Indicates the humidity as a percentage measured by the sensor is in a predefined normal range.
---	---

	Over wet. Indicates the current humidity exceeds the high humidity threshold.
	Dry. Indicates the current humidity violates the low humidity threshold.

A group has the following states according to the total power consumption:

	Indicates the total power consumption of the group falls in the normal range.
	Indicates the total power consumption of the group exceeds the high threshold.
	Indicates the total power consumption of the group violates the low threshold.

3.1.3 Power Device Management

3.1.3.1 Add Device

In order to monitor and control power device UPS/PDU/ATS, these devices must be added to the Management by clicking **Add Device** button on the toolbar.



Add Device button on toolbar

The Add Device dialog will show up by clicking **Add Device** button.

Add Device

Group Name

None

+

Add Device

☐	Name	Location	IP Address	MAC Address	Type
☒	PDU15SW10ATNET	Server Room	192.168.208.211	00-0C-15-00-F...	UPS
☒	RMCARD205	Server Room	192.168.208.214	00-0C-15-01-A0...	UPS
☒	PDU30SWT17ATNET	Server Room	192.168.208.212	00-0C-15-00-F...	ATS
☒	ERP Server	Server Room, Ra...	192.168.210.100	70-5a-0f-2d-2d...	UPS
☐	PDU41002	Server Room	192.168.208.91	00-0C-15-40-56...	PDU

Add Infrastructure

	Name	IP Address	Type
	localhost.localdomain	192.168.208.215	VMware ESXi
	VMware vCenter Ser...	192.168.208.235	VMware vCenter Server

CANCEL

SAVE

Add Device dialog

All the devices already in Management will be shown on the list, choose the devices you want to add from the list then click **SAVE** button to complete. Click the refresh button  to refresh the device list. If the device you want to add is not on the list, go to page **SETTING/Auto-Discover Range** to edit the scan range. Please refer to **SETTING/Auto-Discover Range** for more details.

3.1.3.2 Move Device

Click the setting icon of the device you want to move and select **Move** in the context menu. A **Move** window will display and select the target group from the list. After selecting the target group, click **SAVE** to move the group.

3.1.3.3 Remove Device

Click the setting icon of the device you want to remove and click **Remove** in the context menu. Click **SAVE** to remove the device. When a device is removed, its powered computers and equipment will also be removed.

3.1.3.4 Change Settings

Click the setting icon of the device you want to change setting and click **Settings** in the context menu, a **Setting** window will appear. User can change the Name of this device or configure the proper thresholds to aware of violating consumption thresholds. Once the power consumption violates thresholds, Management will warn administrators of the violation. When the thresholds are set blank, Management will use the thresholds of the **Default Energy** in **REPORTING/Energy Use/Settings** page instead of the thresholds in **Settings** of each power device.

3.1.4 Power Device Details

UPS/PDU/ATS provides further information; this information will show up by clicking info icon of each device. This includes summary, status, information, UPS, and Energy.

Detail ✕

Summary	Status	Information	Energy
Name	ERP Server		
Status	Severe		
Location	Server Room, Rack A		
Contact	Thomas, #1234		
Address	192.168.210.100		
PC and Equip.	6		
Power Source	Utility		
Remaining Runtime	N/A		
Capacity	12%		
Environment Sensor	Not Installed		

Details of a UPS monitored by Local

3.1.4.1 Summary

The **Summary** tab provides an overview of the system information:

- **Name:** The name of the selected device.
- **Status:** Displays the present status of the selected UPS/PDU/ATS.
- **Location:** Where the UPS/PDU/ATS is located.
- **Contact:** Who to contact about the UPS/PDU/ATS.
- **Address:** The IP address of the UPS RMCARD, PDU or Local computer's network interface.
- **PC and Equip.:** The number of the powered computers and equipment.
- **Outlets:** The amount of outlets on the UPS/PDU/ATS.
- **Outlet On:** The outlets which are supplying power.
- **Outlet Off:** The outlets which are not supplying power.
- **Power Source:** The power source of the UPS, e.g. *Utility* or *Battery*.
- **Remaining Runtime:** The estimated amount of time remaining that the UPS can supply power, given its current load.
- **Capacity:** The capacity of the batteries expressed as a percentage of full charge.
- **Statistics:** Indicates the state of the device as *Normal*, *Severe*, *Warning* or *Lost*.
 - **Severe:** Devices with severe-level events such as *Overheat* or *Output is off*.
 - **Warning:** Devices with warning-level events such as *Utility power failure* or *Battery need replacement*.

- **Lost:** Devices which have lost communication with Management.
- **Type:** The type of software the selected device is running, e.g. *Local*, *Remote* or *Equipment*.
- **Current Source:** Indicates which input source is being using and will be also annotated preferred or redundant source.
- **Environment Sensor:** Indicates whether the environment sensor has been installed on the UPS/PDU/ATS. Note: When the sensor cannot be detected anymore, it will be annotated *No Response*. Users can click the **Uninstall** to reflect it if it had been removed physically from the UPS/PDU/ATS.

3.1.4.2 Status

The **Status** tab displays details about the UPS/PDU/ATS.

- **Current:** The output current in Amps.
- **Outlets:** The status of each outlet on the UPS/PDU/ATS and the name of the connected computer or equipment.
- **Input:** Displays the status of the utility power supplied to the UPS.
- **Voltage:** The voltage of the utility power supplied to the UPS.
- **Frequency:** The frequency of the utility power supplied to the UPS in Hertz.
- **Output:** Displays the status of the output power that is being supplied to connected equipment.
- **Load Consumption:** The power draw of the connected equipment expressed as a percentage of the total load capacity. This displays as watts on some UPS models.
- **Battery:** Displays the status of the battery packs.
- **Capacity:** The capacity of the batteries, expressed as a percentage of full charge.
- **Remaining Runtime:** The estimated amount of time that the UPS can supply power to its load.
- **System:** Displays the operating status of the UPS.
- **Envir. Temperature:** Indicates the measured temperature from the environment sensor.
- **Envir. Humidity:** Indicates the measured humidity from the environment sensor.
- **Contact:** Indicates generic equipment connects to this sensor. Users can define the name and state in RMCARD web for each contact and monitor the state is normal.
- **Source A Voltage:** The voltage of the input power supplied to the source A of ATS.
- **Source B Voltage:** The voltage of the input power supplied to the source B of ATS.
- **Load:** The power draw of PDU/ATS supplying power to connected equipment.
- **Bank # Load:** The power of the PDU/ATS bank supplied power to the connected equipment.
- **Bank # Current:** The current of the PDU/ATS bank supplied power to the connected equipment.
- **Phase:** The phase information, including Name, Input Voltage and Current, of a 3-phase PDU.

3.1.4.3 Information

Information tab shows information about the UPS/PDU/ATS.

- **Type:** The type of the device, such as On-Line, Line Interactive or Sinewave Line Interactive for UPS; or Monitored or Switched for PDU/ATS.
- **Model Name:** The model name of the UPS/PDU/ATS.
- **Firmware Version:** The firmware version of the UPS/PDU/ATS.
- **MAC address:** The MAC address of the UPS RMCARD, PDU or Local computer's network interface.
- **Serial Number:** The serial number of the UPS.
Note: This will give the internal serial number on some models.
- **Power Rating:** The Volt-Amp rating (VA) and power rating (Watts) of the UPS.
- **Voltage Rating:** The output voltage rating (Volts) of the UPS.
- **Frequency Rating:** The output frequency rating (Hz) of the UPS.
- **Battery Replacement Date:** The date that the batteries were last replaced. This should be set at the time of battery replacement. If this date has not been set, it is recommended that this date should be set immediately.
- **External Battery Pack:** The amount of external battery packs connected to the UPS.
- **Outlets:** The amount of outlets on the PDU/ATS.

3.1.4.4 UPS

The **UPS** tab shows the connected power sources of PDU/ATS, the IP address and Outlet of UPS.

3.1.4.5 Energy

The **Energy** tab shows the chart how to spend the energy in a specified period and also shows the energy statistics of the current target node and entire system.

Each UPS, PDU, ATS and outlet of Metered by Outlet PDU whose consumption will be logged per hour and each group which contains these UPS/PDU/ATS will work accumulating the consumption of data. These data which logged the consumption in the past can be gathered to render a chart in a past day, a past month, a past year and a past decade accordingly.

Administrators will realize how much energy has been spent in a past period. Energy can be spent more efficiently and reduce the waste.

For PDU and outlets of Metered by Outlet PDU, the Peak Load value will also be recorded. Management will show the Peak Load value, the time when this value happens and the time when the Peak Value is reset.


3.1.5 Power Device Operations

Management provides control functions for a UPS/PDU/ATS. Click the setting icon of each device or the outlet of this device, the context menu will show up.

3.1.5.1 Computers on Outlets

- **Shutdown/Restart:** A shutdown or restart can be initiated on a computer with either Local or Remote installed by going to **Shutdown/Restart** in *Computers on Outlets*. A window will list the computers which can be shut down or restarted.

Note: If a PDU is connected to a UPS, shutting down computers on UPS outlets will result in shutdown computers in the PDU.




A confirmation window lists computers able to be shutdown

3.1.5.2 Power Control

- **Power Off:** Click **Power Off** and a confirmation window will appear. Decide whether to perform an immediate or a sequenced power off then click **OK** to begin. When a UPS or a PDU initiates a sequenced power off, computers connected to the UPS/PDU/ATS that have Local or Remote installed will initiate shutdown prior to the sequenced power off.


Note: A force power off will likely result in connected computers losing power.



A confirmation window of a UPS power off operation

- **Power On:** Click **Power On** to have the UPS/PDU/ATS turn on output power. Decide whether to turn on output power immediately or after a delay in the confirmation window. Click **OK** to begin.


Note: Some computers require manual booting when a UPS or a PDU powers on. To change this, set the computers BIOS to boot when power is restored.



A confirmation window of a UPS power on operation

- **Power Cycle:** Initiates a **Power Cycle** on the UPS/PDU/ATS. This will turn the UPS/PDU/ATS off then back on or vice versa. Decide whether to initiate an immediate or a sequenced power cycle and click **OK** to begin. A sequenced power cycle will cause computers connected to the UPS/PDU/ATS that have Local or Remote installed to shut down prior to the power cycle.

Note: A force power cycle off will likely result in connected computers losing power.



A confirmation window of a UPS power cycle operation

Note: If a PDU is connected to a UPS, a power off or a power cycle to the UPS may also cause all computers on this PDU to shut down.

3.1.5.3 Outlet Control

Click Outlet Control and then a Device Outlet Control window will appear, a table of current outlet status will be shown on the windows. Choose the Action and Outlets you want to control and then click CONTROL OUTLET(S) button.

Device Outlet Control

Control Action : Turn Off

	Outlet Name	Status
☒	#1	On
☐	#2	On
☒	#3	On
☐	#4	On
☐	#5	On
☐	#6	On
☐	#7	On
☐	#8	On

CANCEL

CONTROL OUTLET(S)

Outlet Control Window

Note: Not all PDUs support this function.

3.1.5.4 Battery Test

Click **Battery Test** from the context menu and the UPS will initiate a battery test.

3.1.5.5 Mute

Click **Mute** from the context menu to mute the alarm.

3.1.5.6 Alarm

Click **Alarm** from the context menu to enable or disable the UPS alarm.

3.1.5.7 Preferred Source

Click **Preferred Source** from the context menu to select which input source to be the primary one.

3.1.6 IT Equipment Management

IT equipment is computers that have PowerPanel® Business Local or Remote installed, or generic equipment that is powered by a UPS/PDU/ATS.

3.1.6.1 Modify the Equipment

By choose settings in the context menu, you can modify the *Name*, *Location* and *Contact* fields of the equipment. Enter the new data and click **SAVE**.

- **IP Address:** The IP address of the Local computer, Remote computer or the equipment on this outlet.
- **Name:** The name of the computer or equipment.
- **Location:** Where the computer or equipment is located.
- **Contact:** The contact of this computer or equipment.

3.1.7 IT Equipment Details

3.1.7.1 Summary

The **Summary** tab provides an overview of the equipment information, the operating status of the UPS/PDU/ATS and which outlet it is plugged into.

IT Equipment

- **Name:** The name of this computer or equipment.
- **Status:** The operating status of this computer or equipment.
- **Type:** Either computer or equipment. Computers will either display *Local* or *Remote* depending on which use case of PowerPanel® Business is installed. *Equipment* is displayed for generic equipment.
- **Address:** Indicates the address of this computer or equipment.
- **Location:** Indicates where this computer or equipment is located.
- **Contact:** Indicates the contact of this computer or equipment.
- **Redundant Policy:** Indicates what type of power supply redundancy is installed on the Remote computer.
- **Power Supply:** Indicates the power supply source(s) of the Remote computer.

UPS/PDU/ATS

- **Name:** The name of the UPS/PDU/ATS.
- **Status:** The operating status of the UPS/PDU/ATS.
- **Outlet:** Indicates the outlet number being used by the current equipment. It also indicates whether the outlet type is *NCL*, *Battery* or *CL*.

3.1.8 IT Equipment Operations

Shutdown/Restart

Select **Shutdown** or **Restart** from the context menu and a confirmation window will appear. Click **OK** to initiate the shutdown or restart. This is only valid for a computer with Local or Remote installed.

3.1.8.1 Power Control

- **Power Off:** Select **Power Off** from the context menu. Decide whether to turn off the outlet immediately or in sequence. Click **OK** to begin. A computer which has Local or Remote installed will initiate a graceful shutdown prior to turning off the outlet.
On specified modes, turning off or restarting one outlet of the bank will also turn off other outlets of this bank. This may cause other computers on this bank to be shut down unexpectedly.
- **Power On:** Select **Power On** from the context menu. Decide whether to turn on the outlet immediately or in sequence. Click **OK** to turn on the outlet.
- **Power Cycle:** Select **Power Cycle** from the context menu. Decide whether to restart the outlet. Click **OK** to restart the outlet. A computer which has Local or Remote installed, will also initiate a shutdown prior to the power cycling.
Turning off the outlet of a bank or restarting the outlet of the bank will also cause other computers on other outlets to be shut down.

3.1.8.2 Locate

Select **Locate** from the context menu. The computer uses speakers to generate the audible sounds.

3.1.9 Infrastructure Management

3.1.9.1 Add an Infrastructure

In order to monitor and control the VMware infrastructures, users can click the **Add Device** button on the toolbar. An **Add Device** dialog will appear for users to add an infrastructure.



Add Device button on toolbar

The Add Device dialog will show up by clicking **Add Device** button. User can add VMware infrastructures in the section of **Add Infrastructure**. An “Add an Infrastructure” dialog will show up by clicking the **Add** button . **Note:** VMWare feature is not support on ESXi free edition

Add Device

Group Name

None

+

Add Device

☐	Name	Location	IP Address	MAC Address	Type
☒	PDU15SW10ATNET	Server Room	192.168.208.211	00-0C-15-00-F...	UPS
☒	RMCARD205	Server Room	192.168.208.214	00-0C-15-01-A0...	UPS
☒	PDU30SWT17ATNET	Server Room	192.168.208.212	00-0C-15-00-F...	ATS
☒	ERP Server	Server Room, Ra...	192.168.210.100	70-5a-0f-2d-2d-...	UPS
☐	PDU41002	Server Room	192.168.208.91	00-0C-15-40-56...	PDU

Add Infrastructure

	Name	IP Address	Type
	localhost.localdomain	192.168.208.215	VMware ESXi
	VMware vCenter Ser...	192.168.208.235	VMware vCenter Server

CANCEL

SAVE

Add Device dialog

Add an Infrastructure

Notice:VMWare feature is not support ESXi free edition

Product

VMware ESXi

IP Address/Name

192.168.208.215

User Name

root

Password

.....

CANCEL

SAVE

Add an Infrastructure dialog

The detailed data is described below:

- **Product:** Specifies whether to add a vCenter server or an ESXi host.
- **IP Address/Name:** Configures the IP address or hostname for the vCenter server or the ESXi host.
- **Port:** Sets the port number for Management to access the vCenter host.
- **Username:** Sets the user name to access the vCenter server or ESXi host.
- **Password:** Sets the password for the username.
- **Attach plugin to vCenter Server:** Decides whether to attach a vCenter server plug-in. If this option is enabled, Management will install a plugin which expands the capability of vCenter server to present the Management web interface during establishing connection. After the plugin is installed, the vSphere Client interface will attach a new tab which displays Management web page.

Specify the product type and enter the necessary data. Press the **SAVE** button to add the infrastructure.

3.1.9.2 Update an Infrastructure

Click the setting icon of the vCenter server or ESXi host you wish to remove and select **Update** in the context menu, then the **Update** window will appear and allow you to configure the connection settings.

- **Port:** Sets the port number for Management to access the vCenter server.
- **Username:** Sets the user name to access the vCenter server or ESXi host.
- **Password:** Sets the password for the user name.
- **Attach plugin to vCenter Server:** Decides whether to attach a vCenter server plug-in.

Note: Changing the port, user name or password may cause communication loss with Management.

3.1.9.3 Remove an Infrastructure

Click the setting icon of the vCenter server or ESXi host you wish to remove and select **Remove** in the context menu. The **Remove Infrastructure** window will display. Click **REMOVE** to apply the removal.

If the plugin has been installed in vCenter server, the plugin will also be uninstalled during removal. If the infrastructure has been connected with the power device, the power source will also detach the infrastructure.

3.1.10 Infrastructure Details

The detail information of infrastructure will show up by clicking info icon of each node.

3.1.10.1 Summary

The **Summary** tab provides an overview of the infrastructure information:

- **Virtual Machine:** Indicates the selected infrastructure is virtual machines.
 - **Name:** The name of the selected virtual machine.
 - **Status:** Displays the present status of the selected virtual machine.
 - **Address:** The IP address of the virtual machine when the virtual machine is running.
- **VMware vApp:** Indicates the selected infrastructure is a VMware vApp.
 - **Name:** The name of the selected vApp.
 - **Status:** Displays the present status of the vApp.
 - **VM Amount:** The amount of virtual machines on the target vApp.

- **VMware ESXi Host:** Indicates the selected infrastructure is an ESXi host. It may be the ESXi host to which the selected virtual machine belongs.
 - **Name:** The name of the selected ESXi host.
 - **Address:** The IP address of the ESXi host.
 - **Status:** Displays the present status of the ESXi host.
 - **Type:** Specifies the node is ESX or ESXi host.
 - **VM Amount:** The amount of virtual machines on the target ESXi host.
- **VMware Cluster:** Indicates the selected infrastructure is a Cluster.
 - **Name:** The name of the selected Cluster.
 - **Status:** Displays the present status of the Cluster.
 - **DRS Status:** Displays the present DRS (Distributed Resource Scheduler) status on the target Cluster.
 - **HA Status:** Displays the present HA (High Availability) status on the target Cluster.
 - **ESXi Host Amount:** The amount of ESXi hosts on the target Cluster.
 - **vApp Amount:** The amount of vApps on the target Cluster.
 - **VM Amount:** The amount of virtual machines on the target Cluster.
- **VMware vCenter Server:** Indicates the selected infrastructure is a vCenter server. It may be the vCenter server to which the selected ESXi host or selected virtual machine belongs.
 - **Name:** The name of the selected vCenter server.
 - **Address:** The IP address of the vCenter server.
 - **Status:** Displays the present status of the vCenter server.
 - **ESXi Host Amount:** The amount of the ESXi hosts of the target vCenter server.
- **Storage:** Indicates the selected infrastructure is a Storage.
 - **Name:** The name of the selected Storage.
 - **Type:** Specifies it is local or shared Storage.
 - **Status:** Displays the present status of the Storage.
- **UPS:** Displays detailed information of the UPS which is supplying power to the selected infrastructure.
 - **Name:** The name of the UPS.
 - **Address:** The IP address of the UPS.
 - **Outlet:** Indicates the outlet number and what the bank type of connected outlet.
 - **Status:** Displays the present status of the UPS.


Note: Not each infrastructure provides the same information. The information will vary depending on infrastructure.

3.1.11 Infrastructure Setting Wizard

Click **Settings** in context menu of root ESXi host (an ESXi host which is not under a vCenter server), Cluster, and Storage, a setting wizard will pop up. In the setting wizard, users can configure the Power Source, Shutdown Settings, and Event Action.

3.1.11.1 Shared Storage Setting

This step is only for Storages. Storages can be set as Local Storage or Shared Storage at this step, and only Shared Storage can be configured with power protection, shutdown settings and event action.

The screenshot shows a 'Storage Setting Wizard' window with a progress bar at the top containing six numbered steps. Step 2 is highlighted in red. Below the progress bar, the title 'Shared Storage Settings' is displayed in red. Under the 'Storage Type' label, there are two radio button options: 'Shared Storage' (which is selected) and 'Local Storage'. At the bottom of the window, there are two buttons: 'BACK' and 'NEXT'.

Shared Storage Settings Wizard page of Storage

3.1.11.2 Power Source Setting

The **Power Source** step in the setting wizard allows you to connect or disconnect the infrastructure with the target UPS. Users can choose each infrastructure from the **Infrastructure** column and set power source correctly respectively, only the infrastructure set with proper power source will be protected.

Only root ESXi hosts, Clusters and shared Storages can be set with power protection. In order to make sure that the infrastructure can be protected, you should connect the infrastructure to the target UPS by assigning the correct UPS.

Cluster Setting Wizard

12345

Power Source

Which outlet is the infrastructure connected to?

Infrastructure

192.168.208.230

Power Device

ERP UPS

Model Name

PR1500ERT2U

Outlet

#1

Outlet Preview

BACK

NEXT

Power Source setting page of Cluster

In order to make sure that vCenter servers can be protected, you should complete the following steps according to your environment:

- If the vCenter server is a virtual appliance which has been deployed on the ESXi host, the ESXi host should also be added to the **Service Infrastructure** page. Connect the ESXi host with the UPS.
- If the vCenter server is running on a standalone Windows system, it is recommended to install PowerPanel® Business Local or Remote to setup power protection.

Note: The only allowable power source for Service Infrastructure settings is a UPS system.

3.1.11.3 Shutdown Settings

The Shutdown Settings step configures the shutdown behavior and the necessary shutdown duration for vApp, virtual machine and ESXi host. Moreover, virtual machine migration can also be set in this step.

Cluster Setting Wizard

1
2
3
4
5

Shutdown Settings

Virtual Machine Migration

Enable
☒

Necessary Migration Time(Seconds)

vApp Shutdown

Enable
☒

Necessary Shutdown Time(Seconds)

Virtual Machine Shutdown

Enable
☒

Necessary Shutdown Time(Seconds)

ESXi Shutdown

Enable
☒

Necessary Shutdown Time(Seconds)

BACK
NEXT

Shutdown Settings page of Cluster

- **Virtual Machine Migration** is set if virtual machines migrate to other hosts when power events happen. The necessary migration duration for all virtual machines can also be set here. This option is available in the Cluster Settings Wizard.
- **vApp Shutdown** configures the shutdown of vApp and also the necessary shutdown time for all vApps.
- **Virtual Machine Shutdown** configures the shutdown of a virtual machine and also the necessary shutdown time for all virtual machines.
- **ESXi Shutdown** configures the shutdown of an ESXi host and the necessary shutdown time for all ESXi hosts.

3.1.11.4 Event Action

When an ESXi host, Shared Storage or Cluster has the power source configured properly in the aforementioned section, Management can send the notification to the administrator and initiate a shutdown sequence if the event occurs.

Cluster Setting Wizard

12345

Event Action

Custom
☐

Urgency	Event	Command	Duration	Delay	Shutdown
!	Battery capacity is critically low		< 1 sec.	Inactive	Instant
!	Network communication lost with UPS in a power event		< 1 sec.	Inactive	5 min.
!	Network communication lost		< 1 sec.	Inactive	Instant
⚠	Utility power failure		< 1 sec.	Inactive	Inactive

BACKNEXT

Event Action setting page of Cluster

The **Event Action** step lists all events and allows users to configure the shutdown delay time for each event. Each event in the **Event Action** step will use the identical *Shutdown for Infrastructure* setting to the according event in the **Event Action/Events** page. When users change the shutdown delay time, the identical setting of the according event will be also changed.

After the *Custom* option is enabled, the selected event will be configurable. Users can change the shutdown delay time for each event and click **NEXT** to apply the setting. When the event occurs, Management will take the new shutdown delay time instead of the default one that can be configured in the **Event Action/Events** page.

3.1.11.5 Alarms for vCenter Server and ESXi Host

The vSphere includes the user-configurable events and alarms system. The alarm system logs the events happening throughout the vSphere and allows users to specify the conditions under which alarms are triggered. Alarms are notifications which are activated in response to events.

The Management will specify the alarm definitions for the vCenter servers and ESXi hosts selected in the inventory after the power source has been configured properly. When the power event occurs, the alarms will be issued from the **Triggered Alarms** view under the **Alarm** tab.

The Management defines the below alarms and issues the alarm when its related events are triggered:

Alarm Definition	Description	Triggered Event	Trigger Level
PPB UPS Communication Event	Alarm is triggered when PowerPanel® Business lost communication	Communication lost with UPS in battery mode.	Alert
		Communication lost with	Warning

with UPS.		UPS.	
PPB UPS Critical Event	Alarm is triggered when a critical UPS event occurs.	Communication established.	Normal
		UPS Low battery.	Alert
		UPS Remaining runtime exhausted.	Alert
		UPS Utility power failure.	Warning
		UPS Power restored.	Normal

For example, when the utility power fails, a warning-level alarm whose name is **PPB UPS Critical Event** will be issued in the **Triggered Alarms** view under the **Alarm** tab. A related event will be logged in the **Events** view of the **Tasks & Events** tab.

Note: Triggered alarms are visible through the vSphere Client or vSphere Web Client connected to a vCenter server.

3.1.12 Group Management

UPS/PDU/ATs and infrastructure nodes can be grouped for easy management. Orders can then be issued to multiple devices in a group.

3.1.12.1 Add Group

Click **Add Group** button “+” on the Add Device dialog to create a new group after clicking **Add Device** button on the toolbar.

Group Name

None



Add Group button on toolbar

You can also choose parents-group in the New Group dialog. Enter the new group name and choose the group under which the new group is, and then click **SAVE** button to add a new group.

New Group

New Group Name

New Group under

None

CANCEL

SAVE

New Group dialog

3.1.12.2 Edit Group

Select **Edit** from the context menu, an **Edit Group** window will appear. User can edit group name, edit devices and infrastructures nodes in the group, and set Energy Consumption Threshold of this group in the edit windows.

Edit Group

Group Name: +

Add Device ↻

☐	Name	Location	IP Address	MAC Address	Type
☐	PDU41002	Server Room	192.168.208.91	00-0C-15-40-56...	PDU
☐	PDU20SWT10ATNET	Server Room_	192.168.208.223	00-0C-15-00-0...	ATS
☐	RMCARD303	Server Room	192.168.208.226	00-0C-15-00-5B...	UPS
☐	PDU30MVT24FNET	Server Room	192.168.208.217	00-0C-15-40-12...	PDU
☐	PDU15SW8FNET	Server Room	192.168.208.222	00-0C-15-40-2C...	PDU

Add Infrastructure +

	Name	IP Address	Type
	localhost.localdomain	192.168.208.215	VMware ESXi

Energy Consumption Alert Threshold

High Threshold: KWh

Low Threshold: KWh

CANCEL **SAVE**

Edit Group dialog

3.1.12.3 Move Group

Click the Setting icon of the group you wish to move and select **Move** in the context menu. Select the target group from the list in the **Group Move** dialog. After selecting the target group, click **SAVE** to move the group.

3.1.12.4 Remove Group

Click the Setting icon of the group you wish to remove and select **Remove** from the context menu. The **GROUP Remove** window will open; click **REMOVE** to remove this group. Removing a group will not remove the sub-groups or the UPS/PDU/ATs belonging to this group. These items will be moved to the main group.

3.1.13 Group Details

Click the information icon of the group, a detail windows will show up. User can find Summary and Energy details in that window.

Summary	Energy
Group Name	Group 1
Statistics	
Normal	2
Sereve	0
warning	0
Communication lost	0
Types	
UPS	1
PDU	0

Summary tab of Details

3.1.13.1 Summary

Each group provides the statistics of all UPS/PDU/ATS from the **Summary** tab of **Details** and includes the following summary information:

- **Group Name:** A name of the selected group.
- **Statistics:** Indicates statistics about the operating conditions of the UPS/PDU/ATS:
 - **Normal:** Indicates a UPS/PDU/ATS which is normal.
 - **Severe:** Indicates a UPS/PDU/ATS with severe-level power events such as *Runtime is insufficient*.
 - **Warning:** Indicates a UPS/PDU/ATS with warning-level power events such as *Utility power failure*.
 - **Communication Lost:** Indicates a UPS/PDU/ATS which has lost communication with Management.
- **Types:** Indicates the statistics of UPS/PDU/ATS.

3.1.13.2 Energy

The **Energy** tab shows the chart how to spend the energy in a specified period and also shows the energy statistics of the current target group.

3.1.14 Group Operations

Some or all devices in a group can have the following commands issued to them:


3.1.14.1 Computers on Outlets

- **Shutdown/Restart:** Select **Shutdown** or **Restart** from the context menu of the selected group and a pop-up window will appear. Pick the computers to shut down or restart from the list. Click **OK** to initiate the shutdown or restart.

Note: If a group contains the UPS systems which have connected with PDU units, shutting down the selected group may cause the computers shutdown on these PDU units.

3.1.14.2 Power Control


- **Power Off:** Click **Power Off** and a confirmation window will appear. Pick the UPS/PDU/ATS from the list and decide whether to perform an immediate or a sequenced power off. Click **OK** to begin. When the UPS/PDU/ATS initiates a sequenced power off, computers with Local or Remote installed will initiate a shutdown prior to the sequenced power off. An immediate power off will likely cause those lose power.



A confirmation window of a bulk power off operation

- **Power On:** Click **Power On** and a popup window appear. Pick the UPS/PDU/ATS from the list and determine whether to perform an immediate or a sequenced power on. Click **OK** to begin.

Note: Some computers require manual booting when a UPS or a PDU powers on. To change this, set the computers BIOS to boot when power is restored.



Power On ✕

Below devices will switch on:

☐ Select All


☐ RMCARD205
 ☐ ERP UPS

* Power off directly without sequence delay.

CANCEL OK

A confirmation window of a bulk power on operation

- **Power Cycle:** Click **Power Cycle** and a popup window appear. Pick the UPS/PDU/ATS from the list and determine whether to perform an immediate or a sequenced power cycle. Click **OK** to begin.



Power Cycle ✕

Below devices will switch restart:

☐ Select All

☐ RMCARD205
 ☐ ERP UPS

* Power off directly without sequence delay.

CANCEL OK

A confirmation window of a bulk power cycle operation

Note: If a group contains the UPS systems which has connected with PDU units, a power cycle or a power off to the selected group will result in computers shutdown on the PDU units.

3.1.14.3 Battery Test

Only UPS units can perform a battery test. Click **Battery Test** from the context menu of the selected group. All UPS units in that group will be listed in the confirmation window. Click **OK** to initiate the battery test on all selected UPS units.

3.1.14.4 Mute

Click **Mute** from the context menu to mute the alarm.

3.1.14.5 Alarm

Click **Alarm** from the context menu to enable or disable the UPS alarm.

3.2 SETTING

3.2.1 Shutdown Events

An event is generated when the UPS/PDU/ATS encounters specific power conditions. The **SETTING/ Shutdown Events** page lists events that can be configured to shut down infrastructures. A shutdown sequence is only initiated by events specific for the target ESXi host.

- **Shutdown:** Determines whether to request the target ESXi host to be shut down and the delay before initiating the shutdown sequence. The shutdown will be canceled if the event is cleared during this delay time. The minimum delay time to initiate shut down is based on the time set for the execution of the notification to complete. This includes the notify delay time.

Note: The Management will use the **Shutdown** setting of each event here as the default shutdown delay time for each according event listed in the **Event Action** step of setting wizards of infrastructures. Refer to **Event Action** section for further details.

3.2.2 Notifications

An event is generated when the UPS/PDU/ATS encounters specific power conditions. The Management can monitor multiple power devices and computers and can be configured to notify users based on the event. The **SETTING/Notifications** page lists events and divides these events into several categories. Each event is allowed to configure the individual notification settings. The severity of each event is marked by a symbol.

The administrator can be notified when an event occurs. See **SETTING/Notification Channels** page for more details about the notification methods and recipient assignment. Use these parameters bellow to configure actions for individual events.

- **Send:** Determines whether to send a notification or not and sets the notification delay. If the event is cleared within the notification delay, the notification of the occurrence and the event cleared notification will not be sent.

- **Repeat:** Determines whether to send one additional notification after the initial notification. Only events which are of severe-level and warning-level type support a repeat notification.


3.2.3 Notification Channels

The administrator can be notified when an event occurs. In **SETTING/Notification Channels** page, users can configure several notification methods.

3.2.3.1 E-mail

- **Service provider is Gmail:**

Select the **Gmail** option at the *Provider* field. Click the **CONNECT** button to ask Google to authorize the Gmail account for an authorization to send an email notification. Fill the sender name and click Apply to save the settings.



The screenshot shows a configuration window titled "E-mail". It contains the following elements:

- Enabled:** A checkbox that is checked with a red checkmark.
- Provider:** Two radio button options: "Other" (unselected) and "Gmail" (selected with a red dot).
- CONNECT:** A red button with white text.
- Gmail Account:** A text input field containing the email address "ppbetest@gmail.com".
- TEST:** A dark grey button with white text.
- APPLY:** A light pink button with dark text.

Email service - Gmail

- **Service provider is Other:**

Select the **Other** option at the *Provider* field. Complete all details of E-mail account, and fields are explained below:

E-mail

Enabled	☒
Provider	☒ Other ☐ Gmail
SMTP server address	smtp.mail.yahoo.com
Connection Security	☐ TLS ☒ SSL ☐ None
Service port	465 Default port: 465
Sender name	ppbtest
Sender E-mail	ppbetest@yahoo.com.tw
Authentication	☒
Username	ppbetest@yahoo.com.tw
Password	••••
TEST APPLY	

Email service

- **Enabled:** Specify whether the Local/Remote can use E-mail to send an email notification to recipients.
- **Provider:** Select the service provider of E-mail account.
- **SMTP server address:** Configure the SMTP server that will be used to send E-mail to a recipient's mailbox.
- **Connection Security:** Sets which secure connection for the SMTP service to sent the E-mail.
- **Service port:** Sets the port number for the SMTP service to use.
- **Sender name & Sender E-mail address:** Configure the sender information for the E-mail.
- **Authentication:** Configure whether the SMTP server requires authentication or not. If authentication is required complete the necessary account and password field.
- **Username:** Sets the account to access the SMTP server.
- **Password:** Sets the password for the account.


3.2.3.2 Short Message Service (SMS)

Short Message Service (SMS) is a communication service used by mobile communication systems, using standardized communications protocols allowing the interchange of short text messages between mobile devices.

The Local/Remote sends mobile text messages to a receiver's mobile phone using an online SMS service. Users can choose **Clickatell** as a platform to send SMS or any SMS provider which sends a message via E-mail or HTTP. All account information and E-mail/HTTP specification must be acquired from the service provider before using SMS. The different SMS providers are described below:

- **Provider is Clickatell:**

Select the **Clickatell** option at the *Service Provider* field. Complete all the account details from Clickatell with the *Username*, *Password* and *HTTP API ID* fields. The **Verify** function can be used once the *Activate>YES* option is checked and this option is selected and parameters are applied.



SMS (Short Message Service) service

- **Provider accepts *HTTP POST* to send messages:**

This specification from an SMS provider is required before using the HTTP POST method to deliver messages to SMS providers. Select the Using HTTP POST option at the *Service Provider* field. Insert **EVENT_ACTION_PHONE_NUMBER** as recipient's mobile phone number and **EVENT_ACTION_MESSAGE** as the event message content described in the specification, and fill in the *URL* and *POST BODY* fields. The expressions will be replaced by the relevant content before the Local/Remote sends a notification to the SMS provider.

e.g.

URL: `http://send-sms-company.com/sms`

POST Body: `user=xxxxxx&password=xxxxxx &to=EVENT_ACTION_PHONE_NUMBER
&text=EVENT_ACTION_MESSAGE`

- **Provider accepts *HTTP GET* to sends messages:**

This specification from the SMS provider is required before using the HTTP GET method.

Select the **Using HTTP GET** option at the *Service Provider* field. Insert the

EVENT_ACTION_PHONE_NUMBER as recipient's mobile phone number and the

EVENT_ACTION_MESSAGE as event message's content described in the specification, and

fill in the *URL* field. The expressions will be replaced by relevant content before the

Local/Remote sends a notification to SMS provider.

e.g.

```
URL: http://send-sms-company.com/sms?user=xxxxxx&password=xxxxxx
&to=EVENT_ACTION_PHONE_NUMBER&text=EVENT_ACTION_MESSAGE
```

- **Provider accepts *E-mail* to send messages:**

This specification from an SMS provider is required before using the E-mail to deliver the messages to SMS providers. Select the **Using E-mail** option at the *Service Provider* field. Insert **EVENT_ACTION_PHONE_NUMBER** as recipient's mobile phone number and the **EVENT_ACTION_MESSAGE** as event message content described in the specification. Fill in the *Address*, *Subject* and *Content* fields. The expressions will be replaced with relevant content before the Local/Remote sends a notification to the SMS provider.

e.g.

```
Address: sms@send-sms-company.com
Subject: xxxxxx
Content: user:xxxxxx
        password:xxxxxx
        to:EVENT_ACTION_PHONE_NUMBER
        text:EVENT_ACTION_MESSAGE
```

Note: Each message sent by the SMS system through the SMS provider will be subject to the SMS provider fee.

3.2.3.3 XMPP Instant Messenger

The XMPP (Extensible Messaging and Presence Protocol) is an open protocol for instant messaging. Users can setup the configuration to receive instant messages when an event has occurred. Users may contact a network administrator to verify if there is a XMPP Instant Messaging server in the network. If there is no XMPP Instant Messaging server, Google talk service can be used. Google Talk software can be downloaded and installed or Gmail can be used to receive event notifications via Google Talk. A local network XMPP Instant Messenger server can be setup by downloading open source XMPP Instant Messenger server software, such as **Openfire**. More server software information can be found on **[XMPP server software list](#)**.

XMPP Instant Messenger

Enabled
☒

Server address

e.g. **Google Talk**

Service name

Service port

Username

Password

TEST

APPLY

XMPP Instant Messenger service

To use XMPP Instant Messaging, users must provide a unique XMPP Instant Messaging Service account as a sender and assign different account as a receiver on **Event Action/Notification Recipient** page.

- **Enabled:** Specifies whether the Local/Remote XMPP Instant Messaging service to notification is active or inactive.
- **Service address:** Sets the XMPP server address according to your XMPP Server configuration. Select **Google Talk** to use predefined settings for Google Talk service.
- **Service name:** Sets the service name on an XMPP Instant Messaging server. This option is usually not required. Contact the systems administrator of the server for the service name if required.
- **Service port:** The port number which the XMPP Instant Messaging server will use.
- **Username:** Sets the account to access the XMPP Instant Messaging server.
- **Password:** Sets the password for the account.

Note: In order to make sure that the sender can send the XMPP notification to recipients, recipients should accept the invitation from sender.

3.2.3.4 Remote Desktop Services

Remote Desktop Services

Enabled

✓

APPLY

Remote Desktop Services

Remote Desktop Service only works on Windows platforms. Options are explained below:

- **Enabled:** Specify whether to use this service to send a notification to recipients.

3.2.4 Recipients

PowerPanel® Business Management can send notifications to multiple recipients in various ways, including Windows Alert Messages, Instant Messages and mobile phone text messages (SMS). The **Notification Recipient** page lists all recipients in the recipient list and displays all defined notifications and whether the notification is active.

RECIPIENTS						
All Recipients						
Name	E-mail	XMPP	RDS Alert	SMS	Active Days	Active Times
✓ Default Receiver	✗	✗	✗	✗	Su,M,Tu,W,Th,F,Sa	00:00 - 00:00
✓ Tony	✓	✓	✗	✓	Su,M,Tu,W,Th,F,Sa	00:00 - 00:00
✗ Doris	✓	✗	✓	✗	Su,M,Tu,W,Th,F,Sa	00:00 - 00:00
✓ Tim	✓	✓	✓	✓	Su,M,Tu,W,Th,F,Sa	00:00 - 00:00

DELETE
EDIT
ADD

Event Action/Recipient page

Recipients can be managed as follows:

- **Add a new recipient:** Click the **ADD** button to open the Add Receiver dialog. Enter all required data and click the **SAVE** button to add a new recipient to the list.

- **Modify the recipient:** Select the recipient you wish to modify and click **EDIT** button. After entering in the new data, click the **SAVE** button to complete.
- **Remove the recipient:** Select the recipient to remove from the recipient list, and then click **DELETE** button to complete the recipient deletion.

The recipient detail settings and descriptions are explained below:


- **Active:** States if the recipient is active.
- **Language:** The language to which the recipient prefers. The notification sent to this recipient uses this language to display content.
- **Recipient Name:** The name of the recipient. The recipient name must be unique.
- **E-mail Address:** The E-mail address of the recipient.
- **XMPP Account:** The XMPP Instant Messaging account of the recipient. See **SETTING/Notification Channels** for more details about XMPP.
- **Computer Username:** The computer user account name which is used to receive the windows alert messages. Due differences in the Messenger Service of different versions of Windows, please refer to the descriptions below:
 - If PowerPanel® Business and the recipients are on **Windows 7, Windows Server 2012 or Windows 8**, and then the alert messages will only be sent to a local user account on the computer running PowerPanel® Business.

Note: Computer Name field and Alert column are only available on the PowerPanel® Business which installed on Windows.

- **Mobile Phone Number:** The mobile number of the recipient to receive the mobile text message. It must contain the country code.
- **Active Days:** Configures the days on which recipients can receive the notification. Users can define the specific ways to notify the assigned administrators on different days.
- **Active Time:** Configures the time which recipients will receive the notification. Users can define the specific ways to notify the assigned administrators during different times.
- **Enabled:** Displays which notification(s) are active for the recipient.
- **Test:** Sends the notification in accordance with current settings in order to verify the function. The service can be tested only when the corresponding service on the Event Action/Settings page is configured as activated.

3.2.5 Auto-Discover Range

In order to search devices and computers in different segments or a specific range, users can set IP range on this page.



SETTING/Auto-Discover Range page

IP ranges can be managed as follows:

- **Add a new IP range:** Click the **ADD** button and an **Add IP Range** dialog will appear. Enter all required data and click the **SAVE** button to add a new IP range to the list.
- **Modify the IP range:** Select the IP range you wish to modify and click **EDIT** button. After entering in the new data, click the **SAVE** button to complete.
- **Remove the IP range:** Select the IP range to remove from the IP range list, and then click **DELETE** to complete the IP range deletion.

The IP range detail settings and descriptions are explained below:

- **Active:** States if the IP range is active.
- **IP Range:** Set the range which used in devices and computers scanning.
- **Comment:** Sets the user-defined comments for this IP range.

3.2.6 Security

3.2.6.1 User

The **Security/User** section is used to change the PowerPanel® Business login account information, including user account, password, and the duration of login session.

User

Info!

Your current password is required to edit User Settings.

×

Current Password

Change Username

New Username

Change Password

New Password

Confirm Password

Session Timeout

Never ▾

CANCEL

APPLY

Security/User section

Change Username or Password

- Enter the password in the *Current Password* field.
- Enter a new username in the *New Username* field if you want to change username. Username must be alphanumeric (0-9, A-Z and a-z).
- Enter a new password in the *New Password* field if you want to change password.
- Click **APPLY** to complete the change.

Session

Session Timeout is the option which determines the duration of the session after the login. If the page isn't accessed during this period and remains inactive, users will be logged out automatically. Users will need to login again.

3.2.6.2 PowerPanel Secret Phrase

The Secret Phrase is used to create secure network communications between PowerPanel® Applications such as Remote and Local, Remote and UPS RMCARD, or Remote and PDU. The default phrase is **powerpanel.encryption.key**. The Secret Phrase can be configured on the **SETTING/Security** page in the Local and Remote, or on the **System/Authentication** page in the PDU and UPS RMCARD web interface. The Secret Phrase which is used in the Remote and devices must match.

Secret Phrase on the System/Security page in the UPS RMCARD205 web

3.2.6.3 HTTPS

PowerPanel® Business allows users to change the secure level and port explained below:

- **HTTPS Secure:** Enable this option for web access to be over the HTTPS connections.
- **HTTPS Port:** Determines which port to be used over the HTTPS connections. The default port is 53568.

Once the secure level is changed, the new secure level will be taken effect. All pages can't be displayed during the duration to restart server.

When HTTPS secure is enabled, the browser warning will be presented after the new level is taken effect. This indicates that the user's browser considers the connection is risky. Users can ignore the warning page and continue the web access, or provide a SSL certificate which is produced by the commercial certificate providers or any trusted certificate authority.

If the user has his own SSL certificate, refer to **Import SSL Certificates** section for further details how to import the new certificate.

3.2.6.4 SSL Certificates

Import SSL Certificates

The user's browser that connects with the PowerPanel® Business web interface will serve the SSL certificate. The certificate proves to the browser that the provider believes that it has issued a certificate to the owner of the PowerPanel® Business. The **SSL Certificates** section allows users to import your own SSL certificate and *SSL Certificate* displays the date and result for the last time to import SSL certificates. Users can import the certificates as following steps:

- Click the **IMPORT** button to start the *SSL Certificates Wizard*.
- Upload the SSL certificate file.
- Enter the *Key Passphrase* field and the *Keystore Password* field. Click the **IMPORT** button to import the SSL certificates.

Note: Applying for a certificate from the commercial certificate provider will be subject to the provider fee.

Add SSL Certificate into Trust List

A certificate trust list is a pre-defined list of SSL certificates that have been signed by a trusted entity. A certificate trust list of PowerPanel® Business is used to identify the certificate authority of another one with whom interacts. When importing a new SSL certificate, this will result in communication loss between the Local, Remote and Management.

As an example, when the Remote that has been connected with the Local imports a new SSL certificate, the Clint cannot interact with the Local. Users must to add the certificate of Remote into the trust list of the Local manually and thus the Local considers the Remote's SSL certificate valid.

Users can follow the steps to add the certificate into the trust list – Remote and Local, for example:

- Place the SSL certificate of the Remote as file extension of **.crt** in the `<Local_installation_directory>/jre/lib/security`.
- Switch to the `<Local_installation_directory>/jre/lib/security` directory in the command prompt.
`cd <Local_installation_directory>/jre/lib/security`
- Run the below command to add the certificate to the trust list.
`<Local_installation_directory>/jre/bin/keytool.exe -import -trustcacerts -file <cert_name>.crt -alias <alias_name> -keystore cacerts.`
- Enter “*changeit*” as the password for the certificate addition.
- Enter “y” to apply the certificate addition.
- Restart the Local service to reload the trust list and take effect. Refer to **How to restart PowerPanel Business service** of **FAQ** chapter for further details about how to restart PowerPanel® Business service.

Note: **Local_installation_directory** is the directory where the PowerPanel® Business Local installation locates; **cert_name** is the filename of the certificate file and **alias_name** is the alias for the certificate available in the trust list.

Note: The aforementioned steps are applicable to the interactions between PowerPanel® Business software.

Note: Due to security reasons, user may have to change the password to access the trust list. Refer to **How to change the password to access the trust list**.

3.2.6.5 SNMP

The Management can interact and access device information via SNMPv1 and SNMPv3. Fewer early UPS and PDU models which only accept SNMPv1 demands and newer models which support SNMPv3 can be controlled by Management.

Protocol Version: User can determine which SNMP protocol to use over the network communication between Management and devices. It is recommended to choose **Both** option because Remote attempts on the correct SNMP protocol for device to interact.

SNMPv1

SNMP Community. The Management uses this community to authenticate communication between the PDU and UPS in order to access their information. The default community is **private**. By default, the UPS/PDU/ATS uses **private** as the community with write permission, and **public** with read only permission. The community used by the Management to access the UPS/PDU/ATS must have write permission for an administrative power control.

SNMP Trap Community. The Management uses the community to authenticate the SNMP trap from the monitored PDU and UPS RMCARD. The community default is **public**. The IP address of the Management computer must be added to the Trap Receiver list on the **Network/Trap Notification** page of the UPS RMCARD and the PDU to ensure that the community must match.

Note: The community can be configured on the **Network/Access Control (or Network Service/SNMPv1 Service)** page in the UPS remote management card (RMCARD) web or on the **Network/SNMP Settings (or Network Service/SNMPv1 Service)** page in the PDU web.

Note: The SNMP community is limited to 15 characters in the PDU and UPS RMCARD.

Note: If you have firewall software installed, configure the settings to allow access through port 3052 (UDP/TCP), port 53568 (TCP), port 162 (UDP) and port 53566(UDP). These ports must open because the Management uses them to establish the communication with PDU and UPS RMCARD.

SNMPv3

The Management will use the below SNMPv3 settings to interact with a secure device. These settings can be configured on the **SETTING/Security** page of Management and on the **Network Service/SNMPv3 Service** page of the UPS RMCARD/PDU/ATS web. These settings must be matched one.

- **User Name:** Specifies a username match for protocol.
- **Authentication Protocol:** Sets the protocol to be used for authenticating the network communication between the Remote and devices.
- **Authentication Key:** Sets the authentication key which is used for the aforementioned authentication protocol.


- **Privacy Protocol:** Sets the privacy protocol to be used for encrypting data during transmission between the Remote and devices.
- **Privacy Key:** Sets the privacy key to encrypt data for the aforementioned privacy protocol.

3.2.7 Advanced

3.2.7.1 Import and Export Profile Settings

Import and Export Profile Settings feature allows users to export the profile settings of PowerPanel® Business Management and quickly import the settings to multiple PC/Servers. After the setup of PowerPanel® Business Management has been completed, users can use the Export feature to save the profile settings. If a new PC/Server is going to be set up with PowerPanel® Business Management later, users can upload the profile settings with the Import feature to complete the setup immediately.

Note: The profile settings of PowerPanel® Business Management can only be imported to PowerPanel® Business Management.



SETTING/Advanced page in the Management

3.2.7.2 Energy Event Command Scripts

The PowerPanel® Business Management software can be configured to respond to specific events and perform command execution. The **SETTING/Advanced** page lists events that can be set to perform command execution. For details of each event, please refer to **Event Details** section.

MANAGEMENT POWERPANEL Business CyberPower

DASHBOARD **SETTING** REPORTING HELP

ADVANCED

System Command Scripts

Active	Urgency	Event	Command	Duration	Delay
☐	Warning	Power consumption is too high		< 1 sec	Instant
☐	Warning	Power consumption is too low		< 1 sec	Instant

CANCEL APPLY

Group Command Scripts

Active	Urgency	Event	Command	Duration	Delay
☐	Warning	Power consumption is too high		< 1 sec	Instant
☐	Warning	Power consumption is too low		< 1 sec	Instant

CANCEL APPLY

UPS Command Scripts

Active	Urgency	Event	Command	Duration	Delay
☐	Severe	Battery capacity is critically low		< 1 sec	Instant
☐	Severe	Network communication lost with UPS in a power event		< 1 sec	Instant
☐	Severe	System is overheated		< 1 sec	Instant
☐	Severe	Network communication lost		< 1 sec	Instant
☐	Warning	UPS is faulty		< 1 sec	Instant
☐	Warning	Utility power failure		< 1 sec	Instant
☐	Warning	Batteries are not present		< 1 sec	Instant

SETTING/Advanced page in the Management

The severity of each event is marked by a symbol. Severe level (❗) indicates users must be alerted and the computer shut down to avoid an improper shutdown. Warning level (⚠) indicates a warning and users should be notified when it occurs. If a warning condition persists, a system shutdown may be imminent. Information level (ℹ) indicates the state of the UPS or that the utility power condition has changed.

A command will be executed when an event occurs.

- **Active:** Determines whether to execute a command. If the check box is unchecked, the command for this event and the corresponding event will not be executed.
- **Command:** Sets a command file to be executed when an event occurs. Shell scripts for the command file uses ".cmd" as the filename extension. For more information about shell scripts read the detailed description in the "default.cmd" file in the "extcmd" folder in the PowerPanel® Business installation directory. Customized shell scripts must be saved in the "extcmd" folder in the PowerPanel® Business installation directory. The command file will be listed on the *Command/File* list and can be executed when the power event occurs.
Note: The command file name will be displayed in italics if the command file which had used cannot be found in the "extcmd" folder.
- **Duration:** Sets the estimated time for the command to complete. If the event requires the computer to shut down, this delay provides time for commands and scripted actions to complete before the shutdown is initiated.
- **Delay:** Determines whether to execute a command and sets the delay for the command execution. If the event is cleared within the command execution delay, the command for this event and the corresponding event will not be executed.

The following environment variables can be placed in external commands to identify which event and which stage to be executed.

- **%EVENT_STAGE%:** Indicates what stage of firing event to execute the commands. When an event first happens, it enters the **OCCUR** stage and the assigned commands will be executed. When an event is ended, the variable will be **FINISH** and the assigned commands will be executed.
- **%EVENT%:** Indicates which event is fired to execute the commands.
- **%EVENT_CONDITION%:** Indicates which the detailed event condition of a firing event.
- **%MODULE_NO%:** Indicates which UPS module on a firing event. This variable is used on Modular UPS models.

The following table lists all details of **%EVENT%** and **%EVENT_CONDITION%** variables.

%EVENT%	%EVENT_CONDITION%	Event Name
BATTERY_CRITICAL_LOW		Battery capacity is critically low.
ENTER_BYPASS		Enters bypass mode.
BATTERY_EXHAUSTED		Battery has been depleted.
EMERGENCY_OFF		EPO is active.
BATTERY_FULL		Battery is fully charged.
SHUTDOWN		Shutdown initiated.
BYPASS_FAILURE		Bypass power source has failed.
CAPACITY_INSUFFICIENT		Insufficient inverter capacity.
LOSS_REDUNDANT		Not enough power redundancy modules.
ABNORMAL		UPS input abnormality.
	NO_NEUTRAL	No neutral input.
	WIRING_FAULT	Site wiring fault.
FATAL_ABNORMAL⁴		UPS fatal internal abnormality.
	OUTPUT_OVERLOAD	Output is overloaded.
	BYPASS_OVERLOAD	Bypass is overloaded.
	MODULE_OVERLOAD	Module is overloaded.
	SHORT_CIRCUIT	Output circuit-short.
	MODULE_RECTIFIER_OVERHEAT ¹	Module rectifier is overheated.
	MODULE_INVERTER_OVERHEAT ¹	Module inverter is overheated.
	MODULE_INVERTER_PROTECTED ¹	Module inverter is protected.
	BATTERY_REVERSED	The polarity of battery is reversed.
	BYPASS_SEQUENCE_ERROR	The phase sequence of bypass is wrong.

COMMUNICATION_FAILURE⁴		
	LOST_IN_LOCAL	Local communication lost.
	LOST_IN_NETWORK ³	Network communication lost.
FAULT⁴		
	GENERIC_FAULT	UPS is faulty.
	BYPASS_FAN_FAULT	Bypass fan is faulty.
	BYPASS_FAULT	Bypass is faulty.
	MODULE_RECTIFIER_FAULT ¹	Module rectifier is faulty.
	MODULE_INVERTER_FAULT ¹	Module inverter is faulty.
	MODULE_FAN_FAULT ¹	Module fan is faulty.
NO_BATTERY		Batteries are not present.
RUNTIME_INSUFFICIENT		Available runtime is insufficient.
UTILITY_FAILURE		Utility power failure.
URGENT_COMMUNICATION_FAILURE⁴		
	LOST_IN_LOCAL	Local communication lost in a power event.
	LOST_IN_NETWORK	Network communication lost in a power event.
RUNTIME_WILL_EXHAUST		Remaining runtime will be exhausted.
OUTPUT_WILL_STOP		The output power is going to stop soon.
INPUT_NEAR_OVERLOAD²		Input is near overload.
INPUT_OVERLOAD²		Input is overloaded.
SHUTDOWN_TIME_INSUFFICIENT²		Shutdown time is in insufficient.
ATS_FAULT⁵		ATS is faulty.
ALL_SOURCE_FAILURE⁵		Both input sources have power loss, ATS will not change input source
CURRENT_SOURCE_FAILURE⁵		ATS has automatically switched to redundant power source.
REDUNDANT_SOURCE_FAILURE⁵		ATS redundant power source has experienced a power failure.
ENV_SENSOR_LOST⁶		Environmental sensor is not responsive.
ENV_SENSOR_OVERHEAT⁶		Temperature is over the high threshold.
ENV_SENSOR_UNDERCOOL⁶		Temperature is under the low threshold.
ENV_SENSOR_OVERWET⁶		Humidity is over the high threshold.

ENV_SENSOR_OVERDRY⁶	Humidity is under the low threshold.
POWER_LOST	Power supply redundancy has been lost.
MBO_OUTLET_OVERLOAD⁷	A PDU outlet is overloaded.
MBO_OUTLET_NEAR_OVERLOAD⁷	A PDU outlet is near overload.

¹: This event only occurs for the Modular UPS in Local.

²: This event only occurs for the PDU in Remote.

³: This event only occurs in Remote.

⁴: This **%EVENT%** variable must come with a **%EVENT_CONDITION%** variable.

⁵: This event only occurs for the ATS in Remote.

⁶: This event only occurs for the environmental sensor for UPS/PDU/ATS in Remote.

⁷: This event only occurs for the Metered by Outlet PDU in Remote.

3.2.8 Event Details

The section lists the power events of PowerPanel® Business Management. The events are divided into below categories:

System

- **Power consumption is too high.** System power consumption has gone above the high threshold.
- **Power consumption is too low.** System power consumption has gone below the low threshold.

Group

- **Power consumption is too high.** Device group power consumption has gone above the high threshold.
- **Power consumption is too low.** Device group power consumption has gone below the low threshold.

UPS

- **System is overheated.** Internal UPS temperature is too high.
- **Network communication lost. Management** cannot establish communication with UPS on the network or established network communication has been interrupted.
- **UPS is faulty.** UPS has an internal malfunction. The UPS may not be operating properly and will not be able to affect a proper shutdown.
- **Utility power failure.** Utility power failure, battery power will be supplied.

- **Battery is not present.** Batteries are not present; the UPS cannot provide battery power in this condition.
- **Available runtime is too low.** There is not sufficient runtime for PowerPanel® Business to perform a complete shutdown based on current configuration even if the battery is 100% charged.
An excessive load or long shutdown time may cause this event. Reduce some UPS load or set a more accurate shutdown time to avoid this event.
- **UPS fatal internal abnormality.** The UPS is experiencing one or more of the following fatal abnormalities; UPS may shut down or stop output power unexpectedly.
- **Power consumption is too high.** UPS power consumption has gone above the high threshold.
- **Power consumption is too low.** UPS power consumption has gone below the low threshold.
- **Shutdown initiated.** A computer which connects with UPS initiated the shutdown process. The computer will shut down or enter hibernation.
- **Battery has fully charged.** Battery has fully charged. The capacity of battery is full.
- **Battery capacity is critically low.** Battery capacity is critically low; power could be lost immediately.
- **An outlet on a UPS has turned on.** A UPS outlet has been turned on. The outlet can afford the power to its connected equipment.

PDU

- **Network communication lost.** Management cannot establish communication with PDU on the network or established network communication has been interrupted.
- **Input is near overload.** A PDU is near an overload condition. The load level is near the safe load threshold for the PDU.
- **Input is overloaded.** A PDU is in an overload condition. The safe load threshold has been exceeded.
- **Power consumption is too high.** Power the specific PDU consumes has been exceeded the high threshold.
- **Power consumption is too low.** Power the specific PDU consumes has been violated the low threshold.
- **Shutdown initiated.** A computer connected to the UPS has initiated the shutdown process. The computer will shut down or enter hibernation soon.
- **A PDU outlet is overloaded.** An outlet of Metered by Outlet PDU is in an overload condition. The safe load threshold has been exceeded.
- **A PDU outlet is near overload.** An outlet of Metered by Outlet PDU is near an overload condition. The load level is near the safe load threshold for the outlet.


ATS

- **Network communication lost.** Management cannot establish communication with a ATS on the network or established network communication has been interrupted.
- **ATS is faulty.** ATS has an internal malfunction and may not operate properly.
- **Both input sources have power loss, ATS will not change input source.** ATS will not switch from one input source to another because both are experiencing power failures.
- **Input is near overload.** An ATS is near an overload condition. The load level is near the safe max load threshold for the ATS.
- **Input is overloaded.** An ATS is in an overload condition. The safe max load threshold for the ATS has been exceeded.
- **Power consumption is too high.** ATS power consumption has gone above the high threshold.
- **Power consumption is too low.** ATS power consumption has gone below the low threshold.
- **Shutdown initiated.** A computer connected to the ATS has initiated the shutdown process. The computer will shut down or enter hibernation soon.

3.3 REPORTING

3.3.1 System Logs

The **System Logs** page in Management provides users logs of recorded details from operations performed in Management. The logs can be used for analysis or to determine whether operations have been performed correctly.




MANAGEMENT		POWERPANEL Business	CyberPower
DASHBOARD SETTING REPORTING HELP		N71T340 [192.168.210.100]	
SYSTEM LOGS			
System Logs Page: 1			
Date & Time	Event		
2019-02-20 02:17:37 PM	✓ ESXi(localhost.localdomain@192.168.208.215) was removed		
2019-02-20 02:16:37 PM	✓ ESXi(localhost.localdomain@192.168.208.215) was removed		
2019-02-20 02:16:37 PM	✓ ESXi(localhost.localdomain@192.168.208.215) was disconnected from outlet #5 of UPS(ERP UPS@192.168.210.100). Event: ESXi(localhost.localdomain@192.168.208.215) was disconnected from outlet #5 of UPS(ERP UPS@192.168.210.100). Description: Remove a vCenter Server or ESXi host in Service Infrastructure page. Target: ESXi(localhost.localdomain@192.168.208.215) Message: To disconnect ESXi(localhost.localdomain@192.168.208.215) with the outlet #5 of UPS(ERP UPS@192.168.210.100) is completed.		
2019-02-19 06:12:25 PM	✓ Storage(datastore1) was disconnected from outlet #1 of .		
2019-02-19 03:14:06 PM	✓ ESXi(localhost.localdomain@192.168.208.215) was connected with outlet #5 of UPS(ERP UPS@192.168.210.100).		
2019-02-19 03:04:45 PM	✓ UPS(ERP UPS@192.168.210.100) was requested to shutdown.		
2019-02-19 03:04:27 PM	✓ UPS(ERP UPS@192.168.210.100) was requested to shutdown.		
2019-02-19 03:01:21 PM	✓ UPS(ERP Server@192.168.210.100) was requested to restart.		
2019-02-19 03:01:21 PM	✓ UPS(ERP Server@192.168.210.100) was requested to shutdown.		
2019-02-19 02:42:31 PM	✓ ESXi(localhost.localdomain@192.168.208.215) was connected with outlet #5 of UPS(ERP Server@192.168.210.100).		
2019-02-19 12:22:20 PM	✓ ESXi(localhost.localdomain@192.168.208.215) was disconnected from outlet #1 of UPS(ERP Server@192.168.210.100).		
2019-02-19 12:21:21 PM	✓ ESXi(localhost.localdomain@192.168.208.215) was connected with outlet #1 of UPS(PDU15SW10ATNET@192.168.210.100).		
2019-02-19 12:20:45 PM	✓ ESXi(localhost.localdomain@192.168.208.215) was connected with outlet #1 of UPS(PDU15SW10ATNET@192.168.208.211).		
2019-02-18 04:02:55 PM	✓ UPS(ERP Server@192.168.208.73) was removed		
2019-02-18 04:02:37 PM	✓ 3 devices were added		
2019-02-15 04:04:12 PM	✓ UPS(ERP Server@192.168.208.73) was added		
1970-01-01 08:00:00 AM	⚠ Device(192.168.210.100) failed to be added		

Logs page

Each log has details which can be viewed by clicking the icon next the each log. Using the paging toolbar at the top of the log list allows users to view older logs by changing the page displayed; clicking the refresh icon updates the logs displayed in the list.

3.3.2 Event Logs

The **Event Logs** page records the event logs that can be analyzed whether the devices and the system are functioning well. Each log records what event occurred of the device.



Date & Time	Event
2019-02-21 12:18:19 PM	Battery of UPS(PDU1SSW10ATNET 192.168.208.211) has fully recharged.
2019-02-21 12:18:15 PM	Network communication of UPS(PDU1SSW10ATNET 192.168.208.211) with Center is successful.
2019-02-21 12:18:13 PM	Network communication of UPS(PDU1SSW10ATNET 192.168.208.211) with Center has failed.
2019-02-21 12:16:24 PM	Network communication of UPS(ERP UPS 192.168.210.100) with Center is successful.
2019-02-21 12:16:20 PM	Network communication of UPS(ERP UPS 192.168.210.100) with Center has failed.
2019-02-21 12:12:16 PM	Network communication of UPS(ERP UPS 192.168.210.100) with Center is successful.
2019-02-21 12:12:15 PM	Network communication of UPS(ERP UPS 192.168.210.100) with Center has failed.
2019-02-21 12:10:02 PM	Battery of UPS(PDU1SSW10ATNET 192.168.208.211) has fully recharged.
2019-02-21 12:09:54 PM	Network communication of UPS(PDU1SSW10ATNET 192.168.208.211) with Center is successful.
2019-02-21 12:09:51 PM	Network communication of UPS(PDU1SSW10ATNET 192.168.208.211) with Center has failed.
2019-02-21 12:08:20 PM	Local communication with the UPS(ERP UPS 192.168.210.100) has been lost.
2019-02-21 12:08:16 PM	Network communication of UPS(ERP UPS 192.168.210.100) with Center is successful.
2019-02-21 12:08:13 PM	Network communication of UPS(ERP UPS 192.168.210.100) with Center has failed.
2019-02-21 12:03:13 PM	Battery of UPS(PDU1SSW10ATNET 192.168.208.211) has fully recharged.
2019-02-21 12:03:01 PM	Network communication of UPS(PDU1SSW10ATNET 192.168.208.211) with Center is successful.

Event Logs page

Using the **Previous** and **Next** at the upper right corner of the event log list helps users to view the other range of filtered log result backward or forward. Clicking **Refresh** will update the log result to display in the list according to the current filter options and paging settings.

Export

Click the **Save** shortcut at the right upper corner of the event log table and select **CSV** or **PDF** file as the export file format. The exported file will be saved in the default download directory of your web browser.

Clear All Logs

Click the **Delete** shortcut at the right upper corner of the event log table, a confirm dialog will show up, all event logs will be removed immediately after clicking **DELETE**. The log clearing is permanent and once applied the log files cannot be recovered.

3.3.2.1 Settings


- **Entry Expiration:** This option specifies how long the log files will be retained.
- **Log to Windows Event Viewer:** Determines to log events to Event Viewer additionally. Users can launch the **Control Panel > Administration Tools > Event Viewer** to review all events in the **Application** category of the **Windows Logs** directory.

Note: Event Viewer is only function on the Windows platforms. If this option is not activated, you can activate this option by installing the PowerShell through Windows Update.

- **Max Records:** Indicates the maximum number of events that will be displayed.

3.3.2.2 Filter

After the configuration of the filter section is configured, click **APPLY** button to filter the logs.



Filter pane on REPORTING/Event Logs page


- **Dates:** Selects the Date for the events to be displayed.
- **Day:** Selects the Day(s) for the events to be displayed.
- **Time(Hours):** Selects the time range for the events.
- **Weekday:** Choose the days of the event occurrence.
- **Priority:** The events can be filtered by Priority.
- **Event Category:** The events can be filtered by category. The events can be further divided by **Power Event** and **System Event** categories, and choosing the specific event.
- **Records Per Page:** Specify the number of records to show per page.

3.3.3 Energy Use

The **Energy Use** page shows a chart of how energy is spent in a specified period of time and also shows the energy statistics of the current target node and entire system.

3.3.3.1 Settings

In this section, users can assign the rate of power consumption and carbon emission, and set energy use alerts. When the rates are updated, the information presented in the Statistics page will also be updated.



Energy Use/Settings

Management has the capability of reminding users of power consumption violations. The **Setting** page allows users to configure thresholds. When power consumption thresholds are violated, **Management** will notify the user.

- **Cost Per kWh:** Select the country the UPS is located in.
- **CO2 Emitted per kWh:** The weight of equivalent emitted carbon when one kWh power is consumed and the unit of measurement.
- **Energy Use Alerts**

Set the notifications thresholds for PowerPanel® Business Management.

- **System Threshold.** When the power consumption of the entire system exceeds the high threshold or violates the low threshold, the event “**Power consumption is too high.**” or “**Power consumption is too high.**” of system will occur, respectively.
- **Device & Groups Threshold.** When the power consumption of the group or power equipment exceeds the high threshold or violates the low threshold, the event “**Power consumption is too high.**” or “**Power consumption is too high.**” of group or device will occur, respectively.

3.3.3.2 kWh Cost History


Because the rate of power consumption can vary over time, users can assign rates for different periods of time. Associated costs of historical periods will show in the table and user can edit or delete selected data. When rates are updated, the information displayed in the Metric section will also be updated.

kWh Cost History	
Date Range	Cost per kWh
2019-02-11 through 2019-02-13	\$0.13
2019-02-14 through Today	\$0.12
DELETE EDIT	

Energy Use/kWh Cost History

3.3.3.3 Metrics

The **Statistics** page shows a chart of how energy is spent in a specified period of time and also shows the energy statistics of the current target node and entire system.



REPORTING/Energy Use page

The consumption of each UPS, PDU, ATS and outlet of Metered by Outlet PDU is logged on an hourly basis and each group that contains these UPS, PDU and ATS will accumulate the consumption data. Data logged can be used to render a chart over the past day, past month, past year and all past information accordingly. Users can see how much energy has been spent in a historical period of time.

The total and average power consumption of each selected group that contains UPS, PDU and ATS will be shown according to current chart. Management will also show the statistics on the total power consumption of today, this month, this year and entire system in the *System Energy* block.

3.4 HELP

3.4.1 PowerPanel® Business

This section is an overview which includes the PowerPanel® Business and host operating system. It also provides resources about contact website for assistances.

3.4.2 Content

The **Content** page provides an overview which introduces the brief functions of what Local, Remote or Management do and indicates how to get related online-help content for current function page. It indicates a button to access to online-help directly.

4 Technical Support

4.1 Troubleshooting

1. I cannot access the PowerPanel® Business web interface after complete installation.

Please follow the below steps resolve the problem:

- Make sure that there is no other application utilizing port 3052 (UDP/TCP) and port 53568 (TCP). Use a command prompt with the command “netstat -o” to obtain information about which ports are used by which programs.
- Ensure the **PowerPanel® Business** service is running on the hosted computer. If the service is stopped, restart the service and then try again in the same way.
- Make sure the port 3052 (UDP/TCP) and port 53568 (TCP) on the hosted computer are not blocked by a firewall.
- Make sure the URL in the address filed of the browser for a remote computer is correct.

2. The PowerPanel® Business installation failed.

If the installation file is from CyberPower web site, it may have downloaded incompletely or become corrupt. Download the installation file again.

3. I failed to extend the off-delay time of Necessary shutdown time option.

- The communities on the **SETTING/Security** page in the Remote and on the **Network/Access of Control** page in the PDU may be not matched. Confirm that the communities with the write permission are matched.
- The Remote may use the community without write permission to access the PDU. Please promote the permission of the community which is used by the Remote to access the PDU.

4. The shutdown occurs earlier than expected time.

It may be caused by the following conditions:

- When batteries have been used for a long time, they are unable to reach a full charge. Check to see if the output load is too high. A high load on the UPS will cause the batteries to discharge faster and the remaining runtime quickly decrease. Disconnect some load from the UPS to reduce the load in order to extend the runtime.
- Verify that the batteries are fully-charged. If the capacity is too low, please charge the batteries to full capacity.

5. Pages cannot be displayed after I set up another port number in the Security/Network page.

The port that was set up in the **SETTING/Security** page may be occupied by other applications or services. This indicates that the pages can't be accessed through the assigned port.

6. The host name and IP address at the Local's banner on the vMA of the VMware ESXi host displays Unknown.

Follow below steps to correct this condition:

- Run the command '*sudo vi /etc/hosts*' with root permission.
- Add the below snippet with the IP address and hostname.

```
192.168.1.1 hostname
```

Note: IP address and host name can be inquired using the commands '*ifconfig*' and '*hostname*'.

- Restart the service using the commands '*sudo service ppbed stop*' and '*sudo ppbed service start*'
- Login the page again. The host name and IP address will be correct.

7. I have downloaded the Linux installer from the website. The installer cannot be launched.

Before launching the PowerPanel® Business installer, you must change its access permission on the installer. You must have executable permission on the PowerPanel Business installer; otherwise the message "**Permission Denied**" will be displayed.

Run the below example command to change its permission of the 32-bit installer on 32-bit Linux platform.

```
sudo chmod u+x ppb-XXX-linux-x86.sh
```

 (XXX is the version number of PowerPanel® Business.)

Run the below example command to change its permission of the 64-bit installer on 64-bit Linux platform.

```
sudo chmod u+x ppb-XXX-linux-x86_64.sh
```

 (XXX is the version number of PowerPanel® Business.)

After the permission of the PowerPanel® Business installer is changed, the installation procedure will be allowed to launch.

8. Inability to Shutdown NAS during Power Failure.

When using sshpass tool cannot shut the NAS down during power failure, the version of the sshpass tool may be 1.04.

The sshpass tool whose version is 1.04 will result in inability to shutdown NAS. You must check whether the version of the sshpass tool is 1.04. If the version is 1.04, you must change another version.

9. The PowerPanel® Business installation file's digital signature is not valid.

It is caused because the operating system does not support the SHA-256 signature the installation file uses. Please follow the solutions below to resolve the problem for different versions of Windows:

- On Windows 8.1, Windows 8, Windows 7, Windows Server 2012 or Windows Server 2008 R2, please update the Windows via **Windows Update** to support SHA-256 signatures.
- On the version earlier than Windows 7 or Windows Server 2008 R2, please click **Allow** or **Run** when security warning dialog appeared after the installation file is opened.

4.2 FAQ

1. **If multiple computers are connected to a single UPS, how do I determine which computer to install the Local or the Remote on to ensure each computer can be shut down gracefully in event of power outage?**

The computer that is connected to the UPS with a serial or USB cable should install the Local, and the remaining ones should install the Remote.

2. **After the PowerPanel® Business installation is complete, how do I access the web interface?**

On Windows, you can select the **Start > All programs >PowerPanel Business >PowerPanel Business Local** (or **PowerPanel Business Remote/ PowerPanel Business Management**) for local use. You can also enter the URL, **http://hosted_computer_IP_address:3052/management**, in the address field of the web browser from a remote computer.

On Linux, you only enter the URL, **http://localhost:3052/management**, the address field of the web browser from a remote computer for a local access. You can also enter the URL, **http://hosted_computer_IP_address:3052/management**, in the address field of the web browser from a remote computer.

3. **Which operation systems are supported by PowerPanel® Business software? And which browser supports them?**

Refer to the [Getting Started/Prerequisites](#) for more details.

4. **How can I make PowerPanel® Business run a program when a particular event has occurred?**

Create a .cmd file and save it into the **extcmd** folder of PowerPanel® Business installation folder. Then write a command to run your own programs into this script file. Please refer to the **default.cmd** in the **extcmd** folder to write your own script.

5. **I am not sure what the IP address of the UPS/PDU/ATS is. How can I obtain the correct IP address?**

Use the **Power Device Network Utility** tool to help you to find the correct IP address of UPS/PDU/ATS. This device list will list the all CyberPower device's IP address on the local network.

6. How do I uninstall PowerPanel® Business?

On Windows, go to **Start > Control Panel > Add or Remove Programs**. Click the **Change/Remove** button of **PowerPanel® Business** to uninstall the program.

On Linux and VMware ESXi, only PowerPanel® Business Remote can be installed. The default installation directory is **/usr/local/PPB** on the Linux platforms and **/opt/PPB** on VMware ESXi. Execute the **uninstall.sh** command in the installation directory to uninstall the program.

7. How can I get a notice when a power condition has cleared?

When a power condition is clear, it will broadcast a notification and also run the command file. A custom script can be created for events. The script can utilize the environment variable **EVENT_STAGE** to compare the key **OCCUR** to identify an event that has occurred or **FINISH** to identify an event that has cleared.

8. What network protocol is used in PowerPanel® Business?

SNMP is used on communications between Remote, Management, PDU or UPS with remote management card. **HTTP** and **HTTPS** are used between the Local and the Remote.

9. What the network ports are used by PowerPanel® Business?

Port 3052 (UDP/TCP), port 53568 (TCP), port 161(UDP), port 162 (UDP) and port 53566(UDP)

10. How do I ensure that the SNMP settings between the Remote and UPS/PDU/ATS are properly setup?

To receive the trap notification from the UPS/PDU/ATS all the time, follow steps to verify the SNMP settings:

- Open the **Network/Trap Notification** page on the UPS/PDU/ATS web and the **SETTING/Security** page on the Remote.
- Confirm that the IP address of the Remote can be found on the **Network/Trap Notification** page of the UPS/PDU/ATS web. If the IP address can be searched, skip the step 3.
- If the IP address of the Remote could not be found, click the **Trap Receiver** shortcut of the **Network/Trap Notification** page to enter the **Trap Configuration** page. Enter the required data to add a new trap receiver.
- If the IP address of the Remote could be found, verify the SNMP settings are matched.

11. How do I determine that if my computer is using hibernation or not?

If the operating system is Windows 7, Windows Server 2008, Windows 8, Windows 10, Windows Server 2012 or Windows Server 2016 please follow the below steps to enable the hibernation.

- Open the **Command Prompt** dialog box.
- Use the command **powercfg.exe -hibernate on** to enable the hibernation.

12. Which series does my UPS model belong to?

Check the UPS model and determine to which series your UPS belongs:

- If the model name conforms to the format of "OLxxxxRMXL", "OLxxxx", it belongs to *Smart App Online* series.
- If the model name conforms to the format of "PRxxxxLCDRM", "PRxxxxLCDRT", "PPxxxxSWRM" or "PPxxxxSW", it belongs to *Smart App Sinewave* series.
- If the model name conforms to the format of "ORxxxxLCDRM" or "ORxxxxLCDRT", it belongs to *Smart App Intelligent LCD* series.
- If the model name conforms to the format of "OPxxxx" or "CPSxxxxAVR", it belongs to *Smart App AVR* series.
- If the model name conforms to the format of "OLxxxxTEXL" or "OLxxxxEXL-M", it belongs to *Paragon Tower* series.
- If the model name conforms to the format of "PRxxxxELCDRT" or "PRxxxxELCDRTXL", it belongs to *Professional Rack Mount LCD* series.
- If the model name conforms to the format of "PRxxxxE", it belongs to *Professional Rack Mount* series.
- If the model name conforms to the format of "PPxxxxE", it belongs to *Professional Tower* series.
- If the model name conforms to the format of "ORxxxxELCD", it belongs to *Office Rack Mount* series.
- If the model name conforms to the format of "OPxxxxE", "OPxxxxTE", "OPxxxxUE" and "OPxxxxUTE", it belongs to *Office Tower* series.


13. How do I upload the installer to vMA?

- Login the **vSphere Client**.
- Select the VMware host.
- Click **Configuration**.
- Select the target datastore from the right hand side.
- Right click the target datastore and click **Browse Datastore**.
- Click **Upload** button on the toolbar and select the file you want to upload.
- Click **OK** button to continue with the upload files into the target datastore.


14. How do I upgrade the virtual hardware version of vMA?

For vMA running on ESXi 5.x, it is recommended to upgrade the virtual hardware to version 8. To upgrade the virtual hardware version of VMA as below steps:

- Start the vSphere Remote and power off the target vMA.
- Right-click the virtual machine and select the **Upgrade Virtual Hardware** menu option to upgrade virtual hardware.



- Click **Yes** to continue with the vMA upgrade.



- Power on the vMA to make the changes take effect.

15. How do I restart the PowerPanel® Business service?

For windows, restart the service from the **PowerPanel® Business Service > Services > Administrative Tools > Control Panel**.

For Linux, run the commands in order to restart the service: `sudo service ppbed stop` and `sudo service ppbed start`.

16. I cannot add the new SSL certificate into the trust list.

Due the duplicate alias name is available in the trust list, the certificate cannot be added. In order to add the new certificate into the list, the certificate which has the duplicate alias name should be removed from the list. Follow the steps to remove the certificate:

- Switch to the `<Local_installation_directory>/jre/lib/security` directory in the command prompt.
`cd <Local_installation_directory>/jre/lib/security`

- Run the below command to remove the certificate from the trust list.
`<Local_installation_directory>/jre/bin/keytool.exe -delete -alias <alias_name> -keystore cacerts`
- Enter “*changeit*” as the password for the certificate removal.
- Enter “y” to apply the certificate removal.
- Restart the Local service to reload the trust list and take effect. Refer to **How to restart PowerPanel® Business service** of **FAQ** chapter for more details.

5 Glossary

- **Citrix XenServer:** A virtual-machine monitor allows several guest operating systems to execute on the same computer hardware concurrently. XenServer is supported by Citrix systems, Inc.
- **IP address:** An IP address is a series of numbers that identifies a particular computer or NIC on a network. IP is an abbreviation for Internet Protocol.
- **HTTPS:** Abbreviation for HTTP Secure. It provides encryption and secure identification of servers by using HTTP with SSL/TLS protocol. HTTPS connection is usually used for the sensitive transaction.
- **Power Device Network Utility:** Is an easy to use tool to setup network configurations of the UPS RMCARD/PDU/ATS. This includes setting the IP address, subnet mask, or gateway of UPS RMCARD/PDU/ATS.
- **PDU:** A PDU is a device which provides power output controls for individual outlets and connected equipment. PDU is an abbreviation for Power Distribution Unit.
- **SNMP:** The simple network management protocol. It is used by network management systems for monitoring network-attached devices for conditions that warrant administrative attention.
- **SSL:** Abbreviation for Secure Sockets Layer. SSL is a transaction security standard that provides data encryption, server authentication, and message integrity.
- **TCP/UDP:** Family of protocols for the transport and network layers.
- **TLS:** Abbreviation for Transport Layer Security. TLS is a cryptographic protocol which provides communication security over the internet. TLS and SSL provide data encryption and server authentication for message reliability.
- **vMA:** Abbreviation for vSphere Management Assistant. A virtual machine that includes prepackaged software and supported by the VMware, Inc. allows administrators to run scripts and Locals to manage ESXi hosts.
- **VMware ESXi:** An enterprise-level computer virtualization product offered by VMware, Inc. It is a component of VMware's larger offering, VMware Infrastructure, and adds management and reliability services to the core server products.
- **Virtual Appliance:** A virtual machine image is designed to run on a virtualization platform developed by VMware, Inc. It is intended to eliminate the installation, configuration and maintenance costs associated with running complex stacks of software.
- **VMware vCenter:** A vSphere's centralized tool that allows for the management of multiple ESXi servers and virtual machines from different ESXi servers through a single console application.
- **Microsoft Hyper-V Server:** A native hypervisor-based server virtualization product being offered by Microsoft Corporation.
- **ATS:** ATS is an electrical switch that switches a load between two sources. It can switch power automatically to a generator or other standby power source after a power outage. ATS is an abbreviation for Automatic Transfer Switch.

- **Environment Sensor:** A sensor accessory that can be installed on UPS/PDU/ATS for monitoring environment condition and obtaining information about the temperature and humidity.

CyberPower®

Cyber Power Systems, Inc.

www.cyberpower.com

For USA and Canada:

4241 12th Ave East, Suite 400

Shakopee, MN 55379

Toll-free: (877) 297-6937

For all other regions:

Please visit our website for local contact information.