

2021 FORD F-SERIES SUPER DUTY® CHASSIS CAB

TECHNICAL SPECIFICATIONS



BODY

Construction/materials	Fully boxed steel frame under-cab, and C-channel aft-of-cab made from high-strength steel, aluminum bed and cab
Body style	Body-on-frame
Trim levels	XL, XLT, Lariat
Final assembly location	Kentucky Truck Plant, Ohio Assembly Plant

DRIVETRAIN

Standard layout	Front engine, rear drive
Optional layout	Front engine, 4x4 (electronic-shift-on-the-fly transfer case)

ENGINES

	6.2-liter V8	7.3-liter V8	6.7-liter Power Stroke® V8 diesel
Configuration	90-degree V8, single overhead cam	90-degree V8, single in-block cam	90-degree V8 diesel, single turbocharger, in-block cam and overhead valves
Block/head material	Cast iron block, aluminum heads	Cast iron block, aluminum heads	Compacted graphite iron block, aluminum heads
Displacement	6.2 liters (379 cubic inches)	7.3 liters (445 cubic inches)	6.7 liters (406 cubic inches)
Bore x stroke	4.02 inches x 3.74 inches	4.22 inches x 3.98 inches	3.9 inches x 4.25 inches
Compression ratio	9.8:1	10.5:1	15:8:1
Valvetrain	Two valves per cylinder, roller rocker shaft	Pushrod and rocker arms, two valves per cylinder	Pushrod and rocker arms, four valves per cylinder
Recommended fuel	87 octane/E85	87 octane	Ultra-low sulfur diesel/B20
Fuel delivery	Sequential multi-port electronic	Sequential multi-port electronic	High-pressure common rail
Engine control system	Electronic	Electronic	Electronic
Intake manifold	Naturally aspirated, tuned intake	Naturally aspirated, tuned intake	Variable geometry turbocharger with charge air cooler
Dyno certified horsepower	385 @ 5,750 rpm	350 @ 3,900 rpm	330 @ 2,600 rpm
Dyno certified torque	430 lb.-ft. @ 3,800 rpm	468 lb.-ft. @ 3,900 rpm	825 lb.-ft. @ 2,000 rpm
Oil life monitor	oil life monitor®	oil life monitor®	Intelligent oil life monitor®

ELECTRICAL

Starter	6.2-liter F350 XL and XLT, 200 amp; Lariat, 240 amp
Alternator	7.3-liter F350, F450 and F550 XL/XLT, 240 amp, Lariat, 397 amp 6.7-liter F350, F450 and F550 XL/XLT, 240 amp, Lariat, 332 amp
Battery group, CCA	6.2-liter F350 XL SRW/DRW, 12-volt, 650-CCA/72-amp-hr 6.2-liter F350 XLT/Lariat SRW/DRW, 12-volt, 750-CCA/78-amp-hr 7.3-liter F450/F550 XL/XLT, 12-volt, 750-CCA/78-amp-hr 7.3-liter F450/F550 Lariat, dual 12-volt, 750-CCA/78-amp-hr 6.7-liter dual 12-volt, 750-CCA/78-amp-hr

TRANSMISSION

TorqShift® 10-speed heavy duty automatic transmission with SelectShift™

Configuration	Aluminum 10-speed, available live-drive access on driver side	Aluminum 10-speed, live-drive access on driver side	Aluminum 10-speed, live-drive access on driver side
Engine	6.2-liter V8	7.3-liter V8	6.7-liter Power Stroke V8
Gear ratios:			
First	4.615:1	4.615:1	4.615:1
Second	2.919:1	2.919:1	2.919:1
Third	2.132:1	2.132:1	2.132:1
Fourth	1.773:1	1.773:1	1.773:1
Fifth	1.519:1	1.519:1	1.519:1
Sixth	1.277:1	1.277:1	1.277:1
Seventh	1:1	1:1	1:1
Eighth	0.851:1	0.851:1	0.851:1
Ninth	0.687:1	0.687:1	0.687:1
Tenth	0.632:1	0.632:1	0.632:1
Reverse	-4.695:1	-4.695:1	-4.695:1

STEERING

Assist	Power hydraulic
--------	-----------------

BRAKES

Type	Four-wheel vented-disc, ABS (standard)
Front (rotor diameter)	14.29-inch (363 millimeter) F-350
	15.39-inch (391 millimeter) F-450/F-550
Rear (rotor diameter)	14.29-inch (363 millimeter) F-350
	15.75-inch (400 millimeter) F-450/F-550

WHEELS

Type	Steel or aluminum
Size	17-inch SRW/DRW, 18-inch SRW F-350; 19.5-inch F-450/F-550
Number of studs	Eight F-350; 10 F-450/F-550
Bolt circle diameter	6.7-inch F-350 SRW
	7.87-inch F-350 DRW
	8.86-inch F-450/F-550

PASSENGER AND FUEL CAPACITIES

Seating capacity (maximum)	Regular Cab	SuperCab	CrewCab
	Three	Six	Six
Midship fuel tank capacity, SRW F-350 with 68D payload downgrade package	26.5 gallons	26.5 gallons	26.5 gallons
Aft-of-axle fuel tank capacity SRW F-350/DRW F-350/F-450/F-550; with 68D payload downgrade on SRW F-350 package	40 gallons	40 gallons	40 gallons
Fuel capacity DRW – dual diesel tanks	66.5 gallons	66.5 gallons	66.5 gallons

FORD F-SERIES SUPER DUTY®



CHASSIS SPECIFICATIONS

Maximum GCWR	40,000 lbs.
Maximum GVWR	19,500 lbs.
Maximum payload	12,750 lbs.
Maximum conventional hitch tow	18,500 lbs.

Front suspension

Type	Twin-I-beam, F-350 4x2 Solid twin-coil monobeam axle, F-350 4x4, F-450/F-550
Maximum front GAWR	5,250 lbs, F-350 SRW 4x2 5,990 lbs, F-350 SRW 4x4 7,500 lbs, F-350 DRW 4x2 5,990 lbs, F-350 DRW 4x4 7,500 lbs, F-450 4x2 7,500 lbs, F-450 4x4 7,500 lbs, F-550 4x2 7,500 lbs, F-550 4x4
Springs	Coil
Shock absorbers	Gas type
Stabilizer bar	Standard

Rear suspension

Type	Solid axle
Maximum rear GAWR	7,230 lbs, F-350 SRW 4x2 7,230 lbs, F-350 SRW 4x4 12,880 lbs, F-350 DRW 4x2 10,040 lbs, F-350 DRW 4x4 12,880 lbs, F-450 4x2 12,880 lbs, F-450 4x4 14,706 lbs, F-550 4x2 14,706 lbs, F-550 4x4
Springs	Leaf
Shock absorbers	Gas type
Stabilizer bar	Standard

FORD F-SERIES SUPER DUTY®




EXTERIOR DIMENSIONS (INCHES UNLESS OTHERWISE NOTED)

Cab to axle drivetrain	Regular Cab				SuperCab		CrewCab	
	60	84	108	120	60	84	60	84
	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4	4x2/4x4
Wheelbase	145.3	169.3	193.3	205.3	167.9	191.9	179.8	203.8
Length overall	230.7*	254.8**	278.8	290.7	253.3	277.4	265.2	289.2
Height, F-350 SRW (without options)	79.1/81.9	–	–	–	79.3/82.0	–	79.4/82.1	–
Height, F-350 DRW (without options)	79.3/82.2	79.2/82.0	–	82.3/82.3	79.6/82.2	–	79.7/82.3	–
Height, F-450 DRW (without options)	82.6/82.6	82.4/82.4	–	82.4/82.4	82.5/82.5	82.5/82.4	82.8.7/82.6	82.6/82.5
Height, F-550 DRW (without options)	82.6/82.6	82.4/82.4	82.5/82.4	82.4/82.4	82.7/82.5	82.5/82.5	82.8/82.8	82.6/82.6
Track, front, F-350 SRW	68.3	–	–	–	68.3	–	68.3	–
Track, front, F-350 DRW	69.1	69.1	–	–	69.1	–	69.1	–
Track, front, F-450 DRW	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8
Track, front, F-550 DRW	74.8	74.8	74.8	74.8	74.8	74.8	74.8	74.8
Track, rear, F-350 SRW	68.1	–	–	–	68.1	–	68.1	–
Track, rear, F-350 DRW (tire center width)	71.1	71.1	–	–	71.1	–	71.1	–
Track, rear, F-450 DRW (tire center width)	74.0	74.0	74.0	74.0	74.0	74.0	74.0	74.0
Track, rear, F-550 DRW (tire center width)	74.0	74.0	74.0	74.0	74.0	74.0	74.0	74.0
Rear axle clearance, F-350 SRW	9.0/8.9	–	–	–	9.0/9.0	–	9.0/8.9	–
Rear axle clearance, F-350 DRW	8.4/8.3	8.4/8.4	–	–	8.4/8.4	–	8.4/8.4	–
Rear axle clearance, F-450 DRW	8.5/8.5	8.6/8.6	8.6/8.6	8.6/8.6	8.6/8.6	8.6/8.6	8.6/8.6	8.6/8.6
Rear axle clearance, F-550 DRW	8.5/8.5	8.6/8.6	8.6/8.6	8.6/8.6	8.6/8.6	8.6/8.6	8.6/8.6	8.6/8.6
Frame rail width, F-350 SRW	34.1	–	–	–	34.1	–	34.1	–
Frame rail width, F-350 DRW	34.1	34.1	–	–	34.1	–	34.1	–
Frame rail width, F-450 DRW	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2
Frame rail width, F-550 DRW	34.2	34.2	34.2	34.2	34.2	34.2	34.2	34.2
Rear axle to end of frame	47.2*	47.2**	47.2	47.2	47.2	47.2	47.2	47.2
Overhang, front	38.3	38.3	38.3	38.3	38.3	38.3	38.3	38.3
Base Curb Weight, 4x2 Only								
6.2-liter SRW F-350, 17-inch Wheels	5,426 lbs.	–	–	–	5,722 lbs.	–	5,963 lbs.	–
6.7-liter SRW F-350, 17-inch Wheels	6,167 lbs.	–	–	–	6,515 lbs.	–	6,758 lbs.	–
7.3-liter SRW F-350, 17-inch Wheels	5,426 lbs.	–	–	–	5,722 lbs.	–	5,963 lbs.	–
6.2-liter SRW F-350, 18-inch Wheels	5,626 lbs.	–	–	–	5,922 lbs.	–	6,163 lbs.	–
6.7-liter SRW F-350, 18-inch Wheels	6,367 lbs.	–	–	–	6,715 lbs.	–	6,958 lbs.	–
7.3-liter SRW F-350, 18-inch Wheels	5,626 lbs.	–	–	–	5,922 lbs.	–	6,163 lbs.	–
6.2-liter DRW F-350	6,053 lbs.	6,100 lbs.	–	–	6,394 lbs.	–	6,540 lbs.	–
6.7-liter DRW F-350	6,792 lbs.	6,861 lbs.	–	–	7,149 lbs.	–	7,301 lbs.	–
7.3-liter DRW F-350	6,053 lbs.	6,100 lbs.	–	–	6,394 lbs.	–	6,540 lbs.	–
7.3-liter DRW F-450	6,641 lbs.	6,709 lbs.	6,890 lbs.	6,942 lbs.	6,947 lbs.	7,133 lbs.	6,947 lbs.	7,267 lbs.
6.7-liter DRW F-450	7,390 lbs.	7,455 lbs.	7,635 lbs.	7,696 lbs.	7,697 lbs.	7,909 lbs.	7,697 lbs.	8,015 lbs.
7.3-liter DRW F-550	6,641 lbs.	6,709 lbs.	6,890 lbs.	6,942 lbs.	6,947 lbs.	7,133 lbs.	7,112 lbs.	7,267 lbs.
6.7-liter DRW F-550	7,390 lbs.	7,455 lbs.	7,635 lbs.	7,696 lbs.	7,697 lbs.	7,909 lbs.	7,842 lbs.	8,015 lbs.
7.3-liter DRW F-550	6,681 lbs.	6,749 lbs.	6,930 lbs.	6,982 lbs.	6,987 lbs.	7,173 lbs.	7,152 lbs.	7,307 lbs.
6.7-liter DRW F-550	7,430 lbs.	7,495 lbs.	7,675 lbs.	7,736 lbs.	7,737 lbs.	7,949 lbs.	7,882 lbs.	8,055 lbs.

*89.4- inch with optional aft-axle frame extension, F-450, F-550, 273.0- inch overall length

**79.6- inch with optional aft-axle frame extension, F-550, 287.2- inch overall length

FORD F-SERIES SUPER DUTY®



INTERIOR DIMENSIONS (INCHES UNLESS OTHERWISE NOTED)

	Regular Cab		SuperCab		CrewCab	
	4x2/4x4		4x2/4x4		4x2/4x4	
Front headroom	40.8		40.8		40.8	
Front shoulder room	66.7		66.7		66.7	
Front hip room	62.5		62.5		62.5	
Front legroom	43.9		43.9		43.9	
Rear headroom	–		40.3		40.4	
Rear shoulder room	–		65.8		65.9	
Rear hip room	–		64.7		64.7	
Rear legroom	–		33.5		43.6	
Volume (cu. ft.)						
Passenger, front	64.6		64.6		64.6	
Passenger, rear	–		51.4		67.1	
Passenger, total	64.6		116		131.7	
Cargo, behind first row	11.6		31.6		52.1	

PAYLOAD PACKAGE SELECTOR (LBS.)

	Maximum GVWR	Regular Cab				SuperCab		CrewCab	
		145- inch wheelbase; 60 inches, cab to axle	169- inch wheelbase; 84 inches, cab to axle	193- inch wheelbase; 108 inches, cab to axle	205- inch wheelbase; 120 inches, cab to axle	167.5- inch wheelbase; 60 inches, cab to axle	191.5- inch wheelbase; 84 inches, cab to axle	179.4- inch wheelbase; 60 inches, cab to axle	203.4- inch wheelbase; 84 inches, cab to axle
SRW F-350 4x2	9,800	4,370	–	–	–	4,070	–	3,830	–
	10,000	4,520	–	–	–	4,220	–	3,980	–
	10,500	4,870	–	–	–	–	–	–	–
	10,900	–	–	–	–	4,970	–	–	–
	11,000	–	–	–	–	–	–	4,830	–
	11,100	4,730	–	–	–	–	–	–	–
	11,500	–	–	–	–	4,780	–	4,540	–
SRW F-350 4x4	9,800	3,960	–	–	–	3,640	–	3,420	–
	10,000	4,110	–	–	–	3,790	–	3,560	–
	10,900	4,860	–	–	–	–	–	–	–
	11,300	–	–	–	–	4,940	–	–	–
	11,400	–	–	–	–	–	–	4,820	–
	11,500	4,690	–	–	–	4,350	–	4,120	–
DRW F-350 4x2	14,000	7,940	7,900	–	–	7,600	–	7,460	–
	16,000	–	–	–	–	8,300	–	–	–
	16,500	–	–	–	–	8,800	–	–	–
DRW F-350 4x4	14,000	7,550	7,500	–	–	7,200	–	7,040	–
DRW F-450 4x2	15,000	8,350	8,290	8,110	8,050	8,050	7,860	7,880	7,730
	16,000	9,350	9,290	9,110	9,050	9,050	8,860	8,880	8,730
	16,500	9,850	9,790	9,610	9,550	9,550	9,360	9,380	9,230
DRW F-450 4x4	15,000	8,040	7,950	7,800	7,730	7,690	7,530	7,570	7,440
	16,000	9,040	8,950	8,800	8,730	8,690	8,530	8,570	8,440
	16,500	9,540	9,450	9,300	9,230	9,190	9,030	9,070	8,940
DRW F-550 4x2	17,500	10,850	10,790	10,610	10,550	10,550	10,360	10,380	10,230
	18,000	11,350	11,290	11,110	11,050	11,050	10,860	10,880	10,730
	19,000	12,310	–	–	–	–	–	–	–
	19,500	12,070	12,750	12,570	12,510	12,510	12,320	12,340	12,190

FORD F-SERIES SUPER DUTY®




PAYLOAD PACKAGE SELECTOR CONTINUED (LBS.)

	Maximum GVWR	Regular Cab				SuperCab		CrewCab	
		145- inch wheelbase; 60 inches, cab to axle	169- inch wheelbase; 84 inches, cab to axle	193- inch wheelbase; 108 inches, cab to axle	205- inch wheelbase; 120 inches, cab to axle	167.5- inch wheelbase; 60 inches, cab to axle	191.5- inch wheelbase; 84 inches, cab to axle	179.4- inch wheelbase; 60 inches, cab to axle	203.4- inch wheelbase; 84 inches, cab to axle
DRW F-550 4x4	17,500	10,540	10,450	10,300	10,230	10,190	10,030	10,070	9,940
	18,000	11,040	10,950	10,800	10,730	10,690	10,530	10,570	10,440
	19,000	12,000	—	—	—	—	—	—	—
	19,500	11,750	12,410	12,260	12,190	12,150	11,990	12,030	11,900

CONVENTIONAL TOWING – MAXIMUM LOADED TRAILER WEIGHT RATINGS (LBS.)

	Rear axle	Axle ratio	Maximum GVWR	Regular Cab					
				F-350 4x2	F-350 4x4	F-450 4x2	F-450 4x4	F-550 4x2	F-550 4x4
6.2-liter gas V8	SRW	3.73	19,500	13,200	12,700	—	—	—	—
	SRW	4.30	23,000	13,500	13,500	—	—	—	—
	DRW	3.73	20,000	13,000	12,600	—	—	—	—
	DRW	4.30	23,500	16,500	16,100	—	—	—	—
6.7-liter Power Stroke turbo diesel V8	DRW	4.10	20,000	—	—	—	—	11,600	—
	SRW	3.73	30,000	13,500	13,500	—	—	—	—
	DRW	3.73	31,500	17,500	17,500	—	—	—	—
	DRW	4.10	32,500	17,500	17,500	17,500	17,500	18,500	18,500
	DRW	4.88	32,500	—	—	—	—	18,500	18,500
	DRW	4.30	35,000	—	—	17,500	17,500	—	—
	DRW	4.30	37,000	—	—	—	—	18,500	18,500
	DRW	4.88	40,000	—	—	—	—	18,500	18,500
7.3-liter gas V8	DRW	3.73	22,500	15,500	15,100	—	—	—	—
	SRW	4.30	26,000	13,500	13,500	—	—	—	—
	DRW	4.30	26,000	17,500	17,500	—	—	—	—
	DRW	4.88	28,000	—	—	17,500	17,500	18,500	18,500

FORD F-SERIES SUPER DUTY®



CONVENTIONAL TOWING – MAXIMUM LOADED TRAILER WEIGHT RATINGS (LBS.)

				SuperCab					
	Rear axle	Axle ratio	Maximum GCWR	F-350 4x2	F-350 4x4	F-450 4x2	F-450 4x4	F-550 4x2	F-550 4x4
6.2-liter gas V8	SRW	3.73	19,500	12,900	12,400	–	–	–	–
	SRW	4.30	23,000	13,500	13,500	–	–	–	–
	DRW	3.73	20,000	12,700	12,300	–	–	–	–
	DRW	4.30	23,500	16,200	15,800	–	–	–	–
6.7-liter Power Stroke turbo diesel V8	DRW	4.10	20,000	–	–	–	–	–	–
	SRW	3.73	30,000	13,500	13,500	–	–	–	–
	DRW	3.73	31,500	17,500	17,500	–	–	–	–
	DRW	4.10	32,500	17,500	17,500	17,500	17,500	18,500	18,500
	DRW	4.88	32,500	–	–	–	–	18,500	18,500
	DRW	4.30	35,000	–	–	17,500	17,500	–	–
	DRW	4.30	37,000	–	–	–	–	18,500	18,500
	DRW	4.88	40,000	–	–	–	–	18,500	18,500
7.3-liter gas V8	DRW	3.73	22,500	15,200	14,800	–	–	–	–
	SRW	4.30	26,000	13,500	13,500	–	–	–	–
	DRW	4.30	26,000	17,500	17,500	–	–	–	–
	DRW	4.88	28,000	–	–	17,500	17,500	18,500	18,500

CONVENTIONAL TOWING – MAXIMUM LOADED TRAILER WEIGHT RATINGS (LBS.)

				CrewCab					
	Rear axle	Axle ratio	Maximum GCWR	F-350 4x2	F-350 4x4	F-450 4x2	F-450 4x4	F-550 4x2	F-550 4x4
6.2-liter gas V8	SRW	3.73	19,500	12,600	12,200	–	–	–	–
	SRW	4.30	23,000	13,500	13,500	–	–	–	–
	DRW	3.73	20,000	12,500	12,100	–	–	–	–
	DRW	4.30	23,500	16,000	15,600	–	–	–	–
6.7-liter Power Stroke turbo diesel V8	DRW	4.10	20,000	–	–	–	–	–	–
	SRW	3.73	30,000	13,500	13,500	–	–	–	–
	DRW	3.73	31,500	17,500	17,500	–	–	–	–
	DRW	4.10	32,500	17,500	17,500	17,500	17,500	18,500	18,500
	DRW	4.88	32,500	–	–	–	–	18,500	18,500
	DRW	4.30	35,000	–	–	17,500	17,500	–	–
	DRW	4.30	37,000	–	–	–	–	18,500	18,500
	DRW	4.88	40,000	–	–	–	–	18,500	18,500
7.3-liter gas V8	DRW	3.73	22,500	15,000	14,600	–	–	–	–
	SRW	4.30	26,000	13,500	13,500	–	–	–	–
	DRW	4.30	26,000	17,500	17,500	–	–	–	–
	DRW	4.88	28,000	–	–	17,500	17,500	18,500	18,500

FORD F-SERIES SUPER DUTY®




FIFTH WHEEL/GOOSENECK TOWING – MAXIMUM LOADED TRAILER WEIGHT RATINGS (LBS.)

				Regular Cab					
	Rear axle	Axle ratio	Maximum GCWR	F-350 4x2	F-350 4x4	F-450 4x2	F-450 4x4	F-550 4x2	F-550 4x4
6.2-liter gas V8	SRW	3.73	19,500	13,100	12,700	–	–	–	–
	SRW	4.30	23,000	16,600	16,200	–	–	–	–
	DRW	3.73	20,000	13,000	12,600	–	–	–	–
	DRW	4.30	23,500	16,500	16,100	–	–	–	–
6.7-liter Power Stroke turbo diesel V8	DRW	4.10	20,000	–	–	–	–	11,600	–
	SRW	3.73	30,000	22,700	22,200	–	–	–	–
	DRW	3.73	31,500	23,700	23,300	–	–	–	–
	DRW	4.10	32,500	24,700	24,300	24,100	23,800	24,100	23,800
	DRW	4.88	32,500	–	–	–	–	24,100	23,800
	DRW	4.30	35,000	–	–	26,600	26,300	–	–
	DRW	4.30	37,000	–	–	–	–	28,600	28,300
	DRW	4.88	40,000	–	–	–	–	31,600	31,300
7.3-liter gas V8	DRW	3.73	22,500	15,500	15,100	–	–	–	–
	DRW	4.30	26,000	19,000	18,600	–	–	–	–
	SRW	4.30	26,000	19,600	19,200	–	–	–	–
	DRW	4.88	28,000	–	–	20,400	20,100	20,400	20,100

FIFTH WHEEL/GOOSENECK TOWING – MAXIMUM LOADED TRAILER WEIGHT RATINGS (LBS.)

				SuperCab					
	Rear axle	Axle ratio	Maximum GCWR	F-350 4x2	F-350 4x4	F-450 4x2	F-450 4x4	F-550 4x2	F-550 4x4
6.2-liter gas V8	SRW	3.73	19,500	12,800	12,400	–	–	–	–
	SRW	4.30	23,000	16,300	15,900	–	–	–	–
	DRW	3.73	20,000	12,600	12,200	–	–	–	–
	DRW	4.30	23,500	16,100	15,700	–	–	–	–
6.7-liter Power Stroke turbo diesel V8	DRW	4.10	20,000	–	–	–	–	–	–
	SRW	3.73	30,000	22,300	21,900	–	–	–	–
	DRW	3.73	31,500	23,400	23,000	–	–	–	–
	DRW	4.10	32,500	24,400	24,000	23,800	23,500	23,800	23,500
	DRW	4.88	32,500	–	–	–	–	23,800	23,400
	DRW	4.30	35,000	–	–	26,300	26,000	–	–
	DRW	4.30	37,000	–	–	–	–	28,300	28,000
	DRW	4.88	40,000	–	–	–	–	31,300	30,900
7.3-liter gas V8	DRW	3.73	22,500	15,100	14,700	–	–	–	–
	DRW	4.30	26,000	18,600	18,200	–	–	–	–
	SRW	4.30	26,000	19,300	18,800	–	–	–	–
	DRW	4.88	28,000	–	–	20,100	19,700	20,100	19,700

FORD F-SERIES SUPER DUTY®



FIFTH WHEEL/GOOSENECK TOWING – MAXIMUM LOADED TRAILER WEIGHT RATINGS (LBS.)

	Rear axle	Axle ratio	Maximum GCWR	CrewCab					
				F-350 4x2	F-350 4x4	F-450 4x2	F-450 4x4	F-550 4x2	F-550 4x4
6.2-liter gas V8	SRW	3.73	19,500	12,600	12,200	–	–	–	–
	SRW	4.30	23,000	16,100	15,700	–	–	–	–
	DRW	3.73	20,000	12,500	12,100	–	–	–	–
	DRW	4.30	23,500	16,000	15,600	–	–	–	–
6.7-liter Power Stroke turbo diesel V8	DRW	4.10	20,000	–	–	–	–	–	–
	SRW	3.73	30,000	22,100	21,300	–	–	–	–
	DRW	3.73	31,500	23,200	22,800	–	–	–	–
	DRW	4.10	32,500	24,200	23,800	23,700	23,400	23,700	23,400
	DRW	4.88	32,500	–	–	–	–	23,600	23,300
	DRW	4.30	35,000	–	–	26,200	25,900	–	–
	DRW	4.30	37,000	–	–	–	–	28,200	27,900
	DRW	4.88	40,000	–	–	–	–	31,100	30,800
7.3-liter gas V8	DRW	3.73	22,500	15,000	14,600	–	–	–	–
	DRW	4.30	26,000	18,500	18,100	–	–	–	–
	SRW	4.30	26,000	19,100	18,500	–	–	–	–
	DRW	4.88	28,000	–	–	19,900	19,600	19,900	19,600

WARRANTY

Bumper to bumper:	Three years/36,000 miles
Powertrain:	Five years/60,000 miles
Safety restraint system:	Five years/60,000 miles
Corrosion (perforation only):	Five years/unlimited miles
Roadside assistance program:	Five years/60,000 miles

FORD F-SERIES SUPER DUTY®

