



# Lithonia Lighting Basics™

LED Running Man Signs and Combos

## Emergency Lighting for All Languages

The EXRM, ECRM, and ECBRM by Lithonia Lighting® are high-performing signs and combos with directional "Running Man" face plates. These fixtures safely identify all exits and provide a minimum of 90-minutes of illumination upon the loss of AC power. All three products are ideal for public environments like airports, schools and restaurants. Don't let translation be a barrier to safely exiting any building.

### Features and Benefits:

- Single or double-sided signs
- Ceiling, wall or flush mount
- Standard and Arrow panels included
- Automatically performs monthly and annual testing with multi-status diagnostics functions
- Quick installation



EXRM



ECBRM



ECRM

Learn more about the EXRM, ECRM, and ECBRM at [www.lithonia.com](http://www.lithonia.com)

## Commercial LED Running Man Signs and Combos

	EXRM	ECRM	ECBRM
			
<b>Best Use</b>	Means of egress marking	Means of egress markings and illumination over doorways	Means of egress markings and illumination over doorways
<b>Mounting</b>	Top, side, and back mount	Top, side, and back mount	Top, side, and back mount
<b>Housing/Construction</b>	White thermoplastic. 5VA flame rated and impact-resistant	White thermoplastic, classic square, dual lamp heads. 5VA flame rated and impact-resistant	White thermoplastic, adjustable lightbar. 5VA flame rated and impact-resistant
<b>Ambient Temperature Range</b>	0°C - 50°C (32°F - 122°F)	0°C - 50°C (32°F - 122°F)	0°C - 50°C (32°F - 122°F)
<b>Voltage</b>	Dual-voltage 120/347 standard	Dual-voltage 120/347 standard	Dual-voltage 120/347 standard
<b>Optics</b>	-	1W / white LED lamp head	up to 3W
<b>Weight</b>	2 lbs	3.75 lbs	3.75 lbs
<b>Certification/Ratings i.e., DLC, CSA, etc.</b>	CSA Damp, CSA 22.2 No. 141, NFPA 101, FCC, OSHA	CSA Damp, CSA 22.2 No. 141, NFPA 101, FCC, OSHA	CSA Damp, CSA 22.2 No. 141, NFPA 101, FCC, OSHA
<b>Battery</b>	9.6V maintenance-free, rechargeable, nickel-cadmium	9.6V maintenance-free, rechargeable, nickel-cadmium	9.6V maintenance-free, rechargeable, nickel-cadmium
<b>Test Switch</b>	Yes	Yes	Yes
<b>Emergency Backup</b>	90 minutes	90 minutes	90 minutes
<b>Remote Capacity</b>	Yes, with EL option using ERE remotes	Yes, with HO option using ERE remotes	Yes, using ERE remotes
<b>Acuity Controls</b>	No	No	No
<b>Warranty</b>	5-year limited warranty	5-year limited warranty	5-year limited warranty
<b>Application</b>	Small commercial indoor applications requiring lower mounting heights	Small commercial indoor applications requiring lower mounting heights	Small commercial indoor applications requiring lower mounting heights



Visit [www.lithonia.com](http://www.lithonia.com) for more information or email: [TechSupport-Emergency@AcuityBrands.com](mailto:TechSupport-Emergency@AcuityBrands.com)

One Lithonia Way | Conyers, Georgia 30012 | 800.334.8694 | [www.acuitybrands.com](http://www.acuitybrands.com)  
 ©2020 Acuity Brands Lighting, Inc. All rights reserved. | LL\_9279.02\_0720

**AcuityBrands**®