

Club Car[®]

UP TO THE TASK

Rental-ready vehicles
deliver results that
grow business.

CARRYALL



**UNMATCHED
VERSATILITY,
EXCEPTIONAL
RELIABILITY**

The only utility vehicles that can keep up with your customers.

Your renters rely on work vehicles to perform day in and day out, on task after task, with little maintenance, even less attention, and zero headaches. Because we understand that, the Carryall® series by Club Car is designed, developed, and engineered to enable their best work with ease, positioning you—and everyone you serve—for success.

Built to exacting standards with automotive-grade strength, industry-leading longevity, and a customizable design, Carryalls are the first and best choice for hardworking teams everywhere.

CARRYALL



- 3 **CARRYALL 1700**
- 4 **CARRYALL 1500**
- 6 **CARRYALL 700/500/300**
- 8 **CUSTOMIZATION & DURABILITY**
- 9 **TEMPO 2+2/ TRANSPORTER/ TRANSPORTER XL**
- 10 **INTELLITACH**
- 12 **OPTIONS & ACCESSORIES**
- 13 **RENTAL VEHICLE SPECIFICATIONS**

1700

“Our customers demand a real workhorse for use in the toughest commercial applications, and the Club Car utility vehicles have proven they are up to the challenge.”

**– Greg Pasquale,
Director of Product Support
Synergy Equipment**



CARRYALL 1700

**POWERFUL HAULING
FOR ANY JOB SITE**

The industry’s only automatic four-wheel drive vehicle has room for up to four people and all their gear.

				
Max Speed 25 mph		Max Vehicle Capacity 1600 lbs		Horsepower 20 hp (gasoline) 20 hp (diesel)

**1,000 JOBS,
ONLY ONE CARRYALL**

Things can get rocky out there for your customers. Team members come and go. Budgets fluctuate. Responsibilities (and liabilities) expand. But the Carryall® utility vehicle remains a constant. It keeps on working, hauling cargo, transporting crews, and saving time and money. Now, it's more versatile than ever: by combining leading-edge innovations with the quality you expect, the Carryall is the one utility vehicle that can tackle 1,000 jobs. It stands alone.



CARRYALL 1500

**ALL-AROUND
HIGH-PERFORMANCE MACHINE**

The perfect combination of muscle and flexibility packed on a rustproof, aircraft-grade aluminum frame.



Max Speed
25 mph



Max Vehicle
Capacity
1450 lbs



Horsepower
20 hp (gasoline)
20 hp (diesel)



**REDESIGNED FROM
THE GROUND UP**

Our 2- and 4-passenger 4x4 cabs for Carryall provide greater overall comfort, safety, protection from the elements, and performance.



TANK-LIKE DURABILITY, TRUCK-LIKE PERFORMANCE

These vehicles are in it for the long haul.

Carryall® utility vehicles are known for delivering years of trouble-free service. The new vehicles continue that tradition. They retain the core components users prize in the Carryall brand: the rustproof, corrosion-resistant, aircraft-grade aluminum frame and body; tough ArmorFlex™ front body with automotive finish; self-compensating rack-and-pinion steering; independent front suspension system; and unparalleled reliability. But they also incorporate innovative new features and benefits that add even more value.



CARRYALL 300

EASY TO HANDLE

With the tightest turning radius in its class, Carryall 300 delivers unsurpassed maneuverability.



Max Speed
17 mph



Max Vehicle
Capacity
800 lbs



Horsepower
14 hp (gasoline)
3.3 hp (electric)



CARRYALL 500

JACK OF ALL TRADES

Versatile, rugged, the best choice for those with various tasks.



Max Speed
17 mph



Max Vehicle
Capacity
1200 lbs



Horsepower
14 hp (gasoline)
3.7 hp (electric)



CARRYALL 700

FOR THE LONG HAUL

High hauling capacity with the legendary, rugged Carryall design.



Max Speed
17 mph



Max Vehicle
Capacity
1500 lbs



Horsepower
14 hp (gasoline)
3.7 hp (electric)

**EASY HANDLING,
TOUGH HAULING**

Carryall 300 is the perfect solution for light-duty industrial and commercial jobs.



300



500



700

OUTFITTED FOR THE TASK AT HAND

Carryall UTVs are built for hundreds of needs.

No team ever has just one job to do. With the industry's widest range of commercial accessories, including ladder racks, refreshment centers, specialized lighting, and more, we can deliver your rental vehicles equipped with application-specific features designed to improve user productivity.



FACILITIES ENGINEERING

Our facilities engineering Carryall vehicle comes with a van box or dual-locking tool box system to help teams stay on the move.



SECURITY

Security continues to evolve, and the Carryall 300 security vehicle is designed to flex with your customers' changing needs.



GROUPS MAINTENANCE

Club Car's new Carryall 700 grounds maintenance vehicle with hose reel has the reliable power to get the job done on any terrain.



AMBULANCE SERVICES

The Carryall 300 and 1700 ambulance vehicles have a small profile, tight handling, and extra space, allowing for the secure transport of patients.



COMFORTABLE, SAFE PASSENGER TRANSPORT

Built for durable flexibility on campuses, resorts, and more.

Driven by powerful yet quiet gas or zero-emissions electric engines, Club Car Transporter, Transporter XL, and Tempo™ 2+2 vehicles are designed with automotive-grade safety details and packed with comfort and convenience features. They're smart, steady solutions that provide peace of mind for anyone who transports guests.



Tempo 2+2

THE MOST ECONOMICAL PEOPLE MOVER

Boasting the tightest turn radius in the industry, the Tempo 2+2 adds comfort to sporty handling.

Max Speed 15 mph	Max Vehicle Capacity 800 lbs	Seating Capacity 4



TRANSPORTER | TRANSPORTER XL

MADE FOR CREWS AND CARGO

Available with a fold-down rear seat to carry up to 300 lbs. and equipped with rustproof aluminum chassis, body, and bed.

Max Speed 17 mph	Max Vehicle Capacity 1500 lbs	Seating Capacity 4-8



"The Club Cars have proven dependable in the hands of some very demanding rental customers in some of the harshest environments imaginable."

– **Greg Pasquale,**
Director of Product
Support
Synergy Equipment

READY FOR ANY TERRAIN

Our IntelliTrak™ all-wheel drive system senses the ground it's on and automatically adjusts between 1- to 4-wheel drive to match the terrain. With no levers, buttons, or training needed, the driver can focus on the job at hand—and trust that the vehicle can cover any ground.





IntelliTach

EQUIPPED WITH JOB-SPECIFIC ESSENTIALS

Help customers get a variety of jobs done quickly—and reduce the need for expensive construction equipment—with our exclusive IntelliTach™ quick-change tool attachment system.

OPTIONS & ACCESSORIES

Ask your Club Car sales representative for details.



Front Bucket



Plow Blade



Pallet Forks

ALL THE ACCESSORIES YOUR RENTERS NEED

Specialized add-ons put frequently used tools front and center.

If it's necessary to the job, Club Car has it. Be the single source for all your customers' vehicle needs with these standard accessories: turn signals, tail lights, and horn, heavy-duty bed box, backup buzzer, tube bumper, safety light strobe, and canopy.





CARRYALL 1700³



GASOLINE



DIESEL

CARRYALL 1500²



GASOLINE



DIESEL



**DIESEL
W/INTELLITACH**



GASOLINE

ENGINE	Kawasaki 4-cycle, industrial grade	Kubota D722, industrial grade	Kawasaki 4-cycle, industrial grade	Kubota D722, industrial grade	Kubota D722, industrial grade	Kawasaki 4-cycle, industrial grade
HORSEPOWER	201 hp (15 kW) rated @ 3400 RPM per SAE J1349	20 hp (15 kW) rated @ 3600 RPM per SAE J1995	201 hp (15 kW) rated @ 3400 RPM per SAE J1349	20 hp (15 kW) rated @ 3600 RPM per SAE J1995	20 hp (15 kW) rated @ 3600 RPM per SAE J1995	201 hp (15 kW) rated @ 3400 RPM per SAE J1349
BATTERIES	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve
STEERING	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering
FRONT SUSPENSION	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks
REAR SUSPENSION	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle
BRAKES	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc
PARK BRAKE	Mechanical disc	Mechanical disc	Mechanical disc	Mechanical disc	Mechanical disc	Mechanical disc
TIRES	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply	All-terrain, 25 x 10.5-12, 4-ply
BED L x W x H	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)
WHEELBASE	114 in (290 cm)	114 in (290 cm)	82 in (208 cm)	82 in (208 cm)	82 in (208 cm)	82 in (208 cm)
GROUND CLEARANCE	8.2 in (21 cm)	8.2 in (21 cm)	8.2 in (21 cm)	8.2 in (21 cm)	7.3 in (19 cm) - under differential 11.1 in (28 cm) - under floorboard	8.2 in (21 cm)
FUEL TANK CAPACITY	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)
CURB WEIGHT	1630 lb (739 kg)	1750 lb (794 kg)	1430 lb (649 kg)	1550 lb (703 kg)	1751 lb (794 kg)	1387 lb (626 kg) w/o ROPS 1451 lb (658 kg) w/ ROPS
BED CAPACITY	800 lb (363 kg)	800 lb (363 kg)	Standard 800 lb (363 kg); with HD Suspension 1050 lb (476 kg)	Standard 800 lb (363 kg); with HD Suspension 1050 lb (476 kg)	Standard 800 lb (363 kg)	Standard 800 lb (363 kg); with HD Suspension 1500 lb (680 kg)
PAYLOAD CAPACITY	1600 lb (726 kg)	1600 lb (726 kg)	With HD Suspension 1450 lb (658 kg)	With HD Suspension 1450 lb (658 kg)	1200 lb (544 kg)	Standard 1200 lb (544 kg); with HD Suspension 1900 lb (862 kg)
TOWING CAPACITY	2000 lb (907 kg)	2000 lb (907 kg)	2000 lb (907 kg)	2000 lb (907 kg)	2000 lb (907 kg)	1300 lb (590 kg)
OVERALL HEIGHT	80.3 in (204 cm)	80.3 in (204 cm)	80.3 in (204 cm)	80.3 in (204 cm)	80.3 in (204 cm)	53.4 in (136 cm) w/o ROPS 80.3 in (204 cm) w/ ROPS
OVERALL LENGTH	154 in (391 cm)	154 in (391 cm)	124.6 in (317 cm)	124.6 in (317 cm)	121 in (307 cm) - w/o attachment arm and w/ cylinders stored 136 in (345 cm) - w/ attachment arm and cylinder fully extended 155 in (394 cm) - max extended position	124.6 in (317 cm)
OVERALL WIDTH	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)
SPEED RANGE	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)	19 mph (30 km/h)
LIMITED WARRANTY	1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain	1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain	1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain	1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain	1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain	1 yr/1000 hr limited vehicle 2 yr/2000 hr limited powertrain

AWD & 2WD

Dark Gray

Colors may vary by product

Dark Green



CARRYALL 300



GASOLINE



ELECTRIC

CARRYALL 500



GASOLINE



ELECTRIC

CARRYALL 700



GASOLINE



ELECTRIC

	CARRYALL 300		CARRYALL 500		CARRYALL 700	
ENGINE	Kohler EFI, 4-cycle Gas	48-volt DC	Kohler EFI, 4-cycle Gas	48-volt DC	Kohler EFI, 4-cycle Gas	48-volt DC
HORSEPOWER	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.3 hp (2.4 kW) rated, peak 13 hp (9.6 kW)	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW)	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW)
BATTERIES	12-volt 500 CCA 105 min reserve	Six 8-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid
CHARGER	N/A	E.R.I.C. Shelf Charger (650 W high frequency)	N/A	On-board DeltaQ QuiQ (1 kW high frequency)	N/A	On-board DeltaQ QuiQ (1 kW high frequency)
STEERING	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion
FRONT SUSPENSION	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
BRAKES	Rear-wheel, self-adjusting mechanical drum	Rear-wheel, self-adjusting mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum
PARK BRAKE	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock
BODY AND FINISH	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish
TIRES	20 x 10-10, 6-ply	20 x 10-10, 6-ply	20 x 10-10, 6-ply, premium tread	20 x 10-10, 6-ply, premium tread	20 x 10-10, 6-ply, premium tread	20 x 10-10, 6-ply, premium tread
BED L x W x H	36.2 x 47.5 x 10.5 in (92 x 121 x 27 cm)	36.2 x 47.5 x 10.5 in (92 x 121 x 27 cm)	44.2 x 47.5 x 10.5 in (112 x 121 x 27 cm)	44.2 x 47.5 x 10.5 in (112 x 121 x 27 cm)	65.5 x 47.5 x 10.5 in (166 x 121 x 27 cm)	65.5 x 47.5 x 10.5 in (166 x 121 x 27 cm)
WHEELBASE	65.5 in (166 cm)	65.5 in (166 cm)	78.1 in (198 cm)	78.1 in (198 cm)	99.1 in (252 cm)	99.1 in (252 cm)
GROUND CLEARANCE	5.2 in (13 cm)	5.6 in (14 cm)	5.6 in (14.2 cm)	5.6 in (14.2 cm)	5.6 in (14.2 cm)	5.6 in (14.2 cm)
FUEL TANK CAPACITY	5.5 gal (20.8 L)	N/A	5.5 gal (20.8 L)	N/A	5.5 gal (20.8 L)	N/A
CURB WEIGHT	817 lb (371 kg)	1105 lb (501 kg)	907 lb (411 kg)	1393 lb (632 kg)	993 lb (450 kg)	1475 lb (669 kg)
SPEED RANGE	15–17 mph (24–27 km/h)	5–17 mph (8–27 km/h)	15–17 mph (24–27 km/h)	5–17 mph (8–27 km/h)	15–17 mph (24–27 km/h)	5–17 mph (8–27 km/h)
LIMITED WARRANTY	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle

Dark Gray

Dark Green

Bright Blue

**Tempo** 2+2**GASOLINE****ELECTRIC****TRANSPORTER****GASOLINE****ELECTRIC****TRANSPORTER XL****GASOLINE****ELECTRIC**

ENGINE	Kohler EFI, 4-cycle Gas	48-volt DC	Kohler EFI, 4-cycle Gas	48-volt DC	Kohler EFI, 4-cycle Gas	48-volt DC
HORSEPOWER	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.3 hp (2.4 kW) rated; peak 13 hp (9.6 kW)	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW)	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW)
GOVERNOR GUARD	Ground speed	N/A	Ground speed	N/A	Ground speed	N/A
BATTERIES	12-volt 500 CCA 105 min reserve	Six 8-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid
CHARGER	N/A	E.R.I.C. (650 W high frequency)	N/A	On-board DeltaQ QuiQ (1 kW High Frequency)	N/A	On-board DeltaQ QuiQ (1 kW High Frequency)
STEERING	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion
FRONT SUSPENSION	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
BRAKES	Rear wheel mechanical drum	Rear wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum
PARK BRAKE	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, multi-lock
BODY AND FINISH	Molded-in color, aluminum finish	Molded-in color, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish	ArmorFlex® with automotive paint/clearcoat, aluminum finish
TIRES	18 x 8.50-8, 4-ply rated, premium tread	18 x 8.50-8, 4-ply rated, premium tread	20 x 10-10, 6-ply rated, premium tread	20 x 10-10, 6-ply rated, premium tread	20 x 10-10, 6-ply rated, premium tread	20 x 10-10, 6-ply rated, premium tread
BED L x W x H	N/A	N/A	37 x 47.5 x 10.5 in (94 x 120 x 27 cm) (Cargo Box)	37 x 47.5 x 10.5 in (94 x 120 x 27 cm) (Cargo Box)	N/A	N/A
WHEELBASE	65.5 in (166 cm)	65.5 in (166 cm)	99.1 in (252 cm)	99.1 in (252 cm)	132.1 in (336 cm)	132.1 in (336 cm)
GROUND CLEARANCE	4.5 in (11 cm)	4.5 in (11 cm)	5.6 in (14 cm)	5.2 in (14 cm)	5.6 in (14 cm)	5.2 in (14 cm)
FUEL TANK CAPACITY	5.5 gal (20.8 L)	N/A	5.5 gal (20.8 L)	N/A	5.5 gal (20.8 L)	N/A
CURB WEIGHT	N/A	N/A	932 lb (423 kg) stakeside; 943 lb (428 kg) with rear seat	1494 lb (678 kg) stakeside; 1505 lbs (684 kg) with rear seat	1104 lb (501 kg) 8 passenger	1646 lb (747 kg) 8 passenger
SPEED RANGE	12–15 mph (19.3–24.1 km/h)	5–15 mph (8–24.1 km/h)	15–17 mph (24–27 km/h)	5–17 mph (24–27 km/h)	15–17 mph (24–27 km/h)	5–17 mph (24–27 km/h)
LIMITED WARRANTY	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle

Dark Gray

Dark Green

Bright Blue

*Other colors available upon request

Colors may vary by product

CARRYALL

Talk to your Club Car sales representative to
make the most of your rental fleet

LEARN MORE AT CARRYALL.COM

