

RF Power Tape and Reel Information

RF EMBOSSED TAPE AND REEL ORDERING INFORMATION

Package	Tape Width (mm)	Pitch (mm) (inch)	Reel Size (mm) (inch)	Devices Per Reel and Minimum Order Quantity	Device Suffix
ACP-1230S-4L2L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	150	R6
	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	50	R5
DFN 2 × 2	12	8.0 ± 0.1 (.315 ± .004)	178 (7)	1,000	T1
DFN 4 × 6	16	8.0 ± 0.1 (.315 ± .004)	178 (7)	1,000	T1
NI-360H-2SB	32	24.0 ± 0.1 (.945 ± .004)	330 (13)	50	R5
NI-400H-2S	32	32.0 ± 0.1 (1.26 ± .004)	330 (13)	250	R3
NI-400S-2S	32	32.0 ± 0.1 (1.26 ± .004)	330 (13)	250	R3
NI-780H-2L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	250	R3
NI-780S-2L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	250	R3
NI-780GS-2L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	250	R3
NI-780H-4L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	250	R3
NI-780S-4L	32	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-780GS-4L	32	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-780S-2L2L	44	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-780S-2L2LA	44	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-780GS-2L2LA	44	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-780S-2L4S	44	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-780S-4L2L	44	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-780S-4L4L	44	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-780GS-4L4L	44	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-780S-4L4S	44	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-860	56	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
	56	28.0 ± 0.1 (1.10 ± .004)	330 (13)	50	R5
NI-880H-2L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	250	R3
NI-880S-2L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	250	R3
NI-880XS-2L	56	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-880XGS-2L	56	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-880XS-2L4S	56	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-880XS-4L4S	56	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
NI-1230H-4S	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	150	R6
	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	50	R5
NI-1230S-4S	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	150	R6
	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	50	R5
NI-1230S-4L2L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	150	R6
NI-1230GS-4L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	150	R6
NI-1230H-4S4S	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	150	R6
NI-1230S-4S4S	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	150	R6
OM-780-2L	32	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
OM-780G-2L	32	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
OM-780-2L2L	32	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
OM-780-4L	32	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
OM-780G-4L	32	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3

(continued)

UPDATED SEPTEMBER 2016

RF Power Tape and Reel Specifications (continued)

RF EMBOSSED TAPE AND REEL ORDERING INFORMATION (continued)

Package	Tape Width (mm)	Pitch mm (inch)	Reel Size mm (inch)	Devices Per Reel and Minimum Order Quantity	Device Suffix
OM-780-4L2L	32	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
OM-880X-2L2L	56	28.0 ± 0.1 (1.10 ± .004)	330 (13)	250	R3
OM-1230-4L2L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	150	R6
OM-1230-4L2S	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	150	R6
OM-1230-4L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	150	R6
OM-1230G-4L	56	32.0 ± 0.1 (1.26 ± .004)	330 (13)	150	R6
OM-270-2	24	16.0 ± 0.1 (.631 ± .004)	178 (7)	50	R5
PLD-1.5	16	8.0 ± 0.1 (.315 ± .004)	330 (7)	1,000	T1
	16	8.0 ± 0.1 (.315 ± .004)	330 (7)	100	R4
PLD-1.5W	16	8.0 ± 0.1 (.315 ± .004)	330 (7)	1,000	T1
	16	8.0 ± 0.1 (.315 ± .004)	330 (7)	100	R4
PQFN 5 × 5	16	8.0 ± 0.1 (.315 ± .004)	330 (13)	1,000	T1
PQFN 8 × 8	16	12.0 ± 0.1 (.472 ± .004)	330 (13)	1,000	T1
QFN 3 × 3	12	8.0 ± 0.1 (.315 ± .004)	178 (7)	1,000	T1
QFN 4 × 4	12	8.0 ± 0.1 (.315 ± .004)	330 (13)	1,000	T1
QFN 6 × 6	16	12.0 ± 0.1 (.472 ± .004)	178 (7)	1,000	R1
SOT-89 ⁽¹⁾	12	8.0 ± 0.1 (.315 ± .004)	178 (7)	1,000	T1
SOT-89 ⁽²⁾	12	8.0 ± 0.1 (.315 ± .004)	180 (7)	1,000	T1
SOT-363	8	4.0 ± 0.1 (.157 ± .004)	178 (7)	3,000	T1
TO-270-2	24	16.0 ± 0.1 (.631 ± .004)	330 (13)	500	R1
TO-270G-2	24	12.0 ± 0.1 (.471 ± .004)	330 (13)	500	R1
TO-270WB-4	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WBL-4	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WBG-4	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WB-6A	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WB-14	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WBG-14	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WB-15	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WBG-15	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WB-16	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WBG-16	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WBL-16	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WBLG-16	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WB-17	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-270WBG-17	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1
TO-272-2	44	20.0 ± 0.1 (.631 ± .004)	330 (13)	500	R1
TO-272WB-4	44	20.0 ± 0.1 (.788 ± .004)	330 (13)	500	R1
TO-272WB-14	44	20.0 ± 0.1 (.788 ± .004)	330 (13)	500	R1
TO-272WB-16	44	20.0 ± 0.1 (.788 ± .004)	330 (13)	500	R1
TO-272WBLG-16	44	24.0 ± 0.1 (.945 ± .004)	330 (13)	500	R1

1. 98ASA10586D

2. 98ASA00241D

How to Reach Us:

Home Page:
nxp.com

Web Support:
nxp.com/support

Information in this document is provided solely to enable system and software implementers to use NXP products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits based on the information in this document. NXP reserves the right to make changes without further notice to any products herein.

NXP makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does NXP assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in NXP data sheets and/or specifications can and do vary in different applications, and actual performance may vary over time. All operating parameters, including "typicals," must be validated for each customer application by customer's technical experts. NXP does not convey any license under its patent rights nor the rights of others. NXP sells products pursuant to standard terms and conditions of sale, which can be found at the following address: nxp.com/SalesTermsandConditions.

NXP, the NXP logo, Freescale, the Freescale logo, and Airfast are trademarks of NXP B.V. All other product or service names are the property of their respective owners.
© 2016 NXP B.V.

