TOSHIBA

©-STUDIO *908

- > Departmental/Light Production
- > Advanced Paper Handling
- > Proven Reliability
- > High Volume
- > Solutions Ready





C	Para Mandala Irahinda I OD 000 Charat DODE 0 100 Charat Dana and Caracatha 1 TR Hand Distribution DOI 00
System Overview	Base Models Include LCD, 250-Sheet DSPF, 3,100-Sheet Paper Capacity, 1 TB Hard Disk Drive, PCL6®, Adobe® PostScript® 3TM Network Printing, Color Network Scanning, Pull Out Keyboard, Application
	Communication Module And External Accounting Module
Туре	Console, Monochrome Multi-Function Digital Document System
Display	10.1" (Diagonally Measured) Color Dot Matrix High-Resolution Touch Panel Tilting Display. 1024 x 600 (WSVGA
Functions	Copy, Print, Network Print, Network Scan And Document Filing ¹
Copy System	Dry Electrostatic Transfer/Dual Component Developer/Magnetic Brush Development/OPC/White LED
оору оуоко	Exposure/Heat Roller Fusing
Originals	Sheets and Bound Documents
Max. Original Size	11" x 17"
Copy Size	Min. 5.5" x 8.5", Max. 12" x 18"
Copy Speed	90 PPM (8.5" x 11")
Multiple Copy	Max. 9,999 Copies
First Copy Time	Platen Glass: 4.0 Seconds, DSPF: 6.3 Seconds
Warm Up Time	210 Seconds ²
Magnification	25% to 400% in 1% Increments (with Document Feeder 25%-200%)
Original Feed	250-Sheet DSPF
Scan Speed	Up to 240 IPM² (Monochrome or Color)
Original Sizes	5.5" x 8.5", 8.5" x 11", 8.5" x 11" R, 8.5" x 14", 11" x 17"
Paper Capacity	Standard: 3,100 Sheets/Maximum: 8,500 Sheets
Paper Feed	Standard: Tandem Tray 1 - 1,200 Sheets (Letter Size), Tandem System. Tray 2 - 800 Sheets (Letter Size)
	Trays 3/4 - 500 Sheets ea. (Letter/Legal/Ledger/Statement/12" x 18"). Multi-Bypass Tray (for Machine)
	100 Sheets (Letter/Legal/ Ledger/Statement/ 12" x 18"), Optional: Multi-Bypass (for LCT) - 500 Sheets
	(Letter/Legal/Ledger/Statement/12" x 18"), LCT (2-Drawer) - 2,500-Sheets Each Drawer (Letter/Legal
Danar Waighte & Types	Ledger/12" x 18"), Letter LCC - 3,500 Sheets (Letter), Ledger LCC - 3,000 Sheets. Tandem Trays - 16-28 lb Bond, Trays 3/4 - 16 lb Bond to 100 lb Bristol, Multi-Bypass Tray (fo
raper weights & Types	
	Machine) -15 lb Bond to 110 lb Cover, Multi-Bypass Tray (for LCT) - 15 lb Bond to 100 lb Bristol, LCT (2-Drawer) - 15 lb Bond to 110 lb Cover, Letter LCC - 16 lb Bond to 110 lb Cover, Ledger LCC - 16 lb
	Bond to 110 lb Cover ² . Supported Paper Types Include Thin, Plain, Recycled, Color, Letter Head, Pre-
	Printed and Pre-Punched and Glossy.
Duplexing	Standard Automatic Duplex Copying and Printing
CPU	Up to 1.91 GHz Multi-Processor Controller
Interface	RJ-45 Ethernet 10/100/1000 Base-T, USB 2.0 (2 Host Ports, Front and Rear), USB 2.0 (1 Device)
IIIteriaee	Wireless 802.11 a/b/g/n
Memory	Standard 6 GB
Hard Disk Drive	1TB
Copy Resolution	Scan: 1200 x 1200 dpi / 600 x 600 dpi
Copy Modes	Monochrome/Grayscale
Exposure Ctrl. Modes	Text, Text/Printed-Photo, Printed-Photo, Text Photo, Photo, Map, Pale-Color. Settings: Auto or 9 Step Manual
Halftone	256 Gradations/2 Levels (Monochrome)
Copy Features	Scan-Once Print-Many, Electronic Sorting, Offset-Stacking, Auto Paper Selection (APS), Auto Magnification
	Selection (AMS), Auto Tray Switching (ATS), Black-White Reversal, Blank Page Skip, Book Copy, Book
	Divide, Card Shot, Center Erase, Centering, Cover Pages, Dual Page Copy, Edge Erase, Image Edit, Image
	Preview, Insert Pages, Job Build, Job Programs, Margin Shift, Mirror Image, Mixed Size Original, Multi-Page
	Enlargement, Original Count, Pamphlet Style, Proof Copy, Repeat Layout, Reserve Copy, Rotated Copy
	Stamp, Stamp Custom Image, Suppress Background, Tab Copy, Tab-Paper Insertion, Tandem Copy, Tone
	Save Mode, Transparency Inserts, Watermark, 2-In-1 / 4-In-1 / 8-In-1 Multi Shot
Account Control	Up to 1,000 Users. Supports User Authentication Via Local, LDAP, and Active Directory® for Copy, Print
	Scan and Document Management
Cloud Supported Svcs.	
Network Protocols	TCP/IP (IPv4, IPv6, IPsec), HTTP/HTTPS, IPP/IPP-SSL, FTP/FTPS, SNMPv3, SMTP/SMTP-SSL, POP3
	POP3-SSL, LDAP/LDAP-SSL, 802.1x for Windows and Unix.
Network and	Includes IP/MAC Address Filtering, Protocol Filtering, Port Control, TLS Encryption, Kerberos, Active
Data Security	Directory Integration, Data Encryption, End-Of-Lease, Data Overwrite (up to 10x), DoD 5220.22-M
Firmware Management	Flash ROM with Local (USB), Network Update Capability and Firmware Update 1 to N with SRDM
	(Sharp Remote Device Management)
Device Setup	Web-Based Management with User/Administrator Level Login, Cloning (1 to N) with SRDM and Remote
	Front Panel Access
Service/Functions	Remote Front Panel, Remote Access to Service Logs and Click Counts
Accessibility Features	Free Stop Tilting Front Panel, Adjustment of Key Touch Sound and Speed, Concave Key, Document Feede
	Free Stop, Job Programs, Remote Front Panel, Universal Grip for Paper Trays, and Disable Screen Timeou
Environmental	International ENERGY STAR Program Ver. 2.0, Law on Promoting Green Purchasing. European
Standards	RoHS (Restriction of Hazardous Substances)
	AC 208-240 VAC, 60 HZ, 20 A Receptacle
Power Source	
Power Consumption	Maximum: 3.55 kW or Less

Network Printing System

PDL	PCL6 Compatible, True Adobe PostScript 3
Resolution	1200 x 1200 dpi
Print Speed	90 Pages Per Minute (8.5" x 11")
Print Drivers	Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows 10, Windows Server® 2008, Windows
	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows
	PPD, MAC OSX® (Including 10.6 to 10.12), All MAC PPD, Linux® PPD
Mobile Printing	AirPrint, Android Printing Framework (Sharp Print Service Plugin), Sharpdesk Mobile
Print Features	Auto Configuration, Serverless Print Release, Bar Code Font Printing, Carbon Copy Print, Chapter
	Inserts, Color Adjustment Settings, Color Mode, Confidential Print, Continuous Printing, Custom Image
	Registration, Different Cover Page/Last Page/ Other Page, Document Control, Document Filing, Duplex
	Printing, Electronic Sorting, Folding, Form Overlay, Hidden Pattern Print, Image Rotation, Image Stamp,
	Image Type, Job Bypass Print, Job Retention, Layout Print, Margin Shift, Multiple Pamphlet, Network
	Tandem Print, N-Up Printing, Offset Stacking, Page Interleave, Pamphlet Style, Poster Print, Proof Print,
	Print and Send, Punching, Stapling, Tab Paper Print, Tab Printing, Toner Save Mode, Transparency
	Inserts, Tray Status, User Authentication, Watermarks, Zoom Print
Direct Printing	File Types: TIFF, JPEG, PCL, PRN, TXT, PDF, Encrypted PDF, Compressed PDF/A1, PostScript, DOCX,
_	VLSV DDTV and DNG Mathods: ETD Wah Page Email Natural Folder and LISP

Network Printing	System	(continued)
Network Printing	System	n (continuea)

Resident Fonts	80 Outline Fonts (PCL), 139 Fonts (PS)
Interface	RJ-45 Ethernet 10/100/1000 Base-T, USB 2.0
Operating Systems	Windows Vista, Windows 7, Windows 8, Windows 8.1, Windows 10, Windows Server® 2008, Windows
and Environments	Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Mac OS X10.4-10.11, UNIX®, Linux,
	Citrix® (XenApp 5.0-7.6), Windows Remote Desktop Services, SAP Device Types¹
Drinting Dretecolo	LDD IDD IDDS DAD Dow TCD (Port 0100) ETD DOD2 LTTD Novell Beauty/Porinter LDD and LDD for Llaiv

Network Scanning System

Scan Modes	Standard: Color, Monochrome, Grayscale
Max. Original Size	11" x 17"
Optical Resolution	600 dpi
Output Modes	600 dpi, 400 dpi, 300 dpi, 200 dpi, 100 dpi
Image Formats	Monochrome: TIFF, PDF, Encrypted PDF, Searchable PDF, DOCX, XLSX, PPTX, TXT and RTF. Color,
	Grayscale: Color TIFF, JPEG, PDF, Encrypted PDF1, PDF/A1, Compressed PDF1, Searchable PDF
	DOCX, XLSX, PPTX, TXT and RTF.
Image	Monochrome Scanning: Uncompressed, G3 (MH), G4 (MR/MMR)
Compression	Color/Grayscale: JPEG (High, Middle, Low)
Scan Destinations	Email, Desktop, FTP, Folder (SMB), USB
One-touch Destinations	Up to 2,000 (Combined Scan Destinations)
Group Destinations	Up to 500
Programs	48 (Combined)
Max. Jobs	Up to 100
Enhanced Email Integ.	. Standard Gmail Connector, Standard Exchange Connector (On-Premise)
Sharp OSA Platform	Application Communication Module (MX-AMX2) and External Accounting Module (MX-AMX3) Standard

4K 100-Sheet Stapler/Finisher (MX-FN21: option)

Туре	4,000-Sheet Console Stapler Finisher (100-Sheet Stapling)	
Output Trays	Upper Tray: Moving Offset Tray (Up to 1,500 Letter Sheets) Middle Tray: 250 Sheets (Letter, Non-	
	Stapled), Lower Tray: Moving Offset Tray (Up to 2,500 Letter Sheets)	
Stapling Capacity	Up to 100 Sheets (Letter/Statement)	
Stapling Media	Plain Paper, Letter/Legal/Ledger or Mixed	
Stapling Positions	1 Front, 1 Rear, or 2 Point Stitching	
Hole Punching	Optional Three-Hole Punch Unit MX-PN13B	
Power Source	20 VAC, 60 HZ, 15 Amps	
Power Consumption	200w/350w with MX-FD10	
Weight	Approx. 134.5 lb	
Dimensions	Approx. 35.25" (W) x 30" (D) x 41" (H) (with Tray Extended)	

4K 100-Sheet Stapler/Saddle-Stitch Finisher (MX-FN22: option)

Туре	4,000-Sheet Console Stapler Finisher (100-Sheet Stapling)	
Output Trays	Upper Tray: Moving Offset Tray (Up to 1,500 Letter Sheets) Middle Tray: 250 Sheets (Letter, Non-	
	Stapled), Lower Tray: Moving Offset Tray (Up to 2,500 Letter Sheets)	
Stapling Capacity	Up to 100 Sheets (Letter/Statement)	
Stapling Media	Plain Paper, Letter/Legal/Ledger or Mixed	
Stapling Positions	1 Front, 1 Rear, or 2 Point Stitching	
Saddle Stitch	Center Stitch/Center Fold (2 Staples) Letter/Legal/Ledger Paper, Saddle-Stitch Up to 5 Sets (16-20	
	Sheets)/10 Sets (11-15 Sheets)/15 Sets (6-10 Sheets)/Max. Sets: 25 (1-5 Sheets)	
Hole Punching	Optional Three-Hole Punch Unit MX-PN13B	
Power Source	120 VAC, 60 HZ, 15 Amps	
Power Consumption	200W/350W with MX-FD10	
Weight	Approx. 134.5 lb	
Dimensions	Approx. 35.25" (W) x 30" (D) x 41" (H) (with Tray Extended)	

Optional Equipment

MX-CF11	Inserter
MX-FD10	Multi-Folding Unit
MX-LC12	3,500-Sheet Large Capacity Cassette (Letter)
MX-LC3N	3,000-Sheet Large Capacity, Ledger (e-STUDIO908 Only)
MX-LC13N	5,000-sheet Large Capacity 2-Drawer Air Feed Tray (Ledger)
MX-MF11	500-Sheet Multi-Bypass Tray (for MX-LC13)
MX-FN21	4K Stacking 100-Sheet Staple Finisher
MX-FN22	4K Stacking 100-Sheet Staple/Saddle Stitch Finisher
MX-CF11	2-Tray Inserter Unit
MX-FD10	Multi-Folding Unit
MX-RB16	Large Capacity Tray Mounting Kit
MX-RB18	Curl Correction Unit
MX-RB13	Relay Unit
MX-TM10	Trimmer Unit
MX-PN13B	3-Hole Punch Unit (for MX-FN21/FN22)
MX-SL10N	Status Indicator
MX-FX15	Fax Expansion Kit (e-STUDIO908 Only)

Supplies

T1207U	Toner Cartridge (Yield 120K @ 5%)
6LS00016000	Developer D1207
Staple2400	Staple Cartridge (for MX-FN22 - Saddle)
Stanle2600	Staple Cartridge (for MX-FN21/FN22)

¹Some features require optional equipment. See your local dealer.
²Specification may vary depending on product configuration, machine settings and operating conditions.

Designs and specifications are subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage of a Letter-sized page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

Midwest

West Coast

South

25530 Commercentre Drive, Lake Forest, CA 92630

Tel: 949-462-6000 **East Coast** 959 Route 46 East, 5th Floor, Parsippany, NJ 07054

Tel: 973-316-2700

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631

Tel: 773-380-6000

2037 Bakers Mill Rd., Dacula, GA 30019

Tel: 678-546-9385

25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000

Web Site www.business.toshiba.com

© 2021 Toshiba America Business Solutions, Inc. Electronic Imaging Division Inv. Code 22394 908 Spec Sheet 03/21