

# SAFETY DATA SHEET

## Goof Off Adhesive Gunk Remover

Page: 1 of 7

Revision: 09/18/2019  
Supersedes Revision: 08/13/2019

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Goof Off Adhesive Gunk Remover  
**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113  
**Phone Number:** (901)775-0100  
**Web site address:** www.wmbarr.com  
**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346  
**Information:** W.M. Barr Customer Service (800)398-3892  
**Product Code:** FG790, FG795, FG796

### 2. HAZARDS IDENTIFICATION

**Skin Corrosion/Irritation, Category 2**  
**Serious Eye Damage/Eye Irritation, Category 2**  
**Skin Sensitization, Category 1**



**GHS Signal Word:** **Warning**

**GHS Hazard Phrases:** Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.

**GHS Precautionary Phrases:** Avoid breathing gas/mist/vapors/spray.  
Wash hands thoroughly after handling.  
Contaminated work clothing should not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.

**GHS Response Phrases:** IF ON SKIN: Wash with plenty of soap and water.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Specific treatment see label.  
If skin irritation occurs, get medical advice/attention.  
If skin irritation or rash occurs, seek medical advice/attention.  
If eye irritation persists, get medical advice/attention.  
Take off contaminated clothing and wash before re-use.  
Wash contaminated clothing before reuse.

**GHS Storage and Disposal Phrases:** Dispose of contents/container according to local, state and federal regulations.

**Potential Health Effects (Acute and Chronic):** See above.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
112-80-1	Oleic acid {9-Octadecenoic acid (Z)-}	7.0 -13.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	7.0 -13.0 %
5989-27-5	d-Limonene	1.0 -5.0 %
100-51-6	Benzenemethanol {Benzyl alcohol}	3.0 -7.0 %

# SAFETY DATA SHEET

## Goof Off Adhesive Gunk Remover

Page: 2 of 7

Revision: 09/18/2019

Supersedes Revision: 08/13/2019

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

### 4. FIRST AID MEASURES

#### Emergency and First Aid Procedures:

##### Skin:

Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

##### Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

##### Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

##### Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down.

### 5. FIRE FIGHTING MEASURES

**Flash Pt:** None Method Used: Setaflash Closed Cup (Rapid Setaflash)

**Explosive Limits:** LEL: N.D. UEL: N.D.

**Autoignition Pt:** N.D.

**Suitable Extinguishing Media:** Use carbon dioxide, dry powder, water spray, or foam.

**Unsuitable Extinguishing Media:** Solid streams of water may be ineffective and spread material.

**Fire Fighting Instructions:** Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

Product does not sustain combustion.

**Flammable Properties and Hazards:** Flashpoint: No flash to boiling. This material does not exhibit a flashpoint per the Setaflash Closed Cup test method.

**Hazardous Combustion Products:** Oxides of carbon.

# SAFETY DATA SHEET

## Goof Off Adhesive Gunk Remover

### 6. ACCIDENTAL RELEASE MEASURES

#### Steps To Be Taken In Case Material Is Released Or Spilled:

Vapors may cause flash fire or ignite explosively.

Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc.

Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills: Dike far ahead of spill for later disposal.

Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

### 7. HANDLING AND STORAGE

#### Precautions To Be Taken in Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

#### Precautions To Be Taken in Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	ACGIH TLV	TLV: 20 ppm	
		OSHA PELs	PEL: 50 ppm	

# SAFETY DATA SHEET

## Goof Off Adhesive Gunk Remover

Page: 4 of 7

Revision: 09/18/2019

Supersedes Revision: 08/13/2019

<b>Respiratory Equipment (Specify Type):</b>	<p>For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.</p> <p>For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.</p> <p>A dust mask does not provide protection against vapors.</p>
<b>Eye Protection:</b>	<p>Safety glasses should be worn during normal handling of this material.</p> <p>Where contact with the eyes or face is likely, a faceshield or chemical splash goggles should be worn to prevent eye contact.</p>
<b>Protective Gloves:</b>	<p>Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.</p>
<b>Other Protective Clothing:</b>	<p>Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.</p>
<b>Engineering Controls (Ventilation etc.):</b>	<p>Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.</p> <p>Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.</p>
<b>Work/Hygienic/Maintenance Practices:</b>	<p>Wash hands thoroughly after use and before eating, drinking, smoking, or using the restroom.</p> <p>Do not eat, drink, or smoke in the work area.</p> <p>Discard any clothing or other protective equipment that cannot be decontaminated.</p> <p>Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.</p>

# SAFETY DATA SHEET

## Goof Off Adhesive Gunk Remover

Page: 5 of 7

Revision: 09/18/2019  
Supersedes Revision: 08/13/2019

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical States:</b>	[ ] Gas [ X ] Liquid [ ] Solid
<b>Appearance and Odor:</b>	Clear orange gel. Odor threshold not determined.
<b>pH:</b>	7 - 7.4
<b>Melting Point:</b>	N.D.
<b>Boiling Point:</b>	> 37.70 C
<b>Flash Pt:</b>	None Method Used: Setaflash Closed Cup (Rapid Setaflash)
<b>Evaporation Rate:</b>	N.D.
<b>Flammability (solid, gas):</b>	No data available.
<b>Explosive Limits:</b>	LEL: N.D. UEL: N.D.
<b>Vapor Pressure (vs. Air or mm Hg):</b>	N.D.
<b>Vapor Density (vs. Air = 1):</b>	N.D.
<b>Specific Gravity (Water = 1):</b>	0.9663 - 0.9784
<b>Density:</b>	8.04 - 8.14 LB/GL
<b>Solubility in Water:</b>	soluble
<b>Saturated Vapor Concentration:</b>	N.D.
<b>Octanol/Water Partition Coefficient:</b>	N.D.
<b>Percent Volatile:</b>	89.82 % by weight.
<b>VOC / Volume:</b>	191.0600 G/L
<b>Autoignition Pt:</b>	N.D.
<b>Decomposition Temperature:</b>	N.D.
<b>Viscosity:</b>	800 - 1500 CPS
<b>Additional Physical Information</b>	ND = Not determined NE = Not established

### 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	None known
<b>Stability:</b>	Unstable [ ] Stable [ X ]
<b>Conditions To Avoid - Instability:</b>	None known
<b>Incompatibility - Materials To Avoid:</b>	Oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b>	Can include aldehydes, ketones, organic acids, oxides of citrus terpenes
<b>Possibility of Hazardous Reactions:</b>	Will occur [ ] Will not occur [ X ]
<b>Conditions To Avoid - Hazardous Reactions:</b>	None known

# SAFETY DATA SHEET

## Goof Off Adhesive Gunk Remover

### 11. TOXICOLOGICAL INFORMATION

**Toxicological Information:** This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.  
CAS# 111-76-2:  
Acute toxicity, LC50, Inhalation, Rat, 450.0 PPM, 4 H.  
Result:  
Behavioral: Ataxia.  
Nutritional and Gross Metabolic: Weight loss or decreased weight gain.  
- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983

Acute toxicity, LD50, Skin, Species: Rabbit, 220.0 MG/KG.  
Result:  
Effects on Embryo or Fetus: Extra embryonic structures (e.g., placenta, umbilical cord).  
Effects on Embryo or Fetus: Other effects to embryo.  
Specific Developmental Abnormalities: Musculoskeletal system.  
- Dow Chemical Company Reports., Dow Chemical USA, Health and Environment Research, Toxicology Research Lab, Midland, MI 48640, Vol/p/yr: MSD-46,

Acute toxicity, LD50, Oral, Rat, 250.0 mg/kg.  
Result:  
Lungs, Thorax, or Respiration: Changes in pulmonary vascular resistance.

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.  
Result:  
Effects on Newborn: Apgar score (human only).  
Effects on Newborn: Other neonatal measures or effects.  
Effects on Newborn: Drug dependency.  
- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

**Carcinogenicity/Other Information:**

IARC 3: Not Classifiable as to Carcinogenicity in Humans.  
ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
112-80-1	Oleic acid {9-Octadecenoic acid (Z)-}	n.a.	n.a.	n.a.	n.a.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	n.a.	3	A3	n.a.
5989-27-5	d-Limonene	n.a.	3	n.a.	n.a.
100-51-6	Benzenemethanol {Benzyl alcohol}	n.a.	n.a.	n.a.	n.a.

### 12. ECOLOGICAL INFORMATION

**General Ecological Information:** This product has not been tested as a whole.

# SAFETY DATA SHEET

## Goof Off Adhesive Gunk Remover

Revision: 09/18/2019  
Supersedes Revision: 08/13/2019

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose of in accordance with local, state, and federal laws.

Do not place material in general trash.

Do not allow material to enter bodies of water or sewers.

### 14. TRANSPORT INFORMATION

#### LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Not Regulated.  
**DOT Hazard Class:**  
**UN/NA Number:**

### 15. REGULATORY INFORMATION

#### EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
112-80-1	Oleic acid {9-Octadecenoic acid (Z)-}	No	No	No
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	No	No	Yes-Cat. N230
5989-27-5	d-Limonene	No	No	No
100-51-6	Benzenemethanol {Benzyl alcohol}	No	No	No

#### CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

112-80-1	Oleic acid {9-Octadecenoic acid (Z)-}	TSCA: Inventory
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	CAA HAP,ODC: Yes - Cat. TSCA: Inventory
5989-27-5	d-Limonene	TSCA: Inventory
100-51-6	Benzenemethanol {Benzyl alcohol}	TSCA: Inventory

#### Additional Regulatory Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

### 16. OTHER INFORMATION

**Revision Date:** 09/18/2019  
**Preparer Name:** EHS Department

**Additional Information About This Product:** No data available.

#### Company Policy or Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.