



**ANTI CORROSION FORMULA**


## ACF-50 Technical Data

ACF-50, Anti Corrosion Formula, is a state of the art anti-corrosion lubricant compound, specifically designed for the Aero Space Industry. ACF-50's unique chemistry offers excellent penetration, coupled with an unmatched 24 months of "active" corrosion protection.

Designed specifically to perform as both a Corrosion Inhibiting Compound (CIC) and a Corrosion Prevention Compound (CPC). ACF-50's blend of non-flammable, non-toxic, polar bonding inhibitors and moisture-displacing additives penetrate deep into corrosion cells to actively remove electrolytes. No longer in contact with the metal surface, these electrolytes evaporate. ACF-50's resulting dielectric fluid film acts as an "off-switch" for the corrosion process.



- ◊ Complete anti-corrosion solutions for airframe, avionics and ground support equipment.
- ◊ Significantly reduces corrosion events in both Structure & Avionics.
- ◊ Ultra Thin Film promotes weight reduction, improving payload capacity.
- ◊ ACF-50 is blended utilizing superior quality control ISO 9002 standards and has an excellent customer satisfaction record with a 0.0% return rate.
- ◊ Removal not required for re-application, creates no HAZMAT residue.
- ◊ ACF-50 is Non-Toxic according to EPA / OSHA standards.



### ACF-50 Applications

**FUSELAGE • STABILIZERS • AVIONICS • MICRO SWITCHES**  
**CANNON PLUGS • ANTENNA MOUNTS**

Single Engine & Light Twins  
 Spray into: wing sections, hinges, teleflex cables, air vent cables, trim cables, throttle cables, battery boxes, engine compartments

Rotorwing Aircraft  
 Spray into: tail boom section, engine gear, air vent cables, rotor

Cargo & Regional Airlines  
 Spray into: wing sections, landing gear compartments, cargo door, brackets, garbage chutes, galleys, lavatory areas, belly skin sections, main spar sections, seat tracks.

Float Equipped & Amphibious  
 Spray into: floats, wing sections, bilge area, exterior of motors, connectors.



Turbo Props / Business Jets  
 Spray into: trim drum actuators, landing gear and compartments, wheel hubs, thrust reverse mechanisms. Wipe





# Prevents and Deactivates Existing Corrosion

## ACF-50 Corrosion Abatement Procedure 2024-T3 Aluminum Fogged in a Sulfurous Acid/Salt for 192 hours

 <p>Panels pretreated with ACF-50 showed an average weight loss of only <b>1.9 mg</b>.</p> <p><b>Conclusion:</b> ACF-50 prevents the formation of new corrosion cells.</p>	 <p>Untreated panels showed and average weight loss of <b>150.1 mg</b>.</p> <p><b>Conclusion:</b> Untreated panels corrode rapidly.</p>	 <p>Untreated panels exposed for 96 hours, then treated with ACF-50 and exposed for an additional 96 hours showed a loss of only</p> <p><b>Conclusion:</b> ACF-50 stops the corrosion process on contact.</p>
--	--	--

## ACF-50 Performance Qualified

### MIL-PRF 81309

CHARACTERISTICS / REQUIREMENTS	RESULTS
- Minimum flash point / 60°C (140°F)	Conforms / 175°F
- Synthetic Sea Water Displacement / No visible corrosion	Conforms
- Removability / Not more than 3 cycles to remove	Conforms
- Abrasives / Not present	Conforms
- Maximum Film Thickness / Type II: 0.0005 inches	Conforms
- Sprayability / Sprayable	Conforms
- Corrosivity / No visible corrosion	Conforms
- Staining / No visible evidence of staining	Conforms
- Minimum Dielectric Breakdown / 25,000 volts	Conforms / 38,000 volts
- Mixability of Compounds / No evidence of separation	Conforms
- Lubricity of Compounds / Less than 0.20	Conforms
- Effect on Electric Components / No change	Conforms
- Effect on Electric Connectors / No increase in resistance	Conforms

### Commercial Aircraft Test Approvals

TEST IDENTITY	TEST METHOD	RESULTS
Airbus Industrie TNA 007.10138	- Corrosion Resistance To: Turco Toilet Fluid, Orange Juice, Coke, Coffee, De-Icing Fluid 3:4-1;2:1:4, %5 NaOH, %5 HCl, 5% HNO <sub>3</sub> , %10 CH <sub>3</sub> COOH, %45 Ethanol	
BMS 3-23E Table II	- Corrosion Inhibiting Characteristics MIL-C-1617D / ASTM G34	Pass
BMS 3-23E Table II	- Water Displacement Ability / MIL-C-1617D	Pass
BMS 3-23E Table II	- Functional Penetration Test	Pass
Douglas Aircraft CSD #1	- Immersion Corrosion Test / ASTM F 483	Conforms
Douglas Aircraft CSD #1	- Sandwich Corrosion Test	Conforms
Douglas Aircraft CSD #1	- Painted Surfaces / ASTM F 502	Conforms
Douglas Aircraft DMS 2150	- Salt Fog Exposure/ ASTM B 117	Conforms
Douglas Aircraft DMS 2150	- Viscosity / ASTM D 445	Conforms
MISC.	- Humidity Resistance / AMS 3066B	Conforms
MISC.	- Polyimide Insulated Wire / MIL-C-87937B	Conforms

## ACF-50 OEM Engine & Airframe Approvals

**BOMBARDIER**  
DASH 8 100-300  
Corrosion Preventative Compound  
Electrical System - SYD-8-20-001  
Structural AMM-51-31-00 REF 13-16  
BAMS 565-006 TYPE III



**ATR REGIONAL TRANSPORT • ATR 42-72**  
Corrosion Protection  
Ref. JIC-122351-PRO-10 000



**BAE SYSTEMS • BAE 146-100**  
Corrosion Preventative Compound  
Material Spec 89/042



**EMBRAER / EM RJ 130-145**  
Periodic Lubrication of Landing Gear  
SNL 145-32-0035 Nov/2008



**HAWKER-BEECHCRAFT / BEECH 1900C-D**  
Corrosion Control  
Manual 114-590021-197



AEROCOMMANDER • AIR TRACTOR • BOEING HELICOPTER • BELL HELICOPTER TEXTRON • BRITISH AEROSPACE • CANADAIR • CESSNA • CIRRUS • CONCORDE BATTERY • ENSTROM ERICKSON • EXTRA AIRCRAFT • GE ENGINES • GULFSTREAM AEROSPACE • HILLER AIRCRAFT • LAKE AIRCRAFT • LOCHEED MARTIN • MCDONNELL DOUGLAS CORP • MD HELICOPTER MOONEY AIRCRAFT • PILATUS AIRCRAFT • PIPER • PRATT & WHITNEY • ROBINSON • ROLLS ROYCE • SAFRAN ENGINES • SIKORSKY • SCHWEIZER • VAN AIRCRAFT • WIPAIRE

## ACF-50 Health & Safety



Scan QR code for Safety Data Sheet  
Operators should use standard safety precautions when using ACF-50.  
Refer to Safety Data Sheet for complete health and safety information.



LEAR CHEMICAL RESEARCH CORPORATION

AVIATION



www **cjaerospace.com.au**

PH **+612 9540 4587**

SYDNEY BRANCH: Unit 6, 3 Box Road Taren Point NSW 2229 Australia

CAIRNS BRANCH: 2/29 Johnston Street Stratford QLD 4870 Australia