

Kinetis MCUs based on ARM® Cortex™-M4 and ARM Cortex-M0+ Cores: Status, New Products and Roadmaps AMF-IND-T0493

Paulo Knirsch

Global Kinetis Product Marketing Microcontrollers Business Unit



October 2013

Treatment, the President logic, Addition, Co. S. Costelland, Costelland, Costelland, Costelland, Costelland, Efficient Collegation, Supplication, State Proceeds that Safe-National Ingo, States in Costelland, Co

NP

rreescale - A Global Leader in

Microcontrollers and Digital Networking Processors



>5,500 Engineers

>6,000 Patent Families

Five Core Product Groups

Four Primary
Markets

Microcontrollers

Automotive



Automotive MCU

Digital Networking

Analog & Sensors

RF

Networking










NP

Microcontroller Markets



- 32-bit architectures over 40% of total MCU
- 8-bit down 23% in 2 yrs; \$5.3B '10 to \$4.1B '12
- 32-bit has become the key market growth driver with ARM architecture leading

Market Trends ...

- Internet of Things (IoT)
 - Security & connectivity
- Software as building blocks to get to market faster
- Low power
- Human Machine Interface (HMI)
- Miniaturization: smaller form factor





INTERNET OF THINGS

Different Services,
Different Technologies
Different Meanings for Everyone

And the Word "SMART" Is Everywhere!

Smart Lighting Smart Grid Pedestrian Navigation Smart Remote Appliance Avoidance Cars Smart MANY M2M Homes OTHER BLDG Smart Automation Auto SERVICES Tags Safety Smart **Parking** Air Quality Supply Chain Control Automation Smart Smart Health Energy

Technology Innovations

Miniaturization & advances in packaging technologies

Advances in flash

New class of powerful but low-cost & low-power MCUs

Cloud-based services

Applications

Our Vision

Be the leader in the broad-based and connected MCU market supporting the Internet of Things (IoT)



Temperature etc.

Embedded Processing

MCU MPU Hybrid MCU/MPU Network Processor

Connectivity

NFC GPS 6LoPAN BT/BTLE Sub-Gig Wi-Fi* ZigBee* RFID Cellular


Software

Technology



ternet of Things Building Blocks

Freescale has the industry's broadest range of solutions built on ARM® technology for industrial, consumer, automotive and networking applications.



Industry's most scalable ultra-low-power, mixed-signal MCU solutions based on the ARM®

Cortex™-M and Cortex™-M0+ architectures.

Real-time, highly integrated solutions with best-in-class 2D graphics to enable your system to control, interface, connect, secure and scale.

Industry's most versatile solutions for multimedia and display applications, with multicore scalability and market-leading power, performance & integration.

Industry's first softwareaware, core-agnostic networking system architecture for the smarter, more capable networks of tomorrow – end to end.

Find your ideal solution at the price, performance and power level you desire, and leverage the extensive software and tool bundles available to speed and ease your design process.





Strategic R&D Investments



- Industry's most scalable portfolio built on the ARM® architecture
- Industry-first ARM Cortex™-M4 MCU
- Industry-first ARM Cortex-M0+ MCU

ARM



- Unique asymmetrical-multiprocessing architecture
- Real-time, highly integrated solutions with best-in-class 2D graphics

ARM



- Number 1 eReader processor
- First quad-core for mobile devices
- Multimedia with power efficiency

ARM



NP

Illy Refreshed And Expanded Portfolio:

Industry's Widest Portfolio of ARM Based MCU + MPU

Products

i.MX6 Availability NOW! i.MX Applications
Processors

Your Interface to the World.

Performance

Availability NOW!

Kinetis L Series

Ultra-low power/cost ARM Cortex-M0+ MCU families from 48MHz / 8KB with mixed-signal, connectivity and HMI features in low pin-count packages.

Availability NOW!

Kinetis E Series

Robust, 5V ARM
Cortex-M0+ & ARM
Cortex-M4 MCU families
for use in high electrical
noise environments.
Safety features for highreliability applications.



Kinetis K Series

Industry-first ARM
Cortex-M4 MCU families
from 50MHz / 32KB with
low power, FlexMemory,
mixed-signal and broad
connectivity, HMI and
security features.



Rich Apps in Real Time.



General Purpose

Segment Focused

Kinetis W Series

Integrated wireless connectivity ARM Cortex-M4 and M0+ MCU families with classleading sub-1 GHz and 2.4 GHz RF transceivers.

Integration

Leading Performance - Low Power - Scalability - Industrial-grade Reliability & Temp

Freescale Bundled IDE, RTOS & Middleware - Rapid Prototyping Platform - Broad ARM Ecosystem Support





Kinetis Enablement Overview

Kinetis MCU

ARM Cortex-M0+ Core

48MHz, 1.77 CoreMark/MHz, 2-Stage Pipeline, 1-Cycle GPIO, Micro Trace Buffer

ARM Cortex-M4 Core

50-150MHz, 3.40 CoreMark/MHz, HW-divide, MAC, DSPcommands, FPU option

Differentiators

Low-power, Performance, Flex-Memory, Mixed-Signal, Security, HMI Features

Special Functions

Analog Pre-Processing, 24b-Sigma Delta ADC, sub -1GHz & 2.4 GHz Transceiver



Freescale Bundle

Hardware

Freedom board, Tower Platform

Software

CodeWarrior, Processor Expert, Driver Suite, eGUI, PEG, FreeMASTER

RTOS

MQX, MQX Lite




ARM Eco System







Growing Importance of Enablement





rategy to Reach and Expand a Broad Base of **Customers**


Designing with Freescale ...

Solves Real Problems Now...

... And Here's How

Fast Complete

Shorter Customer Development Cycles



Scalable runtime software -cross platform and feature-rich to reuse and redeploy software investment

RTOS & Middleware Freescale MQX™ RTOS & Middleware



Modular hardware design simplifies mix-and-match solutions for plug-and-play development


Tower System for Fast Prototyping

Market-Driven Solutions



Easy Affordable

Increased Project Complexity



Solutions for industry standards future-proof customers' investments







Broad development tools support enabling developers to leverage existing investments immediately

In-House & 3rd-Party **Development Environments**







Addressing customers' pain points early in the design cycle leads to increased customer loyalty and provides "sticky" solutions for the future





Kinetis Development Software



IDE





- CodeWarrior eclipse-based Basic, Standard, Professional and Free Suite with 128k code size limit
- Processor Expert/Driver
 Suite configuration and code generation tool







RTOS

- MQX Free real-time operating system with USB & Ethernet stacks and file system
- MQX Lite Free and lightweight RTOS for small microcontrollers







Middleware

- eGui Free and lightweight graphic frame-work for small microcontrollers
- PEG high performance, high value tool for medium to high end MCUs with a licence fee associated







Libraries & Tools

- FreeMaster Real-time monitor and control of an app
- Math & Motor Control Lib Wide group of algorithms
- Made For iPod supports development and rapid prototyping of electronic accessories for iPod, iPhone and iPad devices





Kinetis Development Hardware







Freedom Platform

- The new Freescale platform for Kinetis L and Kinetis K microcontroller
- Compatible with Arduino shields
- 4 different boards available today







Tower System

- The established and proven platform with highest flexibility and re-usability
- Over 50 add-on boards available.





Device Specific

 Evaluation boards addressing special functions and capabilities of Kinetis devices








Reference Designs

- Home Energy Gateway, 1ph Meter, 3ph Meter, pre-/postpaid Meter, Home Area Network, Home Display, ...
- Available through Freescale RSM



NP

Robust Software & Development Ecosystem Applications





2010: Processor Expert, Chipwerks, Swell

2002: AMC, Lineo

2008: Intoto

netis K/L Series: Packaging **Common Packages**

Kinetis K Series Package

Kinetis L Series Package

*Proposed

*Proposed



32QFN 5 x 5 mm 0.5mm pitch (K10/20) (KL0/1/2)



48QFN 7 x 7 mm 0.5mm pitch (K10/20)(KL1/2)



32LQFP 7 x 7 mm 0.8mm pitch (K10/20)(KL0x)



48LQFP 7 x 7 mm 0.55mm pitch (K10/20) (KL0)



64LQFP 10 x 10 mm 0.5mm pitch (K10/20/30/40/50) (KL1/2/3/4)



80LQFP 12 x 12 mm 0.5mm pitch (K10/20/30/40/50) (KL1/2)



100LQFP 14 x 14 mm 0.5mm pitch (K10/20/30/40/50/60) (KL2/3/4)



64MAPBGA 5 x 5 mm 0.5mm pitch (K10/20) (KL1*/2*/3*/4*)



121MAPBGA 8 x 8 mm 0.65mm pitch (K1/2/30/40/50/60) (KL2/3/4)

Kinetis K Series only



56CSP 2.9x3.3x0.56 mm 0.4mm pitch (K10*/20*)



90CSP 3.9x4.4x0.56 mm 0.4mm pitch (K10*/20*)



121CSP 5.3x5.3x0.56 mm 0.4mm pitch (K10/20/60)



143CSP 6.5x5.6x0.56 mm 0.4mm pitch (K61)

Kinetis L Series only

New



2x2x0.56 mm 0.4mm pitch (KL02)

New



2.3x2.3x0.56 mm 0.4mm pitch (KL05*)



35CSP 2.55x3x0.56 mm 0.4mm pitch (KL15*/25*)



144LQFP 20 x 20 mm 0.5mm pitch (K10/20/30/40/50/60)



144MAPBGA 13 x 13 mm 1.0mm pitch (K10/20/30/40/50/60)



256MAPBGA 17 x 17 mm 1.0mm pitch (K60/70)



16QFN 3x3x1 mm 0.5mm pitch (KL02)



24QFN 4 x4x1 mm 0.5mm pitch (KL0x)



Presents, the Francolo logs, AWIvo, D.S., Code/EST, CadeMartor, CateFire, CodeFires, C. Mare, the Energy Efficient Solutions legs, Xinsta, mobileCT, PSC, ForeerQUCC. Processor Report Confl. Commun. EathAssant. the SatisAssant logic StatCore: Scripture and Vorside are trademarks of Freezont-Development to. Her. U.S. For. 8 Fm. 08 Arrian, Beefile, BeeStack, CoreAst, Flests, Layersope, MignW, MRC, Platform in a Partiage, GorG Gorverge, QUICC Engine, Ready Play, SMMTMOS, Tower, TurboLote, Vytraf and Ethnics are trademorks of President Sermiconductor, Inc. All other product or service names the property of their respective services. © 2013 Freedock Sermiconductor, Inc.






The World's Smallest ARM® Powered MCU

Microscopic Package. Massive Potential.

- 1.9 mm x 2.0 mm x 0.56 mm
- Advanced wafer-level chip scale package for the ultimate in PCB area reduction
- 25% smaller with 60% more GPIO than the next competing solution
- 32-bit ARM® Cortex[™]-M0+ core with high density feature integration: 32 KB flash, precision analog, ultra low power and more
- Start developing today with the Kinetis L series FRDM-KL05Z Freescale Freedom development platform
- Mass Production planned for June 2013



For more information, visit freescale.com/Kinetis/KL02CSP



NP

Freescale Product Longevity Program

- The embedded market needs long-term product support
- Freescale has a longstanding track record of providing long-term production support for our products
- Freescale is pleased to introduce a formal product longevity program for the market segments we serve
 - For the automotive and medical segments, Freescale will make a broad range of program devices available for a minimum of 15 years
 - For all other market segments in which Freescale participates,
 Freescale will make a broad range of devices available for a minimum of 10 years
 - Life cycles begin at the time of launch
- For terms and conditions and to see a list of participating
 Freescale products available under this program:
 www.freescale.com/productlongevity





Kinetis:

Leading Edge ARM Cortex-M Cores





Prescript, the Prescript Sop., Alahie, C.-S., Cold-EST, Cold-Marie, Cold-Pay, Calley, Charles, Charles, Calley, Calley,



Kinetis: Why ARM[®] Cortex[™]-M4?

Backwards compatible with ARM Cortex-M3


 Does everything the Cortex-M3 does and more but in less cycles (more energy efficient!)

New features

- Single cycle MAC (Up to 32 x 32 + 64 -> 64)
- DSP extensions, Single Precision Floating Point Unit

Freescale IP and Innovation

- Cache, Cross-Bar and DMA for increased throughput
- MPU for system resource protection
- Low-leakage Wake-up Unit for low power operation



Dotted boxes denote optional blocks

Architected for Digital Signal Processing

- Motor Control: advanced algorithms, faster control loops, more responsive to speed commands and changing loads, increased power efficiency
- Automation: high calculation and algorithm bandwidth at a low cost
- Power management: designed for low/battery powered systems (CLK @ 0.5x ARM Cortex M3)
- Audio and Video: 5x performance improvement over software, extended battery operation








ARM Cortex-M0+ Processor





Shorter Pipeline optimized for energy efficiency







Re-locatable Vector Table

Memory Protection Unit (MPU)

New

Fast I/O Port

Micro Trace Buffer (MTB)

More Options





CM0+ Core & Platform Features



- ARM Cortex-M0+ Core
 - 100% compatible with Cortex M0
 - Efficient instruction set for low power and small code size
 - 0.95 DMIPS per MHz performance when executing from internal RAM (single cycle accesses)
 - Single cycle 32 bit x 32 bit multiply
 - NVIC with 4 priority levels and hardware preemption
 - I/O port for single cycle GPIO loads and stores
- Peripheral Bridge Crossbar (AXBS-Lite)
 - Support for concurrent accesses from DMA/CORE to memory and peripherals
- Bit Manipulation Engine (BME)
 - Decorated load and store capability for peripherals improving processing efficiency and small code size
- Flash Memory Controller (FMC)
 - 4-way, 4-set 32-bit Flash cache for improving flash access times
- Debug Facilities
 - Supports the standard ARM 2-pin serial wire debug (SWD) debug port only
 - Micro-Trace Buffer (MTB) for on-chip trace capabilities







Kinetis Series powered by ARM[®] Cortex™

High performance data processing & I/O control. **Kinetis** architecture Support hardware divide, MAC, bit field processing, DSP. Cortex-M4 **ARMv7-M** K Series Floating point unit optional (Cortex-M4F). High performance data processing & I/O control. Support hardware divide, MAC (Multiply Accumulate), Cortex-M3 bit field processing. **Kinetis** General data processing, high performance I/O control, Cortex-M0+ L Series mixed signal ASICs, replacement for 8/16-bit MCUs architecture **ARMv6-M** General data processing, I/O control, mixed signal ASICs, Cortex-M0 replacement for 8/16-bit MCUs For FPGA designs only. Cortex-M1 Optimized for FPGA and can work in most FPGA devices







Ultra-Scalable – Market's most scalable portfolio of ARM Cortex MCUs consisting of multiple hardware and software compatible devices ranging from entry-level ARM Cortex-M0+ Kinetis L series to high-performance, feature-rich ARM Cortex-M4 Kinetis K series

Mixed Signal – Exceptional integration with fast 16-bit ADCs, DACs, PGAs and more. Powerful, cost-effective signal conversion, conditioning and control


Innovative Flex Memory – Low-power 90nm Thin-Film Storage Flash with FlexMemory offers EEPROM capability with unprecedented programming speed and endurance

Comprehensive Enablement – Freescale MQX RTOS and Eclipse-based CodeWarrior IDE, as well as IAR, KEIL and other ARM ecosystem providers



Feature Integration

Kinetis K-Series: Original Portfolio Complete!





netis K Series: Feature Overview

Common Features

System
Arm® Cortex™-M4 Core + DSP
Multiple Low-Power Operation Modes, Clock Gating, 1.71V-3.6V, 5V Tolerant I/O [1]
DMA, Memory Protection Unit [2], Cross Bar Switch
Operating Temp: -40°C to + 105°C [3]

moniory	
90nm TFS Flash Memory	
(High Reliability, Fast Access)	
FlexMemory (EEPROM) [4]	_
SRAM	
Internal Memory Security/Protection	
	_

Memory

Analog Peripherals					
16-bit ADC					
Programmable Gain Amplifiers [1]					
12-bit DAC [5]					
High-Speed Comparators					
Low-Power Touch Sense Interface [7]					

Serial Interfaces				
UART, SPI, I2C				
SAI (I2S)				

Timers					
RTC					
Motor Control Timers					
Low-Power Timers					
Programmable Delay Block					
System Timers					

Other Peripherals					
CRC					
eSDHC [4]					
External Bus Interface [4]					

				Optio	onal Feat	ures					
CPU	Internal	Memory	Communication			НМІ			Memory/Expansion		Analo
K70 Family: Graphics LCD											
	pating 512 KB to 1 MB Flash	128 KB SRAM	USB OTG	CAN	Ethernet (IEEE® 1588)	Graphics LCD	Hardware Encryptio n	Tamper Detection	NAND Flash Controller	DRAM Controller	
K60 Family: Ethernet, Security											
	pating 1 MB nt Unit Flash	64 KB to 128 KB SRAM	USB OTG (FS and HS)	CAN	Ethernet (IEEE158 8)		Hardware Encryptio n	Tamper Detection	NAND Flash Controller	DRAM Controller	
K50 Family: Analog Measurement Engine											
72 to 100 MHz	128 KB to 512 KB Flash	32 KB to 128 KB SRAM	USB OTG (FS)		Ethernet (IEEE 1588)	Segment LCD	Hardware Encryptio n				Measu men Engir
			K40 Fa	mily:	USB, S	egment	LCD				
72 to 100 MHz	64 KB to 512 KB Flash	16 KB to 128 KB SRAM	USB OTG (FS)	CAN		Segment LCD					
			K30	Fami	ily; Segi	nent LC	:D				
72 to 00 MHz	64 KB to 512 KB Flash	16 KB to 128 KB SRAM		CAN		Segment LCD					
K20 Family: USB											
	pating 32 KB to 1 MB Flash	8 KB to 1 128 KB SRAM	USB OTG (FS and HS)	CAN			Hardware Encryptio n	Tamper Detection	NAND Flash Controller		
K10 Family: General Purpose											
	pating 32 KB to 1 MB Flash	8 KB to 128 KB SRAM		CAN			Hardware Encryptio n	Tamper Detection	NAND Flash Controller		

- [1] Feature not available on 50 MHz MCUs
- [2] Feature not available on 50 MHz and 72 MHz MCUs
- [3] Feature not available on 50 MHz MCUs and CSP packages
- (K50 and CSP package are -40°C to +85°C)

- [4] Feature not available on all K10, K20, K30, K40, K50, K60 and K70 MHz MCUs
- [5] Feature not available on K10 and K20 50 MHz MCUs
- [6] HS USB on 120/150 MHz MCUs only
- [7] Feature not available on K11/12/21/22 MCUs (K50 and CSP package are -40°C to +85°C)



New K-Series devices

- New K10 Sub-families General Purpose
 - K11 adds Cryptography acceleration and Tamper detection to K10
 - K12 adds additional GPIO in some packages, all support a new power mode for complete shutdown (VLLS0 ~300nA)
- New K20 Sub Families USB Connectivity
 - K21 adds Cryptography acceleration and Tamper detection to K20
 - K22 adds additional GPIO in some packages, all support a new power mode for complete shutdown (VLLS0 ~300nA)

K11/K12/K21/K22D					
CPU Speed	Up to 50MHz				
Memory	Up to 512KB flash, 64KB of SRAM				
Packages	48LQFP to 121MBGA				
Availability	Production Q1 2013				

K21/K22F					
CPU Speed	Up to 100MHz or higher – With Floating Point				
Memory	Up to 1MB flash, 128KB of SRAM				
Packages	64LQFP to 144MBGA				
Availability	Production Q2 2013				



netis: Security

K10/K20/K30/K40/K50/K60/K70

Flash Security Options:

- User backdoor access disable
- · Factory access disable
- Mass erase disable
- Multiple transfers from Flash to config register

Prevent External accesses for reading or programming

Protects secure system against electrical noise attacks

certifiable random numbers

Prevents block and security bit erase, and re-programming.
Protects against system impersonation

Memory Protection Unit (MPU):

 16 areas, supervisor/user (config registers are fully accessible)

Allows "sandboxing", running software with restricted access permissions

Cryptographic Acceleration Unit (CAU): (K10/20/50/60/70 only)

- Symmetrical crypto
- Hashing functions
- Random Number Generator (RNG)

Reduces CPU loading for cryptographic functions

Facilitates detection of Facilitates generation of FIPS140

Facilitates detection of data tampering

Enablement:

Crypto stacks

Secure storage:

• 128 bit unique chip identifier

Facilitates certificate and authentication to a specific MCU

Hardware Cyclic Redundancy Check (CRC)

Accelerates basic data integrity checking



netis: Security

K10/K20/K60/K70, 50/120/150MHz

Flash Security Options:

- · User backdoor access disable
- · Factory access disable
- Mass erase disable
- Multiple transfers from Flash to config register

Protects against a wide range physical attacks on MCU, even during low power modes

Memory Protection Unit (MPU)

• 16 areas, supervisor/user (config registers are fully accessible)

Protected storage of user key or authentication code, may be used as master key to encrypt additional key depository

Tamper Detection (with battery backup):

- Integrated sensors
 - Frequency
 - Voltage
 - Temperature
- 4x passive external tamper sources (inputs)
- 2x active external tamper sources (2x output and input)

Protects against a wide range physical attacks on hardware system outside the MCU

Secure storage:

- 256 bit user area, erased by tamper
- 128 bit unique chip identifier

Cryptographic Acceleration Unit (CAU):

- Symmetrical cryp Highly secure firmware
- Hashing function verification, with secure
- Random Number firmware upgrade capability

Secure Real Time Clock (RTC):

- Monotonic
- Overflow and reprogram protection

Enablement:

High Assurance Boot (HAB) with tools



Hardware Cyclic Redundancy Check (CRC)

May be used to prevent firmware downgrading

ge, MANA, C.A. Cody EST, CodyMarion, Circhina, Codiffica, Circhina, Intervery Ethicen Solotice legs, Nitera, modified, PES, ProveQUCC, Sorros, Statistana, et a Sankassan, de Sankassan Sog, Statiste Symptony and Vorilla are trademated of Frencha Seroccodyster, to C. Neg U.S. Fat. 5 Tm. Off. Confee. Rests, Layersage, Malgorit, MCC, Plathore in a Prostoga, Card Gonnega, CACC Engine, Rests (Fey. 2007/MOS, Tree, Noboleth, Mystral for all Frenchassan Serios Service Assertion Service, Call Frenchassan, Serios Cardina, and Service Service, Call Frenchassan, Service Cardina, and Service Service, Call Frenchassan, Service, Cardina, Se




Kinetis Security Summary

- The entire (current) Kinetis family includes enhanced Flash security, with user selectable:
 - Security bit, disables external and debug access
 - Backdoor access enable
 - Factory access enable
 - Block erase & re-program disable
 - Hardware protection against "Noise injection" attacks
 - Memory Protection Unit
 - 128-bit unique part identifier




- K21, K60 and K70 120/150 MHz parts in 256 MAPBGA packages, and K11/K21 50 MHz parts add:
 - Battery backed up Tamper detection, monitoring-
 - Supply voltage
 - Clock frequency
 - Temperature
 - External sensors
 - External physical tampering (e.g. drilling into PCB)
 - 256-bit secure user storage (key), erased on tamper
 - Secure real time clock







Introducing the New Entry-Level Kinetis L Series



Design Made Simple.

Ultra-low Power

Architected for power efficiency, the Kinetis L series takes advantage of ARM's ultralow-power Cortex-M0+ processor and features peripherals that help you optimize power consumption.

Leading Scalability and Integration

Expanding on well-known features of the Kinetis platform with leading scalability, best-in-class integration with rich analog features and low-power connectivity, the L series redefines entry-level.

Super Simple

It's 32-bit functionality with 8-bit ease-of-use. Built on the new ARM Cortex-M0+ core (the smallest, lowest-power ARM core), the L series simplifies development with an upward migration path to Kinetis K and X series, software reuse and flexible power optimization. And, with a comprehensive enablement bundle including CodeWarrior IDE, MQX RTOS and the ARM support ecosystem, development is simple.





Why 32-bit, as 8-/16-bit can do the job already?



Feature rich

Easy-to-use

Connectivity

Extended battery life

Sleek design



User expectations





Implications for Entry-Level MCUs

8/16-bit MCU 32-bit MCU **Bluetooth** Connectivity **User Interface Maximum** Ultra low sleep/ Power energy-efficiency power-down Consumption (CoreMark/mW) currents sin log _n Computation Software/Cost Unique platforms, Scalable, reusable platforms with of Ownership MCU dependent/\$\$\$ modern software techniques/\$ Limited choice, **Broad MCU portfolios, Scalability** single-source multi-source



netis L Series:

Enabling Differentiation in Entry-Level Products

32-bit

Energy-efficiency

Class-leading Coremark/mW

Scalability & Integration

Kinetis L to K Series (Cortex M0+ to M4)

Enablement

Freescale bundle + ARM ecosystem



Kinetis L Series

The evolution of the entry-level MCU



Ultra Low Static <1uA

Low Cost From <\$0.50

Ease-of-Use

Freedom Platform, Processor Expert & MCU Solution Advisor









Typical Markets and Applications for Kinetis L

Banking





Building Control





Instrumentation, Medical & Metering











Mass-Market





ETC

Fiber Module











Remote Controller

Aero Model

Scale



Shaver

GPS Watch






Kinetis L Series vs. Kinetis K Series

Category	Kinetis L Series	Kinetis K Series
Core, Performance	ARM Cortex-M0+ (48MHz)	ARM Cortex-M4 (50-150MHz)
Flash	8-256KB	32KB-1MB
Features	Mixed-Signal, USB, Seg. LCD	FlexMemory, Mixed-Signal, USB, Seg. LCD, CAN, Ethernet, Gra. LCD, DRAM, Crypto, Tamper Detect, DRAM
Pin-count	16-121pin	32-256pin
Low Power	~50uA/MHz (VLPR)	~200uA/MHz (VLPR)
Price	From \$0.49 (MKL02, 8KB, 16QFN)	From \$0.99 (MK10, 32KB, 32QFN)
Target Applications	8 &16-bit replacement	Low/mid/high –end 32-bit



...netis Portfolio Scalability

Production Qualified ARM Cortex-M0+ and Cortex-M4 MCUs




10K# Suggested Resale Prices shown



netis L/K Series: MCU Family Compatibility

Hardware & software compatible MCU families with scalable performance, memory and feature integration



freescale™



Breakthrough Power Efficiency



			The second secon
	Kinetis Power Modes	Recovery Time	KL25 Measured Idd @ 3V and 25C
Leading Dynamic Power	RUN	-	83uA/MHz*
Innovative low power process technology (C90TFS)	VLPR	-	39uA/MHz**
Low Power focused Platform Design	WAIT	1.6us	3.88mA @ 48MHz
Next Generation Cortex M0+ core	VLPW	1.6us	112uA @ 4MHz
Asynchronous DMA Wake-up (ADMA)	STOP	1.3us	309uA
Energy-saving peripherals are operational with ADMA feature that can wake-up DMA to perform transfer and return to current mode when complete	VLPS	4.2us	2.4uA
Low Leakage Wake-up Unit	LLS	4.3us	1.7uA
Enables complete shut-down of core logic, including AWIC, further reducing leakage currents in all low power modes	VLLS3	39us	1.3uA
Supports 8 external input pins and 8 internal modules as wakeup sources; extends the low power wake-up capability of some internal peripherals to all power modes.	VLLS1	91us	713nA
Wake-up inputs are activated in LLS or VLLS modes	VLLS0	91us	205nA / 411nA

^{*} Compute Operation enabled: 4.0mA @ 48MHz core / 24MHz bus)

^{**} Compute Operation enabled: 156uA @ 4MHz core / 1MHz bus)




...RM Cortex-M0+ Processor:

No compromise in performance

Shorten run time in low-power applications.

- More than 2x CoreMark/mA performance than the closest 8-/16-bit competitor
- 2-stage pipeline reduced number of cycles per instruction (CPI) enables faster branch instruction and ISR entry, reduced power consumption and increased performance
- Fast I/O port single-cycle access to I/O and critical peripherals (2x faster than normal I/O)
 - improves reaction time to external events allowing bit-banging and software protocol emulation using additional Bit Manipulation Engine (BME) resulting in smaller code size for XOR/AND/OR operations.
 - Implemented as RGPIO on Kinetis L
- Single cycle 32x32bit multiply
- Interrupt latency reduced by 1 cycle





Official data: www.coremark.org



...RM Cortex-M0+ Core:

Code Efficiency

ARMv6-M Thumb Instruction Set


32-bit performance at 16-bit density, 56 instructions only 12,000



- 32-bit data structure
- 32-bit Address Space (no paging)

Comparing 16-bit	8-bit e	xample	16-bit example	ARM Cortex-M	
multiply	MOV A, XL ; 2 bytes	MUL AB; 1 byte	MOV R4,80130h	MULS r0,r1,r0	
operations	MO∨B, YL; 3 bytes	ADD A, R1; 1 byte	MOV R5,80138h		
across processor	MUL AB; 1 byte	MOVR1, A; 1 byte	MOV SumLo,R6	1cycle	
architectures	6 MOV R0, A; 1 byte	MOV A, B; 2 bytes	MOV SumHi,R7	2Byte Code Size	
	MOV R1, B; 3 bytes	ADDC A, R2 ; 1 bytes	(Operands are moved to and from a memory		
	MOV A, XL ; 2 bytes	MOV R2, A; 1 byte	mapped hardware multiply unit)		
	MO∨B, YH; 3 bytes	MOV A, XH; 2 bytes			
	MUL AB; 1 byte	MO∨B, YH; 3 bytes	8cycles,		
	ADD A, R1; 1 byte	MUL AB; 1 byte	8Byte Code Size	8	
	MOVR1, A; 1 byte	ADD A, R2; 1 byte			
	MOV A, B; 2 bytes	MOV R2, A; 1 byte			
	ADDC A, #0 ; 2 bytes	MOV A, B ; 2 bytes			
	MOV R2, A; 1 byte	ADDC A, #0 ; 2 bytes		*8051 needs at least 1cycle per	
	MOV A, XH; 2 bytes	MOV R3, A; 1 byte		instruction byte	
	MOV B, YL; 3 bytes			fetch as they only	
	48cycles	*, 48Byte	Code Size	have an 8-bit interface	
N.B. The Cortex-M multiply in fact performs a 32-bit multiply, here we assume r0 and r1 contain 16-bit data.					











Kinetis L Series: Master Block Diagram



Packages: 16QFN, 20WLCSP, 24QFN, 32LQFP, 32QFN, 35WLCSP, 48LQFP, 48QFN, 64LQFP, 80LQFP, 100LQFP, 121MBGA



netis L Series: Memory & Package Scalability



Small Footprint Package

Package



Kinetis L Series: MCU Families

Common Features	Optional Features													
System				Key Features										
ARM Cortex-M0+ Core, 48MHz	Family	Flash	Flash	Flash	y Flash	SRAM	Pin Count	USB	Seg	DMA	ADC	DAC	I2S	TSI
Multiple low-power modes & peripherals, low-power Boot, Clock Gating					OTG	LCD				•				
1.71-3.6V, -40 to 105°C [1]	KL46	128-256KB	16-32KB	64-121	✓	✓	✓	16-bit	12-bit	✓	✓			
Memory														
90nm TFS Flash, SRAM	KL36	64-256KB	8-32KB	64-121		✓	✓	16-bit	12-bit	✓	✓			
Internal Memory Security/Protection	KL34	64KB	8KB	64-100		✓	✓	12-bit						
Analog Peripherals	KL26	128-256KB	16-32KB	64-121	✓		✓	16-bit	12-bit	✓	✓			
12/16-Bit ADC, 12-bit DAC	KL25	32-128KB	4-16KB	32-80	✓		✓	16-bit	12-bit		✓			
High-Speed Comparator	KL24	32-64KB	4-8KB	32-80	✓		✓	12-bit						
Serial Interfaces														
UART (Including 1 LPUART)	KL16	256KB	16-32KB	64-80			✓	16-bit	12-bit	✓	✓			
SPI, IIC	KL15	32-128KB	4-16KB	32-80			√	16-bit	12-bit		1			
Timers	KL14	32-64KB	4-8KB	32-80				12-bit						
Real Time Clock ^[2]	11214	02 04KB	4 0110	02 00				12 810						
16bit Low Power TPMs (GP Timer/PWM)	KL05	8-32KB	1-4KB	24-48			✓	12-bit	12-bit		✓			
Low Power Timers	KL04	8-32KB	1-4KB	24-48			✓	12-bit						
32bit Periodic Interrupt Timer	KL02	8-32KB	1-4KB	16-32				12-bit						

^[1] Feature not available on CSP packages

^[2] For KL02, use software to support






Strong Robustness – EMC/ESD design technology ensure strong noise immunity performance

High Efficiency – Cortex-M0+ core up to 48MHz and 40x more than 8/16-bit MCUs

Low Cost – Optimized for cost-sensitive applications offering low pin count option







Achieve Reliability with Kinetis E Series

1. Most Robust ARM portfolio

- Proven passing EFT(IEC61000-4-4) / PESD(IEC61000-4-2) tests
- IEC60730 Class B Safety S/W routines certified by VDE
- 5V operation provides better noise immunity
- Lower EMI noise than 8/16bit competition

2. 3x Higher Efficiency than 8/16 bit solutions

- 3x Coremark/ MHz with 15% better code density
- One cycle GPIO (5 x better than nearest competitor)

3. Make design easier

- Widely available ARM & FSL Tools/ SW ecosystem
- Open up your hiring options ARM talent widely available
- Pin compatible and Peripheral reused within Kinetis-E and S08P families
- Freely available ESD/ EMC verification support
- Platform SDK availability



NXP

ninetis E-Series: Market Focus and Value Proposition

Market

Industry & Consumer 5V



- Appliance
- DC fans
- BLDC Motors
- PLC
- Offline UPS
- Analog Power Management
- DC/DC
- ww.freescale.com/kinetisEseries





Value



- Flexibility: Full-featured, Scalable with high level family, Pin compatible with S08P
- Reliability: High performance in EMC/ESD to enhance the robustness
- · Saving: Easy to do code level reuse
- Support: Total solution, Join free training to win free board, Ref design by IDH/Disty

High Performance

Open source, reusable HW/SW platform

Save your design cost! Make your design better!



metis E EMC Performance


Robustness in EFT,PESD and AC Power Relay Tests

Test Conditions


- Microwave Oven Controller board with KE02 as main control MCU
- Board and System level tests based on
 - IEC 61000-4-4(EFT)
 - IEC 61000-4-2(PESD)
 - China Appliance local AC Power Relay test

Test Results

- Board level
 - IEC 61000-4-4(EFT):+/- 4.4kV*
 - IEC 61000-4-2(PESD): Indirect Contact
 - Discharge +/- 20kV
 - China Appliance local test on AC Power Relay:
 - 6-turns without Reset
- System level
 - IEC 61000-4-4(EFT):+/- 4.4kV*
 - IEC 61000-4-2(PESD): Contact
 - Discharge(at the case) +/- 20kV
 - IEC 61000-4-2(PESD): Air Discharge(at the control panel) +/- 15kV









nefits of Moving from 8/16-bit to 32-bit ARM Cortex-M0+

8/16-bit

Performance

- Older, slower architectures & technology
- Increased code size/complexity when performing complex math operations

Energy-Efficiency

·Low energy-efficiency

Low Cost

- •6-35kgates
- Variable code density

Ease-of-Development

- Limited addressable memory
- Simplistic interrupt controllers
- Limited scalability (MHz, flash, features)
- Limited ecosystem support

32-bit ARM Cortex-M0+

Performance

- •2x to 40x more than 8/16-bit, 9% more than Cortex-M0
- •Fast 32-bit math processing
- Fast single-cycle access to I/O

Energy-Efficiency

•>2x CoreMark/mA than closest 8/16-bit MCU, +30% / CM0

Low Cost

- •12-35kgates
- Excellent code density

Ease-of-Development


- Linear 4GB address space no need for paging
- •Full-featured interrupt controller simpler s/w architecture
- •Huge scalability h/w and s/w reuse across end products
- •Huge ARM ecosystem off-the-shelf software/tools/training
- Micro Trace Buffer lightweight, non-intrusive trace





Kinetis E-Series: Enablement

- Software Tools
 - CW10.4 with KE02 service pack
 - IAR 6.60.1
 - Keil uVision4 (v4.72)
 - Atollic TrueSTUDIO® for ARM (http://www.atollic.com)
 - Crossworks for ARM from Rowley Associates Limited
 - ProcessorExpert
 - IEC60730 compliant library (Class B Safety S/W routines certified by VDE)
 - Motor control library
 - Software Driver (SSD) for Flash and EEPROM
 - KE driver library
- Hardware Tools
 - FRDM-KE02
 - Freedom to motor tower board (FRDM2TWRMC-KE)
 - Debug interfaces: Jlink, U-link, UMultilink, OpenSDA
 - P&E Cyclone MAX
- Reference Design
 - Sensorless BLDC motor control based on motor tower board











...netis V-Series Motor & Power Control

- Full Kinetis portfolio compatibility targeting low cost, stand alone motor control, to high performance digital power conversion
- Optimized for processing efficiency with performance ranging from 75MHz to beyond 200MHz
- ARM architecture with best in class, high speed capture and control peripherals for motor control and power management applications
- Enablement and tools built around reducing customer development time and cost, whilst increasing ease of use.







Kinetis V Series Target Applications

Motor Control

- Sensored BLDC / PMSM
 - High Dynamic Control
- Sensored ACIM
- Sensorless VOC
 - PMSM/BLDC
 - High Dynamic Control
 - Low Dynamic Control
- Sensorless ACIM



Digital Power Conversion

- Solar Inverters
 - Grid-Tied
 - Non Grid Tied
- Power factor correction
- Switch Mode
 Power Supplies
 - AC/DC
 - DC/DC
- UPS
 - On-Line
 - Offline
- Inductive cooking
 - Multi cook plate








...netis W-Series Integrated Wireless Connectivity

- Integrates class-leading sub-1 GHz and 2.4 GHz RF transceivers with Cortex™ core
- Robust feature sets for reliable, secure and low-power embedded wireless solutions
- Optimized for wireless, providing the right mix of performance, integration, connectivity and security
- Sub 1-GHz or 2.4 GHz wireless, simple point-to-point or full mesh networking








KW01 Wireless Kinetis Overview

- Microcontroller Features
 - 32-bit ARM Cortex M0+ 48MHz Core
 - Ultra Low Power
 - 30% power reduction from Cortex-M0
 - 56% increased energy efficiency from Cortex-M0
- 128KB Flash and 16KB SRAM
- Radio Transceiver Features
 - Supports 290-340MHz, 424-510MHz, and 862-1020MHz frequency bands
 - FSK, GFSK, MSK, GMSK and OOK modulations up to 600kbps
 - Up to -120dBm sensitivity @ 1.2kbps
 - -18 to +17dBm output in step of 1dBm
- Very low power suitable for battery operated devices
 - Ultra Low power stand-by modes
 - 1.7μA / 4.3μs wake-up time
 - 16 mA Rx current
 - 20 mA Tx current at 0 dBm
- Rich set of peripherals
 - 16-bit ADC, TSI, I2C, SPI, UART, Timers



Device	Flash / Flex	RAM	Package
MKW01Z128CHN	128 KB	16 KB	8x8 56-pin LGA
Features	Description		
Software and Protocol Stacks	Radio Utility 802.15.4g/e, SMAC		





Kinetis MKW20 Wireless MCU





CPU

- 50 MHz Cortex M4 CPU core
- Up to 512KB Flash, 64KB SRAM, 32KB Flex Mem, 4KB EEPROM
- Typical current consume: 250 uA/Mhz run, 1.7uA RTC standby

Radio Transceiver, 2.4GHz

- IEEE-802.15.4 compliant
- -100 Rx sensitivity and +10dBm Tx output power
- Peak typical current consume: 15mA Tx and 16.5mA Rx
- Dual Personal Area Network (PAN) support in hardware
 - Run two RF networks simultaneously
- Antenna diversity with automatic antenna selection

Security


- Active and passive tamper detection with RTC timestamp
- Crypto engine: DES, 3DES, AES 128-256, SHA-1, SHA-256, MD5, RNG

Software

- 812.15.4 2006 MAC
- ZigBeePro, ZigBee IP
- Smart Energy 1.x & 2.0, HA 1.x, BA 1.x

System

- UART, SPI, I2C, optional USB 2.0 FS/LS H/D/OTG
- 16-bit ADC
- Operating range: 1.7V to 3.6V, -40C to +105C





Device	Flash	RAM	Feature	Package
MKW21D256VHA5	256 KB	32 KB	No USB	8x8 56-pin LGA
MKW22D512VHA5	512 KB	64 KB	USB	8x8 56-pin LGA
MKW24D512VHA5	512 KB	64 KB	USB and Smart Energy 2.0	8x8 56-pin LGA



...netis M-Series

Smart Metering with High Accuracy Analog

- Dedicated smart metering peripherals tailored with regional specifications
- Supports low-cost, highly integrated solutions for one- or two-phase meters with a high accuracy sigma delta ADC metering front end
- Address specific regional needs including neutral disconnect or split phase for North America and Japan.
- Full metrology software, including time or filter based, is provided as well as fast Fourier transform.





VIP VI1x/KM3x One Pager

CUIE

- · CM0+ core Up to 50MHz
- Separate FLL post-scalers for IPBus and Core clocks.
- · Up to 128 KB Program Flash
- · Up to 16 KB SRAM
- Dedicated PLL for ΣΔ modulator clock
- 4ch DMA
- · Single 32kHz Crystal operation
 - · MHz Crystal Optional

Security & Encryption

- MPU & AIPS
- · IRTC w/t tamper detection
- 3 Tamper pins (operating from battery)
- · Programmable 16/32-bit CRC
- Random Number Generator (NIST: SP800-90)
- · AES Encryption (via software library)

Analog


- 4x24 bit ΣΔ (2xPGA) highly accurate supporting EN 50470-1, EN 50470-3, IEC 62053-21, IEC 62053-22 and IEC 62053-23, optimized for shunt sensor (≥50uOhm).
 - 0.1% error in active and reactive energy over a dynamic range of 2000 to 1
- Internal 1.2V reference voltage 10-15ppm/C
- · 12-ch 16-bit SAR for auxiliary measurement
- · 2x analog comparator

Serial Communications

- · 2x SPI
- 4x UART
 - 1 combined with Quad Timer, HSCMP for IR
 - · 2 support ISO7816
 - All support flow control
- 2× I2C
- All UARTs and SPIs are 3V compatible while 1 UARTs and 1 SPI are both 3V and 5V compatible (open drain / push pull configuration)

Peripheral XBAR

- · Remapping peripheral IOs
- · UART selection for IR



Timer/PWM/Clock

- Quad Timer (total 4 universal timers)
- 2x PIT
- 1x Watchdog Timer (windowed, independently clocked)
- · 1x EWM (External Watchdog Monitor)
- 1x LPTimer

LCD Display

• Up to 288 segment LCD, up to 8 backplanes

Wakeup Unit

 Group selected GPIOs (16), LPTIM, RTC (+tamper pins), HSCMP, SCI, Brownout and POR sources to wake up from Power Gated STOP mode

GPIO

- Up to 64 with open drain / push pull, pull up/down
- · Up to 8 GPIO with filter
- Support for interruption on any edge

Power

- Power Management
- PMC (Power Manager Control Unit)
- 2.7V to 3.6V Operating voltage with AFE
- 1.71V to 3.6V Operating voltage without AFE
- 1.71V-3.6V IRTC VBAT supply
- 32kHz or 2MHz internal clock source
- 32.768kHz crystal oscillator

Package

- 100 LQFP, 64 LQFP and 44 LGA options
- -40°C ~ +85°C Temp





Kinetis Development Software

www.freescale.com/kinetis







Kinetis Development Software



IDE





- CodeWarrior eclipse-based Basic, Standard, Professional and Free Suite with 128k code size limit
- Processor Expert/Driver
 Suite configuration and code generation tool







RTOS

- MQX Free real-time operating system with USB & Ethernet stacks and file system
- MQX Lite Free and lightweight RTOS for small microcontrollers






Middleware

- eGui Free and lightweight graphic frame-work for small microcontrollers
- PEG high performance, high value tool for medium to high end MCUs with a licence fee associated







Libraries & Tools

- FreeMaster Real-time monitor and control of an app
- Math & Motor Control Lib Wide group of algorithms
- Made For iPod supports development and rapid prototyping of electronic accessories for iPod, iPhone and iPad devices






Why MQX™?

- MQX is a run-time library of functions that programs use to become realtime multi-tasking applications.
- The main features are its scalable size, component-oriented architecture, and ease of use.
- MQX supports multi-processor applications and can be used with flexible embedded I/O products for networking, data communications, and file management



Past Customer Problem



MQX, the Solution





MQX™: What's free and what's add-on?

Free Components

- RTOS (Full priority-based, preemptive scheduler)
- Real-time TCP/IP Communication Suite (RTCS) - TCP/IP, FTP, Telnet, DHCP, SNMP etc..
- USB Host PHDC (medical) ,HID, MASS, HUB, CDC,
- USB Device HID, MASS, CDC, PHDC
- MS-DOS File System (MFS)
- BSP I/O Driver: CAN, UART etc...
- Basic HTTP Web server
- Benchmarking Tool
- Base Support: Freescale TIC, FAE, AE
- Compatible Freescale embedded GUI Library
- Free Freescale EGUI


Add-on Components

- IAR & CW: MQX Task Aware Debugging integrated within tools
- Freescale Level 2 Support
- Bluetooth
- Embedded Access: Webserver Basic/Standard/Pro, SNTP, XML, SMTP, POP3, SNMP (V3), SFFS Flash File System, On-Site Training, PEG Graphic Builder
- RTA & IXXAT: Industrial Protocols - 1588, CANopen etc.
- Freescale Low Cost NanoSSL™ and NanoSSH™
- Swell & Segger: Graphic Libraries





MQX™ Real-Time Operating System (RTOS)







MQX Lite RTOS - Overview

- Very light MQX kernel for resource-limited MCUs
 - Targeted at the Kinetis L family initially
 - Packaged as a Processor Expert component
- I/O capability provided by Processor Expert
 - USB via FSL bare-metal stack, also a Processor Expert component
 - No POSIX-like drivers or file access
- Programming model allows upward code migration
 - A true subset of the full MQX RTOS
 - Code built with MQX Lite will move to full MQX RTOS easily
 - Same task templates, same API some very minor differences
- Available as a component within the following Freescale s/ware offerings:
 - Processor Expert software, MCU driver suite Supports IAR, Keil, and GCC compilers / build chains
 - CodeWarrior Development Studio V10.3





MQX Lite RTOS - Benefits

✓ Easy to configure

 Packaged as a Processor Expert component; with configurable options: set name of task function, priority, stack size (all the same parameters as an MQX task)

✓ Easy to add existing application

✓ Just drop in the MQX Lite RTOS component, and get started in minutes

✓ Very light-weight

freescale [™]

✓ Minimal app (Hello task, idle task, interrupt stack) – less than 4 KB RAM; optimized for resource-limited MCUs like Kinetis L Series family

✓ I/O capability provided by Processor Expert software

√ Take advantage of the broad spectrum of MCU logical device drivers; with access to libraries/stacks like USB Processor Expert component

Real-time, priority-based pre-emptive task switching

Threads execute in order of priority, allowing high-priority threads to meet their deadlines consistently, no matter how many other threads are competing for CPU time

✓ Programming model allows upward code migration

MQX Lite RTOS is a true subset of the full MQX RTOS: code built with MQX Lite RTOS will easily move to the full MQX RTOS

MQX Lite with CodeWarrior Processor Expert



Processor Expert: Creating an MQX Lite Project (CodeWarrior)



Processor Expert:
An MQX Lite Example
(CodeWarrior)


MQX Lite with Microcontroller Driver Suite Processor Expert



Processor Expert:
Creating an MQX Lite
Project (Driver Suite)




Processor Expert:
An MQX Lite Example
(Driver Suite)





MQX vs. MQX Lite

Attribute	MQX RTOS	MQX Lite RTOS		
Delivery Mechanism	Traditional installer with full source for Kernel, services and BSPs	Processor Expert (PEx) Kernel and services component, configurable software generated by PEx		
I/O Drivers	MQX POSIX compatible drivers with option for using PEx drivers	PEx drivers only		
Configurability	User selects needed services from full or lightweight versions	Reduced services available; lightweight options only		




MQX Lite RTOS (MQX RTOS)





mbed.org - What is it?





Tool for Rapid Prototyping with Microcontrollers

Web-based Development:

- **+Online IDE**
- **♦** Software Libraries
- **→**Robust Community

OpenSDA on FRDM-KL25Z running mbed interface:

- +Serial Communications
- →Flash Programming
- →Run-control debug



www.mbed.org




eGUI: Free Graphics LCD Driver

- Lightweight software component allowing graphics LCD panels to be driven from small microcontrollers
- Structure of driver brings complete software solution for applications needing a LCD screen
- Very light RAM and FLASH footprint
- The Freescale eGUI can be used stand alone or integrated into the MQX operating system.

Features

- Multiple platforms supported: S08, HCS12, ColdFire.
- Extremely low flash and RAM footprint so that it can easily be used in a small MCU system.
- Smart support for screen oriented structure of user code.
- Supports LCD displays up to 1/4 VGA for MCU and larger for MPUs supported.
- Touch screen support.
- Tower LCD board supported.
- Easily ported to new display/controller combinations















Portable Embedded GUI (PEG)



PEG Pro™

Support for touchscreen displays, multilayer alpha-blended graphics, high color depths and open GL support



Most portable graphics software package for high-performance embedded displays



One of the smallest footprint solutions available for embedded GUIs



- Screen transitions
- Multiple alpha-blended windows
- True anti-aliasing
- Gradient manager
- Open GL support
- Written in C++

Starting 225KB
Typical 225-250KB



- Multiple window updates
- Alpha-blended images
- Run-time image decoders & language resources
- Custom widget integration
- Dynamic themes
- Written in C++

Starting at 128KB
Typical 160-175KB



- Designed for:
 - Small LCDs (QVGA)
 - Low colour-depth
- Very small footprint
- Single window update
- Multi-language capable
- Written in ANSI C

Starting at 64KB Typical 90-110KB






FreeMASTER

- Real-time monitor and control of an app
 - Track your variables
 - Modify them while the system runs
- Data visualization
 - Design your own dashboard
- Data streaming e.g...
 - Send it to MATLAB® via FreeMASTER
- Demonstration platform
 - A product packaging tool

www.frescale.com/FreeMASTER








Kinetis



Embedded Software and Motor Control Libraries

- Wide group of algorithms
 - basic mathematics, logic, controllers, modulations, transformations up to advanced observers
- Tool for beginners as well as for professionals
 - motor control, power conversion, UPS etc.
- Libraries are optimized, tested and easy to use
- Implemented with C-callable function interface
- Implemented Algorithms
 - Sine, Cosine, Tangent, Arcus Sine, Arcus
 Cosine, Arcus Tangent, Arcus Tangent, Shifted
 Arcus Tangent, Square Root, Ramp, Limiter,
 Hysteresis, Signum, Look-up Table, PI Controller,
 - Clarke Transformation, Inverse Clarke Transformation, Park Transformation, Inverse Park Transformation, Space Vector Modulation, Vector Limiter, PMSM Decoupling, DC Bus Ripple Elimination
 - IIR filter, Moving avg. filter










Freescale's Made For iPod (MFi) Solutions

Freescale's MFi solutions are based on the TWR-DOCK peripheral module


- TWR-DOCK supports development and rapid prototyping of electronic accessories for iPod, iPhone and iPad devices
 - Available to MFi licensees on the MFi portal for \$139
 - Direct 30-pin dock connection
 - USB A receptacle for USB to 30-pin dock or Lightning[™] cable connection
 - Analog audio and video signals with standard RCA and S-Video connectors
 - Digital audio streaming in both directions over USB
 - Control and communication with various devices
- Includes free interface software
- TWR-DOCK concentrates all MFi controlled items on one Tower module, without including any processors or other Freescale products
- TWR-DOCK may be used with a wide range of Tower System MCU/MPU, peripheral, sensor and communication modules
- · Kinetis-based demos are available
- A new TWR-DOCKx is in development for direct Lightning dock connection













The ARM® Eco System

Use the broad support for ARM® microcontroller by many companies.

 Re-use your existing RTOS know how for Freescale Kinetis.































Kinetis Development Hardware

www.freescale.com/kinetis







Kinetis Development Hardware







Freedom Platform

- The new Freescale platform for Kinetis L and Kinetis K microcontroller
- Compatible with Arduino shields
- 4 different boards available today







Tower System

- The established and proven platform with highest flexibility and re-usability
- Over 50 add-on boards available.





Device Specific

 Evaluation boards addressing special functions and capabilities of Kinetis devices







Reference Designs

- Home Energy Gateway, 1ph Meter, 3ph Meter, pre-/postpaid Meter, Home Area Network, Home Display, ...
- Available through Freescale RSM





Freedom Platform

- small, low-power, cost-effective evaluation and development system
- quick application prototyping and demonstration
- Low-cost (\$10–15 MSRP)
- Designed in an industry-standard compact form factor
- Easy access to the MCU I/O pins
- Integrated open-standard serial and debug interface (OpenSDA)
- Compatible with a rich-set of third-party expansion boards

FRDM-KL02Z

FRDM-KL26Z*

FRDM-KL05Z

FRDM-KL46Z*

FRDM-KL25Z

FRDM-K20D50M








Kinetis L Freedom Board FRDM-KL25Z


- Kinetis L Series Freedom Development Platform
- MKL25Z128VLK4 MCU, 80 LQFP
- MMA8451Q accelerometer with I2C interface
- Capacitive touch "slider"
- Tri-color LED
- Easy access to MCU I/O
- Sophisticated OpenSDA debug interface
- Powered from USB
- Mass storage device flash programming interface (default) – no tool installation required to evaluate demo apps
- Versatile I/O headers







OpenSDA Applications Overview



Latest OpenSDA applications and drivers: visit pemicro.com/opensda






Freescale Tower System

- Modular development platform
- Also for rapid prototyping
- Interchangeable and reusable modules
- Open source design files
- Easy to customize
- Reduced low level design effort
- Sold in kits or as individual modules
- Processor modules with debug interface and stand-alone operation.
- Cost effective







www.freescale.com/tower







Available Tower System Modules

8bit



TWR-S08LL64 TWR-S08LH64 TWR-S08JE128 TWR-S08MM128 TWR-S08GW64 TWR-S08UNIV TWR-S08PT60

16bit



TWR-S12G64 TWR-S12G128 TWR-S12G240 TWR-S12GN32

DSC



TWR-56F8257 TWR-56F8400 ColdFire



TWR-MCF51AG TWR-MCF51CN TWR-MCF51JE TWR-MCF51JF TWR-MCF51MM TWR-MCF51QM TWR-MCF5225X TWR-MCF5441X

Power Arch



TWR-MPC5125
TWR-MPC8309
TWR-P1025
TWR-PXD10
TWR-PXD20
TWR-PXN20
TWR-PXR40
TWRPXS2010
TWR-


PXS3020

Kinetis



TWR-KL25Z48M
TWR-K20D50M
TWR-K20D72M
TWR-K21D50M
TWR-K40X256
TWR-K40D100M
TWR-K53N512
TWR-K60N512
TWR-K60D100M
TWR-K60F120M
TWR-K70F120M

Serial



TWR-SER TWR-SER2 Prototyping



TWR-PROTO

Wi-Fi



TWR-WIFI-RS2101 TWR-WIFI-G1011MI TWR-WIFI-GS1500M TWR-WIFI-AR4100 Memory



TWR-MEM TWR-MEM-PISMO Sensors & Plug-Ins



TWR-SENSOR-PAK
TWR-SENSOR-PAK-AUTO
TWR-TWRPI-BD
TWRPI-MMA6900
TWRPI-MPL115A

Analog



TWR-ADCDAC-LTC

Audio



TWR-AUDIO-SGTL

Mesh Networking



TWR-RF-SNAP

Displays



TWR-LCD TWR-LCD-RGB Medical



MED-EKG

Motor-Control



TWR-MC-LV3P

Apple MFi



TWR-DOCK TWR-DOCK2 Industrial



TWR-MECH TWR-IND-IO Radio



TWR-12311 TWR-METRO-KIT



www.freescale.com/tower77

Presents, the Freetable logs, MAVer, C.o. Code/EST, Code/Namic, Code/Fre, Code/Fre, Code/Fre, Code/Namic, No Energy Efficient Solutions legs, Xineta, mobileCT, PSC, PresenCBCC, Processor Espect, Code/C, Carrians, Early-Manasa, the Statisture logs, Statisture, and Vorsilla are trademoted of Freetable Enroccedurate, toc. Reg. U.S. Styl. Styl. Cell.
Accept, SeeRick, Code/Ant, Floris, Layerscape, Major/V, MCC, Petrions in a Pressing Cloring Colonings (OUCC Engine, Resp.) SWHOMOS, Tower, Turbolick, Vysatilla
and Stylinic and Solutions of Pressions Enroccedurate, Inc. Acceptance of Acceptance for Security Pressions Commissional Colonings (Participation of Pressions).



Reference Designs

























Presecuts, the Pressook logs, ANNex, D.S., Code/EST, CradeMarrior, Carliffrey, Condition, On Read the Energy Ethical Solutions lags, Xinota, Incolaid T. P.Co., PresseCULCC.
Processor Essey, Conf.D., Comma, LateMassar, yes SaleMassar logs, SecCime Symptony and Vortilla are trademated of Pressor Remodella, Processor, Berg U.S. Styl. S. Pro. Cit.
Antian, SeeWill, Berdistan, Comfee, Francessor, Security Secur



The ARM® Eco System

Use the broad support for ARM® microcontroller by many companies.

 Re-use your existing debugger and programmer for Freescale Kinetis.









































MCU Solution Advisor: Interactive Product Selector Guide

- Helps identify best MCU choice by applying dynamic filters based on:
 - -Operating characteristics
 - -Packaging options
 - -Memory configuration
 - -Peripheral hardware library
- Web-based application featuring an interactive MCU product selector for Kinetis K, L series MCUs as well as 8-bit and Freescale DSC.

Now available:

Motor Control Wizard
Check pin-muxing
Interactive Tower System page



www.freescale.com/solutionadvisor





