SMA Fixed Attenuator

DC to 6000 MHz **1W** 4dB 50Ω

Maximum Ratings

Operating Temperature -45°C to 100°C Storage Temperature -55°C to 100°C

Permanent damage may occur if any of these limits are exceeded

Features

- wideband coverage, DC to 6000 MHz
- 1 watt rating
- rugged unibody construction
- · off-the-shelf availability
- · very low cost

Applications

- impedance matching
- · signal level adjustment



Generic photo used for illustration purposes only

CASE STYLE: FF704 Connectors Model


SMA

+RoHS Compliant

VAT-4+

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Outline Drawing



Outline Dimensions (inch)

| wt | Е | D | В |
|-------|------|-------|-------|
| grams | .312 | 1.43 | .410 |
| 10.0 | 7.92 | 36.32 | 10.41 |

Electrical Specifications


| FREQ. RANGE (MHz) | ANGE (dB) | | | VSWR (:1) | | MAX. INPUT POWER | | | |
|-------------------------------|-----------|----------|---------|--------------|----------|------------------------|-----------|---------|-----|
| | | DC-3 GHz | 3-5 GHz | 5-6 GHz | DC-6 GHz | DC-3 GHz | 3-5 GHz | 5-6 GHz | (W) |
| f _L f _U | Nom. | Тур. | Тур. | Тур. | Тур. | Тур. Мах. | Тур. Мах. | Тур. | |
| DC-6000 | 4±0.3 | 0.20 | 0.15 | 0.20 | 0.55 | 1.05 1.20 | 1.15 1.45 | 1.45 | 1.0 |


Attenuation varies by 0.3 dB max. over temperature.


Typical Performance Data

| Frequency (MHz) | Attenuation (dB) | VSWR (:1) |
|--------------------|------------------|--------------|
| | | |
| 0.03 | 4.06 | 1.01 |
| 50.00 | 4.01 | 1.00 |
| 100.00 | 4.02 | 1.01 |
| 500.00 | 4.09 | 1.03 |
| 1000.00 | 4.15 | 1.05 |
| 2000.00 | 4.27 | 1.05 |
| 3000.00 | 4.40 | 1.03 |
| 4000.00 | 4.51 | 1.10 |
| 5000.00 | 4.68 | 1.22 |
| 6000.00 | 5.15 | 1.41 |

Electrical Schematic







A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Terms"): Purchases of this part. Ferrormance and updany authorities and contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

^{**} Flatness= variation over band divided by 2.