

Highlighted Products in this catalog are in stock at 3E Windsor Heights and/or 3E Omaha.
One day shipping to all other 3E locations.



CONNECT AND PROTECT

HOFFMAN on Demand Specifier's Guide



Quick Ship Program

FULL PRODUCT RANGE.
LOCALLY AVAILABLE NOW!

hoffman.nvent.com/hod



The HOFFMAN on Demand Specifier's Guide, Volume 1, is published by Hoffman Enclosures Inc., 2100 Hoffman Way, Anoka, MN 55303. Extracts from this literature may be copied or reproduced only with prior approval from Hoffman's Marketing Communications Department by emailing info@nvent.com and if the originator is credited. Hoffman's policy is to continually develop and improve products. The company reserves the right to change product detail and technical specifications. We cannot accept any liability for publication errors and omissions.

Subject to change without notice. Phone 763-422-2211 nVent.com/hoffman © 2019 Hoffman Enclosures Inc.



One nVent

Explore nVent — backed by more than 100 years of excellence — at nVent.com



Welcome to the future of connection and protection



CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER
nVent.com

Product Selection Quick Reference

Product Selection Quick Reference



										
Most Common Type Ratings		Pushbutton	Junction Box (up to 16 x 14)	Wall Mount (16 x 16 to 60 x 36)	Free Stand and Floor Mount (60 x 48 and Larger)		Modular Enclosure Solutions	HMI (Human-Machine Interface)	Industrial Wireway	Thermal Management
12		Pushbutton Enclosures, Type 12, page 18	Continuous Hinge with Clamps, Type 12, page 15 Screw Cover, Type 12, page 16	Concept Two-Door, Type 12, page 11 Continuous Hinge with Clamps LP, Type 12, page 11 Continuous Hinge Two-Door with Handle, Type 12, page 12 Wall-Mount Disconnect Enclosure With Handle, Type 12, page 13 Mild Steel Sequestr External Disconnect Enclosure, Type 12, page 14	Free-Stand, Type 12, Single or Dual Access, page 30 Heavy-Duty Free-Stand Disconnect Enclosure, Type 12, page 31 Modular Disconnect Enclosure, Type 12, page 32 Two-Door with Floor Stands and 3-Point Latch, Type 12, page 34 Two-Door with Floor Stands Disconnect Enclosure, Type 12, page 33		Industrial Packages, Type 12, page 40	Mild Steel Consolets, page 54 Syspend 180-Max Suspension System, Type 12, page 55 Syspend 281-Max Suspension System, Type 12, page 64	Lay-In Wireway, NEMA Type 12, page 78	SpectraCool Compact Indoor, page 95
	4	Extra-Deep Pushbutton Enclosures, Type 4, page 18	Continuous Hinge with Clamps, Type 4, page 15 Continuous Hinge with Quarter-Turn Latch, Type 4, page 16 Screw Cover, Contoured, Type 4, page 17	Concept Single-Door, Type 4 and 12, page 10 Continuous Hinge with Clamps LP, Type 4, page 12 Continuous Hinge with 3-Point Latch, Type 4, page 12 Concept Disconnect Enclosure, Type 4, page 13	Free-Stand, Type 4 with 3-Point Latch, page 32 Free-Stand Disconnect with Quick-Release Continuous Hinge, Type 4, page 30 Two-Door with Floor Stands and 3-Point Latch, Type 4, page 34			Concept HMI, Type 4, page 52		SpectraCool Indoor, page 94 SpectraCool Narrow Indoor, page 95 T-Series Compact Outdoor, page 96
	4X	30.5-mm and 22.5-mm Pushbutton Enclosures, Type 4X, page 23	Continuous-Hinge with Clamps, Type 4X, page 22 Continuous Hinge, Type 4X, page 24 PolyPro, Type 4X, page 26 Qline D, Type 4X, page 26	Concept, Type 4X, page 19 Continuous Hinge with Clamps LP, Type 4X, page 20 Continuous Hinge with 3-Point Latch, Type 4X, page 21 HOFFMAN Watershed, Type 4X, page 21 Hinge-Cover with Quick-Release Latches, Type 4X, page 24 Ultrix, Type 4X, page 25	Free-Stand, Type 4X, Single and Dual Access, page 37 Two-Door with 3-Point Latches, Type 4X, page 36					

